

MPE Calculations

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The MPE calculation for this exposure is shown below.

Using the Antennas with highest output power:

The peak radiated output power (EIRP) is calculated as follows:

| <i>Antenna</i> | <i>Frequency (GHz)</i> | <i>Power input to the antenna (P) (dBm)</i> | <i>Power gain of the antenna (G) (dBi)</i> | <i>EIRP (P+G) (dBm)</i> | <i>EIRP $\text{Log}^{-1}(\text{dBm}/10)$ (mW)</i> |
|----------------------|----------------------------|---|--|---------------------------------|--|
| Hitachi HFT38D4/39D4 | 2.4 | 24.81 | 1.87 | 26.68 | 465.59 |
| Hitachi HFT38D4/39D5 | 5 | 20.12 | 2.99 | 23.11 | 204.64 |

$$\text{EIRP} = P + G$$

Where

P = Power input to the antenna (mW).

G = Power gain of the antenna (dBi)

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

| <i>Antenna</i> | <i>Frequency (GHz)</i> | <i>Antenna Gain (G) (dBi)</i> | <i>Numeric Antenna Gain $\text{Log}^{-1}(\text{dBm}/10)$ (dB)</i> |
|----------------------|----------------------------|---------------------------------------|--|
| Hitachi HFT38D4/39D4 | 2.4 | 1.87 | 1.54 |
| Hitachi HFT38D4/39D5 | 5 | 2.99 | 1.99 |

$$G = \text{Log}^{-1} (\text{dB antenna gain}/10)$$

Power density at the specific separation:

| <i>Antenna</i> | <i>Frequency (GHz)</i> | <i>Power input to the antenna (P) (mW)</i> | <i>Numeric Power Gain of the Antenna (G) (dB)</i> | <i>Maximum Power Spectral Density $S=PG/(4R^2\pi)$ (mW/cm²)</i> | <i>Maximum Power Spectral Density Limit (mW/cm²)</i> |
|----------------------|----------------------------|--|---|---|---|
| Hitachi HFT38D4/39D4 | 2.4 | 302.69 | 1.54 | 0.093 | 1.00 |
| Hitachi HFT38D4/39D5 | 5 | 102.80 | 1.99 | 0.041 | 1.00 |

$$S = PG/(4R^2\pi)$$

Where

S = Maximum power density (mW/cm²)

P = Power input to the antenna (mW).

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The maximum permissible exposure (MPE) for the general population is 1mW/cm².

The power density at 20cm does not exceed the 1mW/cm² limit. Therefore, the exposure condition is compliant with FCC rules.