



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	AirTies Wireless Networks
Applicant Address	Gülbahar Mah. Avni Dilligil Sok. Celik Is Merkezi No 5 meclidiyekoy ISTANBUL, 34394 Turkey
FCC ID	Z3WAI4820
Manufacturer's company	SHENZHEN GONGJIN ELECTRONICS CO.,LTD.
Manufacturer Address	2F/3F/4F Baiying Building, 1019#Naihai RD, Nanshan Dist., Shenzhen, Guangdong, CHINA

Product Name	2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name	AirTies
Model No.	Air 4820
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5725 ~ 5850 MHz
Received Date	Apr. 02, 2014
Final Test Date	Apr. 15, 2016
Submission Type	Class II Change

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01r02, KDB662911 D01 v02r01, KDB644545 D03 v01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	7
3.7. Table for Class II Change	7
3.8. Table for Supporting Units	8
3.9. Table for Parameters of Test Software Setting	8
3.10. EUT Operation during Test	9
3.11. Duty Cycle	9
3.12. Test Configurations	10
4. TEST RESULT	12
4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement.....	12
4.2. 6dB Spectrum Bandwidth Measurement	19
4.3. Maximum Conducted Output Power Measurement.....	24
4.4. Power Spectral Density Measurement	27
4.5. Radiated Emissions Measurement	34
4.6. Band Edge Emissions Measurement	46
4.7. Frequency Stability Measurement	52
4.8. Antenna Requirements	56
5. LIST OF MEASURING EQUIPMENTS	57
6. MEASUREMENT UNCERTAINTY.....	58
APPENDIX A. TEST PHOTOS	A1 ~ A2


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR440257-08	Rev. 01	Initial issue of report	Apr. 21, 2016

1. VERIFICATION OF COMPLIANCE

Product Name : 2 Port Gigabit Ethernet 11ac/11n Wireless Router
Brand Name : AirTies
Model No. : Air 4820
Applicant : AirTies Wireless Networks
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 02, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.407(a)	26dB Spectrum Bandwidth and 99% Occupied Bandwidth	Complies	-
4.2	15.407(e)	6dB Spectrum Bandwidth	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	2.25 dB
4.4	15.407(a)	Power Spectral Density	Complies	18.47 dB
4.5	15.407(b)	Radiated Emissions	Complies	1.27 dB
4.6	15.407(b)	Band Edge Emissions	Complies	0.21 dB
4.7	15.407(g)	Frequency Stability	Complies	-
4.8	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (4TX, 4RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	IEEE 802.11a: OFDM IEEE 802.11n/ac: see the below table
Data Modulation	IEEE 802.11a/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) IEEE 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	IEEE 802.11a: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table
Frequency Range	5725 ~ 5850 MHz
Channel Number	5 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	<For Non-Beamforming Mode> IEEE 802.11a: 16.50 MHz <For Beamforming Mode> IEEE 802.11ac MCS0/Nss1 (VHT20): 18.32 MHz IEEE 802.11ac MCS0/Nss1 (VHT40): 37.77 MHz IEEE 802.11ac MCS0/Nss1 (VHT80): 75.54 MHz
Maximum Conducted Output Power	<For Non-Beamforming Mode> IEEE 802.11a: 26.52 dBm <For Beamforming Mode> IEEE 802.11ac MCS0/Nss1 (VHT20): 26.70 dBm IEEE 802.11ac MCS0/Nss1 (VHT40): 26.35 dBm IEEE 802.11ac MCS0/Nss1 (VHT80): 22.32 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Communication Mode	☒ IP Based (Load Based) ☐ Frame Based
Beamforming Function	☒ With beamforming for 802.11n/ac. ☐ Without beamforming
Operate Condition	☒ Indoor ☐ Outdoor

Antenna and Band width

Antenna	Four (TX)		
Band width Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	4	MCS 0-31
802.11n (HT40)	4	MCS 0-31
802.11ac (VHT20)	4	MCS 0-9/Nss1-4
802.11ac (VHT40)	4	MCS 0-9/Nss1-4
802.11ac (VHT80)	4	MCS 0-9/Nss1-4

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT supports HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT supports VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:

HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	MOSO	MSP-C1500IC12.0-18W-US	Input: 100-240V ~ 50/60Hz 0.7A max Output: 12.0V, 1.5A
Adapter 2	MOSO	MSP-C1000IC12.0-12B-US	Input: 100-240V ~ 50/60Hz 0.5A max Output: 12.0V, 1A
Adapter 3	MOSO	MSA-C1000IC12.0-12W-US	Input: 100-240V ~ 50/60Hz 0.5A max. Output: 12.0V, 1A
Others			
RJ-45 cable*1: Non-shielded, 1.5m			


3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
					5725 ~ 5850 MHz
1	Airties	Airties#1	Printed Antenna	N/A	1.03
2	Airties	Airties#1	Printed Antenna	N/A	1.03
3	Airties	Airties#1	Printed Antenna	N/A	1.03
4	Airties	Airties#1	Printed Antenna	N/A	1.03

Note: The EUT has four antennas.

Ant.1, Ant.2, Ant.3 and Ant.4 will transmit/receive the same signal simultaneously.

Ant.1, Ant.2, Ant.3 and Ant.4 can be used as transmitting/receiving antennas



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Ant.
Max. Conducted Output Power	11a/BPSK	Band 4	6Mbps	149/157/165	1+2+3+4
Power Spectral Density	11ac VHT20	Band 4	MCS0/Nss1	149/157/165	1+2+3+4
26dB Spectrum Bandwidth & 99% Occupied Bandwidth Measurement	11ac VHT40	Band 4	MCS0/Nss1	151/159	1+2+3+4
6dB Spectrum Bandwidth Measurement	11ac VHT80	Band 4	MCS0/Nss1	155	1+2+3+4
Radiated Emission Above 1GHz Band Edge Emission	11a/BPSK	Band 4	6Mbps	149/157/165	1+2+3+4
	11ac VHT20	Band 4	MCS0/Nss1	149/157/165	1+2+3+4
	11ac VHT40	Band 4	MCS0/Nss1	151/159	1+2+3+4
	11ac VHT80	Band 4	MCS0/Nss1	155	1+2+3+4
Frequency Stability	20 MHz	Band 4	-	157	1
	40 MHz	Band 4	-	151	1
	80 MHz	Band 4	-	155	1

Note 1: VHT20/VHT40 covers HT20/HT40, due to same modulation. The power setting for 802.11n HT20 and HT40 are the same or lower than 802.11ac VHT20 and VHT40.

Note 2: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11n/ac, after evaluating, beamforming mode has been evaluated to be the worst case, so it was selected to test and record in this test report.

3.6. Table for Testing Locations

Test Site Location					
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.				
TEL:	886-3-656-9065				
FAX:	886-3-656-9085				
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR440257-01AA.

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Changing 5GHz Band 4 to "New Rules" from "Old Rules".	1. 26dB Bandwidth and 99% Occupied Bandwidth 2. 6dB Spectrum Bandwidth 3. Maximum Conducted Output Power 4. Power Spectral Density 5. Radiated Emissions (above 1GHz) 6. Band Edge Emissions 7. Frequency Stability
Changing Applicant Address. Applicant Address: Gülbahar Mah. Avni Dilligil Sok. Celik Is Merkezi No 5 meciyekoy ISTANBUL, 34394 Turkey.	After evaluating, it is not necessary to re-test all test items.

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB

<For Non-Beamforming Mode>

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

<For Beamforming Mode>

Support Unit	Brand	Model	FCC ID
Notebook*2	DELL	E4300	DoC
RX Device	AirTies	Air4820	DoC

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

<For Non-Beamforming Mode>

Test Software Version	DOS		
Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	5745 MHz	5785 MHz	5825 MHz
802.11a	17	21	20

<For Beamforming Mode>

Test Software Version	DOS		
Mode	Test Frequency (MHz)		
	NCB: 20MHz		
	5745 MHz	5785 MHz	5825 MHz
802.11ac MCS0/Nss1 VHT20	17	21	19
Mode	NCB: 40MHz		
802.11ac MCS0/Nss1 VHT40	5755 MHz	5795 MHz	
	16	20	
Mode	NCB: 80MHz		
802.11ac MCS0/Nss1 VHT80	5775 MHz		
	16		

3.10. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.

The program was executed as follows:

1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by RX Device and transmit duty cycle no less 98%

3.11. Duty Cycle

<For Non-Beamforming Mode>

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11a	0.564	0.616	91.56%	0.38	1.77


<For Beamforming Mode>

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11ac MCS0/Nss1 VHT20	3.448	3.724	92.59%	0.33	0.29
802.11ac MCS0/Nss1 VHT40	1.673	1.929	86.73%	0.62	0.60
802.11ac MCS0/Nss1 VHT80	4.228	5.036	83.96%	0.76	0.24

3.12. Test Configurations


3.12.1. Radiation Emissions Test Configuration

<For Non-Beamforming Mode>



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	Power cable	No	1.5m

<For Beamforming Mode>



Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	RJ-45 cable	No	1.5m
3	Power cable	No	1.5m

4. TEST RESULT

4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.1.1. Limit

No restriction limits.

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

26dB Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW > RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.1.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission.
Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.1.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.1.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

Temperature	24°C	Humidity	60%
Test Engineer	Clemens Fang		

<For Non-Beamforming Mode>


Mode	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11a	5745 MHz	19.13	15.54
	5785 MHz	27.39	16.50
	5825 MHz	19.74	14.76

<For Beamforming Mode>

Mode	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11ac MCS0/Nss1 VHT20	5745 MHz	24.52	18.15
	5785 MHz	28.78	18.32
	5825 MHz	24.61	18.23
802.11ac MCS0/Nss1 VHT40	5755 MHz	44.06	37.48
	5795 MHz	58.41	37.77
802.11ac MCS0/Nss1 VHT80	5775 MHz	82.90	75.54


<For Non-Beamforming Mode>

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5745 MHz




Date: 14.APR.2016 23:59:38

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5785 MHz



Date: 15.APR.2016 00:00:18


26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5825 MHz



Date: 15.APR.2016 00:01:02


<For Beamforming Mode>

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5745 MHz




Date: 14.APR.2016 23:44:43

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5785 MHz




Date: 14.APR.2016 23:45:27

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5825 MHz




Date: 14.APR.2016 23:46:13

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5755 MHz




Date: 14.APR.2016 23:44:04

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5795 MHz



Date: 14.APR.2016 23:43:17

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 /
Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5775 MHz



Date: 14.APR.2016 23:42:17

4.2. 6dB Spectrum Bandwidth Measurement

4.2.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB789033 D02 v01r02 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (C) Emission Bandwidth.
3. Multiple antenna system was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.2.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24°C	Humidity	60%
Test Engineer	Clemens Fang		

<For Non-Beamforming Mode>

Mode	Frequency	6dB Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11a	5745 MHz	6.32	500	Complies
	5785 MHz	5.62	500	Complies
	5825 MHz	4.81	500	Complies

<For Beamforming Mode>


Mode	Frequency	6dB Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11ac MCS0/Nss1 VHT20	5745 MHz	17.22	500	Complies
	5785 MHz	17.62	500	Complies
	5825 MHz	17.62	500	Complies
802.11ac MCS0/Nss1 VHT40	5755 MHz	36.41	500	Complies
	5795 MHz	36.41	500	Complies
802.11ac MCS0/Nss1 VHT80	5775 MHz	75.07	500	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

<For Non-Beamforming Mode>


6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5825 MHz



Date: 14.APR.2016 23:57:34


<For Beamforming Mode>

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
/ 5745 MHz




Date: 14.APR.2016 23:53:15

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
/ 5755MHz



Date: 14.APR.2016 23:54:15

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5775 MHz



Date: 14.APR.2016 23:55:40

4.3. Maximum Conducted Output Power Measurement

4.3.1. Limit

Frequency Band	Limit
☒ 5.725~5.85 GHz	The maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm). If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	AVERAGE

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01r02 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Output Power

Temperature	24°C	Humidity	60%
Test Engineer	Clemens Fang	Test Date	Apr. 14, 2016 ~ Apr. 15, 2016

<For Non-Beamforming Mode>

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Ant. 4	Total		
802.11a	5745 MHz	16.41	17.21	16.96	16.73	22.86	30.00	Complies
	5785 MHz	19.85	20.57	20.77	20.76	26.52	30.00	Complies
	5825 MHz	19.15	19.77	19.58	19.56	25.54	30.00	Complies

<For Beamforming Mode>

Mode	Frequency	Conducted Power (dBm)					Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Ant. 4	Total		
802.11ac	5745 MHz	16.41	17.63	17.31	17.68	23.31	28.95	Complies
MCS0/Nss1	5785 MHz	19.62	21.15	20.94	20.85	26.70	28.95	Complies
VHT20	5825 MHz	18.14	19.27	19.16	19.35	25.03	28.95	Complies
802.11ac	5755 MHz	15.65	16.94	16.43	16.81	22.51	28.95	Complies
MCS0/Nss1	5795 MHz	19.78	20.83	20.52	20.11	26.35	28.95	Complies
VHT40								
802.11ac	5775 MHz	15.58	16.79	16.25	16.47	22.32	28.95	Complies
MCS0/Nss1								
VHT80								

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.05 \text{ dBi}$, so limit = 30 - (7.05 - 6) = 28.95 dBm.

4.4. Power Spectral Density Measurement

4.4.1. Limit

The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Band		Limit
☒	5.725~5.85 GHz	30 dBm/500kHz

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1000 kHz
VBW	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times
Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.	

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01r02 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements and sum the spectra across the outputs.
4. For 5.725~5.85 GHz, the measured result of PSD level must add $10\log(500\text{kHz}/\text{RBW})$ and the final result should $\leq 30 \text{ dBm}$.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	60%
Test Engineer	Clemens Fang		

<For Non-Beamforming Mode>

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	9.75	-3.01	6.74	28.95	Complies
157	5785 MHz	13.47	-3.01	10.46	28.95	Complies
165	5825 MHz	12.51	-3.01	9.50	28.95	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.05 \text{ dBi}$, so limit = 30 - (7.05 - 6) = 28.95 dBm/500kHz.

<For Beamforming Mode>

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
149	5745 MHz	10.22	-3.01	7.21	28.95	Complies
157	5785 MHz	13.49	-3.01	10.48	28.95	Complies
165	5825 MHz	11.84	-3.01	8.83	28.95	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
151	5755 MHz	6.43	-3.01	3.42	28.95	Complies
159	5795 MHz	10.17	-3.01	7.16	28.95	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4

Channel	Frequency	Power Density (dBm/MHz)	10log(500kHz/RBW) Factor (dB)	Power Density (dBm/500kHz)	Power Density Limit (dBm/500kHz)	Result
155	5775 MHz	3.17	-3.01	0.16	28.95	Complies


Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 7.05 \text{ dBi}$, so limit = 30 - (7.05 - 6) = 28.95 dBm/500kHz.

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


<For Non-Beamforming Mode>

Power Density Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4 / 5785 MHz




<For Beamforming Mode>


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3+ Ant. 4 / 5785 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3+ Ant. 4 / 5795 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3+ Ant. 4 / 5775 MHz



4.5. Radiated Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results for Radiated Emissions (1GHz~40GHz)

<For Non-Beamforming Mode>

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11a CH 149 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11489.70	63.39	74.00	-10.61	42.74	14.82	39.20	33.37	165	132	Peak
2	11492.50	51.66	54.00	-2.34	31.01	14.82	39.20	33.37	165	132	Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11488.50	51.37	54.00	-2.63	30.72	14.82	39.20	33.37	175	361	Average
2	11495.70	63.28	74.00	-10.72	42.63	14.82	39.20	33.37	175	361	Peak

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11a CH 157 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11564.52	67.74	74.00	-6.26	47.04	14.89	39.20	33.39	166	80 Peak	HORIZONTAL
2	11566.04	52.73	54.00	-1.27	32.03	14.89	39.20	33.39	166	80 Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11567.10	66.88	74.00	-7.12	46.18	14.89	39.20	33.39	174	360 Peak	VERTICAL
2	11567.80	52.33	54.00	-1.67	31.63	14.89	39.20	33.39	174	360 Average	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11a CH 165 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11644.60	64.54	74.00	-9.46	43.80	14.95	39.20	33.41	231	81	Peak
2	11645.30	51.00	54.00	-3.00	30.26	14.95	39.20	33.41	231	81	Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	11646.80	65.82	74.00	-8.18	45.08	14.95	39.20	33.41	177	0	Peak
2	11647.32	51.65	54.00	-2.35	30.91	14.95	39.20	33.41	177	0	Average

<For Beamforming Mode>

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11492.46	52.22	54.00	-1.78	31.57	14.82	39.20	33.37	158	147	Average	HORIZONTAL
2	11493.38	64.82	74.00	-9.18	44.17	14.82	39.20	33.37	158	147	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11487.32	63.18	74.00	-10.82	42.53	14.82	39.20	33.37	180	360	Peak	VERTICAL
2	11493.56	50.08	54.00	-3.92	29.43	14.82	39.20	33.37	180	360	Average	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 157 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11567.76	63.81	74.00	-10.19	43.11	14.89	39.20	33.39	161	155	Peak	HORIZONTAL
2	11569.98	49.96	54.00	-4.04	29.26	14.89	39.20	33.39	161	155	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11566.84	63.63	74.00	-10.37	42.93	14.89	39.20	33.39	176	360	Peak	VERTICAL
2	11574.44	52.09	54.00	-1.91	31.39	14.89	39.20	33.39	176	360	Average	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 165 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	11647.90	49.90	54.00	-4.10	29.16	14.95	39.20	33.41	166	70	Average	HORIZONTAL
2	11648.98	62.98	74.00	-11.02	42.24	14.95	39.20	33.41	166	70	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	11645.44	52.47	54.00	-1.53	31.73	14.95	39.20	33.41	178	360	Average	VERTICAL
2	11651.46	62.70	74.00	-11.30	41.93	14.98	39.20	33.41	178	360	Peak	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11505.54	50.20	54.00	-3.80	29.55	14.82	39.20	33.37	156	84 Average	HORIZONTAL
2	11510.36	64.02	74.00	-9.98	43.38	14.82	39.20	33.38	156	84 Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11506.02	65.04	74.00	-8.96	44.39	14.82	39.20	33.37	173	354 Peak	VERTICAL
2	11507.70	51.63	54.00	-2.37	30.98	14.82	39.20	33.37	173	354 Average	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 159 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	11586.04	49.90	54.00	-4.10	29.18	14.92	39.20	33.40	165	179	Average	HORIZONTAL
2	11587.32	63.43	74.00	-10.57	42.71	14.92	39.20	33.40	165	179	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	11589.56	50.07	54.00	-3.93	29.35	14.92	39.20	33.40	177	360	Average	VERTICAL
2	11589.60	62.97	74.00	-11.03	42.25	14.92	39.20	33.40	177	360	Peak	VERTICAL

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11550.66	62.99	74.00	-11.01	42.29	14.89	39.20	33.39	161	89 Peak	HORIZONTAL
2	11552.02	49.63	54.00	-4.37	28.93	14.89	39.20	33.39	161	89 Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11552.52	63.03	74.00	-10.97	42.33	14.89	39.20	33.39	174	360 Peak	VERTICAL
2	11553.64	49.71	54.00	-4.29	29.01	14.89	39.20	33.39	174	360 Average	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.725-5.85 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.6.3. Test Procedures

The test procedure is the same as section 4.5.3.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For Non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

<For Non-Beamforming Mode>

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11a CH 149, 157, 165 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Channel 149

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5713.00	64.35	68.20	-3.85	52.27	10.78	34.43	33.13	226	345	Peak	VERTICAL
2	5723.00	77.86	78.20	-0.34	65.78	10.77	34.44	33.13	226	345	Peak	VERTICAL
3	5737.80	103.56			91.49	10.77	34.44	33.14	226	345	Average	VERTICAL
4	5738.20	117.32			105.25	10.77	34.44	33.14	226	345	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5711.00	62.24	68.20	-5.96	50.16	10.78	34.43	33.13	214	211	Peak	HORIZONTAL
2	5723.00	63.43	78.20	-14.77	51.35	10.77	34.44	33.13	214	211	Peak	HORIZONTAL
3	5792.60	119.01			106.95	10.73	34.48	33.15	214	211	Peak	HORIZONTAL
4	5793.00	109.36			97.30	10.73	34.48	33.15	214	211	Average	HORIZONTAL
5	5850.00	64.47	78.20	-13.73	52.23	10.90	34.51	33.17	214	211	Peak	HORIZONTAL
6	5860.80	63.33	68.20	-4.87	51.03	10.96	34.52	33.18	214	211	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit Line	Over Limit	Read Level	CableLoss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5832.20	108.13			95.95	10.85	34.50	33.17	264	183	Average	VERTICAL
2	5832.20	118.76			106.58	10.85	34.50	33.17	264	183	Peak	VERTICAL
3	5852.60	76.99	78.20	-1.21	64.75	10.90	34.51	33.17	264	183	Peak	VERTICAL
4	5860.60	67.99	68.20	-0.21	55.69	10.96	34.52	33.18	264	183	Peak	VERTICAL

Item 1, 2 are the fundamental frequency at 5825 MHz.

<For Beamforming Mode>

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149, 157, 165 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Channel 149

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5711.40	64.53	68.20	-3.67	52.45	10.78	34.43	33.13	205	317 Peak	HORIZONTAL
2	5725.00	77.88	78.20	-0.32	65.80	10.77	34.44	33.13	205	317 Peak	HORIZONTAL
3	5738.20	113.99			101.92	10.77	34.44	33.14	205	317 Peak	HORIZONTAL
4	5751.80	102.61			90.54	10.76	34.45	33.14	205	317 Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5745 MHz.

Channel 157

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5711.40	60.61	68.20	-7.59	48.53	10.78	34.43	33.13	221	47 Peak	VERTICAL
2	5724.20	62.13	78.20	-16.07	50.05	10.77	34.44	33.13	221	47 Peak	VERTICAL
3	5787.40	104.31			92.25	10.74	34.47	33.15	221	47 Average	VERTICAL
4	5787.40	115.28			103.22	10.74	34.47	33.15	221	47 Peak	VERTICAL
5	5852.00	62.33	78.20	-15.87	50.09	10.90	34.51	33.17	221	47 Peak	VERTICAL
6	5868.20	61.63	68.20	-6.57	49.33	10.96	34.52	33.18	221	47 Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5785 MHz.

Channel 165

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	5823.00	116.49			104.31	10.85	34.50	33.17	202	311 Peak	HORIZONTAL
2	5831.80	105.52			93.34	10.85	34.50	33.17	202	311 Average	HORIZONTAL
3	5850.00	77.86	78.20	-0.34	65.62	10.90	34.51	33.17	202	311 Peak	HORIZONTAL
4	5863.00	67.61	68.20	-0.59	55.31	10.96	34.52	33.18	202	311 Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 5825 MHz.

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151, 159 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Channel 151

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5713.00	53.28	54.00	-0.72	41.20	10.78	34.43	33.13	206	294	Average	HORIZONTAL
2	5714.00	71.28	74.00	-2.72	59.20	10.78	34.43	33.13	206	294	Peak	HORIZONTAL
3	5725.00	77.78	78.20	-0.42	65.70	10.77	34.44	33.13	206	294	Peak	HORIZONTAL
4	5739.00	103.03			90.96	10.76	34.45	33.14	206	294	Average	HORIZONTAL
5	5739.00	113.91			101.84	10.76	34.45	33.14	206	294	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 5755 MHz.

Channel 159

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5706.00	63.29	74.00	-10.71	51.21	10.78	34.43	33.13	207	301	Peak	HORIZONTAL
2	5715.00	50.69	54.00	-3.31	38.61	10.78	34.43	33.13	207	301	Average	HORIZONTAL
3	5717.00	65.89	78.20	-12.31	53.81	10.78	34.43	33.13	207	301	Peak	HORIZONTAL
4	5778.00	102.89			90.83	10.74	34.47	33.15	207	301	Average	HORIZONTAL
5	5782.00	115.76			103.70	10.74	34.47	33.15	207	301	Peak	HORIZONTAL
6	5850.00	74.72	78.20	-3.48	62.48	10.90	34.51	33.17	207	301	Peak	HORIZONTAL
7	5860.00	53.42	54.00	-0.58	41.12	10.96	34.52	33.18	207	301	Average	HORIZONTAL
8	5872.00	69.20	74.00	-4.80	56.90	10.96	34.52	33.18	207	301	Peak	HORIZONTAL

Item 4, 5 are the fundamental frequency at 5795 MHz.

Temperature	22°C	Humidity	54%
Test Engineer	Brian Sun	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Ant. 1 + Ant. 2 + Ant. 3 + Ant. 4
Test Date	Apr. 10, 2016		

Channel 155

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	5715.00	51.95	54.00	-2.05	39.87	10.78	34.43	33.13	237	291	Average	HORIZONTAL
2	5715.00	67.48	74.00	-6.52	55.40	10.78	34.43	33.13	237	291	Peak	HORIZONTAL
3	5717.00	70.76	78.20	-7.44	58.68	10.78	34.43	33.13	237	291	Peak	HORIZONTAL
4	5782.00	111.40			99.34	10.74	34.47	33.15	237	291	Peak	HORIZONTAL
5	5809.00	95.42			83.30	10.79	34.49	33.16	237	291	Average	HORIZONTAL
6	5854.00	71.03	78.20	-7.17	58.79	10.90	34.51	33.17	237	291	Peak	HORIZONTAL
7	5860.00	53.51	54.00	-0.49	41.21	10.96	34.52	33.18	237	291	Average	HORIZONTAL
8	5868.00	70.50	74.00	-3.50	58.20	10.96	34.52	33.18	237	291	Peak	HORIZONTAL

Item 4, 5 are the fundamental frequency at 5775 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.7. Frequency Stability Measurement

4.7.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.7.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Sweep Time	Auto

4.7.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
7. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
8. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.7.4. Test Setup Layout



4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.7.7. Test Result of Frequency Stability

Temperature	24°C	Humidity	60%
Test Engineer	Clemens Fang	Test Date	Apr. 14, 2016 ~ Apr. 15, 2016

Mode: 20 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5785 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5784.9969	5784.9955	5784.9937	5784.9916
110.00	5784.9957	5784.9944	5784.9928	5784.9909
93.50	5784.9943	5784.9932	5784.9920	5784.9898
Max. Deviation (MHz)	0.0057	0.0068	0.0080	0.0102
Max. Deviation (ppm)	0.99	1.18	1.39	1.77
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5785 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5784.9982	5784.9970	5784.9951	5784.9929
10	5784.9969	5784.9956	5784.9941	5784.9923
20	5784.9957	5784.9944	5784.9928	5784.9909
30	5784.9943	5784.9932	5784.9918	5784.9902
40	5784.9927	5784.9912	5784.9896	5784.9876
Max. Deviation (MHz)	0.0090	0.0102	0.0117	0.0144
Max. Deviation (ppm)	1.56	1.77	2.03	2.50
Result	Complies			

Mode: 40 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5755 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5755.0008	5754.9994	5754.9976	5754.9955
110.00	5754.9996	5754.9983	5754.9967	5754.9948
93.50	5754.9982	5754.9971	5754.9959	5754.9937
Max. Deviation (MHz)	0.0018	0.0029	0.0041	0.0063
Max. Deviation (ppm)	0.32	0.51	0.72	1.10
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5755 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5755.0021	5755.0009	5754.9990	5754.9968
10	5755.0008	5754.9995	5754.9980	5754.9962
20	5754.9996	5754.9983	5754.9967	5754.9948
30	5754.9982	5754.9971	5754.9957	5754.9941
40	5754.9966	5754.9951	5754.9935	5754.9915
Max. Deviation (MHz)	0.0068	0.0063	0.0078	0.0105
Max. Deviation (ppm)	1.18	1.10	1.36	1.83
Result	Complies			

Mode: 80 MHz / Ant. 1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)			
(V)	5775 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
126.50	5775.0060	5775.0046	5775.0028	5775.0007
110.00	5775.0048	5775.0035	5775.0019	5775.0000
93.50	5775.0034	5775.0023	5775.0011	5774.9989
Max. Deviation (MHz)	0.0060	0.0046	0.0028	0.0011
Max. Deviation (ppm)	1.04	0.79	0.48	0.19
Result	Complies			

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)			
(°C)	5775 MHz			
	0 Minute	2 Minute	5 Minute	10 Minute
0	5775.0073	5775.0061	5775.0042	5775.0020
10	5775.0060	5775.0047	5775.0032	5775.0014
20	5775.0048	5775.0035	5775.0019	5775.0000
30	5775.0034	5775.0023	5775.0009	5774.9993
40	5775.0018	5775.0003	5774.9987	5774.9967
Max. Deviation (MHz)	0.0120	0.0109	0.0087	0.0059
Max. Deviation (ppm)	2.07	1.88	1.50	1.02
Result	Complies			

4.8. Antenna Requirements

4.8.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.8.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jul. 21, 2015	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 18, 2016	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 13, 2015	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-17	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-1	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G-2	N/A	18GHz ~ 40 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
Test Software	Audix	E3	6.2009-10-7	N/A	N/A	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec. 09, 2015	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-6	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-7	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-8	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-9	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz – 26.5 GHz	Nov. 02, 2015	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 02, 2015	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%