



# MPE ESTIMATION

FCC ID: 2AJ9T-NG-C4100A

## 1, Limit for General Population/ Uncontrolled Exposures

| Frequency        | Power density (mW/ cm <sup>2</sup> ) | Averaging time(minutes) |
|------------------|--------------------------------------|-------------------------|
| 300MHz----1.5GHz | F/1500                               | 30                      |
| 1.5GHz---100GHz  | 1.0                                  | 30                      |

Note: F= Frequency in MHz

## 2, Estimation Result

| Mode     | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (numerical) | MPE (mW/cm <sup>2</sup> ) |
|----------|--------------------------|--------------------|-----------------------|-------------------|--------------------------|---------------------------|
| 2.4GWIFI | 15.56                    | 15±1(16)           | 39.81                 | 4                 | 2.5119                   | 0.01990                   |

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2111084260-E**, antenna gain=4dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01990 mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----