



Date: 24.JUN.2019 10:42:10





Test Model

Band-edge Conducted Emissions



Date: 24.JUN.2019 10:41:49





Date: 24.JUN.2019 10:31:03



Date: 24.JUN.2019 10:31:50





Date: 24.JUN.2019 10:31:31







Date: 24.JUN.2019 10:34:44







Date: 24.JUN.2019 10:36:04



Date: 24.JUN.2019 10:35:47









Date: 24.JUN.2019 10:43:14



Band-edge Conducted Emissions

Date: 24.JUN.2019 10:43:44

Test Model

9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

 $VBW \geq RBW$

Sweep = auto Detector function = peak



Trace = max hold For Below 1GHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 100 kHz for VBW > RBW Sweep = auto Detector function = peak Trace = \max hold For Below 30MHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 9kHz $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold For Below 150KHz: The EUT was placed on a turn table which is 0.8m above ground plane. Maximum procedure was performed on the highest emissions to ensure EUT compliance. Span = wide enough to fully capture the emission being measured RBW = 200Hz $VBW \ge RBW$ Sweep = auto Detector function = peak Trace = max hold Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT. measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the

measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	26°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

Freq.	Ant.Pol.	Emis Level(d	sion BuV/m)	Limit 3m	(dBuV/m)	Over(dB)		
(IVIHZ)	H/V	PK È	ÁÝ	PK	AV	PK	AV	

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor



Spurious Emission below 1GHz (30MHz to 1GHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		46.1577	40.05	-11.28	28.77	40.00	-11.23	QP			
2		64.3201	34.49	-13.42	21.07	40.00	-18.93	QP			
3		86.9210	37.30	-15.71	21.59	40.00	-18.41	QP			
4	*	235.4032	45.34	-10.37	34.97	46.00	-11.03	QP			
5		408.7667	28.89	-5.79	23.10	46.00	-22.90	QP			
6		974.0436	29.23	3.37	32.60	54.00	-21.40	QP			





No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
-		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.7174	36.36	-14.16	22.20	40.00	-17.80	QP			
2		47.3670	30.52	-11.21	19.31	40.00	-20.69	QP			
3		97.4133	35.03	-13.05	21.98	43.50	-21.52	QP			
4		176.1914	36.59	-13.87	22.72	43.50	-20.78	QP			
5	*	235.1970	48.53	-10.38	38.15	46.00	-7.85	QP			
6		947.0990	30.03	2.90	32.93	46.00	-13.07	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	0
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		33.5624	30.62	-13.29	17.33	40.00	-22.67	QP			
2		46.5234	30.64	-11.26	19.38	40.00	-20.62	QP			
3		101.2885	30.55	-12.55	18.00	43.50	-25.50	QP			
4		175.8057	37.35	-13.91	23.44	43.50	-20.06	QP			
5	*	235.4033	48.56	-10.37	38.19	46.00	-7.81	QP			
6		320.0772	34.15	-7.93	26.22	46.00	-19.78	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	45.9358	41.85	-11.29	30.56	40.00	-9.44	QP			
2		95.5107	35.68	-13.35	22.33	43.50	-21.17	QP			
3	1	169.0054	39.17	-14.33	24.84	43.50	-18.66	QP			
4		231.3120	40.74	-10.49	30.25	46.00	-15.75	QP			
5		407.8720	29.82	-5.80	24.02	46.00	-21.98	QP			
6	9	979.6097	28.66	3.50	32.16	54.00	-21.84	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	6
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	46.4826	41.84	-11.27	30.57	40.00	-9.43	QP			
2		64.0670	34.61	-13.39	21.22	40.00	-18.78	QP			
3		96.3094	36.19	-13.23	22.96	43.50	-20.54	QP			
4		171.9946	38.43	-14.18	24.25	43.50	-19.25	QP			
5	1	235.1970	43.30	-10.38	32.92	46.00	-13.08	QP			
6	Ì	738.3648	28.81	-0.38	28.43	46.00	-17.57	QP			





- N I	-	k	
1.71	0	ю	
	0	Ĵ	

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
3		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		33.7838	30.48	-13.17	17.31	40.00	-22.69	QP			
2		46.8714	29.95	-11.24	18.71	40.00	-21.29	QP			
3		96.6901	31.39	-13.16	18.23	43.50	-25.27	QP			
4		178.6018	32.58	-13.65	18.93	43.50	-24.57	QP			
5	*	237.4760	45.88	-10.28	35.60	46.00	-10.40	QP			
6	1	883.3405	28.27	1.68	29.95	46.00	-16.05	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
2		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		33.8431	30.64	-13.14	17.50	40.00	-22.50	QP			
2		46.8714	29.95	-11.24	18.71	40.00	-21.29	QP			
3		96.6901	31.39	-13.16	18.23	43.50	-25.27	QP			
4		177.7427	33.93	-13.74	20.19	43.50	-23.31	QP			
5	*	236.3338	47.53	-10.33	37.20	46.00	-8.80	QP			
6	1	938.8326	30.23	2.77	33.00	46.00	-13.00	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	45.7550	41.68	-11.30	30.38	40.00	-9.62	QP			
2		84.4054	38.04	-16.46	21.58	40.00	-18.42	QP			
3		96.2250	34.99	-13.24	21.75	43.50	-21.75	QP			
4	, E	175.0368	37.98	-13.97	24.01	43.50	-19.49	QP			
5		233.3487	44.83	-10.44	34.39	46.00	-11.61	QP			
6	į	788.1967	29.58	0.14	29.72	46.00	-16.28	QP			





No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over dB		Antenna Height	Table Degree	
			dBuV	dB	dBuV/m	dBuV/m		Detector	cm	degree	Comment
1	*	45.7550	41.68	-11.30	30.38	40.00	-9.62	QP			
2		95.0096	35.37	-13.44	21.93	43.50	-21.57	QP			
3		232.7358	45.65	-10.46	35.19	46.00	-10.81	QP			
4		470.5232	29.76	-5.17	24.59	46.00	-21.41	QP			
5	22	739.9848	29.21	-0.35	28.86	46.00	-17.14	QP			
6		985.6396	28.80	3.65	32.45	54.00	-21.55	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	5
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		47.2426	28.72	-11.22	17.50	40.00	-22.50	QP			
2		99.9653	28.70	-12.65	16.05	43.50	-27.45	QP			
3	*	237.4760	47.74	-10.28	37.46	46.00	-8.54	QP			
4		324.3140	30.36	-7.76	22.60	46.00	-23.40	QP			
5		665.5117	29.69	-1.51	28.18	46.00	-17.82	QP			
6		995.6264	28.59	3.87	32.46	54.00	-21.54	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		34.3814	31.41	-13.15	18.26	40.00	-21.74	QP			
2		47.2426	29.73	-11.22	18.51	40.00	-21.49	QP			
3		101.4218	29.85	-12.54	17.31	43.50	-26.19	QP			
4		172.7502	37.16	-14.13	23.03	43.50	-20.47	QP			
5	*	237.8927	46.74	-10.26	36.48	46.00	-9.52	QP			
6	5	865.3290	28.60	1.31	29.91	46.00	-16.09	QP			





No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
-		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		46.2185	40.77	-11.28	29.49	40.00	-10.51	QP			
2		84.2576	36.98	-16.47	20.51	40.00	-19.49	QP			
3		179.7800	35.65	-13.55	22.10	43.50	-21.40	QP			
4	*	236.0232	47.07	-10.35	36.72	46.00	-9.28	QP			
5		618.8081	30.26	-1.92	28.34	46.00	-17.66	QP			
6		751.7540	30.56	-0.20	30.36	46.00	-15.64	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	45.8754	41.37	-11.30	30.07	40.00	-9.93	QP			
2		64.1231	34.84	-13.40	21.44	40.00	-18.56	QP			
3		87.5710	36.64	-15.48	21.16	40.00	-18.84	QP			
4	2	236.3338	45.47	-10.33	35.14	46.00	-10.86	QP			
5	Į	550.4652	28.42	-3.86	24.56	46.00	-21.44	QP			
6	(928.1941	28.72	2.62	31.34	46.00	-14.66	QP			





No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		45.9761	30.08	-11.29	18.79	40.00	-21.21	QP			
2		98.8760	30.03	-12.83	17.20	43.50	-26.30	QP			
3		175.2671	36.59	-13.95	22.64	43.50	-20.86	QP			
4	*	238.3102	47.44	-10.25	37.19	46.00	-8.81	QP			
5		397.1110	29.54	-6.12	23.42	46.00	-22.58	QP			
6	1	854.3992	29.07	1.05	30.12	46.00	-15.88	QP			





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		44.6064	28.81	-11.36	17.45	40.00	-22.55	QP			
2		98.7460	27.71	-12.85	14.86	43.50	-28.64	QP			
3		174.1184	37.08	-14.04	23.04	43.50	-20.46	QP			
4	*	237.0600	47.41	-10.30	37.11	46.00	-8.89	QP			
5		601.1630	29.39	-2.14	27.25	46.00	-18.75	QP			
6		979.1804	28.52	3.49	32.01	54.00	-21.99	QP			6