



FCC RF Test Report

APPLICANT : Yulong Computer Telecommunication
Scientific (Shenzhen) Co., Ltd
EQUIPMENT : Smartphone
BRAND NAME : Coolpad
MODEL NAME : Coolpad 3701A
FCC ID : R38YL3701A
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 24, 2017 and testing was completed on Jun. 14, 2017. We, SPORTON International (ShenZhen) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON International (ShenZhen) INC., the test report shall not be reproduced except in full.

Prepared by: Eric Shih / Manager

Approved by: Jones Tsai / Manager



SPORTON International (ShenZhen) INC.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City,
Guangdong Province, China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example	10
3 TEST RESULT	11
3.1 6dB Bandwidth Measurement	11
3.2 Output Power Measurement	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	29
3.6 AC Conducted Emission Measurement	33
3.7 Antenna Requirements	37
4 LIST OF MEASURING EQUIPMENT	38
5 UNCERTAINTY OF EVALUATION	39
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR742403C	Rev. 01	Initial issue of report	Jul. 12, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.71 dB at 4824.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 7.77 dB at 0.160 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Coolpad Information Harbor, High-tech Industrial Park (North), Nanshan District, Shenzhen, P.R.C.

1.2 Manufacturer

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Coolpad Information Harbor, High-tech Industrial Park (North), Nanshan District, Shenzhen, P.R.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	Coolpad
Model Name	Coolpad 3701A
FCC ID	R38YL3701A
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA, HSPA+ (16QAM uplink is not supported)/LTE WLAN2.4G 802.11b/g/n HT20/HT40 WLAN5G 802.11a/n HT20/HT40 WLAN5G 802.11ac VHT20/VHT40/VHT80 Bluetooth V2.1 + EDR/ Bluetooth V4.0 LE
IMEI Code	Conducted: 861273030009071 Conduction: 861273030007810 Radiation: 861273030007877
HW Version	V2
SW Version	117.00.170706.3701A-TMO
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 18.50 dBm (0.0708 W) 802.11g : 24.36 dBm (0.2729 W) 802.11n HT20 : 23.96 dBm (0.2489 W) 802.11n HT40 : 24.26 dBm (0.2667 W)
Antenna Type / Gain	IFA Antenna with gain 2.10 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON International (ShenZhen) INC.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan District, Shenzhen City, Guangdong Province, China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON International (ShenZhen) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH03-SZ	565805

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable(Charging from Adapter)
Remark: For Radiated Test Cases, the tests were performed with Adapter, Earphone, and USB Cable.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8m
4.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
5.	Earphone	Coolpad	N/A	N/A	Unshielded, 1.0m	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 5 + 10 = 15 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng







Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11b Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng

WLAN 802.11b Channel 11


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz







Spurious Emission 2GHz~25GHz





Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng


WLAN 802.11g Channel 01**100kHz PSD reference Level****Low Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11g Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz







Spurious Emission 2GHz~25GHz





Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng


WLAN 802.11g Channel 11**100kHz PSD reference Level****High Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**




Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Sam Zheng

WLAN 802.11n HT20 Channel 01


100kHz PSD reference Level




Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz







Spurious Emission 2GHz~25GHz





Test Mode :	802.11n HT20	Temperature :	24~26℃
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Sam Zheng


WLAN 802.11n HT20 Channel 11**100kHz PSD reference Level****High Channel Plot****Spurious Emission 30MHz~3GHz****Spurious Emission 2GHz~25GHz**



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	03	Test Engineer :	Sam Zheng


WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level




Date: 27.MAY.2017 10:30:34

Low Channel Plot




Date: 27.MAY.2017 10:31:17

Spurious Emission 30MHz~3GHz



Date: 27.MAY.2017 10:36:03

Spurious Emission 2GHz~25GHz




Date: 27.MAY.2017 10:35:02




Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Sam Zheng

WLAN 802.11n HT40 Channel 06


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Sam Zheng

WLAN 802.11n HT40 Channel 09


100kHz PSD reference Level




High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~25℃
Test Engineer :	Tao Cheng	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable(Charging from Adapter)		




Site : CO01-SZ
Condition: FCC 15E QP LISN_20170301_L LINE

Mode : Mode 1
IMEI : 861273030007810

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	40.72	-14.97	55.69	30.30	0.03	10.39	Average
2 *	0.16	57.92	-7.77	65.69	47.50	0.03	10.39	QP
3	0.23	26.85	-25.50	52.35	16.60	0.03	10.22	Average
4	0.23	45.95	-16.40	62.35	35.70	0.03	10.22	QP
5	0.31	25.05	-25.05	50.10	14.80	0.03	10.22	Average
6	0.31	42.85	-17.25	60.10	32.60	0.03	10.22	QP
7	0.42	30.02	-17.40	47.42	19.80	0.03	10.19	Average
8	0.42	43.82	-13.60	57.42	33.60	0.03	10.19	QP
9	0.57	26.49	-19.51	46.00	16.30	0.02	10.17	Average
10	0.57	38.69	-17.31	56.00	28.50	0.02	10.17	QP
11	0.69	26.59	-19.41	46.00	16.40	0.02	10.17	Average
12	0.69	38.89	-17.11	56.00	28.70	0.02	10.17	QP
13	0.93	25.51	-20.49	46.00	15.30	0.06	10.15	Average
14	0.93	37.41	-18.59	56.00	27.20	0.06	10.15	QP
15	15.31	31.09	-18.91	50.00	20.19	0.56	10.34	Average
16	15.31	45.09	-14.91	60.00	34.19	0.56	10.34	QP
17	17.47	32.71	-17.29	50.00	21.30	0.92	10.49	Average
18	17.47	46.01	-13.99	60.00	34.60	0.92	10.49	QP
19	21.04	35.45	-14.55	50.00	23.50	1.32	10.63	Average
20	21.04	45.85	-14.15	60.00	33.90	1.32	10.63	QP



Test Mode :	Mode 1	Temperature :	22~25°C
Test Engineer :	Tao Cheng	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable(Charging from Adapter)		



Site : C001-SZ
 Condition: FCC 15C_QP LISN_20170301_N NEUTRAL
 Project : (FR) 742403
 Mode : Mode 1
 IMEI : 861273030007810

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.15	42.43	-13.39	55.82	32.00	0.03	10.40	Average
2	0.15	50.33	-15.49	65.82	39.90	0.03	10.40	QP
3	0.30	32.25	-17.94	50.19	22.00	0.03	10.22	Average
4	0.30	43.65	-16.54	60.19	33.40	0.03	10.22	QP
5	0.54	30.10	-15.90	46.00	19.90	0.02	10.18	Average
6	0.54	40.40	-15.60	56.00	30.20	0.02	10.18	QP
7	0.81	29.59	-16.41	46.00	19.40	0.03	10.16	Average
8	0.81	38.69	-17.31	56.00	28.50	0.03	10.16	QP
9	1.28	31.20	-14.80	46.00	21.00	0.05	10.15	Average
10	1.28	40.10	-15.90	56.00	29.90	0.05	10.15	QP
11	1.62	30.51	-15.49	46.00	20.30	0.05	10.16	Average
12	1.62	39.01	-16.99	56.00	28.80	0.05	10.16	QP
13	2.61	29.43	-16.57	46.00	19.20	0.04	10.19	Average
14	2.61	38.53	-17.47	56.00	28.30	0.04	10.19	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the Antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr.20.2017	May 27, 2017~ Jun. 14, 2017	Apr.19.2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	May 27, 2017~ Jun. 14, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	May 27, 2017~ Jun. 14, 2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY544500 83	20Hz~8.4GHz	Apr. 20, 2017	Jun. 06, 2017~ Jun. 13, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 46	10Hz~44GHz;	Apr. 20, 2017	Jun. 06, 2017~ Jun. 13, 2017	Apr. 19, 2018	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Jun. 06, 2017~ Jun. 13, 2017	May 13, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 14, 2017	Jun. 06, 2017~ Jun. 13, 2017	May 13, 2018	Radiation (03CH03-SZ)
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-128 5	1GHz~18GHz	Jan. 12, 2017	Jun. 06, 2017~ Jun. 13, 2017	Jan. 11, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 10, 2016	Jun. 06, 2017~ Jun. 13, 2017	Aug. 09, 2017	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 11, 2016	Jun. 06, 2017~ Jun. 13, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Jun. 06, 2017~ Jun. 13, 2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY395013 02	500MHz~26.5G Hz	Jan. 06, 2017	Jun. 06, 2017~ Jun. 13, 2017	Jan. 05, 2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001 985	N/A	NCR	Jun. 06, 2017~ Jun. 13, 2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jun. 06, 2017~ Jun. 13, 2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jun. 06, 2017~ Jun. 13, 2017	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	Jun. 12, 2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	Jun. 12, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	Jun. 12, 2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000 891	100Vac~250Vac	Jul. 16, 2016	Jun. 12, 2017	Jul. 15, 2017	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
--	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
--	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
--	-------



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Sam Zheng	Temperature:	24~26	°C
Test Date:	2017/5/27~2017/6/14	Relative Humidity:	50~53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.49	8.03	0.50	Pass
11b	1Mbps	1	6	2437	13.49	8.99	0.50	Pass
11b	1Mbps	1	11	2462	13.54	8.07	0.50	Pass
11g	6Mbps	1	1	2412	18.88	16.36	0.50	Pass
11g	6Mbps	1	6	2437	18.78	16.36	0.50	Pass
11g	6Mbps	1	11	2462	18.83	16.34	0.50	Pass
HT20	MCS0	1	1	2412	19.58	17.58	0.50	Pass
HT20	MCS0	1	6	2437	19.58	17.60	0.50	Pass
HT20	MCS0	1	11	2462	19.58	17.58	0.50	Pass
HT40	MCS0	1	3	2422	36.76	35.56	0.50	Pass
HT40	MCS0	1	6	2437	36.66	35.17	0.50	Pass
HT40	MCS0	1	9	2452	37.06	35.49	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	18.50	30.00	2.10	20.60	36.00	Pass
11b	1Mbps	1	6	2437	18.25	30.00	2.10	20.35	36.00	Pass
11b	1Mbps	1	11	2462	18.22	30.00	2.10	20.32	36.00	Pass
11g	6Mbps	1	1	2412	24.36	30.00	2.10	26.46	36.00	Pass
11g	6Mbps	1	6	2437	24.30	30.00	2.10	26.40	36.00	Pass
11g	6Mbps	1	11	2462	24.14	30.00	2.10	26.24	36.00	Pass
HT20	MCS0	1	1	2412	23.96	30.00	2.10	26.06	36.00	Pass
HT20	MCS0	1	6	2437	23.90	30.00	2.10	26.00	36.00	Pass
HT20	MCS0	1	11	2462	23.46	30.00	2.10	25.56	36.00	Pass
HT40	MCS0	1	3	2422	24.18	30.00	2.10	26.28	36.00	Pass
HT40	MCS0	1	6	2437	24.26	30.00	2.10	26.36	36.00	Pass
HT40	MCS0	1	9	2452	23.86	30.00	2.10	25.96	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.11	16.13
11b	1Mbps	1	6	2437	0.11	15.78
11b	1Mbps	1	11	2462	0.11	15.67
11g	6Mbps	1	1	2412	0.60	16.10
11g	6Mbps	1	6	2437	0.60	16.06
11g	6Mbps	1	11	2462	0.60	15.97
HT20	MCS0	1	1	2412	0.62	15.15
HT20	MCS0	1	6	2437	0.62	15.08
HT20	MCS0	1	11	2462	0.62	14.96
HT40	MCS0	1	3	2422	1.18	15.14
HT40	MCS0	1	6	2437	1.18	15.11
HT40	MCS0	1	9	2452	1.18	15.05

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-2.63	2.10	8.00	Pass
11b	1Mbps	1	6	2437	-2.50	2.10	8.00	Pass
11b	1Mbps	1	11	2462	-4.35	2.10	8.00	Pass
11g	6Mbps	1	1	2412	-8.78	2.10	8.00	Pass
11g	6Mbps	1	6	2437	-8.56	2.10	8.00	Pass
11g	6Mbps	1	11	2462	-8.80	2.10	8.00	Pass
HT20	MCS0	1	1	2412	-9.44	2.10	8.00	Pass
HT20	MCS0	1	6	2437	-10.27	2.10	8.00	Pass
HT20	MCS0	1	11	2462	-10.76	2.10	8.00	Pass
HT40	MCS0	1	3	2422	-13.39	2.10	8.00	Pass
HT40	MCS0	1	6	2437	-12.99	2.10	8.00	Pass
HT40	MCS0	1	9	2452	-13.46	2.10	8.00	Pass



Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2339.715	56.92	-17.08	74	52.52	31.01	6.65	33.26	173	143	P	H
		2386.23	39.26	-14.74	54	34.28	31.38	6.81	33.21	173	143	A	H
	*	2412	102.12	-	-	97	31.5	6.81	33.19	173	143	P	H
	*	2412	100.23	-	-	95.11	31.5	6.81	33.19	173	143	A	H
		2339.19	54.17	-19.83	74	49.77	31.01	6.65	33.26	250	98	P	V
		2385.18	38.66	-15.34	54	33.82	31.26	6.81	33.23	250	98	A	V
	*	2412	102.12	-	-	97	31.5	6.81	33.19	250	98	P	V
	*	2412	100.28	-	-	95.16	31.5	6.81	33.19	250	98	A	V
802.11b CH 06 2437MHz		2339.68	57.73	-16.27	74	53.33	31.01	6.65	33.26	188	32	P	H
		2380.56	39.06	-14.94	54	34.3	31.26	6.73	33.23	188	32	A	H
	*	2437	101.76	-	-	96.31	31.74	6.86	33.15	188	32	P	H
	*	2437	99.88	-	-	94.43	31.74	6.86	33.15	188	32	A	H
		2492.44	46.82	-27.18	74	40.91	32.1	6.91	33.1	188	32	P	H
		2492.3	37.24	-16.76	54	31.33	32.1	6.91	33.1	188	32	A	H
		2339.96	57.54	-16.46	74	53.14	31.01	6.65	33.26	212	99	P	V
		2380.7	38.6	-15.4	54	33.84	31.26	6.73	33.23	212	99	A	V
	*	2437	101.63	-	-	96.18	31.74	6.86	33.15	212	99	P	V
	*	2437	99.78	-	-	94.33	31.74	6.86	33.15	212	99	A	V
		2494.68	46.43	-27.57	74	40.52	32.1	6.91	33.1	212	99	P	V
		2493.56	35.75	-18.25	54	29.84	32.1	6.91	33.1	212	99	A	V



802.11b CH 11 2462MHz	*	2462	100.61	-	-	95.03	31.86	6.86	33.14	203	29	P	H
	*	2462	98.77	-	-	93.19	31.86	6.86	33.14	203	29	A	H
		2488.12	47.6	-26.4	74	41.69	32.1	6.91	33.1	203	29	P	H
		2487.44	39.02	-14.98	54	33.25	31.98	6.91	33.12	203	29	A	H
	*	2462	100.78	-	-	95.2	31.86	6.86	33.14	250	89	P	V
	*	2462	98.94	-	-	93.36	31.86	6.86	33.14	250	89	A	V
		2487.56	47.82	-26.18	74	41.91	32.1	6.91	33.1	250	89	P	V
		2487.52	38.73	-15.27	54	32.82	32.1	6.91	33.1	250	89	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	52.72	-21.28	74	65.13	33.3	10.89	56.6	185	255	P	H
		4824	52.29	-1.71	54	64.7	33.3	10.89	56.6	185	255	A	H
		4824	49.6	-24.4	74	62.01	33.3	10.89	56.6	185	255	P	V
802.11b CH 06 2437MHz		4874	51.72	-22.28	74	64.38	33.33	10.92	56.91	165	106	P	H
		4874	51.25	-2.75	54	63.91	33.33	10.92	56.91	165	106	A	H
		7311	50.34	-23.66	74	59.65	35.4	13.29	58	174	100	P	H
		4874	49.98	-24.02	74	62.64	33.33	10.92	56.91	165	106	P	V
		7311	48.43	-25.57	74	57.74	35.4	13.29	58	174	100	P	V
802.11b CH 11 2462MHz		4924	51.29	-22.71	74	63.02	33.36	10.99	56.08	150	285	P	H
		4924	50.7	-3.3	54	62.43	33.36	10.99	56.08	150	285	A	H
		7386	48.21	-25.79	74	57.83	35.27	13.12	58.01	155	274	P	H
		4924	50.38	-23.62	74	62.11	33.36	10.99	56.08	150	285	P	V
		7386	48.5	-25.5	74	58.12	35.27	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.8	61.48	-12.52	74	56.5	31.38	6.81	33.21	194	142	P	H
		2389.905	44.35	-9.65	54	39.37	31.38	6.81	33.21	194	142	A	H
	*	2412	101.34	-	-	96.22	31.5	6.81	33.19	194	142	P	H
	*	2412	94.8	-	-	89.68	31.5	6.81	33.19	194	142	A	H
		2389.905	59.15	-14.85	74	54.17	31.38	6.81	33.21	250	99	P	V
		2389.8	42.81	-11.19	54	37.83	31.38	6.81	33.21	250	99	A	V
	*	2412	101.26	-	-	96.14	31.5	6.81	33.19	250	99	P	V
	*	2412	94.11	-	-	88.99	31.5	6.81	33.19	250	99	A	V
802.11g CH 06 2437MHz		2339.68	54.88	-19.12	74	50.48	31.01	6.65	33.26	150	40	P	H
		2384.9	41.22	-12.78	54	36.38	31.26	6.81	33.23	150	40	A	H
	*	2437	100.83	-	-	95.38	31.74	6.86	33.15	150	40	P	H
	*	2437	93.17	-	-	87.72	31.74	6.86	33.15	150	40	A	H
		2489.15	46.83	-27.17	74	40.92	32.1	6.91	33.1	150	40	P	H
		2489.29	37.65	-16.35	54	31.74	32.1	6.91	33.1	150	40	A	H
		2339.12	55.21	-18.79	74	50.81	31.01	6.65	33.26	245	77	P	V
		2384.76	40.6	-13.4	54	35.76	31.26	6.81	33.23	245	77	A	V
	*	2437	100.37	-	-	94.92	31.74	6.86	33.15	245	77	P	V
	*	2437	92.73	-	-	87.28	31.74	6.86	33.15	245	77	A	V
		2489.57	47.44	-26.56	74	41.53	32.1	6.91	33.1	245	77	P	V
		2489.22	38.02	-15.98	54	32.11	32.1	6.91	33.1	245	77	A	V



802.11g CH 11 2462MHz	*	2462	100.49	-	-	94.91	31.86	6.86	33.14	171	143	P	H
	*	2462	93.52	-	-	87.94	31.86	6.86	33.14	171	143	A	H
		2483.88	62.32	-11.68	74	56.55	31.98	6.91	33.12	171	143	P	H
		2483.68	44.93	-9.07	54	39.16	31.98	6.91	33.12	171	143	A	H
	*	2462	100.19	-	-	94.61	31.86	6.86	33.14	185	278	P	V
	*	2462	93.24	-	-	87.66	31.86	6.86	33.14	185	278	A	V
		2483.52	59.31	-14.69	74	53.54	31.98	6.91	33.12	185	278	P	V
		2483.52	43.33	-10.67	54	37.56	31.98	6.91	33.12	185	278	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	46.33	-27.67	74	58.74	33.3	10.89	56.6	185	255	P	H
		4824	45.91	-28.09	74	58.32	33.3	10.89	56.6	185	255	P	V
802.11g CH 06 2437MHz		4874	47.26	-26.74	74	59.92	33.33	10.92	56.91	165	106	P	H
		7311	48.23	-25.77	74	57.54	35.4	13.29	58	174	100	P	H
		4874	45.91	-28.09	74	58.57	33.33	10.92	56.91	165	106	P	V
		7311	48.43	-25.57	74	57.74	35.4	13.29	58	174	100	P	V
802.11g CH 11 2462MHz		4924	46.21	-27.79	74	57.94	33.36	10.99	56.08	150	285	P	H
		7386	48.06	-25.94	74	57.68	35.27	13.12	58.01	155	274	P	H
		4924	47.43	-26.57	74	59.16	33.36	10.99	56.08	150	285	P	V
		7386	48.22	-25.78	74	57.84	35.27	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2390	60.72	-13.28	74	55.74	31.38	6.81	33.21	170	142	P	H
		2360.61	42.49	-11.51	54	37.87	31.13	6.73	33.24	170	142	A	H
	*	2412	100.07	-	-	94.95	31.5	6.81	33.19	170	142	P	H
	*	2412	93.54	-	-	88.42	31.5	6.81	33.19	170	142	A	H
		2389.17	61.46	-12.54	74	56.48	31.38	6.81	33.21	238	68	P	V
		2389.8	42.55	-11.45	54	37.57	31.38	6.81	33.21	238	68	A	V
	*	2412	99.51	-	-	94.39	31.5	6.81	33.19	238	68	P	V
	*	2412	92.35	-	-	87.23	31.5	6.81	33.19	238	68	A	V
802.11n HT20 CH 06 2437MHz		2340.1	55.77	-18.23	74	51.37	31.01	6.65	33.26	217	143	P	H
		2385.18	41.09	-12.91	54	36.25	31.26	6.81	33.23	217	143	A	H
	*	2437	99.55	-	-	94.1	31.74	6.86	33.15	217	143	P	H
	*	2437	92.15	-	-	86.7	31.74	6.86	33.15	217	143	A	H
		2488.87	48.48	-25.52	74	42.57	32.1	6.91	33.1	217	143	P	H
		2488.73	38.1	-15.9	54	32.19	32.1	6.91	33.1	217	143	A	H
		2340.1	56.93	-17.07	74	52.53	31.01	6.65	33.26	192	257	P	V
		2385.32	40.45	-13.55	54	35.61	31.26	6.81	33.23	192	257	A	V
	*	2437	98.68	-	-	93.23	31.74	6.86	33.15	192	257	P	V
	*	2437	90.93	-	-	85.48	31.74	6.86	33.15	192	257	A	V
		2489.5	47.27	-26.73	74	41.36	32.1	6.91	33.1	192	257	P	V
		2488.66	37.21	-16.79	54	31.3	32.1	6.91	33.1	192	257	A	V



802.11n HT20 CH 11 2462MHz	*	2462	99.51	-	-	93.93	31.86	6.86	33.14	215	134	P	H
	*	2462	92.4	-	-	86.82	31.86	6.86	33.14	215	134	A	H
		2484.32	61.83	-12.17	74	56.06	31.98	6.91	33.12	215	134	P	H
		2483.52	43.39	-10.61	54	37.62	31.98	6.91	33.12	215	134	A	H
	*	2462	98.23	-	-	92.65	31.86	6.86	33.14	191	263	P	V
	*	2462	91.11	-	-	85.53	31.86	6.86	33.14	191	263	A	V
		2484.44	58.45	-15.55	74	52.68	31.98	6.91	33.12	191	263	P	V
		2483.56	42.06	-11.94	54	36.29	31.98	6.91	33.12	191	263	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	46.2	-27.8	74	58.61	33.3	10.89	56.6	185	255	P	H
													V
		4824	46.01	-27.99	74	58.42	33.3	10.89	56.6	185	255	P	
802.11n HT20 CH 06 2437MHz		4874	45.81	-28.19	74	58.47	33.33	10.92	56.91	165	106	P	H
		7311	48.42	-25.58	74	57.73	35.4	13.29	58	174	100	P	H
		4874	45.95	-28.05	74	58.61	33.33	10.92	56.91	165	106	P	V
		7311	49.11	-24.89	74	58.42	35.4	13.29	58	174	100	P	V
802.11n HT20 CH 11 2462MHz		4924	46.46	-27.54	74	58.19	33.36	10.99	56.08	150	285	P	H
		7386	48.05	-25.95	74	57.67	35.27	13.12	58.01	155	274	P	H
		4924	46.97	-27.03	74	58.7	33.36	10.99	56.08	150	285	P	V
		7386	48.44	-25.56	74	58.06	35.27	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2339.54	60.18	-13.82	74	55.78	31.01	6.65	33.26	195	131	P	H
		2389.52	37.07	-16.93	54	32.09	31.38	6.81	33.21	195	131	A	H
	*	2422	99.4	-	-	94.14	31.62	6.81	33.17	195	131	P	H
	*	2422	92.84	-	-	87.58	31.62	6.81	33.17	195	131	A	H
		2495.66	46.32	-27.68	74	40.41	32.1	6.91	33.1	195	131	P	H
		2486.07	36.04	-17.96	54	30.27	31.98	6.91	33.12	195	131	A	H
		2340.1	58.8	-15.2	74	54.4	31.01	6.65	33.26	216	128	P	V
		2388.12	37.49	-16.51	54	32.51	31.38	6.81	33.21	216	128	A	V
	*	2422	99.15	-	-	93.89	31.62	6.81	33.17	216	128	P	V
	*	2422	92.73	-	-	87.47	31.62	6.81	33.17	216	128	A	V
		2488.03	46.09	-27.91	74	40.18	32.1	6.91	33.1	216	128	P	V
		2492.79	35.91	-18.09	54	30	32.1	6.91	33.1	216	128	A	V
802.11n HT40 CH 06 2437MHz		2339.82	58.53	-15.47	74	54.13	31.01	6.65	33.26	220	130	P	H
		2339.68	35.78	-18.22	54	31.38	31.01	6.65	33.26	220	130	A	H
	*	2437	98.9	-	-	93.45	31.74	6.86	33.15	220	130	P	H
	*	2437	92.47	-	-	87.02	31.74	6.86	33.15	220	130	A	H
		2483.69	52.33	-21.67	74	46.56	31.98	6.91	33.12	220	130	P	H
		2483.76	38.11	-15.89	54	32.34	31.98	6.91	33.12	220	130	A	H
		2340.1	59.66	-14.34	74	55.26	31.01	6.65	33.26	161	279	P	V
		2389.8	36.19	-17.81	54	31.21	31.38	6.81	33.21	161	279	A	V
	*	2437	98.7	-	-	93.25	31.74	6.86	33.15	161	279	P	V
	*	2437	92.88	-	-	87.43	31.74	6.86	33.15	161	279	A	V
		2485.09	47.85	-26.15	74	42.08	31.98	6.91	33.12	161	279	P	V
		2486.49	37.41	-16.59	54	31.64	31.98	6.91	33.12	161	279	A	V



802.11n HT40 CH 09 2452MHz		2340.1	57.42	-16.58	74	53.02	31.01	6.65	33.26	223	130	P	H
		2339.82	39.99	-14.01	54	35.59	31.01	6.65	33.26	223	130	A	H
	*	2452	98.67	-	-	93.22	31.74	6.86	33.15	223	130	P	H
	*	2452	91.25	-	-	85.8	31.74	6.86	33.15	223	130	A	H
		2498.11	46.66	-27.34	74	40.75	32.1	6.91	33.1	223	130	P	H
		2486.63	36.56	-17.44	54	30.79	31.98	6.91	33.12	223	130	A	H
		2340.38	58.86	-15.14	74	54.46	31.01	6.65	33.26	150	280	P	V
		2339.82	41.11	-12.89	54	36.71	31.01	6.65	33.26	150	280	A	V
	*	2452	98	-	-	92.55	31.74	6.86	33.15	150	280	P	V
	*	2452	90.92	-	-	85.47	31.74	6.86	33.15	150	280	A	V
		2493.14	46.63	-27.37	74	40.72	32.1	6.91	33.1	150	280	P	V
		2486.49	36.41	-17.59	54	30.64	31.98	6.91	33.12	150	280	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

a	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4844	47.7	-26.3	74	60.05	33.31	10.92	56.58	150	350	P	H
HT40		7266	49.78	-24.22	74	59.21	35.46	13.38	58.27	200	360	P	H
CH 03		4844	46.67	-27.33	74	59.02	33.31	10.92	56.58	150	350	P	V
2422MHz		7266	49.05	-24.95	74	58.48	35.46	13.38	58.27	200	360	P	V
802.11n		4874	46.74	-27.26	74	59.4	33.33	10.92	56.91	165	230	P	H
HT40		7311	49.42	-24.58	74	58.73	35.4	13.29	58	186	323	P	H
CH 06		4874	45.52	-28.48	74	58.18	33.33	10.92	56.91	165	230	P	V
2437MHz		7311	48.45	-25.55	74	57.76	35.4	13.29	58	186	323	P	V
802.11n		4904	47.24	-26.76	74	59.29	33.35	10.95	56.35	150	360	P	H
HT40		7356	48.65	-25.35	74	58.08	35.32	13.21	57.96	165	335	P	H
CH 09		4904	46.61	-27.39	74	58.66	33.35	10.95	56.35	150	360	P	V
2452MHz		7356	49.71	-24.29	74	59.14	35.32	13.21	57.96	165	335	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												


15C Emission below 1GHz
2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		31.94	26.41	-13.59	40	31.79	26	0.27	31.65	100	0	P	H
		100.81	21.74	-21.76	43.5	33.2	19.28	0.86	31.6	-	-	P	H
		173.56	22.46	-21.04	43.5	35.16	17.16	1.45	31.31	-	-	P	H
		442.25	26.85	-19.15	46	31.2	24.41	2.54	31.3	-	-	P	H
		734.22	31.9	-14.1	46	32.38	27.62	3.4	31.5	-	-	P	H
		987.39	33.53	-20.47	54	30.89	30	4.14	31.5	-	-	P	H
		35.82	25.92	-14.08	40	32.57	24.62	0.33	31.6	100	200	P	V
		140.58	24.19	-19.31	43.5	36.07	18.33	1.23	31.44	-	-	P	V
		400.54	26.56	-19.44	46	31.56	23.91	2.39	31.3	-	-	P	V
		638.19	31.11	-14.89	46	34.03	25.46	3.12	31.5	-	-	P	V
		744.89	31.43	-14.57	46	31.61	27.88	3.44	31.5	-	-	P	V
		967.02	33.61	-20.39	54	31.24	29.84	4.03	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.




Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.59	8.232	0.121	300Hz
802.11g	87.04	1.362	0.734	1kHz
802.11n HT20	86.70	1.275	0.784	1kHz
802.11n HT40	76.12	0.638	1.568	3kHz



802.11b




802.11g





802.11n HT20





802.11n HT40

