

FCC ID: 2AKXBS1

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-2.876	0.516	-3 ± 1	-2	0.631	< 5	0.19558	3.00	YES
	2.44	-3.168	0.482	-3 ± 1	-2	0.631	< 5	0.19712	3.00	YES
	2.480	-3.274	0.471	-3 ± 1	-2	0.631	< 5	0.19873	3.00	YES

Conclusion:

For the max result : $0.19873 \leq 3.0$ for 1-g SAR, No SAR is required.

Jason chen

Signature:

Date: 2017-02-21

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.