

RF TEST REPORT

For

Audio-Technica Corporation

Product Name: Powered Bluetooth BookShelf Speakers

Test Model(s): AT-SP3X

Report Reference No. : POCE240222002RF001

FCC ID : JFZ-ATSP3X

Applicant's Name : Audio-Technica Corporation

Address : 2-46-1 Nishi-Naruse, Machida, Tokyo 194-8666, Japan

Testing Laboratory : Shenzhen POCE Technology Co., Ltd.

Address : 101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15.247
ANSI C63.10-2013 & KDB 558074 D01 15.247 Meas Guidance v05r02

Date of Receipt : February 19, 2024

Date of Test : February 19, 2024 to February 28, 2024

Data of Issue : February 28, 2024

Result : Pass

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen POCE Technology Co., Ltd. This document may be altered or revised by Shenzhen POCE Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	POCE240222002RF001	February 28, 2024

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

*Keren Huang*Keren Huang / Test Engineer

Supervised by:

*Stone Yin*Stone Yin / Project Engineer

Approved by:

*Tom Chen*Tom Chen / Manager

CONTENTS

1	TEST SUMMARY	5
1.1	TEST STANDARDS	5
1.2	SUMMARY OF TEST RESULT	5
2	GENERAL INFORMATION	6
2.1	CLIENT INFORMATION	6
2.2	DESCRIPTION OF DEVICE (EUT)	6
2.3	DESCRIPTION OF TEST MODES	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	EQUIPMENTS USED DURING THE TEST	8
2.6	STATEMENT OF THE MEASUREMENT UNCERTAINTY	9
2.7	IDENTIFICATION OF TESTING LABORATORY	10
2.8	ANNOUNCEMENT	10
3	EVALUATION RESULTS (EVALUATION)	11
3.1	ANTENNA REQUIREMENT	11
3.1.1	Conclusion:	11
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	12
4.1	CONDUCTED EMISSION AT AC POWER LINE	12
4.1.1	E.U.T. Operation:	12
4.1.2	Test Setup Diagram:	12
4.1.3	Test Data:	13
4.2	OCCUPIED BANDWIDTH	15
4.2.1	E.U.T. Operation:	15
4.2.2	Test Setup Diagram:	15
4.2.3	Test Data:	15
4.3	MAXIMUM CONDUCTED OUTPUT POWER	16
4.3.1	E.U.T. Operation:	16
4.3.2	Test Setup Diagram:	16
4.3.3	Test Data:	17
4.4	POWER SPECTRAL DENSITY	18
4.4.1	E.U.T. Operation:	18
4.4.2	Test Setup Diagram:	18
4.4.3	Test Data:	18
4.5	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	19
4.5.1	E.U.T. Operation:	19
4.5.2	Test Setup Diagram:	19
4.5.3	Test Data:	19
4.6	BAND EDGE EMISSIONS (RADIATED)	20
4.6.1	E.U.T. Operation:	20
4.6.2	Test Setup Diagram:	20
4.6.3	Test Data:	21
4.7	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	23
4.7.1	E.U.T. Operation:	24
4.7.2	Test Setup Diagram:	24
4.7.3	Test Data:	24
4.8	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz)	27

4.8.1	E.U.T. Operation:.....	28
4.8.2	Test Setup Diagram:.....	28
4.8.3	Test Data:	29
5	TEST SETUP PHOTOS	32
6	PHOTOS OF THE EUT	34
APPENDIX		46
1.	-6dB BANDWIDTH	46
2.	99% OCCUPIED BANDWIDTH	48
3.	PEAK OUTPUT POWER	50
4.	POWER SPECTRAL DENSITY	52
5.	BANDEDGE	54
6.	SPURIOUS EMISSION	56

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

Note: 1.N/A -this device(EUT) is not applicable to this testing item

2. RF-conducted test results including cable loss.


2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Audio-Technica Corporation
Address : 2-46-1 Nishi-Naruse, Machida, Tokyo 194-8666, Japan

Manufacturer : Zhong Shan City Richsound Electronic Industrial Ltd
Address : No.16, East ShaGang Road, GangKou Town, ZhongShan City, GuangDong, 528447, China

2.2 Description of Device (EUT)

Product Name:	Powered Bluetooth BookShelf Speakers
Model/Type reference:	AT-SP3X
Trade Mark:	 audio-technica
Product Description:	Powered Bluetooth BookShelf Speakers
Power Supply:	DC18V-2A from adapter
Power Adaptor:	MODEL:FJ-SW248G1802000N INPUT:100-240V~50/60Hz 1.5A Max OUTPUT:18.0V-2.0A.36.0W
Operation Frequency:	2402MHz to 2480MHz
Number of Channels:	40
Modulation Type:	GFSK
Antenna Type:	FPC ANTENNA
Antenna Gain:	2.34dBi
Hardware Version:	94V-0
Software Version:	FCC_assist_1.0.4

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
3	2406MHz	13	2426MHz	23	2446MHz	33	2466MHz
4	2408MHz	14	2428MHz	24	2448MHz	34	2468MHz
5	2410MHz	15	2430MHz	25	2450MHz	35	2470MHz
6	2412MHz	16	2432MHz	26	2452MHz	36	2472MHz
7	2414MHz	17	2434MHz	27	2454MHz	37	2474MHz
8	2416MHz	18	2436MHz	28	2456MHz	38	2476MHz
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	BLE
Lowest channel	2402MHz
Middle channel	2440MHz
Highest channel	2480MHz

2.3 Description of Test Modes


No	Title	Description
TM1	TX mode	Keep the EUT connect to AC power line and works in continuously transmitting mode with GFSK modulation.

☒ Special software is used.

☐ Through engineering command into the engineering mode.
engineering command: ***#3646633#**

☐ Other method:

Special software:



Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

2.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Title	Manufacturer	Model No.	Serial No.
ADAPTER	SHENZHEN FUJIAAPPLIANCE CO.,LTD.	MODEL:FJ-SW248G1802000N INPUT:100-240V~50/60Hz 1.5A Max OUTPUT:18.0V-2.0A.36.0W	/
/	/	/	/

2.5 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2023-12-12	2024-12-11
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	/	/
Cable	SCHWARZ BECK	/	/	2023-12-27	2024-12-26
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Ateennator	561-G071	2023-12-12	2024-12-11
50ΩCoaxial Switch	Anritsu	MP59B	M20531	/	/
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	ID:1164.6607 K03-102109-MH	2023-06-13	2024-06-12
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2023-12-12	2024-12-11

Occupied Bandwidth

Maximum Conducted Output Power

Power Spectral Density

Emissions in non-restricted frequency bands

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	TACHOY	RTS-01	V2.0.0.0	/	/
High Pass filter	ZHINAN	OQHPF1-M1.5-18G-224	6210075	/	/
Power divider	MIDEWEST	PWD-2533	SMA-79	2023-05-11	2026-05-10
RF Sensor Unit	TACHOY	TR1029-2	000001	/	/
Vector signal generator	Keysight	N5181A	MY48180415	2023-11-09	2024-11-08
Signal generator	Keysight	N5182A	MY50143455	2023-11-09	2024-11-08
Spectrum Analyzer	Keysight	N9020A	MY53420323	2023-12-12	2024-12-11

Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)
Band edge emissions (Radiated)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(LF)#1	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2024-02-19	2025-02-18
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2024-02-19	2025-02-18
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Occupied Bandwidth	±3.63%
RF conducted power	±0.733dB
RF power density	±0.234%
Conducted Spurious emissions	±1.98dB
Radiated Emission (Above 1GHz)	±5.46dB
Radiated Emission (Below 1GHz)	±5.79dB
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen POCE Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen POCE Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration No.:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by POCE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client. When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.


3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:


Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.1 Conclusion:




4.1.3 Test Data:

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4820	39.01	9.98	48.99	56.30	-7.31	QP	
2	*	0.4820	31.84	9.98	41.82	46.30	-4.48	AVG	
3		0.8139	10.73	10.08	20.81	46.00	-25.19	AVG	
4		0.8220	28.75	10.14	38.89	56.00	-17.11	QP	
5		1.4460	12.40	9.93	22.33	46.00	-23.67	AVG	
6		1.4500	27.77	9.93	37.70	56.00	-18.30	QP	
7		2.0740	9.19	9.99	19.18	46.00	-26.82	AVG	
8		2.1020	27.38	9.99	37.37	56.00	-18.63	QP	
9		3.3700	27.62	10.05	37.67	56.00	-18.33	QP	
10		3.3700	11.28	10.05	21.33	46.00	-24.67	AVG	
11		25.5260	3.25	10.59	13.84	50.00	-36.16	AVG	
12		29.1820	15.57	10.66	26.23	60.00	-33.77	QP	

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.4820	34.66	9.98	44.64	56.30	-11.66	QP	
2	*	0.4820	27.10	9.98	37.08	46.30	-9.22	AVG	
3		0.8940	21.95	9.98	31.93	56.00	-24.07	QP	
4		0.9620	6.03	10.02	16.05	46.00	-29.95	AVG	
5		1.4460	22.67	9.93	32.60	56.00	-23.40	QP	
6		1.4460	10.31	9.93	20.24	46.00	-25.76	AVG	
7		2.0820	22.92	9.99	32.91	56.00	-23.09	QP	
8		2.0980	3.84	9.99	13.83	46.00	-32.17	AVG	
9		2.6540	22.43	10.01	32.44	56.00	-23.56	QP	
10		2.8900	8.42	10.03	18.45	46.00	-27.55	AVG	
11		25.5260	5.99	10.59	16.58	50.00	-33.42	AVG	
12		28.9420	14.43	10.66	25.09	60.00	-34.91	QP	

Note:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor, Over = Measurement - Limit


4.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.

4.3 Maximum Conducted Output Power


Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power Note: Per ANSI C63.10-2013, if there are two or more antennas, the conducted powers at Core 0, Core 1,..., Core i were first measured separately, as shown in the section above (this product only have one antenna). The measured values were then summed in linear power units then converted back to dBm. Per ANSI C63.10-2013 Section 14.4.3.2.3, the directional gain is calculated using the following formula, where GN is the gain of the nth antenna and NANT, the total number of antennas used. For correlated unequal antenna gain Directional gain = $10 \cdot \log[(10G1/20 + 10G2/20 + \dots + 10GN/20)^2 / NANT]$ dBi For completely uncorrelated unequal antenna gain Directional gain = $10 \cdot \log[(10G1/10 + 10G2/10 + \dots + 10GN/10) / NANT]$ dBi Sample Multiple antennas Calculation: Core 0 + Core 1 + ... Core i. = MIMO/CDD (i is the number of antennas) (#VALUE! mW + mW) = #VALUE! mW = dBm Sample e.i.r.p. Calculation: e.i.r.p. (dBm) = Conducted Power (dBm) + Ant gain (dBi)

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.3.2 Test Setup Diagram:

--



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.


4.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.


4.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>			
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

4.6.1 E.U.T. Operation:


Operating Environment:			
Temperature:	24 °C	Humidity:	49.4 %
Atmospheric Pressure:	101 kPa		
Pretest mode:	TM1		
Final test mode:	TM1		

4.6.2 Test Setup Diagram:




4.6.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	39.90	-6.93	32.97	74.00	-41.03	peak	149		P	
2 *	2310.000	28.42	-6.93	21.49	54.00	-32.51	AVG	149		P	
3	2390.000	40.69	-6.72	33.97	74.00	-40.03	peak	149		P	
4	2390.000	27.96	-6.72	21.24	54.00	-32.76	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	40.58	-8.23	32.35	74.00	-41.65	peak	149		P	
2 *	2310.000	29.61	-8.23	21.38	54.00	-32.62	AVG	149		P	
3	2390.000	40.59	-7.91	32.68	74.00	-41.32	peak	149		P	
4	2390.000	28.86	-7.91	20.95	54.00	-33.05	AVG	149		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	50.02	-7.54	42.48	74.00	-31.52	peak			P	
2 *	2483.500	39.48	-7.54	31.94	54.00	-22.06	AVG			P	
3	2500.000	40.95	-7.48	33.47	74.00	-40.53	peak			P	
4	2500.000	29.42	-7.48	21.94	54.00	-32.06	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	56.50	-6.47	50.03	74.00	-23.97	peak	149		P	
2 *	2483.500	44.90	-6.47	38.43	54.00	-15.57	AVG	149		P	
3	2500.000	40.86	-6.43	34.43	74.00	-39.57	peak	149		P	
4	2500.000	29.46	-6.43	23.03	54.00	-30.97	AVG	149		P	

Remark:

- 1.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 2.Mesurement Level = Reading level + Correct Factor, Margin= Mesurement Level - Limit
Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

4.7 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <p>1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.</p>		


2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor

3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.7.2 Test Setup Diagram:




4.7.3 Test Data:

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.4238	24.25	-2.97	21.28	40.00	-18.72	QP	100		P	
2	72.3376	27.11	-8.38	18.73	40.00	-21.27	QP	100		P	
3	230.9068	28.52	-2.44	26.08	46.00	-19.92	QP	100		P	
4	317.7011	26.57	1.07	27.64	46.00	-18.36	QP	100		P	
5	776.8778	24.91	5.88	30.79	46.00	-15.21	QP	100		P	
6 *	945.4399	24.70	8.98	33.68	46.00	-12.32	QP	100		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.1054	27.44	-2.89	24.55	40.00	-15.45	QP	100		P	
2	73.6170	35.43	-8.27	27.16	40.00	-12.84	QP	100		P	
3	202.1005	26.91	-2.91	24.00	43.50	-19.50	QP	100		P	
4	343.1800	26.10	0.65	26.75	46.00	-19.25	QP	100		P	
5	679.9600	26.50	4.55	31.05	46.00	-14.95	QP	100		P	
6 *	955.4381	24.91	9.21	34.12	46.00	-11.88	QP	100		P	

Remark: Margin= Measurement Level- Limit

Measurement Level=Test receiver reading + correction factor

Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

4.8 Emissions in frequency bands (above 1GHz)


Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>		
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	<p>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>h. Test the EUT in the lowest channel, the middle channel, the Highest channel.</p> <p>i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</p> <p>j. Repeat above procedures until all frequencies measured was complete.</p> <p>Remark:</p> <p>1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.</p>		

	<p>2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor</p> <p>3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.</p>
--	--

4.8.1 E.U.T. Operation:


Operating Environment:					
Temperature:	24 °C	Humidity:	49.4 %	Atmospheric Pressure:	101 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.8.2 Test Setup Diagram:




4.8.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4804.000	41.35	-0.90	40.45	74.00	-33.55	peak	149		P	
2	4804.000	29.40	-0.90	28.50	54.00	-25.50	AVG	149		P	
3	7204.000	42.35	4.13	46.48	74.00	-27.52	peak	149		P	
4	7204.000	29.23	4.13	33.36	54.00	-20.64	AVG	149		P	
5	9601.000	41.73	8.09	49.82	74.00	-24.18	peak	149		P	
6 *	9601.000	28.25	8.09	36.34	54.00	-17.66	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4807.000	42.11	-0.27	41.84	74.00	-32.16	peak	149		P	
2	4807.000	28.73	-0.27	28.46	54.00	-25.54	AVG	149		P	
3	7204.000	41.94	4.09	46.03	74.00	-27.97	peak	149		P	
4	7204.000	28.68	4.09	32.77	54.00	-21.23	AVG	149		P	
5	9601.000	43.88	8.01	51.89	74.00	-22.11	peak	149		P	
6 *	9601.000	29.80	8.01	37.81	54.00	-16.19	AVG	149		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4880.000	37.28	-0.03	37.25	74.00	-36.75	peak	149		P	
2	4880.000	26.49	-0.03	26.46	54.00	-27.54	AVG	149		P	
3	7321.500	41.88	4.36	46.24	74.00	-27.76	peak	149		P	
4	7321.500	28.51	4.36	32.87	54.00	-21.13	AVG	149		P	
5	9753.750	44.11	8.12	52.23	74.00	-21.77	peak	149		P	
6 *	9753.750	30.36	8.12	38.48	54.00	-15.52	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4880.000	39.06	-0.65	38.41	74.00	-35.59	peak	149		P	
2	4880.000	26.99	-0.65	26.34	54.00	-27.66	AVG	149		P	
3	7321.500	41.11	4.31	45.42	74.00	-28.58	peak	149		P	
4	7321.500	28.04	4.31	32.35	54.00	-21.65	AVG	149		P	
5	9753.750	42.33	8.09	50.42	74.00	-23.58	peak	149		P	
6 *	9753.750	28.73	8.09	36.82	54.00	-17.18	AVG	149		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4959.750	44.12	-0.37	43.75	74.00	-30.25	peak	149		P	
2	4959.750	29.65	-0.37	29.28	54.00	-24.72	AVG	149		P	
3	7439.000	42.77	4.49	47.26	74.00	-26.74	peak	149		P	
4	7439.000	29.32	4.49	33.81	54.00	-20.19	AVG	149		P	
5	9918.250	41.36	8.08	49.44	74.00	-24.56	peak	149		P	
6 *	9918.250	28.75	8.08	36.83	54.00	-17.17	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4948.000	44.65	0.19	44.84	74.00	-29.16	peak	149		P	
2	4959.750	28.53	0.23	28.76	54.00	-25.24	AVG	149		P	
3	7439.000	41.89	4.64	46.53	74.00	-27.47	peak	149		P	
4	7439.000	28.18	4.64	32.82	54.00	-21.18	AVG	149		P	
5	9918.250	44.85	8.23	53.08	74.00	-20.92	peak	149		P	
6 *	9918.250	30.55	8.23	38.78	54.00	-15.22	AVG	149		P	


Remark: Margin= Level – Limit; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
Level=Test receiver reading + correction factor

5 TEST SETUP PHOTOS


Conducted Emission at AC power line



Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)



6 PHOTOS OF THE EUT

External





