TEST REPORT

Report No.: CHTEW21110222 Report Verification:

Project No...... SHT2111022701EW

FCC ID.....: 2ARTX-HERO600

Applicant's name: LAVA International Limited

Address...... A-56, Sector 64, Noida 201301

Test item description: Mobile phone

Trade Mark LAVA

Model/Type reference...... HERO 600+

Listed Model(s)

Standard: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample............ Nov.18, 2021

Date of testing...... Nov.18, 2021- Nov.25, 2021

Date of issue...... Nov.26, 2021

Result...... PASS

Compiled by

(position+printed name+signature)..: File administrators Fanghui Zhu

Supervised by

(position+printed name+signature)..: Project Engineer Cheng Xiao

Approved by

(Position+Printed name+Signature): RF Manager Hans Hu

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd.

Tianliao, Gongming, Shenzhen, China

Jang Miri Zhu

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Page: 1 of 33

Report No.: CHTEW21110222 Page: 2 of 33 Issued: 2021-11-26

Contents

3. SUMMARY 3.1. Client Information	3 3 4 5 5
1.2. Report version 2. TEST DESCRIPTION 3. SUMMARY 3.1. Client Information	3 4 5
3. SUMMARY 3.1. Client Information	5
3.1. Client Information	5
3.1. Client Information	5
3.2. Product Description	-
3.3. Radio Specification Description	5
3.4. Testing Laboratory Information	6
4. TEST CONFIGURATION	7
4.1. Test frequency list	7
4.2. Descriptions of Test mode	7
4.3. Test mode	7
4.4. Support unit used in test configuration and system	8
4.5. Testing environmental condition	8
4.6. Measurement uncertainty	8
4.7. Equipment Used during the Test	9
5. TEST CONDITIONS AND RESULTS	11
5.1. Antenna Requirement	11
5.2. AC Conducted Emission	12
5.3. Peak Output Power	15
5.4. 20 dB Bandwidth	16
5.5. 99% Occupied Bandwidth	17
5.6. Carrier Frequencies Separation	18
5.7. Hopping Channel Number	19
5.8. Dwell Time 5.9. Duty Cycle Correction Factor (DCCF)	20 21
5.9. Duty Cycle Correction Factor (DCCF) 5.10. Pseudorandom Frequency Hopping Sequence	21
5.10. Pseudorandom Frequency Hopping Sequence 5.11. Conducted Band edge and Spurious Emission	23
5.12. Radiated Band edge Emission	25 25
5.13. Radiated Spurious Emission	27
6. TEST SETUP PHOTOS	32
7. EXTERANAL AND INTERNAL PHOTOS	33
8. APPENDIX REPORT	33

Report No.: CHTEW21110222 Page: 3 of 33 Issued: 2021-11-26

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- ANSI C63.10:2013: American National Standard for Testing Unlicensed Wireless Devices
- KDB 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2021-11-26	Original

Report No.: CHTEW21110222 Page: 4 of 33 Issued: 2021-11-26

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result
5.1	Antenna Requirement	15.203/15.247 (c)	PASS
5.2	AC Conducted Emission	15.207	PASS
5.3	Peak Output Power	15.247 (b)(1)	PASS
5.4	20 dB Bandwidth	15.247 (a)(1)	PASS
5.5	99% Occupied Bandwidth	-	PASS ^{*1}
5.6	Carrier Frequency Separation	15.247 (a)(1)	PASS
5.7	Hopping Channel Number	15.247 (a)(1)	PASS
5.8	Dwell Time	15.247 (a)(1)	PASS
5.9	Duty Cycle Correction Factor	-	PASS*1
5.10	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS
5.11	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS
5.12	Radiated Band Edge Emission	15.205/15.209	PASS
5.13	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS

Note:

The measurement uncertainty is not included in the test result.

 ^{*1:} No requirement on standard, only report these test data.

Report No.: CHTEW21110222 Page: 5 of 33 Issued: 2021-11-26

3. **SUMMARY**

3.1. Client Information

Applicant:	LAVA International Limited	
Address:	A-56, Sector 64, Noida 201301	
Manufacturer:	LAVA INTERNATIONAL LTD	
Address:	A-154 D, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh, 201301	
Factory:	LAVA INTERNATIONAL LTD	
Address:	A-154 D, Sector-63, Noida, Gautam Buddha Nagar, Uttar Pradesh, 201301	

3.2. Product Description

Name of EUT:	Mobile phone	
Trade Mark:	LAVA	
Model No.:	HERO 600+	
Listed Model(s):	-	
Power supply:	DC 3.7V for battery	
Hardware version:	IL1801 PCB_V2.2 4	
Software version:	Bmobile_Hero600P	

3.3. Radio Specification Description

Bluetooth version:	V3.0
Support function*2:	EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Monopole Wireway Antenna
Antenna gain:	0.90 dBi

Note:

^{*2:} only show the RF function associated with this report.

Report No.: CHTEW21110222 Page: 6 of 33 Issued: 2021-11-26

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.		
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China		
Connect information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn		
Qualifications	Туре	Accreditation Number	
Qualifications	FCC	762235	

Report No.: CHTEW21110222 Page: 7 of 33 Issued: 2021-11-26

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

Channel	Frequency (MHz)
00	2402
01	2403
:	:
39	2441
i i	i i
77	2479
78	2480

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates and recorded the RF output power in the clause 5.3

Note:

- 1) The manufacturer declare that the maximum power value of the product is set as a default value in the enter test mode software.
- 2) All the test data for each data rate were verified, found <u>8DPSK Modulation</u> which is worse case mode

4.3. Test mode

For RF test items:			
The engineering test program was provided and enabled to make EUT continuous transmitting.			
Modulation / Data Rate			
Test Item	GFSK	π/4DQPSK	8DPSK
	1Mbps	2Mbps	3Mbps
Conducted test item	✓	✓	✓
Radiated test item	-	-	✓

Remark:

- For radiated test item, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests.
- The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Report No.: CHTEW21110222 Page: 8 of 33 Issued: 2021-11-26

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Wheth	Whether support unit is used?				
✓ No					
Item	Equipement	Trade Name	Model No.	FCC ID	Power cord
1					
2					

4.5. Testing environmental condition

Туре	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.6. Measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.00 dB
Radiated Emission (30MHz~1000MHz	4.36 dB
Radiated Emissions (1GHz~25GHz)	5.10 dB
Peak Output Power	0.77dB
Power Spectral Density	0.77dB
Conducted Spurious Emission	0.77dB
6dB Bandwidth	70Hz for <1GHz 130Hz for >1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Report No.: CHTEW21110222 Page: 9 of 33 Issued: 2021-11-26

4.7. Equipment Used during the Test

•	Conducted Emission										
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)				
•	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27				
•	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2021/9/14	2022/9/13				
•	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2021/9/17	2022/9/16				
•	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2021/9/13	2022/9/12				
•	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE X_142	EF-NM- BNCM-2M	2021/9/17	2022/9/16				
•	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A				

•	Radiated emission-6th test site										
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)				
•	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2022/09/29				
•	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2021/9/14	2022/9/13				
•	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/04/06	2022/04/05				
•	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2021/04/06	2022/04/05				
•	Pre-Amplifer	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2021/11/5	2022/11/4				
•	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2021/02/26	2022/02/25				
•	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2021/02/26	2022/02/25				
•	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A				

•	Radiated em	ission-7th test s	ite				
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
•	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2022/09/26
•	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2021/9/13	2022/9/12
•	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
•	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2020/4/27	2023/4/27
•	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2021/11/5	2022/11/4
•	Broadband Pre- amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2021/03/05	2022/03/04
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2021/02/26	2022/02/25
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
•	RF Connection Cable	HUBER+SUHNER	HTWE0119-05	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
•	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2021/02/26	2022/02/25
•	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	6m 18GHz S Serisa	N/A	2021/02/26	2022/02/25
•	Test Software	Audix	N/A	E3	N/A	N/A	N/A

Report No.: CHTEW21110222 Page: 10 of 33 Issued: 2021-11-26

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
•	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2021/9/13	2022/9/12
•	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2021/9/13	2022/9/12
•	Spectrum Analyzer	Agilent	HTWE0286	N9020A	MY50510187	2021/9/13	2022/9/12
•	Radio communication tester	R&S	HTWE0287	CMW500	137688-Lv	2021/9/13	2022/9/12
•	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

Report No.: CHTEW21110222 Page: 11 of 33 Issued: 2021-11-26

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responseble party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

⊠ Passed	☐ Not Applicable
----------	------------------

The antenna type is a Monopole Wireway antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



Report No.: CHTEW21110222 Page: 12 of 33 Issued: 2021-11-26

5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Fraguenov rango (MHz)	Limit (dBuV)				
Frequency range (MHz)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

^{*} Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE


- 1. The EUT was setup according to ANSI C63.10 requirements.
- 2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
- The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
- 4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
- 5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
- 6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- 7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
- 8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 4.3

TEST RESULT

 Report No.: CHTEW21110222 Page: 13 of 33 Issued: 2021-11-26



Report No.: CHTEW21110222 Page: 14 of 33 Issued: 2021-11-26



Report No.: CHTEW21110222 Page: 15 of 33 Issued: 2021-11-26


5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
- Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW≥ the 20 dB bandwidth of the emission being measured, VBW≥RBW Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

TEST Data

Please refer to appendix A on the appendix report


Report No.: CHTEW21110222 Page: 16 of 33 Issued: 2021-11-26

5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

TEST Data

Please refer to appendix B on the appendix report


Report No.: CHTEW21110222 Page: 17 of 33 Issued: 2021-11-26

5.5. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input.
- 2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output andthe spectrum analyzer).

Center Frequency =channel center frequency

Span≥1.5 x OBW

RBW = 1%~5%OBW

VBW ≥ 3 × RBW

Sweep time= auto couple

Detector = Peak

Trace mode = max hold

3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

TEST Data

Please refer to appendix C on the appendix report

Report No.: CHTEW21110222 Page: 18 of 33 Issued: 2021-11-26


5.6. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings:
 - Span = wide enough to capture the peaks of two adjacent channels
 - RBW ≥ 1% of the span, VBW ≥ RBW
 - Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

TEST Data

Please refer to appendix D on the appendix report

Report No.: CHTEW21110222 Page: 19 of 33 Issued: 2021-11-26


5.7. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

TEST CONFIGURATION



TEST PROCEDURE

- The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings:
 - Span = the frequency band of operation
 - RBW ≥ 1% of the span, VBW ≥ RBW
 - Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

TEST Data

Please refer to appendix E on the appendix report


Report No.: CHTEW21110222 Page: 20 of 33 Issued: 2021-11-26

5.8. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- Use the following spectrum analyzer settings:
 Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW ≥ RBW
 Sweep = as necessary to capture the entire dwell time per hopping channel,
 Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.3

TEST RESULTS

TEST Data

Please refer to appendix F on the appendix report


Report No.: CHTEW21110222 Page: 21 of 33 Issued: 2021-11-26

5.9. Duty Cycle Correction Factor (DCCF)

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- Use the following spectrum analyzer settings:
 Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW ≥ RBW
 Sweep = as necessary to capture the entire dwell time per hopping channel,
 Detector function = peak, Trigger mode
- 4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.3

TEST Data

Please refer to appendix G on the appendix report

Report No.: CHTEW21110222 Page: 22 of 33 Issued: 2021-11-26

5.10. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems shall have hopping channel carrier fre-quencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Al-ternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier fre-quencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to chan-nel frequencies that are selected at the system hopping rate from a pseudo ran-domly ordered list of hopping fre-quencies. Each frequency must be used equally on the average by each trans-mitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their cor-responding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the friststage. The sequence begins with the frist one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An explame of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


Report No.: CHTEW21110222 Page: 23 of 33 Issued: 2021-11-26

5.11. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section15.247 (d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Connect the antenna port(s) to the spectrum analyzer input.
- 2. Emission level measurement

Set the center frequency and span to encompass frequency range to be measured

RBW = 100 kHz, VBW \geq 3 x RBW

Detector = peak, Sweep time = auto couple, Trace mode = max hold

Allow trace to fully stabilize

Use the peak marker function to determine the maximum amplitude level.

- 3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
- 4. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.3

Report No.: CHTEW21110222 Page: 24 of 33 Issued: 2021-11-26

 $oxed{oxed}$ Passed $oxed{oxed}$ Not Applicable

TEST Data

Please refer to appendix H on the appendix report

Report No.: CHTEW21110222 Page: 25 of 33 Issued: 2021-11-26


5.12. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1. The EUT was setup and tested according to ANSI C63.10.
- 2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
- 4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. Thisis repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
- Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)

Averager level = Peak level + DCCF

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

□ Passed □ Not Applicable

Note:

- 1) Level= Reading + Factor; Factor = Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).

Report No.: CHTEW21110222 Page: 26 of 33 Issued: 2021-11-26

Test channel:		Fest channel: CH00 F				,		Horizontal		
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	40.48	27.96	5.43	37.56	36.31	74.00	-37.69	Peak	
2	2390.03	54.51	27.72	5.53	37.45	50.31	74.00	-23.69	Peak	

Test channel:		est channel: CH00			Polarit	Polarity			Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	40.24	27.96	5.43	37.56	36.07	74.00	-37.93	Peak	
2	2390.03	51.19	27.72	5.53	37.45	46.99	74.00	-27.01	Peak	

Test channel:		CH78			Polarity			ontal
Frequency(N	ИН: Reading(dE	BuV/n Antenna	(dE Cable(dB Preamp(dE Level(dBu	uV/n Limit(dBu	V/n Over lim	nit Remark
2483.50	56.55	27.43	5.64	37.26	52.36	74.00	-21.64	Peak
2483.72	69.30	27.43	5.64	37.26	65.11	74.00	-8.89	Peak
2483.72	38.43	27.43	5.64	37.26	34.24	54.00	-19.76	Average
2500.00	41.42	27.40	5.66	37.26	37.22	74.00	-36.78	Peak

Test	Test channel: CH78		Polar	Polarity			Vertical		
Mark	Frequency(MHz)	Reading(dBuV/m)	Antenna (dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m)	Limit(dBuV/m)	Over limit	Remark
1	2483.5	68. 99	27.43	5.64	37.26	64.8	74	-9.2	Peak
2	2483.5	33. 93	27.43	5.64	37.26	29.74	54	-24.26	Average
3	2500	44.92	27.4	5.66	37.26	40.72	74	-33. 28	Peak

Report No.: CHTEW21110222 Page: 27 of 33 Issued: 2021-11-26

5.13. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak

Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80, Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
Above IGHZ	74.00	Peak

TEST CONFIGURATION

> 9 kHz ~ 30 MHz




30 MHz ~ 1 GHz



Above 1 GHz

Report No.: CHTEW21110222 Page: 28 of 33 Issued: 2021-11-26



TEST PROCEDURE

- The EUT was setup and tested according to ANSI C63.10.
- 2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
- 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 5. Set to the maximum power setting and enable the EUT transmit continuously.
- 6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement: use duty cycle correction factor method (DCCF)

Averager level = Peak level + DCCF

TEST MODE:

Please refer to the clause 4.3

TEST RESULT

Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd = Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.

Report No.: CHTEW21110222 Page: 29 of 33 Issued: 2021-11-26

TEST DATA FOR 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

TEST DATA FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH39 which it was worst case, so only show the worst case's data on this report.

Report No.: CHTEW21110222 Page: 30 of 33 Issued: 2021-11-26

Polarization: Horizontal Level [dBµV/m] 70 60 50 40 30 20 30M 40M 50M 60M 70M 100M 200M 300M 400M 500M 600M 800M Frequency [Hz] x x x MES GM2111236037_red MEASUREMENT RESULT: "GM2111236037 red" 11/23/2021 12:00PM Level Transd Frequency Limit Margin Det. Height Azimuth Polarization dB dBµV/m MHz dBµV/m dB deg cm 21.3 QP 51.340000 18.70 -8.8 40.0 100.0 147.00 HORIZONTAL 59.100000 -9.7 21.4 QP 100.0 131.00 HORIZONTAL 18.60 40.0 26.0 QP 23.6 QP 17.50 22.40 103.720000 -10.3 100.0 43.5 63.00 HORIZONTAL 46.0 119.00 HORIZONTAL -7.7 280,260000 100.0 524.700000 26.90 -1.0 46.0 19.1 QP 100.0 193.00 HORIZONTAL 951.500000 35.10 7.9 46.0 10.9 QP 100.0 131.00 HORIZONTAL Polarization: Vertical Level [dBµV/m] 60 50 40 30 20 10 30M 40M 50M 60M 70M 100M 200M 300M 400M 500M 600M 800M Frequency [Hz] x x x MES GM2111236036_red MEASUREMENT RESULT: "GM2111236036 red" 11/23/2021 11:58AM Level Transd Limit Margin Det. Height Azimuth Polarization Frequency dB dBuV/m dB MHz dBµV/m cm deg 31.940000 19.0 QP 21.00 -12.4 40.0 100.0 50.00 VERTICAL 19.6 QP 20.40 214.00 VERTICAL 57.160000 -9.4 40.0 100.0 25.4 QP 24.6 QP 19.1 QP 43.5 101.780000 18.10 -10.3 100.0 151.00 VERTICAL 21.40 -7.2 26.90 -0.4 291.900000 100.0 127.00 46.0 VERTICAL

46.0

46.0

7.7

10.0 QP

36.00

549.920000

918.520000

VERTICAL

269.00 VERTICAL

163.00

100.0

100.0

Report No.: CHTEW21110222 Page: 31 of 33 Issued: 2021-11-26

TEST DATA FOR 1 GHz ~ 25 GHz

Test	chanı	nel		CH00			Polari	ty		Horizontal	
	Mark	I	Frequency(MHz)	Reading(dBuV/m)	Antenna (dB)	Cable(dB)	Preamp(dB)I	Level(dBuV/m)	Limit(dBuV/m)	Over limit Remark	Ī
		1	1220	45.92	25. 72	3.9	36.62	38.92	74	-35.08 Peak	
		2	2212.88	38. 37	28. 17	5. 32	37.41	34.45	74	-39.55 Peak	
		3	3599.9	47.41	29.4	6.91	36.93	46.79	74	-27.21 Peak	
		4	9609.3	40.41	39. 24	11.93	37.02	54.56	74	-19.44 Peak	
	-	5	9609.3	23. 69	39. 24	11.93	37.02	37. 84	54	1 -16.16 Average	<u> </u>
Test	chanı			23. 69 CH00	39. 24	11.93	Polari			Vertical	
Test	chani Mark	nel					Polari	ty			i I
Test		nel		CH00	Antenna (dB)	Cable(dB)	Polari	ty	Limit(dBuV/m)	Vertical Over limit Remark	
Test		nel	requency(MHz)	CH00 Reading(dBuV/m) 48.37	Antenna (dB) 25.72	Cable(dB) 3.9	Polari Preamp(dB) L 36.62	ty Level(dBuV/m)	Limit(dBuV/m)	Vertical Over limit Remark -32.63 Peak	
Test		nel	requency(MHz) 1220	CH00 Reading(dBuV/m) 48.37	Antenna (dB) 25. 72 28. 12	Cable(dB) 3.9	Preamp(dB) I 36.62 37.42	ty Level(dBuV/m) 41.37	Limit(dBuV/m) 74 74	Vertical Over limit Remark -32.63 Peak -39.63 Peak	
Test		nel	Frequency(MHz) 1220 2242,25	CH00 Reading (dBuV/m) 48. 37 38. 31	Antenna (dB) 25. 72 28. 12 29. 4	Cable(dB) 3.9 5.36 6.91	Preamp(dB) I 36.62 37.42 36.93	ty Level(dBuV/m) 41.37 34.37	Limit(dBuV/m) 74 74 74	Vertical Over limit Remark -32.63 Peak -39.63 Peak -20.64 Peak	+ - -

est cha	nnel		CH39			Pola	rity		Hor	izontal
	Mark	Frequency MHz	Reading	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
	1	1220.00	45.92	25.72	3.90	36.62	38.92	74.00	-35.08	Peak
	2	2212.88	38.37	28.17	5.32	37.41	34.45	74.00	-39.55	Peak
	3	3657.79	44.90	29.40	6.97	37.02	44.25	74.00	-29.75	Peak
	4	9763.82	38.99	39.60	11.61	36.27	53.93	74.00	-20.07	Peak
est cha	nnel		CH39			Pola	rity		Vert	ical
Mark	Fre	equency(MHz) Rea	nding(dBuV/m)	Antenna (dB)	Cable(dB)	Preamp(dB) Level (dBuV/	n) Limit(dB	ıV/m)Over	limit Remark
	1	1220	48.37	25.72	3.9	36.6	2 41.	37	74	-32.63 Peak
	2	2242. 25	38.31	28.12	5. 36	37.43	2 34.	37	74	-39.63 Peak
	3	3657.79	51.03	29.4	6.97	37.0	2 50.3	38	74	-23.62 Peak
	4	9763.82	40.58	39.6	11.61	36. 2	7 55.	52	74	-18. 48 Peak
	5	9763.82	24.65	39.6	11.61	36. 2	7 39. 9	50	54	-14.41 Average

t chan	nel	l	CH78			Polar	ity		Horizont	:al
Mark	F	requency(MHz)	Reading(dBuV/m)	Antenna (dB)	Cable(dB)	Preamp(dB)	Level(dBuV/m) L	.imit(dBuV/m	Over limit	Remark
	1	1220	45.92	25.72	3.9	36.62	38.92	74	4 -35.08	Peak
	2	2212.88	38.37	28.17	5.32	37.41	34.45	74	4 -39.55	Peak
	3	3716.61	42.31	29. 43	7.03	37.09	41.68	74	-32.32	Peak
	4	9920.83	40.35	39.54	12	37.2	54.69	74	-19.31	Peak
	5	9920.83	23.82	39.54	12	37.2	38.16	54	1 -15.84	Average
t chan	nol		CH78	1	1	Polar	itv		Vortical	
t chan			CH78		- ()	Polar	-		Vertical	
t chan			CH78 Reading(dBuV/m)	Antenna (dB)	Cable(dB)	-	-			 Remark
_			Reading(dBuV/m)			Preamp(dB)	Level(dBuV/m) L		Over limit	
_		Frequency(MHz)	Reading(dBuV/m)	25.72	3.9	Preamp(dB) 36.62	Level (dBuV/m) L	 _imit(dBuV/m) Over limit 4 -32.63	Peak
_		Frequency (MHz)	Reading (dBuV/m) 48.37 38.31	25. 72 28. 12	3. 9 5. 36	Preamp(dB) 36.62 37.42	Level (dBuV/m) L	 _imit(dBuV/m) 79) Over limit 4 -32.63 4 -39.63	Peak Peak
_		Frequency(MHz) 1220 2242.25	Reading (dBuV/m) 48.37 38.31 41.81	25. 72 28. 12 31. 58	3. 9 5. 36 8. 77	Preamp(dB) 36.62 37.42 35.21	Level (dBuV/m) I 41.37 34.37 46.95) Over limit 4 -32.63 4 -39.63 4 -27.05	Peak Peak Peak


Report No.: CHTEW21110222 Page: 32 of 33 Issued: 2021-11-26

6. TEST SETUP PHOTOS

Radiated Emission







Report No.: CHTEW21110222 Page: 33 of 33 Issued: 2021-11-26

AC Conducted Emission



7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No. : CHTEW21110221

8. APPENDIX REPORT

Project No.: SHT2111022701EW Radio Specification: Bluetooth EDR

APPENDIX REPORT

Project No.	SHT2111022701EW	Radio Specification	Bluetooth EDR
Test sample No.	YPHT21110227002	Model No.	HERO 600+
Start test date	2021-11-24	Finish date	2021-11-24
Temperature	23.4℃	Humidity	28%
Test Engineer	Xiaoqin Li	Auditor	Xiaodong Zheo


Appendix clause	Test item	Result
А	Peak Output Power	PASS
В	20 dB Bandwidth	PASS
С	99% Occupied Bandwidth	PASS
D	Carrier Frequencies Separation	PASS
Е	Hopping Channel Number	PASS
F	Dwell Time	PASS
G	Duty Cycle Correction Factor (DCCF)	PASS
Н	Band edge and Spurious Emissions(coducted)	PASS


Project No.: SHT2111022701EW Radio Specification: Bluetooth EDR


Appendix A: Peak Output Power

Modulation type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
	00	5.03	4.98		
GFSK	39	4.05	4.02	≤ 30.00	Pass
	78	3.07	3.04		
	00	5.02	499		
π/4DQPSK	39	3.85	3.79	≤ 21.00	Pass
	78	2.55	2.50		
	00	5.33	5.31		
8DPSK	39	4.20	4.16	≤ 21.00	Pass
	78	2.86	2.87		

Project No.: SHT2111022701EW Radio Specification: Bluetooth EDR










Appendix B : 20 dB Bandwidth

Modulation type	Channel	20 dB Bandwidth (kHz)	dwidth (kHz) Limit (kHz)	
	00	980.00		
GFSK	39	932.50	-	Pass
	78	927.50		
	00	1307.50		
π/4DQPSK	39	1302.50	-	Pass
	78	1287.50		
	00	1300.00		
8DPSK	39	1295.00	-	Pass
	78	1287.50		










Appendix C: 99% Occupied Bandwidth

Modulation type	Channel	99% Occupied Bandwidth (MHz) Limit (MHz)		Result
	00	0.95		
GFSK	39	0.93	-	Pass
	78	0.92		
	00	1.19		
π/4DQPSK	39	1.18	-	Pass
	78	1.17		
	00	1.19		
8DPSK	39	1.18	-	Pass
	78	1.17		







Appendix D: Carrier Frequencies Separation

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (kHz) *	Result
GFSK	39	1.00	≥980.00	Pass
π/4DQPSK	39	1.00	≥871.67	Pass
8DPSK	39	1.00	≥866.67	Pass


Note:

^{*:} GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the appendix B. $\pi/4DQPSK$ limit = 2/3 * The maximum 20 dB Bandwidth for $\pi/4DQPSK$ modulation on the appendix B. 8DPSK limit = 2/3 * The maximum 20 dB Bandwidth for 8DPSK modulation on the appendix B




Appendix E: Hopping Channel Number


Modulation type	Channel number	Limit	Result
GFSK	79		
π/4DQPSK	79	≥15.00	Pass
8DPSK	79		





Appendix F: Dwell Time


Modulation type	Packet	Burst Width [ms]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
	DH1	0.37	316	0.12		
GFSK	DH3	1.63	159	0.26	≤ 0.40	Pass
	DH5	2.87	113	0.33		
	2DH1	0.38	317	0.12		
π/4DQPSK	2DH3	1.63	158	0.26	≤ 0.40	Pass
	2DH5	2.88	114	0.33		
	3DH1	0.38	313	0.12		
8DPSK	3DH3	1.63	161	0.26	≤ 0.40	Pass
	3DH5	2.88	113	0.33		

















Appendix G: Duty Cycle Correction Factor (DCCF)


DCCF Calculate Formula					
DCCF=20 * Log(duty cycle) = 20 * Log(T _{on time} / T _{period})					
Modulation type	Test Frequency (MHz)	T _{on time} for single burst [ms]	T _{period} [ms]	Burst Quantity	DCCF [dB]
GFSK	2441	2.86	100	1	-30.87
π/4 DQPSK	2441	2.86	100	1	-30.87
8DPSK	2441	2.86	100	1	-30.87





Appendix H: Band edge and Spurious Emissions (conducted)








































-----End of Report-----