

FCC RF Test Report

(900MHz)

Applicant: Autel Robotics Co., Ltd.

Address of Applicant: 18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China

Equipment Under Test (EUT)

Product Name: Autel Tracker

Model No.: DFAT-1

Trade Mark: 

FCC ID: 2AGNTDFAT240958A

Applicable Standards: FCC CFR Title 47 Part 15C (§15.247)

Date of Sample Receipt: 06 Sep., 2022

Date of Test: 07 Sep., to 28 Sep., 2022

Date of Report Issued: 15 Nov., 2022

Test Result: PASS

Tested by:
Test Engineer**Date:**

15 Nov., 2022

Reviewed by:
Project Engineer**Date:**

15 Nov., 2022

Approved by:
Manager**Date:**

15 Nov., 2022

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	29 Sep., 2022	Original
01	15 Nov., 2022	Update page 4, 12

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions from the Method	5
3.7 Laboratory Facility	5
3.8 Laboratory Location.....	5
3.9 Test Instruments List	6
4 Measurement Setup and Procedure	7
4.1 Test Channel	7
4.2 Test Setup	7
4.3 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and Data Summary.....	10
5.1.2 Test Limit.....	11
5.2 Antenna Requirement	12
5.3 AC Power Line Conducted Emission	13
5.4 Emissions in Restricted Frequency Bands.....	15
5.5 Emissions in Non-restricted Frequency Bands	63

3 General Information

3.1 Client Information

Applicant:	Autel Robotics Co., Ltd.
Address:	18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China
Manufacturer:	Autel Robotics Co., Ltd.
Address:	18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong, 518055, China
Factory:	Autel Robotics Co., Ltd. Guangming Branch
Address:	No.701, Jixie Factory, Building 4, Yanxiang Technology Industrial Park, Gaoxin Road, Dongzhou Community, Guangming street, Guangming district, Shenzhen, Guangdong, China

3.2 General Description of E.U.T.

Product Name:	Autel Tracker
Model No.:	DFAT-1
Operation Frequency:	904.0MHz~926.0MHz
Channel Numbers:	904.0MHz~926.0MHz: 23 for 1.4MHz Bandwidth 13 for 10 MHz Bandwidth 3 for 20 MHz Bandwidth
Channel Separation:	1MHz
Bandwidth:	1.4MHz, 10MHz, 20MHz
Modulation Technology:	QPSK and 16QAM
Antenna Type:	ANT1: Directional antenna ANT2: Omnidirectional antenna
Antenna Gain:	ANT1: 11.2 dBi (declare by applicant) ANT2: 1.77 dBi (declare by applicant)
Antenna Transmit Mode:	MIMO (2TX, 2RX)
Power Supply:	Rechargeable Li-ion Battery DC22.2V, 6550mAh
AC Adapter:	Adapter 1 Model: DF_CHARGER Input: AC100-240V, 50/60Hz, 4.0A Output: 26.4V, 7A Adapter 2 Model: DF_CHARGER Input: AC100-240V, 50/60Hz, 4.0A Output: 26.4V, 7A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

3.3 Test Mode and Environment

Test Mode:	
Transmitting mode:	Keep the EUT in continuous transmitting with modulation
Remark: For AC power line conducted emission and radiated spurious emission (below 1GHz), pre-scan 1.4M-QPSK, 10M-QPSK, 20M-QPSK, 1.4M-16QAM, 10M-16QAM, 20M-16QAM Bandwidth and modulation mode, found 1.4M-QPSK modulation mode was worse case mode. The report only reflects the test data of worst mode.	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar

3.4 Description of Test Auxiliary Equipment

The EUT has been tested as an independent unit.

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Conducted Emission for LISN (9kHz ~ 150kHz)	±3.11 dB
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.62 dB
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	±4.45 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	±5.34 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	±5.34 dB
Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.	

3.6 Additions to, Deviations, or Exclusions from the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L15527**

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	03-07-2022	03-06-2023
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	03-08-2022	03-07-2023
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	04-07-2022	04-06-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-20-2022	01-19-2023
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-20-2022	01-19-2023
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	03-30-2022	03-29-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	03-05-2022	03-04-2023
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-20-2022	01-19-2023
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	10-27-2021	10-26-2022
Coaxial Cable (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-20-2022	01-19-2023
Coaxial Cable (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-20-2022	01-19-2023
Coaxial Cable (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	01-20-2022	01-19-2023
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESR3	WXJ003-2	07-12-2022	07-11-2023
LISN	Schwarzbeck	NSLK 8127	QCJ001-13	02-24-2022	02-23-2023
LISN	Rohde & Schwarz	ESH3-Z5	WXJ005-1	03-30-2022	03-29-2023
LISN Coaxial Cable (9kHz ~ 30MHz)	JYTSZ	JYTCE-1G-NN-2M	WXG003-1	02-24-2022	02-23-2023
RF Switch	TOP PRECISION	RSU0301	WXG003	N/A	
Test Software	AUDIX	E3	Version: 6.110919b		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	10-27-2021	10-26-2022
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	
Temperature Humidity Chamber	ZHONG ZHI	CZ-A-80D	WXJ032-3	03-19-2021	03-18-2023
Power Detector Box	MWRFTTEST	MW100-PSB	WXJ007-4	11-19-2021	11-18-2022
RF Control Unit	MWRFTTEST	MW100-RFCB	WXG006	N/A	
Test Software	MWRFTTEST	MTS 8310	Version: 2.0.0.0		

4 Measurement Setup and Procedure

4.1 Test Channel


According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

900MHz:

Operation Frequency each of channel for 1.4MHz Bandwidth					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	904MHz				
2	905MHz	12	915MHz	22	925MHz
3	906MHz			23	926MHz
Note:					
1. Channel 1, 12 & 19 selected as Lowest, Middle and Highest channel.					
Operation Frequency each of channel for 10MHz Bandwidth					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	909MHz				
2	910MHz	6	915MHz	12	920MHz
3	911MHz			13	921MHz
Note:					
1. Channel 1, 6 & 13 selected as Lowest, Middle and Highest channel.					
Operation Frequency each of channel for 20MHz Bandwidth					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	914	2	915	3	916
Note:					
1. Channel 1, 2 & 3 selected as Lowest, Middle and Highest channel.					

4.2 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 1GHz (3m SAC)



Above 1GHz (3m SAC)



3) Conducted test method



4.3 Test Procedure

Test method	Test step
Conducted emission	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Radiated emission	For below 1GHz: 1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: 1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. 2. EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. 3. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	1. The Wi-Fi antenna port of EUT was connected to the test port of the test system through an RF cable. 2. The EUT is keeping in continuous transmission mode and tested in all modulation modes. 3. Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203 15.247 (b)(4)	See Section 5.2	Pass
AC Power Line Conducted Emission	15.207	See Section 5.3	Pass
Duty Cycle	ANSI C63.10-2013	Appendix – 900MHz	Pass
Conducted Output Power	15.247 (b)(3)	Appendix – 900MHz	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Appendix – 900MHz	Pass
Power Spectral Density	15.247 (e)	Appendix – 900MHz	Pass
Band-edge Emission Conduction Spurious Emission	15.247 (d)	Appendix – 900MHz	Pass
Emissions in Restricted Frequency Bands	15.205 15.247 (d)	See Section 5.4	Pass
Emissions in Non-restricted Frequency Bands	15.209 15.247(d)	See Section 5.5	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by “RF Output Power” and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

5.1.2 Test Limit


Test items	Limit																														
AC Power Line Conducted Emission	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>Quasi-Peak</th><th>Average</th></tr><tr><td>0.15 – 0.5</td><td>66 to 56 Note 1</td><td>56 to 46 Note 1</td></tr><tr><td>0.5 – 5</td><td>56</td><td>46</td></tr><tr><td>5 – 30</td><td>60</td><td>50</td></tr></table> Note 1: The limit level in dBµV decreases linearly with the logarithm of frequency. Note 2: The more stringent limit applies at transition frequencies.	Frequency (MHz)	Limit (dBµV)		Quasi-Peak	Average	0.15 – 0.5	66 to 56 Note 1	56 to 46 Note 1	0.5 – 5	56	46	5 – 30	60	50																
Frequency (MHz)	Limit (dBµV)																														
	Quasi-Peak	Average																													
0.15 – 0.5	66 to 56 Note 1	56 to 46 Note 1																													
0.5 – 5	56	46																													
5 – 30	60	50																													
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.																														
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.																														
99% Occupied Bandwidth	N/A																														
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.																														
Band-edge Emission Conduction Spurious Emission	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).																														
Emissions in Restricted Frequency Bands Emissions in Non-restricted Frequency Bands	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBµV/m)</th><th rowspan="2">Detector</th></tr><tr><th>@ 3m</th><th>@ 10m</th></tr><tr><td>30 – 88</td><td>40.0</td><td>30.0</td><td>Quasi-peak</td></tr><tr><td>88 – 216</td><td>43.5</td><td>33.5</td><td>Quasi-peak</td></tr><tr><td>216 – 960</td><td>46.0</td><td>36.0</td><td>Quasi-peak</td></tr><tr><td>960 – 1000</td><td>54.0</td><td>44.0</td><td>Quasi-peak</td></tr></table> Note: The more stringent limit applies at transition frequencies. <table><tr><th rowspan="2">Frequency</th><th colspan="2">Limit (dBµV/m) @ 3m</th></tr><tr><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>54.0</td><td>74.0</td></tr></table> Note: The measurement bandwidth shall be 1 MHz or greater.	Frequency (MHz)	Limit (dBµV/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dBµV/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Frequency (MHz)	Limit (dBµV/m)		Detector																												
	@ 3m	@ 10m																													
30 – 88	40.0	30.0	Quasi-peak																												
88 – 216	43.5	33.5	Quasi-peak																												
216 – 960	46.0	36.0	Quasi-peak																												
960 – 1000	54.0	44.0	Quasi-peak																												
Frequency	Limit (dBµV/m) @ 3m																														
	Average	Peake																													
Above 1 GHz	54.0	74.0																													

5.2 Antenna Requirement

Standard Requirement:	FCC Part 15 C Section 15.203/15.247 (b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247 (b)(4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The antenna 1 is an o directional antenna, the antenna 2 is an omnidirectional antenna ,the best case gain of the antenna 1 is 11.2 dBi and the best case gain of the antenna 2 is 1.77 dBi . See product internal photos for details. Note: <i>Unequal antenna gains, with equal transmit powers. The transmit signals are correlated, then</i> $\text{Directional gain} = 10 \log[(10^{G_1/20} + 10^{G_2/20})^2 / N_{\text{ant}}]$ So Directional gain = 10.72dBi.	

5.3 AC Power Line Conducted Emission

Product name:	Autel Tracker	Product model:	DFAT-1
Test by:	Mike	Test mode:	900MHz mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz		




	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	36.00	0.04	0.01	36.05	65.78	-29.73	QP
2	0.174	7.76	0.05	0.01	7.82	54.77	-46.95	Average
3	0.234	27.36	0.05	0.02	27.43	62.30	-34.87	QP
4	0.471	11.33	0.05	0.03	11.41	46.49	-35.08	Average
5	0.471	33.10	0.05	0.03	33.18	56.49	-23.31	QP
6	9.603	42.73	0.21	0.12	43.06	60.00	-16.94	QP
7	9.705	32.94	0.22	0.12	33.28	50.00	-16.72	Average
8	15.718	18.08	0.30	0.15	18.53	50.00	-31.47	Average
9	16.750	30.61	0.31	0.16	31.08	60.00	-28.92	QP
10	25.727	10.36	0.38	0.21	10.95	50.00	-39.05	Average
11	28.755	14.25	0.40	0.20	14.85	50.00	-35.15	Average
12	28.755	30.74	0.40	0.20	31.34	60.00	-28.66	QP

Remark:

1. Level = Read level + LISN Factor + Cable Loss.

Product name:	Autel Tracker	Product model:	DFAT-1
Test by:	Mike	Test mode:	900MHz mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz		



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	6.75	0.06	0.01	6.82	56.00	-49.18	Average
2	0.150	34.98	0.06	0.01	35.05	66.00	-30.95	QP
3	0.202	27.64	0.05	0.04	27.73	63.54	-35.81	QP
4	0.471	7.93	0.04	0.03	8.00	46.49	-38.49	Average
5	0.471	31.89	0.04	0.03	31.96	56.49	-24.53	QP
6	9.552	43.86	0.20	0.12	44.18	60.00	-15.82	QP
7	9.705	33.41	0.21	0.12	33.74	50.00	-16.26	Average
8	16.661	13.51	0.29	0.16	13.96	50.00	-36.04	Average
9	16.661	33.31	0.29	0.16	33.76	60.00	-26.24	QP
10	20.056	14.51	0.33	0.19	15.03	50.00	-34.97	Average
11	26.001	14.23	0.41	0.21	14.85	50.00	-35.15	Average
12	30.000	34.67	0.46	0.22	35.35	60.00	-24.65	QP


Remark:

1. Level = Read level + LISN Factor + Cable Loss.

5.4 Emissions in Restricted Frequency Bands

960-1000:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.360	14.40	39.82	25.42	54.00	14.18	PK	Vertical
2	979.640	15.24	40.78	25.54	54.00	13.22	PK	Vertical
3	987.800	14.20	39.91	25.71	54.00	14.09	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	971.280	14.51	39.95	25.44	54.00	14.05	PK	Horizontal
2	983.120	15.02	40.63	25.61	54.00	13.37	PK	Horizontal
3	992.120	14.16	39.91	25.75	54.00	14.09	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.640	15.29	40.71	25.42	54.00	13.29	PK	Vertical
2	983.840	14.45	40.07	25.62	54.00	13.93	PK	Vertical
3	993.520	14.24	39.98	25.74	54.00	14.02	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	971.080	14.34	39.78	25.44	54.00	14.22	PK	Horizontal
2	982.480	14.37	39.96	25.59	54.00	14.04	PK	Horizontal
3	990.400	14.62	40.38	25.76	54.00	13.62	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.440	13.91	39.33	25.42	54.00	14.67	PK	Vertical
2	982.360	14.34	39.93	25.59	54.00	14.07	PK	Vertical
3	993.280	14.69	40.43	25.74	54.00	13.57	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	970.720	14.02	39.46	25.44	54.00	14.54	PK	Horizontal
2	982.800	14.08	39.68	25.60	54.00	14.32	PK	Horizontal
3	992.800	16.08	41.82	25.74	54.00	12.18	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.360	15.24	40.64	25.40	54.00	13.36	PK	Vertical
2	980.440	14.83	40.38	25.55	54.00	13.62	PK	Vertical
3	991.800	13.95	39.70	25.75	54.00	14.30	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	971.360	14.19	39.63	25.44	54.00	14.37	PK	Horizontal
2	981.040	16.23	41.79	25.56	54.00	12.21	PK	Horizontal
3	991.560	14.45	40.20	25.75	54.00	13.80	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

1000-1240:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1051.60	22.92	30.19	53.11	74.00	20.89	PK	Vertical
2	1051.60	12.55	30.19	42.74	54.00	11.26	AV	Vertical
3	1114.00	12.34	30.56	42.90	54.00	11.10	AV	Vertical
4	1114.00	23.00	30.56	53.56	74.00	20.44	PK	Vertical
5	1178.32	23.22	30.72	53.94	74.00	20.06	PK	Vertical
6	1178.32	12.37	30.72	43.09	54.00	10.91	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1048.96	23.65	30.17	53.82	74.00	20.18	PK	Horizontal
2	1048.96	12.56	30.17	42.73	54.00	11.27	AV	Horizontal
3	1114.48	12.40	30.56	42.96	54.00	11.04	AV	Horizontal
4	1114.48	22.81	30.56	53.37	74.00	20.63	PK	Horizontal
5	1180.48	23.48	30.73	54.21	74.00	19.79	PK	Horizontal
6	1180.48	12.40	30.73	43.13	54.00	10.87	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1057.36	22.78	30.23	53.01	74.00	20.99	PK	Vertical
2	1057.36	12.43	30.23	42.66	54.00	11.34	AV	Vertical
3	1119.04	12.38	30.57	42.95	54.00	11.05	AV	Vertical
4	1119.04	23.35	30.57	53.92	74.00	20.08	PK	Vertical
5	1182.16	24.25	30.73	54.98	74.00	19.02	PK	Vertical
6	1182.16	12.39	30.73	43.12	54.00	10.88	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1054.24	23.80	30.21	54.01	74.00	19.99	PK	Horizontal
2	1054.24	12.44	30.21	42.65	54.00	11.35	AV	Horizontal
3	1121.20	12.29	30.58	42.87	54.00	11.13	AV	Horizontal
4	1121.20	23.13	30.58	53.71	74.00	20.29	PK	Horizontal
5	1187.92	22.81	30.75	53.56	74.00	20.44	PK	Horizontal
6	1187.92	12.37	30.75	43.12	54.00	10.88	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1050.16	23.24	30.18	53.42	74.00	20.58	PK	Vertical
2	1050.16	12.63	30.18	42.81	54.00	11.19	AV	Vertical
3	1111.36	12.41	30.55	42.96	54.00	11.04	AV	Vertical
4	1111.36	23.41	30.55	53.96	74.00	20.04	PK	Vertical
5	1165.84	23.10	30.69	53.79	74.00	20.21	PK	Vertical
6	1165.84	12.48	30.69	43.17	54.00	10.83	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1051.60	23.24	30.19	53.43	74.00	20.57	PK	Horizontal
2	1051.60	12.61	30.19	42.80	54.00	11.20	AV	Horizontal
3	1117.36	12.37	30.57	42.94	54.00	11.06	AV	Horizontal
4	1117.36	23.01	30.57	53.58	74.00	20.42	PK	Horizontal
5	1199.20	24.30	30.78	55.08	74.00	18.92	PK	Horizontal
6	1199.20	12.58	30.78	43.36	54.00	10.64	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1056.64	22.80	30.23	53.03	74.00	20.97	PK	Vertical
2	1056.64	12.53	30.23	42.76	54.00	11.24	AV	Vertical
3	1114.72	12.32	30.56	42.88	54.00	11.12	AV	Vertical
4	1114.72	22.72	30.56	53.28	74.00	20.72	PK	Vertical
5	1177.36	23.43	30.72	54.15	74.00	19.85	PK	Vertical
6	1177.36	12.34	30.72	43.06	54.00	10.94	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	1.4M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1047.52	23.66	30.16	53.82	74.00	20.18	PK	Horizontal
2	1047.52	12.58	30.16	42.74	54.00	11.26	AV	Horizontal
3	1111.36	12.22	30.55	42.77	54.00	11.23	AV	Horizontal
4	1111.36	22.64	30.55	53.19	74.00	20.81	PK	Horizontal
5	1181.68	23.60	30.73	54.33	74.00	19.67	PK	Horizontal
6	1181.68	12.38	30.73	43.11	54.00	10.89	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

960-1000:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.200	14.67	40.07	25.40	54.00	13.93	PK	Vertical
2	981.880	15.32	40.90	25.58	54.00	13.10	PK	Vertical
3	993.160	14.48	40.22	25.74	54.00	13.78	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.200	14.43	39.83	25.40	54.00	14.17	PK	Horizontal
2	978.960	14.96	40.49	25.53	54.00	13.51	PK	Horizontal
3	989.600	14.19	39.94	25.75	54.00	14.06	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.240	14.68	40.10	25.42	54.00	13.90	PK	Vertical
2	979.160	15.33	40.86	25.53	54.00	13.14	PK	Vertical
3	989.080	15.27	41.01	25.74	54.00	12.99	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	970.320	15.06	40.49	25.43	54.00	13.51	PK	Horizontal
2	980.200	16.32	41.86	25.54	54.00	12.14	PK	Horizontal
3	991.080	13.92	39.67	25.75	54.00	14.33	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.200	15.04	40.44	25.40	54.00	13.56	PK	Vertical
2	979.240	14.77	40.30	25.53	54.00	13.70	PK	Vertical
3	991.320	15.78	41.53	25.75	54.00	12.47	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.720	14.18	39.61	25.43	54.00	14.39	PK	Horizontal
2	982.040	14.53	40.11	25.58	54.00	13.89	PK	Horizontal
3	993.160	14.37	40.11	25.74	54.00	13.89	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	970.520	15.39	40.83	25.44	54.00	13.17	PK	Vertical
2	980.880	16.13	41.69	25.56	54.00	12.31	PK	Vertical
3	991.560	14.63	40.38	25.75	54.00	13.62	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.480	14.54	39.96	25.42	54.00	14.04	PK	Horizontal
2	979.320	14.26	39.79	25.53	54.00	14.21	PK	Horizontal
3	992.920	15.46	41.20	25.74	54.00	12.80	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

1000-1240:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1054.72	23.71	30.21	53.92	74.00	20.08	PK	Vertical
2	1054.72	12.73	30.21	42.94	54.00	11.06	AV	Vertical
3	1119.52	12.27	30.57	42.84	54.00	11.16	AV	Vertical
4	1119.52	23.73	30.57	54.30	74.00	19.70	PK	Vertical
5	1175.20	23.08	30.72	53.80	74.00	20.20	PK	Vertical
6	1175.20	12.30	30.72	43.02	54.00	10.98	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1059.76	23.31	30.25	53.56	74.00	20.44	PK	Horizontal
2	1059.76	12.31	30.25	42.56	54.00	11.44	AV	Horizontal
3	1115.92	12.40	30.56	42.96	54.00	11.04	AV	Horizontal
4	1115.92	23.40	30.56	53.96	74.00	20.04	PK	Horizontal
5	1179.04	23.48	30.73	54.21	74.00	19.79	PK	Horizontal
6	1179.04	12.33	30.73	43.06	54.00	10.94	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1049.92	23.14	30.18	53.32	74.00	20.68	PK	Vertical
2	1049.92	12.81	30.18	42.99	54.00	11.01	AV	Vertical
3	1113.04	12.38	30.55	42.93	54.00	11.07	AV	Vertical
4	1113.04	22.83	30.55	53.38	74.00	20.62	PK	Vertical
5	1176.16	23.59	30.72	54.31	74.00	19.69	PK	Vertical
6	1176.16	12.35	30.72	43.07	54.00	10.93	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1052.56	23.29	30.20	53.49	74.00	20.51	PK	Horizontal
2	1052.56	12.52	30.20	42.72	54.00	11.28	AV	Horizontal
3	1114.96	12.40	30.56	42.96	54.00	11.04	AV	Horizontal
4	1114.96	23.05	30.56	53.61	74.00	20.39	PK	Horizontal
5	1185.76	22.93	30.74	53.67	74.00	20.33	PK	Horizontal
6	1185.76	12.43	30.74	43.17	54.00	10.83	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1057.12	23.35	30.23	53.58	74.00	20.42	PK	Vertical
2	1057.12	12.67	30.23	42.90	54.00	11.10	AV	Vertical
3	1122.40	12.18	30.58	42.76	54.00	11.24	AV	Vertical
4	1122.40	22.71	30.58	53.29	74.00	20.71	PK	Vertical
5	1185.52	23.10	30.74	53.84	74.00	20.16	PK	Vertical
6	1185.52	12.48	30.74	43.22	54.00	10.78	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1059.52	23.41	30.24	53.65	74.00	20.35	PK	Horizontal
2	1059.52	12.53	30.24	42.77	54.00	11.23	AV	Horizontal
3	1110.64	12.44	30.55	42.99	54.00	11.01	AV	Horizontal
4	1110.64	22.68	30.55	53.23	74.00	20.77	PK	Horizontal
5	1173.04	23.29	30.71	54.00	74.00	20.00	PK	Horizontal
6	1173.04	12.32	30.71	43.03	54.00	10.97	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1056.64	22.99	30.23	53.22	74.00	20.78	PK	Vertical
2	1056.64	12.38	30.23	42.61	54.00	11.39	AV	Vertical
3	1126.24	12.40	30.59	42.99	54.00	11.01	AV	Vertical
4	1126.24	23.11	30.59	53.70	74.00	20.30	PK	Vertical
5	1185.04	23.24	30.74	53.98	74.00	20.02	PK	Vertical
6	1185.04	12.26	30.74	43.00	54.00	11.00	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	10M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1050.64	23.32	30.18	53.50	74.00	20.50	PK	Horizontal
2	1050.64	12.78	30.18	42.96	54.00	11.04	AV	Horizontal
3	1120.00	12.05	30.57	42.62	54.00	11.38	AV	Horizontal
4	1120.00	23.06	30.57	53.63	74.00	20.37	PK	Horizontal
5	1203.28	23.49	30.79	54.28	74.00	19.72	PK	Horizontal
6	1203.28	12.49	30.79	43.28	54.00	10.72	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

960-1000:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.440	16.12	41.52	25.40	54.00	12.48	PK	Vertical
2	977.760	16.27	41.79	25.52	54.00	12.21	PK	Vertical
3	989.240	13.42	39.16	25.74	54.00	14.84	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	967.640	15.15	40.54	25.39	54.00	13.46	PK	Horizontal
2	979.960	15.92	41.46	25.54	54.00	12.54	PK	Horizontal
3	990.240	13.94	39.70	25.76	54.00	14.30	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	968.200	14.95	40.35	25.40	54.00	13.65	PK	Vertical
2	980.680	16.34	41.89	25.55	54.00	12.11	PK	Vertical
3	990.960	14.25	40.00	25.75	54.00	14.00	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	967.960	15.72	41.12	25.40	54.00	12.88	PK	Horizontal
2	979.040	14.98	40.51	25.53	54.00	13.49	PK	Horizontal
3	988.920	15.93	41.67	25.74	54.00	12.33	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.000	13.60	39.01	25.41	54.00	14.99	PK	Vertical
2	980.480	15.75	41.30	25.55	54.00	12.70	PK	Vertical
3	990.960	13.71	39.46	25.75	54.00	14.54	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Pre-amplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	969.600	14.79	40.21	25.42	54.00	13.79	PK	Horizontal
2	980.680	15.85	41.40	25.55	54.00	12.60	PK	Horizontal
3	991.840	14.38	40.13	25.75	54.00	13.87	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	971.200	14.90	40.34	25.44	54.00	13.66	PK	Vertical
2	980.040	16.03	41.57	25.54	54.00	12.43	PK	Vertical
3	992.080	15.14	40.89	25.75	54.00	13.11	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List


NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	970.120	14.67	40.10	25.43	54.00	13.90	PK	Horizontal
2	980.280	14.84	40.39	25.55	54.00	13.61	PK	Horizontal
3	992.160	13.87	39.62	25.75	54.00	14.38	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

1000-1240:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1054.48	24.06	30.21	54.27	74.00	19.73	PK	Vertical
2	1054.48	12.62	30.21	42.83	54.00	11.17	AV	Vertical
3	1112.80	12.30	30.55	42.85	54.00	11.15	AV	Vertical
4	1112.80	22.88	30.55	53.43	74.00	20.57	PK	Vertical
5	1186.96	23.08	30.75	53.83	74.00	20.17	PK	Vertical
6	1186.96	12.45	30.75	43.20	54.00	10.80	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1047.76	23.17	30.16	53.33	74.00	20.67	PK	Horizontal
2	1047.76	12.31	30.16	42.47	54.00	11.53	AV	Horizontal
3	1115.68	12.15	30.56	42.71	54.00	11.29	AV	Horizontal
4	1115.68	22.81	30.56	53.37	74.00	20.63	PK	Horizontal
5	1183.84	23.10	30.74	53.84	74.00	20.16	PK	Horizontal
6	1183.84	12.67	30.74	43.41	54.00	10.59	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1051.60	23.55	30.19	53.74	74.00	20.26	PK	Vertical
2	1051.60	12.58	30.19	42.77	54.00	11.23	AV	Vertical
3	1125.04	12.24	30.59	42.83	54.00	11.17	AV	Vertical
4	1125.04	22.94	30.59	53.53	74.00	20.47	PK	Vertical
5	1190.80	22.76	30.76	53.52	74.00	20.48	PK	Vertical
6	1190.80	12.49	30.76	43.25	54.00	10.75	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M QPSK Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1061.44	23.84	30.26	54.10	74.00	19.90	PK	Horizontal
2	1061.44	12.61	30.26	42.87	54.00	11.13	AV	Horizontal
3	1123.84	12.17	30.58	42.75	54.00	11.25	AV	Horizontal
4	1123.84	22.69	30.58	53.27	74.00	20.73	PK	Horizontal
5	1193.44	22.93	30.76	53.69	74.00	20.31	PK	Horizontal
6	1193.44	12.42	30.76	43.18	54.00	10.82	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1042.48	23.75	30.13	53.88	74.00	20.12	PK	Vertical
2	1042.48	12.57	30.13	42.70	54.00	11.30	AV	Vertical
3	1115.44	12.23	30.56	42.79	54.00	11.21	AV	Vertical
4	1115.44	22.60	30.56	53.16	74.00	20.84	PK	Vertical
5	1181.44	23.64	30.73	54.37	74.00	19.63	PK	Vertical
6	1181.44	12.37	30.73	43.10	54.00	10.90	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1052.80	22.88	30.20	53.08	74.00	20.92	PK	Horizontal
2	1052.80	12.44	30.20	42.64	54.00	11.36	AV	Horizontal
3	1124.32	12.17	30.58	42.75	54.00	11.25	AV	Horizontal
4	1124.32	22.72	30.58	53.30	74.00	20.70	PK	Horizontal
5	1189.12	22.95	30.75	53.70	74.00	20.30	PK	Horizontal
6	1189.12	12.48	30.75	43.23	54.00	10.77	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1055.92	23.07	30.22	53.29	74.00	20.71	PK	Vertical
2	1055.92	12.46	30.22	42.68	54.00	11.32	AV	Vertical
3	1124.32	12.10	30.58	42.68	54.00	11.32	AV	Vertical
4	1124.32	22.61	30.58	53.19	74.00	20.81	PK	Vertical
5	1193.44	22.80	30.76	53.56	74.00	20.44	PK	Vertical
6	1193.44	12.31	30.76	43.07	54.00	10.93	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	20M 16QAM Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	1052.80	23.92	30.20	54.12	74.00	19.88	PK	Horizontal
2	1052.80	12.45	30.20	42.65	54.00	11.35	AV	Horizontal
3	1116.64	12.26	30.56	42.82	54.00	11.18	AV	Horizontal
4	1116.64	23.55	30.56	54.11	74.00	19.89	PK	Horizontal
5	1180.00	23.13	30.73	53.86	74.00	20.14	PK	Horizontal
6	1180.00	12.52	30.73	43.25	54.00	10.75	AV	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor)

5.5 Emissions in Non-restricted Frequency Bands

Below 1GHz:

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	900MHz mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	85.0045	54.27	36.68	-17.59	40.00	3.32	PK	Vertical
2	94.8995	52.06	36.73	-15.33	43.50	6.77	PK	Vertical
3	104.988	53.60	39.12	-14.48	43.50	4.38	PK	Vertical
4	124.972	59.77	42.24	-17.53	43.50	1.26	PK	Vertical
5	134.964	60.18	41.97	-18.21	43.50	1.53	PK	Vertical
6	191.812	51.12	35.37	-15.75	43.50	8.13	PK	Vertical


Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	QP Reading [dBμV/m]	Angle [°]	Verdict
1	125.014	-17.53	40.84	43.50	2.66	58.37	187.1	PASS
2	134.964	-18.21	40.20	43.50	3.30	58.41	189	PASS

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss - Preamplifier Factor)

Product Name:	Autel Tracker	Product Model:	DFAT-1
Test By:	Mike	Test mode:	900MHz mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz		



Suspected Data List

NO.	Freq. [MHz]	Reading[dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	124.972	49.54	32.01	-17.53	43.50	11.49	PK	Horizontal
2	134.964	51.60	33.39	-18.21	43.50	10.11	PK	Horizontal
3	175.029	53.62	36.25	-17.37	43.50	7.25	PK	Horizontal
4	235.466	53.87	39.50	-14.37	46.00	6.50	PK	Horizontal
5	293.769	55.61	42.45	-13.16	46.00	3.55	PK	Horizontal
6	350.035	46.61	35.05	-11.56	46.00	10.95	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss - Preamplifier Factor)

Above 1GHz

900M MIMO - 1.4M-QPSK						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1808.00	75.76	-21.46	54.30	74.00	19.70	Vertical
1808.00	77.68	-21.46	56.22	74.00	17.78	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1808.00	68.81	-21.46	47.35	54.00	6.65	Vertical
1808.00	68.95	-21.46	47.49	54.00	6.51	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1830.00	75.27	-21.25	54.02	74.00	19.98	Vertical
1830.00	77.42	-21.25	56.17	74.00	17.83	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1830.00	68.86	-21.25	47.61	54.00	6.39	Vertical
1830.00	69.44	-21.25	48.19	54.00	5.81	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1852.00	74.88	-21.02	53.86	74.00	20.14	Vertical
1852.00	77.90	-21.02	56.88	74.00	17.12	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
1852.00	68.53	-21.02	47.51	54.00	6.49	Vertical
1852.00	69.61	-21.02	48.59	54.00	5.41	Horizontal
Remark: 1. Level = Reading + Factor. 2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

-----End of report-----