

RF TEST REPORT

Applicant	Smawave Technology Co. ,Ltd
FCC ID	2AU8HSRP820
Product	Ruggedized Router
Brand	Smawave
Model	SRP820
Report No.	R2412A2016-R4
Issue Date	March 24, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15C (2024)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report.....	4
1.2. Test Facility	4
1.3. Testing Location.....	4
2. General Description of Equipment Under Test.....	5
2.1. Applicant and Manufacturer Information	5
2.2. General Information	5
3. Applied Standards.....	6
4. Test Configuration.....	7
5. Test Case Results.....	8
5.1. Maximum output power	8
5.2. 99% Bandwidth and 6dB Bandwidth	13
5.3. Band Edge	33
5.4. Power Spectral Density	46
5.5. Spurious RF Conducted Emissions.....	87
5.6. Unwanted Emission	107
5.7. Conducted Emission.....	154
6. Main Test Instruments.....	157
ANNEX A: The EUT Appearance.....	158
ANNEX B: Test Setup Photos.....	159

Summary of Measurement Results

Number	Test Case	Clause in FCC rules	Verdict
1	Maximum output power	15.247(b)(3)	PASS
2	99% Bandwidth and 6dB Bandwidth	15.247(a)(2) C63.10 6.9	PASS
3	Power spectral density	15.247(e)	PASS
4	Band Edge	15.247(d)	PASS
5	Spurious RF Conducted Emissions	15.247(d)	PASS
6	Unwanted Emissions	15.247(d), 15.205, 15.209	PASS
7	Conducted Emissions	15.207	PASS
Date of Testing: February 13, 2025 ~ February 18, 2025 Date of Sample Received: December 20, 2024			
Note: All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

2. General Description of Equipment Under Test

2.1. Applicant and Manufacturer Information

Applicant	Smawave Technology Co. ,Ltd
Applicant address	2/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China
Manufacturer	Smawave Technology Co. ,Ltd
Manufacturer address	2/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

2.2. General Information

EUT Description	
Model	SRP820
Lab internal SN	R2412A2016/S01
Hardware Version	V1.0
Software Version	20250312_01_SQXR6040_NDAC_V1.2.1
Power Supply	AC adapter
Antenna Type	External Antenna
Antenna Connector	SMA-J antenna (meet with the standard FCC Part 15.203 requirement)
Antenna Gain	4.50 dBi
Additional Beamforming Gain	NA
Direction Gain	Power: 4.50 dBi PSD: 7.51 dBi
Operating Frequency Range(s)	802.11b/g/n(HT20)/ax(HE20): 2412 ~ 2462 MHz 802.11n(HT40)/ax(HE40): 2422 ~ 2452 MHz
Modulation Type	802.11b: DSSS 802.11g/n: OFDM 802.11ax: OFDM
Max. Output Power	26.71 dBm
EUT Accessory	
Adapter	Manufacturer: Dongguan Sunun Power Co., Ltd Model: SA72-240300-A72-35A
Note: The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.	

3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15C (2024) Radio Frequency Devices

ANSI C63.10-2020+Cor.1-2023

Reference standard:

KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the loop antenna is vertical, the others are vertical and horizontal. and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Test Mode	Data Rate		
	Antenna 1	Antenna 2	CDD/MIMO
802.11b	1 Mbps	1 Mbps	1 Mbps
802.11g	6 Mbps	6 Mbps	6 Mbps
802.11n HT20	MCS0	MCS0	MCS8
802.11n HT40	MCS0	MCS0	MCS8
802.11ax HE20	MCS0	MCS0	MCS0
802.11ax HE40	MCS0	MCS0	MCS0

The worst case Antenna mode for each of the following tests for Wi-Fi:

Test Cases	Antenna 1	Antenna 2	MIMO
Maximum output power	O	O	O
6dB Bandwidth	O	--	--
Band Edge	O	--	--
Power Spectral Density	O	O	O
Spurious RF Conducted Emissions	O	--	--
Unwanted Emissions	--	--	O
Conducted Emission	--	--	O
Note: "O": test all bands			

5. Test Case Results

5.1. Maximum output power

Ambient Condition


Temperature	Relative humidity
15°C ~ 35°C	20% ~ 80%

Methods of Measurement

During the process of the testing, The EUT was connected to Power meter with a known loss. The EUT is max power transmission with proper modulation.

The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Test Setup



Limits

Rule Part 15.247 (b) (3) specifies that " For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz: 1 Watt."

Average Output Power	$\leq 1W$ (30dBm)
----------------------	-------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.44$ dB.

Test Results

Power Index							
Channel	802.11b	802.11g	802.11n HT20	802.11ax HE20	Channel	802.11n HT40	802.11ax HE40
CH1	24	24	24	24	CH3	24	24
CH6	24	24	24	24	CH6	24	24
CH11	24	24	24	24	CH9	24	24

Test Mode	Duty cycle	Duty cycle correction Factor (dB)
802.11b	0.702	1.54
802.11g	0.953	0.21
802.11n HT20	0.802	0.96
802.11n HT40	0.802	0.96
802.11ax HE20	0.802	0.96
802.11ax HE40	0.802	0.96
Note: when Duty cycle ≥ 0.98 , Duty cycle correction Factor not required.		

SISO Antenna 1

Test Mode	Carrier frequency (MHz)/ Channel	Average Power Measured (dBm)	Average Power with duty factor (dBm)	Limit (dBm)	Conclusion
802.11b	2412/CH 1	21.31	22.85	30	PASS
	2437/CH 6	21.80	23.34	30	PASS
	2462/CH11	21.71	23.24	30	PASS
802.11g	2412/CH 1	22.73	22.94	30	PASS
	2437/CH 6	23.09	23.30	30	PASS
	2462/CH11	23.08	23.29	30	PASS
802.11n HT20	2412/CH 1	21.42	22.38	30	PASS
	2437/CH 6	22.03	22.99	30	PASS
	2462/CH11	21.77	22.73	30	PASS
802.11n HT40	2422/CH3	22.78	23.74	30	PASS
	2437/CH6	22.27	23.23	30	PASS
	2452/CH9	22.16	23.11	30	PASS
802.11ax HE20	2412/CH 1	21.32	22.28	30	PASS
	2437/CH 6	21.68	22.64	30	PASS
	2462/CH11	21.93	22.89	30	PASS
802.11ax HE40	2422/CH3	22.36	23.32	30	PASS
	2437/CH6	22.21	23.17	30	PASS
	2452/CH9	21.32	22.28	30	PASS
Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor					

SISO Antenna 2

Test Mode	Carrier frequency (MHz)/ Channel	Average Power Measured (dBm)	Average Power with duty factor (dBm)	Limit (dBm)	Conclusion
802.11b	2412/CH 1	21.01	22.55	30	PASS
	2437/CH 6	21.66	23.20	30	PASS
	2462/CH11	21.57	23.11	30	PASS
802.11g	2412/CH 1	22.42	22.63	30	PASS
	2437/CH 6	22.76	22.97	30	PASS
	2462/CH11	22.96	23.17	30	PASS
802.11n HT20	2412/CH 1	21.18	22.13	30	PASS
	2437/CH 6	21.62	22.58	30	PASS
	2462/CH11	22.24	23.19	30	PASS
802.11n HT40	2422/CH3	22.76	23.72	30	PASS
	2437/CH6	22.53	23.48	30	PASS
	2452/CH9	22.51	23.47	30	PASS
802.11ax HE20	2412/CH 1	21.77	22.73	30	PASS
	2437/CH 6	21.35	22.31	30	PASS
	2462/CH11	21.78	22.74	30	PASS
802.11ax HE40	2422/CH3	22.19	23.15	30	PASS
	2437/CH6	21.98	22.94	30	PASS
	2452/CH9	22.00	22.96	30	PASS
Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor					

MIMO

Test Mode	Carrier frequency (MHz) / Channel	MIMO Antenna 1		MIMO Antenna 2		Total Power (dBm)	Limit (dBm)	Conclusion
		Average Power Measured (dBm)	Average Power with duty factor (dBm)	Average Power Measured (dBm)	Average Power with duty factor (dBm)			
802.11b	2412/CH 1	20.98	22.52	21.25	22.79	25.66	30	PASS
	2437/CH 6	21.33	22.87	21.58	23.12	26.01	30	PASS
	2462/CH11	21.17	22.70	22.22	23.76	26.28	30	PASS
802.11g	2412/CH 1	22.47	22.68	22.85	23.06	25.88	30	PASS
	2437/CH 6	22.80	23.01	23.06	23.27	26.15	30	PASS
	2462/CH11	22.82	23.03	23.33	23.54	26.31	30	PASS
802.11n HT20	2412/CH 1	21.42	22.38	21.28	22.23	25.32	30	PASS
	2437/CH 6	22.20	23.16	22.09	23.05	26.11	30	PASS
	2462/CH11	22.04	23.00	22.27	23.23	26.12	30	PASS
802.11n HT40	2422/CH3	21.59	22.55	22.98	23.94	26.31	30	PASS
	2437/CH6	22.69	23.65	22.14	23.09	26.39	30	PASS
	2452/CH9	22.28	23.24	23.15	24.11	26.71	30	PASS
802.11ax HE20	2412/CH 1	21.61	22.57	21.75	22.71	25.65	30	PASS
	2437/CH 6	21.72	22.68	21.83	22.79	25.74	30	PASS
	2462/CH11	21.55	22.51	21.95	22.91	25.73	30	PASS
802.11ax HE40	2422/CH3	22.48	23.44	22.48	23.44	26.45	30	PASS
	2437/CH6	22.24	23.20	22.01	22.97	26.10	30	PASS
	2452/CH9	22.17	23.13	22.56	23.52	26.34	30	PASS

Note: 1.Average Power with duty factor = Average Power Measured +Duty cycle correction factor

2. For Total Power, according to KDB 662911 D01 Multiple Transmitter Output v02r01 1),

The Total Power = $10\log(10^{(\text{Power antenna1 in dBm}/10)} + 10^{(\text{Power antenna2 in dBm}/10)})$.

3. According to KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f(i): If all antennas have the same gain, Directional gain = $G_{\text{ANT}} + \text{Array Gain}$,

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{\text{ANT}} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{\text{ANT}}/N_{\text{SS}})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{\text{ANT}} \geq 5$.

So directional gain = $G_{\text{ANT}} + \text{Array Gain} = 4.5 + 0 = 4.5 \text{ dBi} < 6 \text{ dBi}$. So the power limit is 30dBm

5.2. 99% Bandwidth and 6dB Bandwidth

Ambient Condition


Temperature	Relative humidity
15°C ~ 35°C	20% ~ 80%

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable. RBW is set to 100 kHz; VBW is set to 300 kHz on spectrum analyzer. Dector=Peak, Trace mode=max hold.

The EUT was connected to the spectrum analyzer through a known loss cable. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value.

Test Setup



Limits

Rule Part 15.247 (a) (2) specifies that “Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.”

minimum 6 dB bandwidth	≥ 500 kHz
------------------------	-----------

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936$ Hz.

Test Results:


Test Mode	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 6 dB bandwidth (MHz)	Limit (kHz)	Conclusion
802.11b	2412	12.899	7.017	500	PASS
	2437	13.016	7.092	500	PASS
	2462	13.015	7.106	500	PASS
802.11g	2412	16.473	13.788	500	PASS
	2437	16.460	16.306	500	PASS
	2462	16.451	16.320	500	PASS
802.11n HT20	2412	17.632	17.289	500	PASS
	2437	17.664	16.903	500	PASS
	2462	17.637	17.326	500	PASS
802.11n HT40	2422	36.063	35.939	500	PASS
	2437	36.119	36.075	500	PASS
	2452	36.101	36.274	500	PASS
802.11ax HE20	2412	18.921	18.287	500	PASS
	2437	18.977	18.687	500	PASS
	2462	18.936	17.758	500	PASS
802.11ax HE40	2422	37.671	37.054	500	PASS
	2437	37.794	37.762	500	PASS
	2452	37.734	37.750	500	PASS

99%bandwidth


OBW 802.11ax(HE20) 2412MHz




OBW 802.11ax(HE20) 2437MHz




OBW 802.11ax(HE20) 2462MHz




OBW 802.11ax(HE40) 2422MHz




OBW 802.11ax(HE40) 2437MHz




OBW 802.11ax(HE40) 2452MHz




OBW 802.11b 2412MHz




OBW 802.11b 2437MHz




OBW 802.11b 2462MHz




OBW 802.11g 2412MHz




OBW 802.11g 2437MHz




OBW 802.11g 2462MHz




OBW 802.11n(HT20) 2412MHz




OBW 802.11n(HT20) 2437MHz




OBW 802.11n(HT20) 2462MHz




OBW 802.11n(HT40) 2422MHz



OBW 802.11n(HT40) 2437MHz




OBW 802.11n(HT40) 2452MHz




6 dB bandwidth


-6dB Bandwidth 802.11ax(HE20) 2412MHz




-6dB Bandwidth 802.11ax(HE20) 2437MHz




-6dB Bandwidth 802.11ax(HE20) 2462MHz




-6dB Bandwidth 802.11ax(HE40) 2422MHz




-6dB Bandwidth 802.11ax(HE40) 2437MHz




-6dB Bandwidth 802.11ax(HE40) 2452MHz




-6dB Bandwidth 802.11b 2412MHz




-6dB Bandwidth 802.11b 2437MHz




-6dB Bandwidth 802.11b 2462MHz




-6dB Bandwidth 802.11g 2412MHz




-6dB Bandwidth 802.11g 2437MHz




-6dB Bandwidth 802.11g 2462MHz




-6dB Bandwidth 802.11n(HT20) 2412MHz




-6dB Bandwidth 802.11n(HT20) 2437MHz




-6dB Bandwidth 802.11n(HT20) 2462MHz




-6dB Bandwidth 802.11n(HT40) 2422MHz



-6dB Bandwidth 802.11n(HT40) 2437MHz



-6dB Bandwidth 802.11n(HT40) 2452MHz



5.3. Band Edge


Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	20% ~ 80%

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable the band edge of the lowest and highest channels were measured. The peak detector is used and RBW is set to 100 kHz and VBW is set to 300 kHz on spectrum analyzer. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 15.247(d) specifies that “In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.” If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.”


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
2GHz-3GHz	1.407 dB

Test Results: PASS


Band Edge 802.11ax(HE20) 2412MHz Ref




Band Edge 802.11ax(HE20) 2412MHz Emission




Band Edge 802.11ax(HE20) 2462MHz Ref




Band Edge 802.11ax(HE20) 2462MHz Emission




Band Edge 802.11ax(HE40) 2422MHz Ref




Band Edge 802.11ax(HE40) 2422MHz Emission




Band Edge 802.11ax(HE40) 2452MHz Ref




Band Edge 802.11ax(HE40) 2452MHz Emission




Band Edge 802.11b 2412MHz Ref




Band Edge 802.11b 2412MHz Emission




Band Edge 802.11b 2462MHz Ref




Band Edge 802.11b 2462MHz Emission




Band Edge 802.11g 2412MHz Ref




Band Edge 802.11g 2412MHz Emission




Band Edge 802.11g 2462MHz Ref




Band Edge 802.11g 2462MHz Emission




Band Edge 802.11n(HT20) 2412MHz Ref




Band Edge 802.11n(HT20) 2412MHz Emission




Band Edge 802.11n(HT20) 2462MHz Ref




Band Edge 802.11n(HT20) 2462MHz Emission




Band Edge 802.11n(HT40) 2422MHz Ref




Band Edge 802.11n(HT40) 2422MHz Emission



Band Edge 802.11n(HT40) 2452MHz Ref



Band Edge 802.11n(HT40) 2452MHz Emission



5.4. Power Spectral Density

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	20% ~ 80%

Method of Measurement


During the process of the testing, The EUT was connected to Spectrum Analyzer with a known loss. The EUT is max power transmission with proper modulation.

Method AVGPS-2 was used for this test.

- Measure the duty cycle (D) of the transmitter output signal as described in 11.6
- Set instrument center frequency to DTS channel center frequency
- Set span to at least 1.5 times the OBW
- Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$
- Set VBW $\geq [3 \times \text{RBW}]$
- Detector = power averaging (rms) or sample detector (when rms not available)
- Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$
- Sweep time = auto couple
- Do not use sweep triggering; allow sweep to "free run"
- Employ trace averaging (rms) mode over a minimum of 100 traces
- Use the peak marker function to determine the maximum amplitude level
- Add $[10 \log(1/D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time
- If measured value exceeds requirement specified by regulatory agency then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced)

The conducted Power is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Test setup



Limits

Rule Part 15.247(e) specifies that "For digitally modulated systems, the power spectral density

conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. ”

Limits	$\leq 8 \text{ dBm} / 3\text{kHz}$
--------	------------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.75\text{dB}$.

Test Results:
SISO Antenna 1

Test Mode	Carrier frequency (MHz) / Channel	Read Value (dBm / 30kHz)	Power Spectral Density (dBm / 3kHz)	Limit (dBm / 3kHz)	Conclusion
802.11b	2412/CH 1	0.24	-8.22	8	PASS
	2437/CH 6	1.82	-6.64	8	PASS
	2462/CH11	1.77	-6.69	8	PASS
802.11g	2412/CH 1	-1.5	-11.29	8	PASS
	2437/CH 6	-1.13	-10.92	8	PASS
	2462/CH11	-1.27	-11.06	8	PASS
802.11n HT20	2412/CH 1	-2.71	-11.75	8	PASS
	2437/CH 6	-2.05	-11.09	8	PASS
	2462/CH11	-2.14	-11.18	8	PASS
802.11n HT40	2422/CH3	-4.72	-13.76	8	PASS
	2437/CH6	-4.72	-13.76	8	PASS
	2452/CH9	-4.84	-13.88	8	PASS
802.11ax HE20	2412/CH 1	-5.9	-14.94	8	PASS
	2437/CH 6	-4.23	-13.27	8	PASS
	2462/CH11	-3.82	-12.86	8	PASS
802.11ax HE40	2422/CH3	-6.49	-15.53	8	PASS
	2437/CH6	-6.57	-15.61	8	PASS
	2452/CH9	-6.71	-15.75	8	PASS
Note: Power Spectral Density (dBm/3kHz) =Read Value+Duty cycle correction factor + 10*log10(3/30)					

SISO Antenna 2

Test Mode	Carrier frequency (MHz) / Channel	Read Value (dBm / 30kHz)	Power Spectral Density (dBm / 3kHz)	Limit (dBm / 3kHz)	Conclusion
802.11b	2412/CH 1	0.79	-7.67	8	PASS
	2437/CH 6	1.04	-7.42	8	PASS
	2462/CH11	0.98	-7.48	8	PASS
802.11g	2412/CH 1	-1.84	-11.63	8	PASS
	2437/CH 6	-1.38	-11.17	8	PASS
	2462/CH11	-1.17	-10.96	8	PASS
802.11n HT20	2412/CH 1	-3.2	-12.24	8	PASS
	2437/CH 6	-2.67	-11.71	8	PASS
	2462/CH11	-2.36	-11.40	8	PASS
802.11n HT40	2422/CH3	-4.57	-13.61	8	PASS
	2437/CH6	-4.84	-13.88	8	PASS
	2452/CH9	-4.43	-13.47	8	PASS
802.11ax HE20	2412/CH 1	-4.69	-13.73	8	PASS
	2437/CH 6	-4.37	-13.41	8	PASS
	2462/CH11	-3.89	-12.93	8	PASS
802.11ax HE40	2422/CH3	-6.45	-15.49	8	PASS
	2437/CH6	-6.59	-15.63	8	PASS
	2452/CH9	-6.67	-15.71	8	PASS
Note: Power Spectral Density (dBm/3kHz) =Read Value+Duty cycle correction factor + 10*log10(3/30)					

MIMO

Test Mode	Carrier frequency (MHz))/ Channel	Power Spectral Density				Total PSD	Limit (dBm / 3kHz)	Conclus ion
		Antenna 1		Antenna 2				
		Read Value (dBm / 30kHz)	Power Spectral Density (dBm / 3kHz)	Read Value (dBm / 30kHz)	Power Spectral Density (dBm / 3kHz)	(dBm / 3kHz)		
802.11b	2412/CH 1	1.08	-7.38	0.85	-7.61	-4.49	6.49	PASS
	2437/CH 6	1.01	-7.45	1.10	-7.36	-4.40	6.49	PASS
	2462/CH11	1.07	-7.39	2.21	-6.25	-3.78	6.49	PASS
802.11g	2412/CH 1	-1.64	-11.43	-1.22	-11.01	-8.20	6.49	PASS
	2437/CH 6	-1.09	-10.88	-0.94	-10.73	-7.79	6.49	PASS
	2462/CH11	-1.15	-10.94	-0.86	-10.65	-7.78	6.49	PASS
802.11n HT20	2412/CH 1	-2.98	-12.02	-2.34	-11.38	-8.68	6.49	PASS
	2437/CH 6	-2.42	-11.46	-2.18	-11.22	-8.33	6.49	PASS
	2462/CH11	-2.42	-11.46	-1.91	-10.95	-8.19	6.49	PASS
802.11n HT40	2422/CH3	-4.88	-13.92	-4.33	-13.37	-10.63	6.49	PASS
	2437/CH6	-4.76	-13.80	-4.54	-13.58	-10.68	6.49	PASS
	2452/CH9	-4.63	-13.67	-4.44	-13.48	-10.57	6.49	PASS
802.11ax HE20	2412/CH 1	-4.30	-13.34	-4.64	-13.68	-10.50	6.49	PASS
	2437/CH 6	-4.04	-13.08	-3.96	-13.00	-10.03	6.49	PASS
	2462/CH11	-4.28	-13.32	-3.66	-12.70	-9.99	6.49	PASS
802.11ax HE40	2422/CH3	-6.03	-15.07	-5.95	-14.99	-12.02	6.49	PASS
	2437/CH6	-6.46	-15.50	-5.91	-14.95	-12.21	6.49	PASS
	2452/CH9	-6.43	-15.47	-6.38	-15.42	-12.43	6.49	PASS

Note: 1.Power Spectral Density (dBm/3kHz) =Read Value+Duty cycle correction factor + 10*LOG10(3 / 30)


2. For Total PSD, according to KDB 662911 D01 Multiple Transmitter Output v02r01 2)a),the power spectral density= $10\log(10^{(PSD_{antenna1} \text{ in dBm/10})} + 10^{(PSD_{antenna2} \text{ in dBm/10})})$

3. According to KDB 662911 D01 Multiple Transmitter Output v02r01 F)2)f)(i): If all antennas have the same gain, Directional gain = $G_{ANT} + \text{Array Gain}$. For PSD measurements on all devices, Array Gain= $10\log(N_{ant}/N_{ss})$ dB, so directional gain= $G_{ANT} + \text{Array Gain}$
Gain= $4.50 + 10\log(3/1) = 7.51 > 6\text{dBi}$.


So the PSD limit is $8 + 6 - \text{MAX}(6, \text{directional gain}) \text{ dBm} = 6.49 \text{ dBm}$

SISO Antenna 1


PSD 802.11ax(HE20) 2412MHz




PSD 802.11ax(HE20) 2437MHz




PSD 802.11ax(HE20) 2462MHz




PSD 802.11ax(HE40) 2422MHz




PSD 802.11ax(HE40) 2437MHz




PSD 802.11ax(HE40) 2452MHz




PSD 802.11b 2412MHz




PSD 802.11b 2437MHz




PSD 802.11b 2462MHz




PSD 802.11g 2412MHz




PSD 802.11g 2437MHz




PSD 802.11g 2462MHz




PSD 802.11n(HT20) 2412MHz




PSD 802.11n(HT20) 2437MHz




PSD 802.11n(HT20) 2462MHz




PSD 802.11n(HT40) 2422MHz



PSD 802.11n(HT40) 2437MHz




PSD 802.11n(HT40) 2452MHz




SISO Antenna 2


PSD 802.11ax(HE20) 2412MHz




PSD 802.11ax(HE20) 2437MHz




PSD 802.11ax(HE20) 2462MHz




PSD 802.11ax(HE40) 2422MHz




PSD 802.11ax(HE40) 2437MHz




PSD 802.11ax(HE40) 2452MHz




PSD 802.11b 2412MHz




PSD 802.11b 2437MHz




PSD 802.11b 2462MHz




PSD 802.11g 2412MHz




PSD 802.11g 2437MHz




PSD 802.11g 2462MHz




PSD 802.11n(HT20) 2412MHz




PSD 802.11n(HT20) 2437MHz




PSD 802.11n(HT20) 2462MHz




PSD 802.11n(HT40) 2422MHz



PSD 802.11n(HT40) 2437MHz




PSD 802.11n(HT40) 2452MHz




MIMO


PSD 802.11ax(HE20) 2412MHz Ant1




PSD 802.11ax(HE20) 2412MHz Ant2




PSD 802.11ax(HE20) 2437MHz Ant1




PSD 802.11ax(HE20) 2437MHz Ant2




PSD 802.11ax(HE20) 2462MHz Ant1




PSD 802.11ax(HE20) 2462MHz Ant2




PSD 802.11ax(HE40) 2422MHz Ant1




PSD 802.11ax(HE40) 2422MHz Ant2




PSD 802.11ax(HE40) 2437MHz Ant1




PSD 802.11ax(HE40) 2437MHz Ant2




PSD 802.11ax(HE40) 2452MHz Ant1




PSD 802.11ax(HE40) 2452MHz Ant2




PSD 802.11b 2412MHz Ant1




PSD 802.11b 2412MHz Ant2




PSD 802.11b 2437MHz Ant1




PSD 802.11b 2437MHz Ant2




PSD 802.11b 2462MHz Ant1




PSD 802.11b 2462MHz Ant2




PSD 802.11g 2412MHz Ant1




PSD 802.11g 2412MHz Ant2




PSD 802.11g 2437MHz Ant1




PSD 802.11g 2437MHz Ant2




PSD 802.11g 2462MHz Ant1




PSD 802.11g 2462MHz Ant2




PSD 802.11n(HT20) 2412MHz Ant1




PSD 802.11n(HT20) 2412MHz Ant2




PSD 802.11n(HT20) 2437MHz Ant1




PSD 802.11n(HT20) 2437MHz Ant2




PSD 802.11n(HT20) 2462MHz Ant1




PSD 802.11n(HT20) 2462MHz Ant2




PSD 802.11n(HT40) 2422MHz Ant1




PSD 802.11n(HT40) 2422MHz Ant2




PSD 802.11n(HT40) 2437MHz Ant1




PSD 802.11n(HT40) 2437MHz Ant2



PSD 802.11n(HT40) 2452MHz Ant1



PSD 802.11n(HT40) 2452MHz Ant2



5.5. Spurious RF Conducted Emissions

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	20% ~ 80%

Method of Measurement

The EUT was connected to the spectrum analyzer with a known loss. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. Set RBW to 100 kHz and VBW to 300 kHz, Sweep is set to AUTO.

The test is in transmitting mode.

Test Setup



Limits

Rule Part 15.247(d) pacifies that "In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. "

Test Mode	Carrier frequency (MHz)	Reference value (dBm)	Limit
802.11b	2412	14.13	-15.87
	2437	15.17	-14.83
	2462	14.86	-15.14
802.11g	2412	12.37	-17.63
	2437	12.88	-17.12
	2462	13.87	-16.13
802.11n HT20	2412	13.17	-16.83
	2437	12.56	-17.44
	2462	13.03	-16.97
802.11n HT40	2422	8.46	-21.54
	2437	10.45	-19.55
	2452	9.28	-20.72

802.11ax HE20	2412	10.47	-19.53
	2437	13.32	-16.68
	2462	12.41	-17.59
802.11ax HE40	2422	9.20	-20.8
	2437	9.20	-20.8
	2452	9.46	-20.54


Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.


Frequency	Uncertainty
100kHz-2GHz	0.684 dB
2GHz-26GHz	1.407 dB

Test Results:


Tx. Spurious 802.11ax(HE20) 2412MHz Ref




Tx. Spurious 802.11ax(HE20) 2412MHz Emission




Tx. Spurious 802.11ax(HE20) 2437MHz Ref




Tx. Spurious 802.11ax(HE20) 2437MHz Emission




Tx. Spurious 802.11ax(HE20) 2462MHz Ref




Tx. Spurious 802.11ax(HE20) 2462MHz Emission




Tx. Spurious 802.11ax(HE40) 2422MHz Ref



Tx. Spurious 802.11ax(HE40) 2422MHz Emission



Tx. Spurious 802.11ax(HE40) 2437MHz Ref



Tx. Spurious 802.11ax(HE40) 2437MHz Emission

