

50019898B

Shiva QS PALLADIOM

Model | Modelo | Modelé QSFC-EDU-BP-C
4.5-9.0 V== 5 W 6 in-lb (0,68 N•m)



IEC PELV/
NEC CLASS 2



This device complies with part 15 of the FCC Rules.
Operation is subject to the following conditions:

- (1) This device may not cause harmful interference, and
(2) This device must accept any interference received,
including interference that may cause undesired operation.

FCC ID: JP20137

IC: 2851A-JP20137

SCT: RCPLUS09-0944

HVIN: RFB-A

Pol./Brazil:
betron.com/galvants



DAVEN INSTRUM 90-4
CAN ESD-CSD-1880-030

DIMENSIONS: 1.87" x 2.50"

DR # 3626

PRODUCT INFORMATION

THERMLite SELECT® 219-00

Product Description:

THERMLite SELECT 219-00 is a UL-recognized CSA-accepted, 20-watt glass-encapsulated thermal-imaging assembly, with polycarbonate control coils as appropriate, polycarbonate reflectors, and leaded glass with heat-tension lines.

- THERMLite SELECT 219-00 is a 20-watt glass-encapsulated thermal-imaging assembly, with polycarbonate control coils as appropriate, polycarbonate reflectors, and leaded glass with heat-tension lines.
- THERMLite SELECT 219-00 is a 20-watt glass-encapsulated thermal-imaging assembly, with polycarbonate control coils as appropriate, polycarbonate reflectors, and leaded glass with heat-tension lines.
- THERMLite SELECT 219-00 is a 20-watt glass-encapsulated thermal-imaging assembly, with polycarbonate control coils as appropriate, polycarbonate reflectors, and leaded glass with heat-tension lines.
- THERMLite SELECT 219-00 is a 20-watt glass-encapsulated thermal-imaging assembly, with polycarbonate control coils as appropriate, polycarbonate reflectors, and leaded glass with heat-tension lines.