

Prüfbericht-Nr.: Test report no.:	CN2244RH 001	Auftrags-Nr.: Order no.:	244385665	Seite 1 von 60 Page 1 of 60
Kunden-Referenz-Nr.: Client reference no.:	1288983	Auftragsdatum: Order date:	2022-01-04	
Auftraggeber: Client:	IKEA of Sweden AB Box 702, SE-343 81, Älmhult, Sweden			
Prüfgegenstand: Test item:	VAPPEBY peanut			
Bezeichnung / Typ-Nr.: Identification / Type no.:	E2125 FCC ID: FHO-E2125 IC: 10912A-E2125			
Auftrags-Inhalt: Order content:	Complete test			
Prüfgrundlage: Test specification:	FCC CFR47 Part 15, Subpart C Section 15.247 RSS-Gen Issue 5, Amendment 2, February 2021 RSS-247 Issue 2, February 2017 ANSI C63.10: 2013			
Wareneingangsdatum: Date of sample receipt:	2022-01-24	Refer to photo document		
Prüfmuster-Nr.: Test sample no.:	A003205571-001			
Prüfzeitraum: Testing period:	Refer to test report			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shanghai) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	X <u>Hongfei Wu</u> Signed by: Hongfei Wu		genehmigt von: authorized by:	X <u>Elliot Zhang</u> Signed by: Elliot Zhang
Datum: Date:	2022-07-07		Ausstellungsdatum: Issue date:	2022-07-07
Stellung / Position:	PE		Stellung / Position:	Reviewer
Sonstiges / Other:	HVIN: E2125			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 20dB & 99% BANDWIDTH***RESULT: Pass***5.1.3 PEAK OUTPUT POWER***RESULT: Pass***5.1.4 FREQUENCY SEPARATION***RESULT: Pass***5.1.5 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.6 TIME OF OCCUPANCY***RESULT: Pass***5.1.7 CONDUCTED BAND EDGE AND OUT-OF BAND EMISSIONS***RESULT: Pass***5.2.1 CONDUCTED EMISSION***RESULT: Pass***5.3.1 RADIATED BAND-EDGE***RESULT: Pass***5.3.2 RADIATED SPURIOUS EMISSION***RESULT: Pass*

Contents

1.	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2.	TEST SITES	4
2.1	TEST FACILITIES.....	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	5
2.4	CALIBRATION	5
2.5	MEASUREMENT UNCERTAINTY.....	6
3.	GENERAL PRODUCT INFORMATION	7
3.1	PRODUCT FUNCTION AND INTENDED USE	7
3.2	RATINGS AND SYSTEM DETAILS	7
3.3	INDEPENDENT OPERATION MODES	8
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	8
3.5	SUBMITTED DOCUMENTS.....	8
4.	TEST SET-UP AND OPERATION MODES	9
4.1	PRINCIPLE OF CONFIGURATION SELECTION.....	9
4.2	TEST OPERATION AND TEST SOFTWARE	9
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	9
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	9
5.	TEST RESULTS	10
5.1	CONDUCTED TESTING AT ANTENNA PORT.....	10
5.1.1	<i>Antenna Requirement.....</i>	<i>10</i>
5.1.2	<i>20dB & 99% Bandwidth.....</i>	<i>12</i>
5.1.3	<i>Peak Output Power</i>	<i>15</i>
5.1.4	<i>Frequency Separation</i>	<i>18</i>
5.1.5	<i>Number of Hopping Frequency.....</i>	<i>21</i>
5.1.6	<i>Time of Occupancy</i>	<i>23</i>
5.1.7	<i>Conducted Band Edge and out-of Band Emissions</i>	<i>26</i>
5.2	EMISSION IN THE FREQUENCY RANGE UP TO 30MHZ	33
5.2.1	<i>Conducted Emission.....</i>	<i>33</i>
5.3	EMISSION IN THE FREQUENCY RANGE ABOVE 30MHZ.....	38
5.3.1	<i>Radiated Band-Edge</i>	<i>38</i>
5.3.2	<i>Radiated Spurious Emission.....</i>	<i>41</i>
6.	LIST OF TABLES	60
7.	LIST OF FIGURES	60

1. General Remarks

1.1 Complementary Materials

Null.

2. Test Sites

2.1 Test Facilities

TÜV Rheinland (Shanghai) Co., Ltd.

Shanghai TUV Rheinland Building No. 177, 178 Lane 777, West Guangzhong Rd, Jing'an District, Shanghai, China

The used test equipment is in accordance with CISPR 16 for measurement of radio interference.

The Federal Communications Commission has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance with the requirements of section 2.948 of the FCC rules. The description of the test facility is listed under FCC registration number 958801.

The Innovation, Science and Economic Development Canada has reviewed the technical characteristics of the radiated and conducted emission facility, and has found these test facilities to be in compliance. The description of the test facility is listed under chambers filing number 2932F.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Due Date
3m modified semi-anechoic chamber	Frankonia	SAC3	G1811378	2022-06-27
Bilog antenna	Teseq	CBL 6112D	G1811425	2023-03-10
EMI test receiver	Rohde & Schwarz	ESCI	G1811402	2022-09-01
Spectrum analyser	Rohde & Schwarz	FSV40	G1822702	2023-03-10
Preamplifier	Taiwan EMCI	EMC184045SE	G1825372	2023-05-14
Log periodic antenna	Rohde & Schwarz	HL050	G1811417	2023-03-10
Broadband Horn Antenna	Schwarzbeck	BBHA 9170	9170-305	2023-07-10
Preamplifier	Taiwan EMCI	EMC051845SE	G1825371	2023-05-14
Spectrum Analyzer	Keysight	N9020A	MY54500180	2022-09-07
Thermohygrometer	Testo	608-H1	1241320614	2023-10-12
EMI test receiver	R&S	ESIB26	G1811380	2023-03-06
Artificial main network	R&S	ENV432	G1830003	2022-11-01
EMC measurement software	R&S	EMC32 (Ver 10.20.01)	G1824845	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

Table 2: Measurement Uncertainty

Measurement Type	Frequency	Uncertainty
Antenna Port Conducted Emission	< 1GHz	±0.39dB
	> 1GHz	±0.68dB
Conducted Emission	150kHz - 30MHz	±3.39dB
Radiated Emission	9kHz - 30MHz	±2.93dB
	30MHz - 1GHz	±5.34dB
	> 1GHz	±5.40dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT (Equipment Under Test) is a Bluetooth speaker.

For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Description of EUT	
Product Name:	VAPPEBY peanut
Model No.:	E2125
Operating Voltage:	DC 3.6V (Li-ion Battery) or DC 24V
Technical Specification of Bluetooth Classic	
Frequency Range:	2402 to 2480MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Data Rate:	1Mbps(GFSK), 2Mbps($\pi/4$ DQPSK), 3Mbps(8DPSK)
Antenna Type:	PCB Antenna
Antenna Gain:	1.5 dBi (Provided by the Client)

3.3 Independent Operation Modes

Table 4: Independent Operation Modes

Test Mode	Data Rate	Channel
TM1	1-DH5	00
TM2	1-DH5	39
TM3	1-DH5	78
TM4	2-DH5	00
TM5	2-DH5	39
TM6	2-DH5	78
TM7	3-DH5	00
TM8	3-DH5	39
TM9	3-DH5	78
TM10	1-DH1	Hopping
TM11	1-DH3	Hopping
TM12	1-DH5	Hopping
TM13	2-DH1	Hopping
TM14	2-DH3	Hopping
TM15	2-DH5	Hopping
TM16	3-DH1	Hopping
TM17	3-DH3	Hopping
TM18	3-DH5	Hopping
TM19	Normal Operating Mode	

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Bill of Material
- PCB Layout
- Photo Document
- Circuit Diagram
- Instruction Manual
- Rating Label

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

Test Software used: BT FCC tool, V2.24

Table 5: Power parameter value

Channel Frequency [MHz]	Power Parameter Value
2402	4
2441	4
2480	4

4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment

No.	Equipment Name	Model Name	Manufacturer
1	Adapter	ICPSW24-19-1	IKEA
2	Adapter	ICPSW24-7-3	IKEA

4.4 Countermeasures to achieve EMC Compliance

Null.

5. Test Results

5.1 Conducted Testing at Antenna Port

5.1.1 Antenna Requirement

RESULT:**Pass**

According to the manufacturer declared, the EUT has one PCB antenna, the directional gain of antenna is 1.5 dBi and the antenna is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Table 7: Antenna Requirement

FCC 15.203 – Antenna Requirement 1		
Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	Antenna type:	PCB antenna
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		
Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one PCB antenna can be used	
Verdict:	Pass	

RSS-Gen 6.4 – External Control		
Requirement:	The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the regulatory requirements, including RSS-Gen and the applicable RSSs	
Results:	The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
Verdict:	PASS	

RSS-Gen 6.8 – Antenna Requirement


Requirement: When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.


Results:

a) Antenna Type:	PCB Antenna
b) Manufacture:	N/A
c) Model No.:	N/A
d) Gain with reference to an isotropic radiator:	1.5 dBi


Verdict: PASS


And according to FCC, when the occupied bandwidth limit is not stated in the applicable FCC or reference measurement method, the transmitted signal band width shall be reported as the 99% emission bandwidth.

Figure 1: 20dB & 99% Bandwidth




The cable loss=1dB was provided by the client, and was factored in the result Peak Conducted Output Power

Figure 2: Peak Output Power, TM1 to TM9




5.1.4 Frequency Separation

RESULT:

Pass


Date of testing	: 2022-01-29
Ambient temperature	: 21.0°C
Relative humidity	: 36.3%
Atmospheric pressure	: 101kPa
Test requirement	: FCC Part 15.247(a)(1) RSS-247 Issue 2, February 2017, Clause 5.1(b)
Test procedure	: ANSI C63.10: 2013
Test voltage	: DC 3.6V
Test modes applied	: TM12 , TM15, TM18

Table 10: Frequency Separation

Test Mode	CH.	Frequency [MHz]	Frequency Separation [kHz]	Limit [kHz]
TM12	00	2402	1005	≥ 632.2
	39	2441	1000	≥ 631.4
	78	2480	1001	≥ 630.9
TM15	00	2402	1009	≥ 856.0
	39	2441	995	≥ 854.7
	78	2480	997	≥ 854.7
TM18	00	2402	1000	≥ 832.0
	39	2441	1002	≥ 832.0
	78	2480	999	≥ 832.7

Note:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Figure 3: Frequency Separation




5.1.5 Number of Hopping Frequency

RESULT:


Pass



Date of testing	: 2022-01-29
Ambient temperature	: 21.0°C
Relative humidity	: 36.3%
Atmospheric pressure	: 101kPa
Test requirement	: FCC 15.247(a)(1)(iii) RSS-247 Issue 2, February 2017, Clause 5.1(d)
Test procedure	: ANSI C63.10: 2013
Test voltage	: DC 3.6V
Test modes applied	: TM12, TM15, TM18

Table 11: Number of Hopping Frequency


Frequency Range	Test mode	Measured Quantity of Hopping Channel	Limit
2402 to 2480	TM12	79	≥15
	TM15	79	≥15
	TM18	79	≥15


Figure 4: Number of Hopping Frequency





Hops Over Occupancy Time in 31.6s for DH5 = $1600 / 6 / 79 * 31.6 = 107$.


Figure 5: Time of Occupancy, TM10 to TM18




5.1.7 Conducted Band Edge and out-of Band Emissions

RESULT:**Pass**

Date of testing	:	2022-01-29
Ambient temperature	:	21.0°C
Relative humidity	:	36.3%
Atmospheric pressure	:	101kPa
Test requirement	:	FCC Part 15.247(d) RSS-247 Issue 2, February 2017, Clause 5.5
Test procedure	:	ANSI C63.10: 2013
Test voltage	:	DC 3.6V
Test modes applied	:	TM1 to TM9, TM12, TM15, TM18

Figure 6: Reference Level











Figure 7: Conducted Band Edge


TM12 lower band

TM12 higher band

TM15 lower band

TM15 higher band

TM18 lower band

TM18 higher band
