

Submittal Application Report

FOR
Grant of Certification


FOR


Model: RB952Ui-5ac2nD-US
2412-2462 MHz
Broadband Digital Transmission System
FCC ID: TV7RB952-5AC2ND
IC: 7442A-9525AC

FOR

Mikrotikls SIA
Pernavas 46 Str.
Riga LV-1009 Latvia

Test Report Number: 160414d
IC Test Site Registration: 3041A-1

Authorized Signatory: 
Scot D. Rogers



ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Engineering Test Report for
Grant of Certification Application
FOR
Broadband Digital Transmission System
CFR 47, PART 15C - Paragraph 15.247
Industry Canada RSS-247 Issue1
License Exempt Intentional Radiator
For

Mikrotiks SIA

Pernavas 46 Str.
Riga LV-1009 Latvia

Broadband Digital Transmission System

Model: RB952Ui-5ac2nD-US
Frequency Range 2412-2462 MHz
FCC ID#: TV7RB952-5AC2ND
IC: 7442A-9525AC

Test Date: April 14, 2016

Certifying Engineer: *Scot D. Rogers*

Scot D. Rogers
Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotiks SIA
Model: RB952Ui-5ac2nD-US
Test #: 160414d
Test to: 47CFR 15.247, RSS-247
File: Mikrotik RB952Ui5ac2nD DTS TstRpt 160414d

S/N: 5EB204A373B8/516
FCC ID#: TV7RB952-5AC2ND
IC: 7442A-9525AC
Date: July 28, 2016
Page 2 of 45

Table Of Contents

TABLE OF CONTENTS.....	3
REVISIONS.....	5
FORWARD	6
OPINION / INTERPRETATION OF RESULTS	6
EQUIPMENT TESTED.....	6
EQUIPMENT FUNCTION AND CONFIGURATION.....	7
Equipment Configuration.....	7
APPLICANT COMPANY INFORMATION	8
Equipment information	8
Product Details	9
Antenna and Bandwidth.....	10
IEEE 11a/n Spec.....	11
Accessories	11
Table for Filed Antennas	11
Table for Carrier Frequencies	12
Table for Test Modes	13
Test Result of Occupied Bandwidth	15
APPLICATION FOR CERTIFICATION.....	16
APPLICABLE STANDARDS & TEST PROCEDURES.....	17
EQUIPMENT TESTING PROCEDURES	17
AC Line Conducted Emission Test Procedure	17
Radiated Emission Test Procedure.....	17
Diagram 1 Test arrangement for Conducted emissions	18

Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	19
Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	20
TEST SITE LOCATIONS	20
LIST OF TEST EQUIPMENT	21
UNITS OF MEASUREMENTS	22
ENVIRONMENTAL CONDITIONS.....	22
INTENTIONAL RADIATORS.....	22
Antenna Requirements	22
Restricted Bands of Operation.....	22
Table 1 General Radiated Emissions in Restricted Bands Data	23
Table 2 General Radiated Emissions in Restricted Bands Data	24
Summary of Results for Radiated Emissions in Restricted Bands	24
AC Line Conducted Emissions Procedure	25
Figure 1 AC Line Conducted Emissions Line 1	26
Figure 2 AC Line Conducted Emissions Line 2	26
Table 3 AC Line Conducted Emissions Data (Highest Emissions Line L1)	27
Table 4 AC Line Conducted Emissions Data (Highest Emissions Line L2)	27
Summary of Results for AC Line Conducted Emissions	27
General Radiated Emissions Procedure.....	28
Table 5 General Radiated Emissions from EUT Data (Highest Emissions).....	29
Summary of Results for General Radiated Emissions	29
Operation in the 2400-2483.5 MHz Frequency Band.....	30
Figure 3 Plot of Transmitter Emissions (Across Operational Band 802.11b)	31
Figure 4 Plot of Transmitter Emissions (Across Operational Band, 802.11g)	31
Figure 5 Plot of Transmitter Emissions (Across Operational Band, 802.11n)	32
Figure 6 Plot of Transmitter Low Band Edge (802.11b)	32
Figure 7 Plot of Transmitter Low Band Edge (802.11g)	33
Figure 8 Plot of Transmitter Low Band Edge (802.11n)	33

Figure 9 Plot of Transmitter High Band Edge (802.11b)	34
Figure 10 Plot of Transmitter High Band Edge (802.11g)	34
Figure 11 Plot of Transmitter High Band Edge (802.11n)	35
Figure 12 Plot of Transmitter 6-dB Occupied Band Width (802.11b)	35
Figure 13 Plot of Transmitter 6-dB Occupied Band Width (802.11g)	36
Figure 14 Plot of Transmitter 6-dB Occupied Band Width (802.11n)	36
Transmitter Emissions Data.....	37
Table 6 Transmitter Power and Emissions	37
Table 7 Transmitter Radiated Emission.....	38
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	39
STATEMENT OF MODIFICATIONS AND DEVIATIONS	39
ANNEX.....	40
Annex A Measurement Uncertainty Calculations	41
Annex B Rogers Labs Test Equipment List.....	42
Annex C Rogers Qualifications	43
Annex D FCC Site Registration Letter	44
Annex E Industry Canada Site Registration Letter	45

Revisions

Revision 1 Issued July 28, 2016

Forward

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under 47CFR Paragraph 15.247 and RSS-247 Issue 1 Digital Modulation transmitter operation in the 2412-2462 MHz band.

Name of Applicant: Mikrotiks SIA FRN: 0014 43 1100
 Pernavas 46 Str.
 Riga LV-1009 Latvia

Model: RB952Ui-5ac2nD-US

FCC ID: TV7RB952-5AC2ND IC: 7442A-9525AC

Frequency Range: 2412-2462 MHz (802.11b/g/n mode operation), 2422-2452 MHz (802.11n 40 MHz channel operation)

Total Operating Power: Maximum 0.116-watt total output power, OBW 15,545 or 33,013 kHz

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Frequency Bands 15.205, RSS-GEN 8.10	-1.2	Complies
AC Line Conducted 15.207, RSS-GEN 7.2.4	-14.4	Complies
Radiated Emissions 15.209, RSS-GEN 7.2.5	-1.9	Complies
Harmonic Emissions per 15.247, RSS-247	-1.2	Complies
Peak Power Spectral Density per 15.247, RSS-247	-22.3	Complies

Equipment Tested


<u>Equipment</u>	<u>Model</u>	<u>FCC I.D.</u>
EUT	RB952Ui-5ac2nD-US	TV7RB952-5AC2ND
AC Adapter	FLD301-240120-U	N/A
Power Adapter	POE	N/A
Dell Studio XPS	921LBN1	N/A

Test results in this report relate only to the items tested.

Equipment Function and Configuration

The EUT is a 2412-2462 MHz Digital Transmission System used to transmit data in applications offering broadband wireless connectivity. The design utilizes internal fixed antenna system and offers no provision for antenna replacement or modification. The system provides two transmitter chains and may operate in a 2x2 MiMo configuration. The equipment is marketed for use to provide a wireless link to exchange data information from one point to another. For testing purposes, the EUT transceiver was connected to the manufacturer supplied AC/DC supply and communicating to the laptop computer through Ethernet network interface. This configuration provided operational control of the EUT and communications over the network interface between the EUT and supporting computer system. No other interfacing options are provided. For testing purposes, the RB952Ui-5ac2nD-US received power from the manufacturer provided AC/DC power adapter and was configured to transmit in available data modes during testing with worst-case data presented. The antenna system complies with requirements for unique antenna connection port.

Equipment Configuration



Applicant Company information

Applicants Company	MikroTik (“Mikrotīkls, SIA”)
Applicants Address	Pernavas 46 Str., Riga LV-1009 Latvia
FCC Identifier	TV7RB952-5AC2ND
Industry Canada Identifier	7442A-9525AC
Manufacturer Company	MikroTik (“Mikrotīkls, SIA”)
Manufacturer Address	Pernavas 46 Str., Riga LV-1009 Latvia

Equipment information

Product Marketing Name (PMN) : The PMN is the name or model number under which the product will be marketed/offered for sale in Canada. If the product has PMN, it must be provided.	hAP ac lite
Unique Product Number (UPN): The applicant, made up of a maximum of 11 alphanumeric characters (A-Z, 0-9), assigns the UPN.	5EB204A373B8
Hardware Version Identification Number (HVIN): The HVIN identifies hardware specifications of a product version. The HVIN replaces the ISED Model Number in the legacy E-filing System. An HVIN is required for all products for certification applications.	RB952Ui-5ac2nD-US
Host Marketing Name (HMN) (if applicable): The HMN is the name or model number of a final product, which contains a certified radio module.	n/a
Brand Name	RouterBOARD
Model Number	RB952Ui-5ac2nD-US
Test Rule Part(s)	Under 15.407, PART 15E U-NII-1 & 3; Under 15.247, PART 15C
Test Frequency Range	2.4-2.4835, 5.15-5.25 and 5.725-5.85GHz
Project Number	160414d
Submission Type	Certification

Product Details

Items	Description
Product Type	U-NII [(1TX, 1RX)] WLAN [2x2 MIMO, (2TX, 2RX)]
Radio Type	Transceiver
Power Type	External Power Supply and POE adapter
Modulation	IEEE 802.11a: OFDM IEEE 802.11a/n: see the below table
Data Modulation	IEEE 802.11 a/n: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM) IEEE 802.11 g/n: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11 b: DSSS
Data Rate (Mbps)	IEEE 802.11a/g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n/ac: see the below table IEEE 802.11b: (1/2/5/10/20/40/80/160)
Frequency Range	2400-2483.5 MHz / 5150-5250 MHz / 5725-5850 MHz
Channel Number	802.11b: 11 for 20MHz bandwidth 802.11g/n: 11 for 20MHz bandwidth; 5 for 40MHz bandwidth 802.11a/n: 9 for 20MHz bandwidth; 4 for 40MHz bandwidth 802.11 a/c: 2 for 80 MHz bandwidth
Channel Band Width (99%)	802.11 b: 13.625 MHz 802.11 g: 15.620 MHz 802.11 n (HT-20): 15.620 MHz 802.11 n (HT-40): 33.575 MHz U-NII-1: IEEE 802.11a: 18.462 MHz IEEE 802.11a/n MCS0/Nss1 (VHT20): 18.462 MHz IEEE 802.11a/n MCS0/Nss1 (VHT40): 38.622 MHz IEEE 802.11a/c (VHT80): 80.449 MHz

	<p>U-NII-4:</p> <p>IEEE 802.11a: 17.220 MHz</p> <p>IEEE 802.11a/n MCSO/Nss1 (VHT20): 17.220 MHz</p> <p>IEEE 802.11 a/n MCSO/Nss1 (VHT40): 37.850 MHz</p> <p>IEEE 802.11 a/c MCSO/Nss1 (VHT80): 78.846 MHz</p>
Maximum Conducted Output Power	<p>Band 1:</p> <p>IEEE 802.11a: 9 dBm</p> <p>IEEE 802.11a/n MCSO/Nss1 (VHT20): 9 dBm</p> <p>IEEE 802.11a/n MCSO/Nss1 (VHT40): 6 dBm</p> <p>IEEE 802.11ac MCSO/Nss1 (VHT80): 0 dBm</p> <p>Band 4:</p> <p>IEEE 802.11a: 10.4 dBm</p> <p>IEEE 802.11a/n MCSO/Nss1 (VHT20): 10.4 dBm</p> <p>IEEE 802.11ac MCSO/Nss1 (VHT40): .8.5 dBm</p> <p>IEEE 802.11ac MCSO/Nss1 (VHT40): .4.8 dBm</p>
Carrier Frequencies	Please refer to Table for Carrier Frequencies
Antenna	Please refer to Table for Filed Antenna
Communication Mode	
Beamforming Function	Without beamforming
Operating Mode	Indoor use

Antenna and Bandwidth

Antenna	TX chains		
Bandwidth Mode	20 MHz	40 MHz	80 MHz
IEEE 802.11b			
IEEE 802.11g			
IEEE 802.11n (HT20)			
IEEE 802.11n (HT40)			
IEEE 802.11a			
IEEE 802.11n			
IEEE 802.11ac			

IEEE 11a/n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate/MCS
802.11a (HT20)	1	MCS 0-23
802.11n (HT40)	1	MCS 0-23
802.11a/n (VHT20)	1	MCS 0-9/Nss1-3
802.11a/n (VHT40)	1	MCS 0-9/Nss1-3
802.11a/n (VHT80)	1	MCS 0-9/Nss1-3
<p>Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). The EUT supports HT20 and HT40.</p> <p>Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80, and VHT160 (VHT: Very High Throughput). The EUT does not support 802.11ac.</p> <p>Note 3: Modulation modes consist of below configuration: IEEE 802.11a/n : HT20/HT40; IEEE 802.11a/n: VHT20/VHT40, IEEE 802.11a/c: VHT80</p>		

Accessories

AC Power Adapter	FLD301-240120-U
Power Over Ethernet (POE) adapter	POE

Table for Filed Antennas

Ant.	Brand	Model Name	P/N	Antenna Type	Connector	Gain (dBi)	
						2.4GHZ	5GHZ
1	Mikrotik	-		PIF		1.5dBi	2dBi
2							

Table for Carrier Frequencies

There are two bandwidth systems:

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400-2483.5 MHz	1	2412MHZ	7	2442MHZ
	2	2417MHZ	8	2447MHZ
	3	2422MHZ	9	2452MHZ
	4	2427MHZ	10	2457MHZ
	5	2432MHZ	11	2462MHZ
	6	2437MHZ	-	-

For 20MHz bandwidth systems, use Channel 1,6,11, 36, 40, 44, 48, 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 38, 46, 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400-2483.5MHz	1	2412	2	2422
	6	2437	7	2447
	11	2462	10	2452
5150-5250MHz U-NII-1	36	5180MHz	44	5220MHz
	38	5190MHz	46	5230MHz
	40	5200MHz	48	5240MHz
	42	5210MHz	-	-
5725-5850MHz U-NII-3	149	5745MHz	157	5785MHz
	151	5755MHz	159	5795MHz
	153	5765MHz	161	5805MHz
	155	5775MHz	165	5825MHz

Table for Test Modes

Preliminary tests were performed in different data rates to define the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all possible configurations while searching the worst cases. The following table is a list of the test modes investigated for this report.

Test Items	Mode		Data Rate	Channel	Chain
Max. Conducted Output Power	802.11b		11	1,6,11	1,2
	802.11g		54	1,6,11	1,2
	802.11n HT20		65	1,6,11	1,2
	802.11n HT40		135	2,7,10	1,2
	11 a BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	1
	11a/n VHT20	Band 1&4	MCSO/Nss1	36/40/48/149/157/165	1
	11a/n VHT40	Band 1&4	MCSO/Nss1	38/46/151/159	1
	11a/n VHT80	Band 1&4	MCSO/Nss1	42,155	1
Power Spectral Density	802.11b			1,6,11	1,2
	802.11g			1,6,11	1,2
	802.11n HT20			1,6,11	1,2
	802.11n HT40			2,7,10	1,2
	11a BPSK	Band 1&4	6Mbps	36//40/48/149/157/165	1
	11a/n VHT20	Band 1&4	MCSO/Nss1	36/40/48/149/157/165	1
	11a/n VHT40	Band 1&4	MCSO/Nss1	38/46/151/159	1
	11a/n VHT80	Band 1&4	MCSO/Nss1	42,155	1
26dB, 99% Occupied Bandwidth Measurement	802.11b			1,6,11	1,2
	802.11g			1,6,11	1,2
	802.11n HT20			1,6,11	1,2
	802.11n HT40			2,7,10	1,2
	11a BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	1
	11a/n VHT20	Band 1&4	MCSO/Nss1	36/40/48/149/157/165	1
	11a/n VHT40	Band 1&4	MCSO/Nss1	38/46/151/159	1
	11a/n VHT80	Band 1&4	MCSO/Nss1	42,155	1
	802.11b			1,6,11	1,2
	802.11g			1,6,11	1,2

6dB Spectrum Bandwidth Measurement	802.11n HT20			1,6,11	1,2
	802.11n HT40			2,7,10	1,2
	11a BPSK	Band 4	6Mbps	149/157/165	1
	11a/n VHT20	Band 4	MCSO/Nss1	149/157/165	1
	11a/n VHT40	Band 4	MCSO/Nss1	151/159	1
	11a/n VHT80	Band 4	MCSO/Nss1	42,155	1
Radiated Emission Below 1GHz			-	-	-
Radiated Emission Above 1GHz	802.11b			1,6,11	
	802.11g			1,6,11	
	802.11n HT20			1,6,11	1,2
	802.11n HT40			2,7,10	1,2
	11a BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	1
	11a/n VHT20	Band 1&4	MCSO/Nss1	36/40/48/149/157/165	1
	11a/n VHT40	Band 1&4	MCSO/Nss1	38/46/151/159	1
	11a/n VHT80	Band 1&4	MCSO/Nss1	42,155	1
Band Edge Emission	802.11b			1,6,11	1,2
	802.11g			1,6,11	1,2
	802.11n HT20			1,6,11	1,2
	802.11n HT40			2,7,10	1,2
	11a BPSK	Band 1&4	6Mbps	36/40/48/149/157/165	1
	11a/n VHT20	Band 1&4	MCSO/Nss1	36/40/48/149/157/165	1
	11a/n VHT40	Band 1&4	MCSO/Nss1	38/46/151/159	1
	11a/n VHT80	Band 1&4	MCSO/Nss1	42,155	1
Frequency Stability	20MHz	Band 1&4	-	40/157	
	40MHz	Band 1&4	-	38/151	
	80MHz	Band 1&4	-		

Test Result of Occupied Bandwidth

Mode	Frequency	26dB Bandwidth (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11b	2412 MHz	N/A	10144 kHz	13702 kHz
	2437 MHz	N/A	10144 kHz	13702 kHz
	2462 MHz	N/A	10144 kHz	13702 kHz
802.11g	2412 MHz	N/A	15545 kHz	16426 kHz
	2437 MHz	N/A	15545 kHz	16426 kHz
	2462 MHz	N/A	15545 kHz	16426 kHz
802.11n (HT20)	2412 MHz	N/A	15545 kHz	16426 kHz
	2437 MHz	N/A	15545 kHz	16426 kHz
	2462 MHz	N/A	15545 kHz	16426 kHz
802.11n (HT40)	2422 MHz	N/A	33128 kHz	36378 kHz
	2447 MHz	N/A	33128 kHz	36378 kHz
	2452 MHz	N/A	33128 kHz	36378 kHz
802.11a	5180 MHz	18352 kHz	N/A	18462 kHz
	5200 MHz	18352 kHz	N/A	18462 kHz
	5240 MHz	18352 kHz	N/A	18462 kHz
	5745 MHz	N/A	17220 kHz	17220 kHz
	5785 MHz	N/A	17220 kHz	17220 kHz
	5825 MHz	N/A	17220 kHz	17220 kHz
802.11a/n MCSO/Nss1 VHT20	5180 MHz	18352 kHz	N/A	18462 kHz
	5200 MHz	18352 kHz	N/A	18462 kHz
	5240 MHz	18352 kHz	N/A	18462 kHz
	5745 MHz	N/A	16090 kHz	17220 kHz
	5785 MHz	N/A	16090 kHz	17220 kHz
	5825 MHz	N/A	16090 kHz	17220 kHz
802.11a/n MCSO/Nss1 VHT40	5190 MHz	38526 kHz	N/A	38622 kHz
	5230 MHz	38526 kHz	N/A	38622 kHz
	5755 MHz	N/A	25417 kHz	37850 kHz
	5795 MHz	N/A	25417 kHz	37850 kHz
802.11ac VHT80	5210 MHz	79834 kHz	N/A	80449 kHz
	5775 MHz	N/A	76282 kHz	78846 kHz

Application for Certification

- (1) Manufacturer: Mikrotikls SIA
Pernavas 46 Str.
Riga LV-1009 Latvia
- (2) Identification: Model: RB952Ui-5ac2nD-US
FCC I.D.: TV7RB952-5AC2ND IC: 7442A-9525AC
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from power received from authorized AC/DC power adapter. The EUT provides 5 Ethernet connection ports for communications and power. During testing, the EUT was powered from AC/DC power supply, POE, and connected to CPU through network cable.
- (9) Transition Provisions of 47CFR 15.37 are not requested
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement was addressed in the U-NII filing portion for this product and does not apply to this operational mode and application.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provide in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

The following information is submitted in accordance 47CFR dated October 1, 2015, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247 and Industry Canada RSS-247. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2013, KDB 558074 D01 v03r03, KDB 662911 D02 v01, RSS-247, Issue 1 and RSS-GEN Issue 4, the following information is submitted for processing application for Certification.


Equipment Testing Procedures

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions was performed as defined in ANSI C63.10-2013. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in exhibits for EUT placement used during testing.


Radiated Emission Test Procedure

Radiated emission testing was performed as required and specified in ANSI C63.10-2013 and referenced KDB documents. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. The table permitted orientation of the EUT in each of three orthogonal axis positions during testing. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 25,000 MHz was searched for during preliminary investigation. Refer to diagrams two and three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.




1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.2).
2. The I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. LISN may be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
 - 3.1 All other equipment powered from additional LISN(s).
 - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3 LISN at least 80 cm from nearest part of EUT chassis
4. Non-EUT components of EUT system being tested
5. Rear of EUT, including peripherals, shall all be aligned and flush with edge of tabletop (see 6.2.3.2).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

Diagram 1 Test arrangement for Conducted emissions



1. A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).
 - 1.1 LISN spaced at least 80 cm from nearest part of EUT chassis.
2. Antenna can be integral or detachable, depending on the EUT (see 6.3.1).
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).
4. For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions of tabletop equipment



Frequency: 9 kHz-30 MHz	Frequency: 30 MHz- 1 GHZ	Frequency: Above 1 GHz
Loop Antenna	Broadband Biconilog	Horn
RBW = 9 kHz	RBW = 120 kHz	RBW = 1 MHz
VBW = 30 kHz	VBW = 120 kHz	VBW = 1 MHz
Sweep time = Auto	Sweep time = Auto	Sweep time = Auto
Detector = PK, QP	Detector = PK, QP	Detector = PK, AV
Antenna Height 1m	Antenna Height 1-4m	Antenna Height 1-4m

Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)

Test Site Locations

Conducted EMI The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS

Radiated EMI The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS

Site Registration Refer to Annex for Site Registration Letters

NVLAP Accreditation Lab code 200087-0

List of Test Equipment

A Rohde and Schwarz ESU40 and/or Hewlett Packard 8591EM was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde and Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

Equipment	Manufacturer	Model (SN)	Band	Cal Date	Due
<input checked="" type="checkbox"/> LISN	FCC	FCC-LISN-50-2-10(1PA) (160611)	.15-30MHz	6/15	5/16
<input checked="" type="checkbox"/> Cable	Time Microwave	750HF290-750 (L10M)	9kHz-40 GHz	10/15	10/16
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/15	10/16
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/15	10/16
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/15	10/16
<input type="checkbox"/> Antenna	EMCO	3147 (40582)	200-1000MHz	10/15	10/16
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	5/15	5/17
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/15	10/16
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	5/15	5/17
<input checked="" type="checkbox"/> Antenna	EMCO	6509 (9502-1374)	.001-30 MHz	10/15	10/16
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/15	10/16
<input checked="" type="checkbox"/> Antenna	EMCO	3143 (9607-1277)	20-1200 MHz	5/15	5/16
<input type="checkbox"/> Analyzer	HP	8591EM (3628A00871)	9kHz-1.8GHz	5/15	5/16
<input checked="" type="checkbox"/> Analyzer	HP	8562A (3051A05950)	9kHz-110GHz	5/15	5/16
<input checked="" type="checkbox"/> Analyzer	HP External Mixers	11571, 11970	40GHz-110GHz	5/15	5/16
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	5/15	5/16
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/15	10/16
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/15	10/16
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/15	10/16

Units of Measurements

Conducted EMI Data is in dB μ V; dB referenced to one microvolt

Radiated EMI Data is in dB μ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

RFS (dB μ V/m @ 3m) = FSM (dB μ V) + A.F. (dB) - Gain (dB)

Environmental Conditions

Ambient Temperature 20.1° C

Relative Humidity 31%

Atmospheric Pressure 1020.5 mb

Intentional Radiators

As per 47CFR part 15 subpart C, and Industry Canada RSS-247, Issue 1, the following information is submitted for consideration and demonstration of compliance with regulation and standards.

Antenna Requirements

The EUT incorporates integral antenna system and offers no provision for connection to alternate system. The EUT utilizes permanently attached antennas mounted to the printed circuit board. The antenna connection point complies with the unique antenna connection requirements. The antenna connection point complies with the unique antenna connection requirements. The requirements of 15.203 are fulfilled there are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the on the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in restricted bands. Emissions were investigated at the antenna port and OATS, using appropriate antennas or pyramidal horns, amplification stages, and spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed radiated emission values take into account the measured radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 General Radiated Emissions in Restricted Bands Data

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
2390.0	53.6	N/A	30.6	41.1	N/A	28.2	54.0
2483.5	61.0	N/A	46.3	44.9	N/A	33.0	54.0
4824.0	55.4	N/A	52.2	56.1	N/A	52.8	54.0
4874.0	53.9	N/A	48.7	56.2	N/A	52.8	54.0
4924.0	54.0	N/A	16.6	16.1	N/A	51.2	54.0
7236.0	45.7	N/A	32.3	43.0	N/A	30.4	54.0
7311.0	44.9	N/A	31.7	45.9	N/A	32.8	54.0
7386.0	54.0	N/A	16.6	16.1	N/A	33.0	54.0
12060.0	51.1	N/A	38.0	51.7	N/A	38.4	54.0
12185.0	52.0	N/A	39.3	53.0	N/A	39.2	54.0
12310.0	50.5	N/A	38.1	51.4	N/A	38.2	54.0
14472.0	53.0	N/A	40.2	53.1	N/A	40.0	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Table 2 General Radiated Emissions in Restricted Bands Data

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
125.0	36.3	31.9	N/A	36.8	32.6	N/A	43.5
262.6	49.2	41.2	N/A	44.2	41.2	N/A	46.0
275.0	43.2	38.5	N/A	42.1	37.2	N/A	46.0
283.2	47.2	43.6	N/A	40.8	37.1	N/A	46.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the emissions requirements of 47CFR 15.205, RSS-GEN and RSS-247, Issue 1 Intentional Radiators. The EUT provided a worst-case minimum margin of -1.2 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted Emissions Procedure

The EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. The manufacturer supplied supporting equipment, which provided direct current power to the EUT and was connected to the LISN. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT support equipment power the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing were carried out individually for each current carrying conductor of the EUT support equipment. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequency of each emission displaying the highest amplitude. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then the data was recorded with maximum conducted emissions levels. Refer to figures one and two for plots of the EUT support equipment AC Line Conducted emissions.




Figure 1 AC Line Conducted Emissions Line 1




Figure 2 AC Line Conducted Emissions Line 2

Table 3 AC Line Conducted Emissions Data (Highest Emissions Line L1)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	162.000000000 kHz	45.32	Quasi Peak	-20.04
1	330.000000000 kHz	29.42	Quasi Peak	-30.03
1	354.000000000 kHz	35.86	Quasi Peak	-23.01
2	358.000000000 kHz	30.62	Average	-18.16
1	406.000000000 kHz	38.55	Quasi Peak	-19.18
2	426.000000000 kHz	31.75	Average	-15.58
1	2.018000000 MHz	34.15	Quasi Peak	-21.85
2	13.812000000 MHz	33.51	Average	-16.49
2	14.148000000 MHz	35.53	Average	-14.47
1	14.152000000 MHz	38.39	Quasi Peak	-21.61
2	14.488000000 MHz	32.82	Average	-17.18
2	14.824000000 MHz	30.72	Average	-19.28

Other emissions present had amplitudes at least 20 dB below the limit.

Table 4 AC Line Conducted Emissions Data (Highest Emissions Line L2)

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
1	158.000000000 kHz	45.96	Quasi Peak	-19.60
1	398.000000000 kHz	39.03	Quasi Peak	-18.87
2	402.000000000 kHz	32.36	Average	-15.45
2	406.000000000 kHz	31.30	Average	-16.42
1	414.000000000 kHz	40.69	Quasi Peak	-16.88
2	418.000000000 kHz	30.32	Average	-17.17
1	422.000000000 kHz	40.55	Quasi Peak	-16.86
2	426.000000000 kHz	32.12	Average	-15.21
1	426.000000000 kHz	39.94	Quasi Peak	-17.39
1	1.682000000 MHz	32.11	Quasi Peak	-23.89
2	13.808000000 MHz	32.70	Average	-17.30
2	14.148000000 MHz	28.54	Average	-21.46

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted Emissions

The EUT test system demonstrated compliance to the conducted emissions requirements of 47CFR 15.207, RSS-247 Issue 1 and RSS-GEN. The EUT demonstrated minimum margin of -14.4 dB below the limit. Measurements were taken using the peak, quasi peak, and average, measurement function for each emissions amplitude and were below the limits stated in the specification. Other emissions were present with recorded data representing worst-case amplitudes.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or Double Ridge or pyramidal horns and mixers from 1 GHz to 25 GHz, notch filters, and appropriate amplifiers and external mixers were utilized.

Table 5 General Radiated Emissions from EUT Data (Highest Emissions)

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
125.0	36.3	31.9	N/A	36.8	32.6	N/A	43.5
138.4	43.2	32.7	N/A	36.2	31.7	N/A	43.5
143.3	41.4	34.0	N/A	40.2	33.4	N/A	43.5
144.7	39.2	34.0	N/A	37.0	32.2	N/A	43.5
145.3	38.8	33.4	N/A	36.3	32.4	N/A	43.5
146.7	36.2	32.7	N/A	35.4	30.2	N/A	43.5
147.5	41.1	31.9	N/A	33.9	28.7	N/A	43.5
148.1	39.1	34.3	N/A	35.1	32.3	N/A	43.5
155.6	35.1	31.3	N/A	35.6	29.8	N/A	43.5
216.0	38.5	34.0	N/A	31.9	27.9	N/A	43.5
262.6	49.2	41.2	N/A	44.2	41.2	N/A	46.0
275.0	43.2	38.5	N/A	42.1	37.2	N/A	46.0
283.2	47.2	43.6	N/A	40.8	37.1	N/A	46.0
289.0	47.4	44.1	N/A	40.1	36.9	N/A	46.0
290.9	45.9	43.2	N/A	38.8	35.8	N/A	46.0
300.4	45.2	42.8	N/A	36.0	32.2	N/A	46.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR part 15 and Industry Canada RSS-247 Issue 1 Intentional Radiators. The EUT demonstrated a minimum margin of -1.9 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the 2400-2483.5 MHz Frequency Band

Radiated emissions were measured on the Open Area Test Site (OATS) at a three-meter distance. The EUT utilizes permanently attached printed circuit board antenna. The EUT was placed on a turntable elevated as required above the ground plane at a distance of 3 meters from the FSM antenna located on the OATS. The peak and quasi-peak amplitude of the frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of emissions above 1000 MHz were measured using a spectrum analyzer. Emissions data was recorded from the measurement results. Data presented reflects measurement result corrected to account for measurement system gains and losses. Plots were made of transmitter performance for reference purposes.

This product utilizes permanently attached antenna system and offers no provision for antenna port conducted measurements. As such, the testing procedures as defined in publications KDB 558074 D01 DTS Meas Guidance v03r03, KDB 662911 D02, and ANSI C63.10-2013 were utilized during compliance testing. These procedures provide for antenna port measurement or measurement of maximum field strength and conversion calculations for comparison with requirements. Refer to figures three through fourteen showing plots of the EUT performance displaying compliance with the specifications.

1. The transmitter's peak power was measured as specified in 9.1.2 of KDB 558074
2. Emission DTS Bandwidth was measured in compliance with KDB 558074 paragraph 8.
3. Maximum Power Spectral Density was measured in compliance with KDB 662911 paragraph 10.
4. Unwanted Radiated Emissions were measured in compliance with KDB 558074 paragraph 11 and specified in ANSI C63-10 at a 3-meters distance located on the OATS.
5. Radiated Emissions Levels in restricted bands were measured in compliance with KDB 558074 paragraph 12, specified in ANSI C63-10 at a 3-meters distance located on the OATS.
6. Band-Edge measurements were performed in compliance with KDB 558074 paragraph 13 and specified in ANSI C63-10.




Figure 3 Plot of Transmitter Emissions (Across Operational Band 802.11b)




Figure 4 Plot of Transmitter Emissions (Across Operational Band, 802.11g)




Figure 5 Plot of Transmitter Emissions (Across Operational Band, 802.11n)




Figure 6 Plot of Transmitter Low Band Edge (802.11b)




Figure 7 Plot of Transmitter Low Band Edge (802.11g)




Figure 8 Plot of Transmitter Low Band Edge (802.11n)




Figure 9 Plot of Transmitter High Band Edge (802.11b)




Figure 10 Plot of Transmitter High Band Edge (802.11g)




Figure 11 Plot of Transmitter High Band Edge (802.11n)




Figure 12 Plot of Transmitter 6-dB Occupied Band Width (802.11b)




Figure 13 Plot of Transmitter 6-dB Occupied Band Width (802.11g)




Figure 14 Plot of Transmitter 6-dB Occupied Band Width (802.11n)

Transmitter Emissions Data

Table 6 Transmitter Power and Emissions

Frequency MHz	Calculated Conducted Antenna Port Output Power (Watts) Total / Chain 0 / Chain 1	6-dB Occupied Bandwidth kHz	Calculated Power Spectral Density dBm
20 MHz b-Mode			
2412.0	0.091 / 0.043 / 0.0475	10,144	-6.3
2437.0	0.089 / 0.044 / 0.045	10,144	-6.9
2462.0	0.111 / 0.055 / 0.057	10,144	-6.1
20 MHz g-Mode			
2412.0	0.094 / 0.045 / 0.049	15,545	-10.7
2437.0	0.088 / 0.043 / 0.046	15,545	-11.2
2462.0	0.116 / 0.058 / 0.058	15,545	-11.06
40 MHz Mode			
2422.0	0.094 / 0.046 / 0.049	33,013	-12.8
2447.0	0.096 / 0.046 / 0.050	33,013	-12.2
2452.0	0.095 / 0.045 / 0.050	33,013	-13.2

Table 7 Transmitter Radiated Emission

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
2412.0	101.8	93.6	94.2	86.4	--
4824.0	55.4	52.2	56.1	52.8	54.0
7236.0	45.7	32.3	43.0	30.4	54.0
9648.0	47.6	34.8	48.0	35.3	54.0
12060.0	51.1	38.0	51.7	38.4	54.0
14472.0	53.0	40.2	53.1	40.0	54.0
16884.0	56.0	43.6	56.3	43.4	54.0
2437.0	101.6	94.3	95.2	87.3	--
4874.0	53.9	48.7	56.2	52.8	54.0
7311.0	44.9	31.7	45.9	32.8	54.0
9748.0	48.0	34.7	48.0	35.1	54.0
12185.0	52.0	39.3	53.0	39.2	54.0
14622.0	53.3	40.7	53.4	40.6	54.0
17059.0	56.2	43.1	55.4	42.7	54.0
2462.0	102.7	95.0	96.9	89.5	--
4924.0	54.8	49.0	54.9	51.2	54.0
7386.0	46.7	33.7	46.0	33.0	54.0
9848.0	47.1	34.1	49.9	37.9	54.0
12310.0	50.5	38.1	51.4	38.2	54.0
14772.0	53.3	40.2	53.2	40.3	54.0
17234.0	57.1	44.0	57.2	44.2	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15.247 and Industry Canada RSS-247. The calculated peak power was 0.111-Watt total power. The worst-case total peak power spectral density provided a minimum margin of -22.3 dB below the requirements. The minimum margin harmonic radiated emission provided -1.2 dB margin below requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the 47CFR Part 15C and Industry Canada RSS-247 emissions requirements. There were no deviations or modifications to the specifications.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Site Registration Letter
- Annex E Industry Canada Site Registration Letter

Annex A Measurement Uncertainty Calculations

Measurement uncertainty calculations were made for the laboratory. Result of measurement uncertainty calculations are recorded below for AC line conducted and radiated emission measurements.

Measurement Uncertainty	U _(E)	U _(lab)
3 Meter Horizontal 30-200 MHz Measurements	2.08	4.16
3 Meter Vertical 30-200 MHz Measurements	2.16	4.33
3 Meter Vertical Measurements 200-1000 MHz	2.99	5.97
10 Meter Horizontal Measurements 30-200 MHz	2.07	4.15
10 Meter Vertical Measurements 30-200 MHz	2.06	4.13
10 Meter Horizontal Measurements 200-1000 MHz	2.32	4.64
10 Meter Vertical Measurements 200-1000 MHz	2.33	4.66
3 Meter Measurements 1-6 GHz	2.57	5.14
3 Meter Measurements 6-18 GHz	2.58	5.16
AC Line Conducted	1.72	3.43

Annex B Rogers Labs Test Equipment List

List of Test Equipment	Calibration	Date	Due
Spectrum Analyzer: Rohde & Schwarz ESU40		5/15	5/16
Spectrum Analyzer: HP 8562A, HP Adapters: 11518, 11519, and 11520		5/15	5/16
Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W			
Spectrum Analyzer: HP 8591EM		5/15	5/16
Antenna: EMCO Biconilog Model: 3143		5/15	5/16
Antenna: Sunol Biconilog Model: JB6		10/15	10/16
Antenna: EMCO Log Periodic Model: 3147		10/15	10/16
Antenna: Com Power Model: AH-118		10/15	10/16
Antenna: Com Power Model: AH-840		5/15	5/17
Antenna: Antenna Research Biconical Model: BCD 235		10/15	10/16
Antenna: EMCO 6509		10/15	10/16
LISN: Compliance Design Model: FCC-LISN-2.Mod.cd, 50 μ Hy/50 ohm/0.1 μ f		10/15	10/16
R.F. Preamp CPPA-102		10/15	10/16
Attenuator: HP Model: HP11509A		10/15	10/16
Attenuator: Mini Circuits Model: CAT-3		10/15	10/16
Attenuator: Mini Circuits Model: CAT-3		10/15	10/16
Cable: Belden RG-58 (L1)		10/15	10/16
Cable: Belden RG-58 (L2)		10/15	10/16
Cable: Belden 8268 (L3)		10/15	10/16
Cable: Time Microwave: 4M-750HF290-750		10/15	10/16
Cable: Time Microwave: 10M-750HF290-750		10/15	10/16
Frequency Counter: Leader LDC825		2/16	2/17
Oscilloscope Scope: Tektronix 2230		2/16	2/17
Wattmeter: Bird 43 with Load Bird 8085		2/16	2/17
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140		2/16	2/17
R.F. Generators: HP 606A, HP 8614A, HP 8640B		2/16	2/17
R.F. Power Amp 65W Model: 470-A-1010		2/16	2/17
R.F. Power Amp 50W M185- 10-501		2/16	2/17
R.F. Power Amp A.R. Model: 10W 1010M7		2/16	2/17
R.F. Power Amp EIN Model: A301		2/16	2/17
LISN: Compliance Eng. Model 240/20		2/16	2/17
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08		2/16	2/17
Antenna: EMCO Dipole Set 3121C		2/16	2/17
Antenna: C.D. B-101		2/16	2/17
Antenna: Solar 9229-1 & 9230-1		2/16	2/17
Audio Oscillator: H.P. 201CD		2/16	2/17
ELGAR Model: 1751		2/16	2/17
ELGAR Model: TG 704A-3D		2/16	2/17
ESD Test Set 2010i		2/16	2/17
Fast Transient Burst Generator Model: EFT/B-101		2/16	2/17
Field Intensity Meter: EFM-018		2/16	2/17
KEYTEK Ecat Surge Generator		2/16	2/17
Shielded Room 5 M x 3 M x 3.0 M			

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

Mikrotikls SIA

Model: RB952Ui-5ac2nD-US

Test #: 160414d

Test to: 47CFR 15.247, RSS-247

File: Mikrotik RB952Ui5ac2nD DTS TstRpt 160414d

S/N: 5EB204A373B8/516

FCC ID#: TV7RB952-5AC2ND

IC: 7442A-9525AC

Date: July 28, 2016

Page 42 of 45

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 17 years' experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held


Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.



Scot D. Rogers

Annex D FCC Site Registration Letter

FEDERAL COMMUNICATIONS COMMISSION

**Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046**

April 16, 2015

Registration Number: 90910

Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053

Attention: Scot Rogers,


Re: Measurement facility located at Louisburg
3 & 10 meter site
Date of Renewal: April 16, 2015

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,



Phyllis Parrish
Industry Analyst

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotiks SIA
Model: RB952Ui-5ac2nD-US
Test #: 160414d
Test to: 47CFR 15.247, RSS-247
File: Mikrotik RB952Ui5ac2nD DTS TstRpt 160414d

S/N: 5EB204A373B8/516
FCC ID#: TV7RB952-5AC2ND
IC: 7442A-9525AC
Date: July 28, 2016
Page 44 of 45

Annex E Industry Canada Site Registration Letter



June 08, 2015

OUR FILE: 46405-3041
Authorization No: 010277847-001

Rogers Labs Inc.
4405 West 259th Terrace
Louisburg, KS
USA
66053

Attention: Mr. Scot D. Rogers

Dear Sir:

The Bureau has received your application for the renewal of 3m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**Site# 3041A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: **3041A**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2009 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2009 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2009 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed **three years**. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL; http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Bill Payn
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station AH@
Ottawa, Ontario K2H 8S2
Email: certification.bureau@ic.gc.ca

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotikls SIA
Model: RB952Ui-5ac2nD-US
Test #: 160414d
Test to: 47CFR 15.247, RSS-247
File: Mikrotik RB952Ui5ac2nD DTS TstRpt 160414d

S/N: 5EB204A373B8/516
FCC ID#: TV7RB952-5AC2ND
IC: 7442A-9525AC
Date: July 28, 2016
Page 45 of 45