

Appendix for the Report

Dosimetric Assessment of the Tracking Device Smart Tag from buddi Limited (FCC ID: ZDLST1)

According to the FCC Requirements

SAR Distribution Plots

July 11, 2014

IMST GmbH
Carl-Friedrich-Gauß-Str. 2 - 4
D-47475 Kamp-Lintfort

Customer
TRaC Global Limited
Unit 1, Pendle Place, Skelmersdale
West Lancashire
WN8 9PN

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written approval of the testing laboratory.

1 SAR Distribution Plots

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [ST_325_bahl_3_bottom_bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS850 (Class 10)

Communication System: GPRS 850; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.94$ mho/m; $\epsilon_r = 56.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(6.25, 6.25, 6.25); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 23.01.2014
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.692 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.3 V/m; Power Drift = 0.099 dB

Peak SAR (extrapolated) = 1.14 W/kg

SAR(1 g) = 0.733 mW/g; SAR(10 g) = 0.493 mW/g

Maximum value of SAR (measured) = 0.796 mW/g




Fig. 1: SAR distribution for GPRS 850 (2TX), channel 128, back side, 0 mm (July 04, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [ST_325_bahm_3_bottom_bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS850 (Class 10)

Communication System: GPRS 850; Frequency: 836.6 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 836.6$ MHz; $\sigma = 0.95$ mho/m; $\epsilon_r = 56.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(6.25, 6.25, 6.25); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 23.01.2014
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.15 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 32.9 V/m; Power Drift = 0.185 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.787 mW/g

Maximum value of SAR (measured) = 1.30 mW/g




Fig. 2: SAR distribution for GPRS 850 (2TX), channel 190, back side, 0 mm (July 04, 2014)

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [ST_325_bahh_3_bottom_bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS850 (Class 10)

Communication System: GPRS 850; Frequency: 848.8 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 848.8$ MHz; $\sigma = 0.94$ mho/m; $\epsilon_r = 56.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(6.25, 6.25, 6.25); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 23.01.2014
- Phantom: SAM Sugar 1059; Type: Speag; Serial: 1059
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.785 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.5 V/m; Power Drift = 0.146 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.816 mW/g; SAR(10 g) = 0.547 mW/g

Maximum value of SAR (measured) = 0.888 mW/g




Fig. 3: SAR distribution for GPRS 850 (2TX), channel 251, back side, 0 mm (July 04, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [ST 325 yphl 3 bottom bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS1900 (Class 10)

Communication System: GPRS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 53.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.49, 4.49, 4.49); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.60 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 33.1 V/m; Power Drift = -0.139 dB

Peak SAR (extrapolated) = 2.74 W/kg

SAR(1 g) = 1.48 mW/g; SAR(10 g) = 0.833 mW/g

Maximum value of SAR (measured) = 1.70 mW/g




Fig. 4: SAR distribution for GPRS 1900 (2TX), channel 512, back side, 0 mm (July 10, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [ST 325 yphl 3 bottom bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS1900 (Class 10)

Communication System: GPRS 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.47$ mho/m; $\epsilon_r = 53.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.49, 4.49, 4.49); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.60 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 33.1 V/m; Power Drift = -0.139 dB

Peak SAR (extrapolated) = 2.74 W/kg

SAR(1 g) = 1.48 mW/g; SAR(10 g) = 0.833 mW/g

Maximum value of SAR (measured) = 1.70 mW/g




Fig. 5: SAR distribution for GPRS 1900 (2TX), channel 661, back side, 0 mm (July 10, 2014)

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [ST 325 yphh 3 bottom bat.da4](#)

DUT: Buddi; Type: Smart Tag; Serial: 352964058217325

Program Name: GPRS1900 (Class 10)

Communication System: GPRS 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.49, 4.49, 4.49); Calibrated: 28.01.2014
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.09.2013
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Body/Area Scan (8x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.40 mW/g

Body/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 38.3 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 4.22 W/kg

SAR(1 g) = 2.25 mW/g; SAR(10 g) = 1.27 mW/g

Maximum value of SAR (measured) = 2.58 mW/g




Fig. 6: SAR distribution for GPRS 1900 (2TX), channel 810, back side, 0 mm (July 10, 2014)