

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

|                     |                           |
|---------------------|---------------------------|
| Product Description | Wearing Bluetooth Headset |
| Model Name          | JBuds Band                |
| FCC ID              | 2AHYVBAND                 |

### 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

Where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

### 3. CALCULATION

According to the follow transmitter output power (  $P_t$  ) formula :

BR/EDR

$P_t = 4.179 B_m = 2.62 \text{ mW}$

The result for RF exposure evaluation

$\text{SAR} = (2.62 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.48(\text{GHz})}] = 0.83 < 3.0$  for 1-g SAR

### 4. CONCLUSION

The SAR evaluation is not required.