

June 23, 2022

LAt-Lon, LLC Benjamin Jull 2300 S. Jason St. Denver, CO 90223

Dear Mr. Jull,

Enclosed is the EMC test report for compliance testing of the, Lat-Lon X15500 as tested to the requirements of the

- FCC Part 15 Subpart B
- Innovation, Science, and Economic Development (ISED) Canada ICES-003 Issue 7

Thank you for using the services of Eurofins Electrical and Electronic Testing NA, Inc. Please contact me if you have any questions regarding these results or if Eurofins E&E can be of further service to you.

Sincerely,

Gary Chou

Documentation Department Eurofins Electrical and Electronic Testing NA, Inc.

Reference: EMCS117410-FCC-IC



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins Electrical and Electronic Testing NA, Inc. While use of the A2LA logo in this report reflects Eurofins Electrical and Electronic Testing NA, Inc. accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins Electrical and Electronic Testing NA, Inc. is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

Report: EMCS117636-FCC-ICES



Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	June 23, 2022	Initial Issue.

Report: EMCS117636-FCC-ICES

© 2022, Eurofins Electrical and Electronic Testing NA, Inc.



Table of Contents

Testing Summary	4
Overview	5
Test Site	5
Measurement Uncertainty	5
Equipment Overview	6
Modifications to the EUT	6
Modifications to the Standard	6
Disposition of EUT	6
Electromagnetic Compatibility Emission Criteria	7
Limits for Conducted Disturbance at Mains Terminals	7
Radiated Emissions: Limits of Electromagnetic Radiation Disturbance	9
	Testing Summary Overview Test Site Measurement Uncertainty Equipment Overview Modifications to the EUT Modifications to the Standard Disposition of EUT Electromagnetic Compatibility Emission Criteria Limits for Conducted Disturbance at Mains Terminals Radiated Emissions: Limits of Electromagnetic Radiation Disturbance



1.0 Testing Summary

Test is compliant to the following specification(s).

E&E

- FCC Part 15 Subpart B
- Innovation, Science, and Economic Development (ISED) Canada ICES-003 Issue 7

Alberto Silvider

Alberto Saldiver Test Engineer, Wireless Laboratory

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements.

Gary Chou

Gary Chou Wireless Lab Manager, California

Report: EMCS117636-FCC-ICES



2.0 Overview

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing, Lat-Lon X15500 (PN:22319-5-J117636).

The results obtained relate only to the item(s) tested.

E&E

Model(s) Tested:	X15500
Equipment Emissions Class:	В

2.1 Test Site

All testing was performed at Eurofins Electrical and Electronic Testing NA, Inc., 3162 Belick St. Santa Clara, CA 95054. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology. Eurofins Electrical and Electronic Testing NA, Inc. has been accredited by the American Association for Laboratory Accreditation (A2LA) (Certificate #: 0591.02) in accordance with ISO/IEC 17025:2017.

2.2 Measurement Uncertainty

Measurement uncertainty calculated as per NIST Technical Note (TN) 1297 and ANSI / NCSL Z540-2, as equivalent to EN 55016-4-2 / IEC CISPR 16-4-2.

Test Method	Typical Expanded Uncertainty (dB)	К	Confidence Level
Radiated Emissions, (30 MHz – 1 GHz)	±3.24	2	95%
Radiated Emissions, (1 GHz – 6 GHz)	±3.92	2	95%
Conducted Emission Voltage	±2.44	2	95%
Conducted Emission Telecom	±3.53	2	95%

Measurement Uncertainty



2.4 Equipment Overview

Name of EUT/Model:	Lat-Lon X15500/ X15500
Voltage:	3.3 V
AC or DC:	DC
Voltage Frequency:	N/A
Number of Phases:	1
PN/ SN	22319-5-J117636
EUT Arrangement:	Table Top
System with Multiple Chassis?	False
Highest Internal Frequency (MHz):	2480 MHz

EUT List

Ref. ID	Slot #	Name/Description	Model Number	Part Number	Serial Number	Rev. #
А		Lat-Lon X15500	X15500	22319-5-J117636	22319-5-J117636	N/A

Support Equipment

Ref. ID	Name/Description	Manufacturer	Model Number	Customer Supplied Calibration Data
А	Asset Tracker	Lat-Lon, LLC	N/A	N/A

2.5 Modifications to the EUT

No modifications were made to the EUT.

2.6 Modifications to the Standard

No modifications were made to the Test Standard.

2.7 Disposition of EUT

The test sample including all support equipment (if any), submitted to the Electromagnetic Compatibility Lab for testing was returned to Lat-Lon, LLC upon completion of testing.

3.0 Electromagnetic Compatibility Emission Criteria

3.1 Limits for Conducted Disturbance at Mains Terminals

Test Method: ANSI 63.4:2014

Sample Calculation:

 $R_f - S = M$ where:

 R_{f} = Receiver Reading in dBuV

S = Specification Limit in dBuV

M = Margin to Specification in +/- dB

Test Requirement(s): The following standards specified below are covered in the scope of this section of the test

- FCC Part 15 Subpart B
- Innovation, Science, and Economic Development (ISED) Canada ICES-003 Issue 7

Frequency Range	Class A Lir	nits(dBµV)	Class B Limits (dBµV)		
(MHz)	Quasi-Peak	Average	Quasi- Peak	Average	
0.15 - 0.5	79	66	66 to 56	56 to 46	
0.5 - 5	73	60	56	46	
5 - 30	73	60	60	50	
Nets 1. The large limit dell and est the transition for even size					

The EUT shall meet the Class B limits shown in the table below.

Note 1 – The lower limit shall apply at the transition frequencies.

Note 2 – The limit decreases linearly with the logarithm if the frequency in the range 0.15 MHz to 0.5 MHz.

Conducted Emissions - Limits

Test Procedure: The EUT was placed on a non-metallic table, 80 cm above the ground plane and 40 cm away from the vertical reference ground plane . The method of testing, test conditions, and test procedures of ANSI C63.4-2014 were used. The EUT was powered through a $50\Omega/50\mu$ H LISN. An EMI receiver, connected to the measurement port of the LISN, scanned the frequency range from 150 kHz to 30 MHz in order to find the peak conducted emissions. All peak emissions within 6 dB of the limit were re-measured using a quasipeak and/or average detector as appropriate. Any measured frequency that exhibits a margin of compliance that is less than 3 dB below the specification limit is marked. Eurofins E&E recommends that every emission measured, has at least a 3 dB margin to allow for deviations in the emission characteristics that may occur during the production process. Photographs of test setup are presented below.

Test Software Used: PMM Release Suite Rev 2.04 and Jamila CE Rev 5.3 was used to perform this test.

Test Results:

	FCC Part 15 Subpart B		
	Innovation, Science, and Economic Development		
Test Standard:	(ISED) Canada ICES-003 Issue 7		
	Class B		
Test Name	Conducted Emissions		
Test Dates:	N/A		
Laboratory	Eurofins Electrical and Electronic Testing NA, Inc.		
Test Engineer:	N/A		
Test Results:	N/A		
Additional	DUT is nowered by DC nower so test is not applicable		
Notes:	DOT is powered by DC power so test is not applicable		

Report: EMCS117636-FCC-ICES



3.3 Radiated Emissions: Limits of Electromagnetic Radiation Disturbance

Test Method: ANSI C63.4-2014

Test Requirement(s): The following standards specified below are covered in the scope of this section of the test report:

- FCC Part 15 Subpart B
- Innovation, Science, and Economic Development (ISED) Canada ICES-003 Issue 7

§15.109 (a)/ ICES-003 3.2.2

Except for Class B digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field Strength (dBµV/m)
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

Test Procedure:

The EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semianechoic chamber. The method of testing, test conditions, and test procedures of ANSI C63.4-2014 were used. Any measured frequency that exhibits a margin of compliance that is less than 3 dB below the specification limit is marked. Eurofins E&E recommends that every emission measured, has at least a 3 dB margin to allow for deviations in the emission characteristics that may occur during the production process.

For emissions between 30 MHz and 1000 MHz, a biconilog antenna was located 3m from the EUT on an adjustable mast. A pre-scan was first performed in order to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a quasi-peak detector with a 120 kHz resolution bandwidth.

For emission between 1 GHz and 18 GHz, a double ridged guide horn was located 3 m from the EUT on an adjustable mast. A pre-scan was performed and used to find prominent radiated emissions. For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied depending on the geometry of the EUT. In order to ensure maximized emissions, the horn antenna was positioned both vertically and laterally. Measurements in both horizontal and vertical polarities were made and the data was recorded. Unless otherwise specified, measurements were made using a peak and average detector with a 1 MHz resolution bandwidth.



Test Software Used: BAT EMC was used to perform this test.

Test Results:

	FCC Part 15 Subpart B		
	Innovation, Science, and Economic Development		
Test Standard:	(ISED) Canada ICES-003 Issue 7		
	Class B		
Test Name	Radiated Emissions		
Test Dates:	05/28/2022		
Laboratory	Eurofins Electrical and Electronic Testing NA, Inc.		
Test Engineer:	Alberto Saldiver		
Test Results:	Pass		
Additional	N/A		
Notes:	IN/A		



Test Summary

Test Data

EUT Test Condition		Measurement Detail		
Mode	Normal Operation	Frequency Range	30MHz-1GHz	
Input Power	3.3 Vdc	Detector Function	Quasi-Peak	
Environmental Conditions 25 deg. C, 70% RH		Tested By Alberto Saldiver		
Antenna Polarity & Test Distance: Vertical At 3m				

	Antenna Polarity & Test Distance: Vertical At 3m									
No.	Frequency (MHz)	Polarization	Level Peak[dB(uV/m)]	Limit Peak dB(uV/m)	Margin Peak [dB]	Height (m)	Angle (Deg)	Factor [dB(1/m)]	Pass/ Fail	
1	30.648	Vertical	11.314	40	-28.686	1	111	-9.08	Pass	
2	105.756	Vertical	10.679	43.5	-32.821	2.55	235	-12.26	Pass	
3	624.562	Vertical	16.604	46	-29.396	2.2	145	-3.41	Pass	

Table 1. Radiated Emissions, Test Results



#1 - 30MHz-1GHz (Vertical)

Figure 1. Radiated Emissions, Plot (Vertical)

Report: EMCS117636-FCC-ICES

© 2022, Eurofins Electrical and Electronic Testing NA, Inc.



EUT Test Condition		Measurement Detail				
Mode	Normal Operation	Frequency Range	30MHz-1GHz			
Input Power	3.3 Vdc	Detector Function	Quasi-Peak			
Environmental Conditions	25 deg. C, 70% RH	Tested By Alberto Saldiver				
Antenna Polarity & Test Distance: Horizontal At 3m						

	Antenna Polarity & Test Distance: Horizontal At 3m										
No.	Frequency (MHz)	Frequency (MHz) Polarization Level Peak[dB(uV/m)]		Limit Peak dB(uV/m)	Margin Peak [dB]	Height (m)	Angle (Deg)	Factor [dB(1/m)]	Pass/ Fail		
1	30.852	Horizontal	14.082	40	-25.918	3.85	88	-7	Pass		
2	136.904	Horizontal	6.843	43.5	-36.657	1.03	272	-13.22	Pass		
3	923.166	Horizontal	19.922	46	-26.078	2.12	188	0.73	Pass		

Table 2. Radiated Emissions, Test Results



Figure 2. Radiated Emissions, Plot (Horizontal)

Report: EMCS117636-FCC-ICES



EUT Test Condition		Measurement Detail				
Mode	Normal Operation	Frequency Range	1GHz-13GHz			
Input Power	3.3 Vdc	Detector Function	Quasi-Peak			
Environmental Conditions	25 deg. C, 70% RH	Tested By Alberto Saldiver				
Antenna Polarity & Test Distance: Vertical At 3m						

	Antenna Polarity & Test Distance: Vertical at 3m									
No.	Frequency (MHz)	Source	Polarization	Level Peak[dB(uV/m)]	Limit Peak dB(uV/m)	Margin Peak [dB]	Height (m)	Angle (Deg)	Factor [dB(1/m)]	Pass/ Fail
1	1500.4	Peak	Vertical	42.503	74	-31.497	1.74	234	-2.76	Pass
2	1500.4	Average	Vertical	36.374	54	-17.626	1.74	234	-2.76	Pass
3	2567.2	Peak	Vertical	38.836	74	-35.164	1	35	1.3	Pass
4	2567.2	Average	Vertical	25.95	54	-28.05	1	35	1.3	Pass
5	12598	Peak	Vertical	48.785	74	-25.215	1.67	168	4.19	Pass
6	12598	Average	Vertical	35.691	54	-18.309	1.67	168	4.19	Pass

Table 3. Radiated Emissions, Test Results



Figure 3. Radiated Emissions, Plot

Report: EMCS117636-FCC-ICES



EUT Test Condition		Measurement Detail					
Mode	Normal Operation	Frequency Range	1GHz-13GHz				
Input Power	3.3 Vdc	Detector Function	Quasi-Peak				
Environmental Conditions	25 deg. C, 70% RH	Tested By Alberto Saldiver					
Antenna Polarity & Test Distance: Horizontal At 3m							

	Antenna Polarity & Test Distance: Vertical at 3m									
No.	Frequency (MHz)	Source	Polarization	Level Peak[dB(uV/m)]	Limit Peak dB(uV/m)	Margin Peak [dB]	Height (m)	Angle (Deg)	Factor [dB(1/m)]	Pass/ Fail
1	1187.2	Peak	Horizontal	41.582	74	-32.418	1	315	-4.37	Pass
2	1187.2	Average	Horizontal	36.658	54	-17.342	1	315	-4.37	Pass
3	2585.2	Peak	Horizontal	38.638	74	-35.362	1.79	218	0.86	Pass
4	2585.2	Average	Horizontal	25.389	54	-28.611	1.79	218	0.86	Pass
5	11446	Peak	Horizontal	48.685	74	-25.315	1.6	24	3.62	Pass
6	11446	Average	Horizontal	34.441	54	-19.559	1.6	24	3.62	Pass







Figure 4. Radiated Emissions, Plot

Report: EMCS117636-FCC-ICES





Radiated Emissions, Test Setup- Below 1GHz Front View





Radiated Emissions, Test Setup- Below 1GHz Rear View





. Radiated Emissions, Test Setup- Above 1GHz Front View

Report: EMCS117636-FCC-ICES

© 2022, Eurofins Electrical and Electronic Testing NA, Inc.





Radiated Emissions, Test Setup- Above 1GHz Rear View



E&E

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2017.

Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1S2003	EMI Test Receiver	ROHDE & SCHWARZ	N9030B	10/08/2021	10/08/2022
1S2399	Turntable Controller	SUNOL SCIENCE	SC99V	Not Required	Not Required
1S2486	5 Meter Chamber Control Room	Panashield	5 Meter Control Room	Not Required	Not Required
1S2435	Horn Antenna	ETS-LINDGREN	3117	03/03/2021	03/09/2023
N/A	Preamplifier	EMC Instrument	EMC118A45SE	Note 1	Note 1
1S2668	Preamplifier	Sonoma Instrument	310N	Note 1	Note 1
1S2600	Antenna	TESEQ GmbH	D-12623	05/11/2021	05/ 11/ 2023
Note 1: V	verified by calibrated instrumentation a	at the time of testing			

Table 5. Radiated Emissions, Test Equipment

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.



END OF REPORT

Report: EMCS117636-FCC-ICES