

RF Exposure Evaluation Report

Report No.: 2405Z107560EC

- Applicant: Zhuhai Glory Technology Co., Ltd
- Address: 8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China
- Product Name: WIRELESS NETWORK CAMERA
- Product Model: GL-228XK-I1V1B
- Multiple Models: GL-228XL-I1V1B
 - Trade Mark: N/A
 - FCC ID: 2BMPT-228XK-I1V1B
 - Standards: 47 CFR §1.1310

KDB 447498 D01 General RF Exposure Guidance v06

- Test Date: 2025-02-13
- Test Result: Complied
- Report Date: 2025-02-19

Reviewed by:

Frank Tin

Approved by:

Jacob Gong

Frank Yin Project Engineer Jacob Kong Manager

Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk " \star "

Report Template: TR-4-E-016/V1.2



Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd

2. The results in this report apply only to the sample tested.

3. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

4. The information marked "#" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description		
00	2025-02-19	Original		



Contents

1	General Information			
	1.1	Client Information	4	
	1.2	Product Description of EUT	4	
	1.3	Laboratory Location	4	
2 RF Exposure Evaluation				
	2.1	Standard	5	
	2.2	Result	6	



1 General Information

1.1 Client Information

Applicant:	Zhuhai Glory Technology Co., Ltd				
Address:	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China				
Manufacturer:	Zhuhai Glory Technology Co., Ltd				
Address:	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China				

1.2 Product Description of EUT

The EUT is WIRELESS NETWORK CAMERA that contains Wi-Fi HaLow radio.

Sample Serial Number	2V9U-2 (assigned by WATC)
Sample Received Date	2024-12-02
Sample Status	Good Condition
Frequency Range	903.5-926.5MHz for 802.11ah(1MHz channel bandwidth)
	905-925MHz for 802.11ah(2MHz channel bandwidth)
	906-926MHz for 802.11ah(4MHz channel bandwidth)
	908-924MHz for 802.11ah(8MHz channel bandwidth)
Maximum Conducted Output Power	27.86dBm
Modulation Technology	OFDM
Antenna Gain [#]	2.45dBi(It is provided by the applicant.)
Spatial Streams	1T1R
Power Supply	Power by battery or Charging by AC Adapter
Adapter Information	N/A
Modification	Sample No Modification by the test lab

1.3 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: <u>qa@watc.com.cn</u>

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.



2 **RF Exposure Evaluation**

2.1 Standard

According to §1.1310, radio frequency devices shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Table	1 to § 1.1310(e)(1)-Lim	its for Maximum Permissil	ole Exposure (MPE	E)
Frequency range (MHz) Electric field strength (V/m)		Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
	(i) Limits for O	ccupational/Controlled Expos	ure	
0.3-3.0	614	1.63	*(100)	<i>≤</i> 6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
	(ii) Limits for Gener	al Population/Uncontrolled Ex	posure	
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

S = PG/4 π R² = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_i}{S_{Limit,i}} \leq 1$$



2.2 Result

Radio	Frequency (MHz)	Maximum Conducted Power including Tune-up Tolerance		Antenna Gain		Min. test separation distance	Power Density (mW//cm ²)	MPE Limit (mW/cm ²)	Verdict
		(dBm)	(mW)	(dBi)	(numeric)	(cm)			
WiFi	902-928	28.0	631	2.45	1.76	20	0.221	0.601	Pass

Note: The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Result: the device meet MPE limit at 20cm distance

---End of Report---