

RF EXPOSURE EVALUATION REPORT

FCC ID : Z64-CC3235MOD
Equipment : Dual-Band Wi-Fi® Module
Brand Name : Texas Instruments
Model Name : CC3235MODSM2MOB
CC3235MODSF12MOB
Marketing Name : SimpleLink™ Wi-Fi® CC3235MOD Dual-Band Wireless
Microcontroller Module
Applicant : Texas Instruments Incorporated
12500 TI BLVD., Dallas Texas, 75243
Manufacturer : Texas Instruments Incorporated
12500 TI BLVD., Dallas Texas, 75243
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1091 and it complies with applicable limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	6
4.1. Standalone Power Density Calculation	6



History of this test report

Report No.	Version	Description	Issued Date
FA8D1930	Rev. 01	Initial issue of report	Jul. 11, 2019

**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	Dual-Band Wi-Fi® Module
Brand Name	Texas Instruments
Model Name	CC3235MODSM2MOB CC3235MODSF12MOB
Marketing Name	SimpleLink™ Wi-Fi® CC3235MOD Dual-Band Wireless Microcontroller Module
FCC ID	Z64-CC3235MOD
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz
Mode	WLAN: 802.11a/b/g/n HT20
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Reviewed by: Jason Wang

Report Producer: Wan Liu

Antenna Information				
Antenna Type	Brand Name	Model	2.4GHz ~ 2.5GHz(dBi)	4.9GHz~5.8GHz(dBi)
Chip	Pulse	<u>W3078</u>	1.7	4.3
	Yageo	<u>ANT5320LL04R2455A</u>	2.17	3.51
	Ethertronics	<u>M830520</u>	1	2.6
PCB		<u>1000423</u>	-0.6	4.5
	Laird	<u>CAF94504</u>	2	4
		<u>CAF94505</u>	2	4
Dipole	LSR	<u>001-0012</u>	2	2
		<u>080-0013</u>	2	2
		<u>080-0014</u>	2	2
PIFA		<u>001-0016</u>	2.5	3
		<u>001-0021</u>	2.5	3
Note: The EUT used a dual-band chip antenna (Antenna 3 from Ethertronics)				

Note: The EUT used a dual-band chip antenna (Antenna 3 from Ethertronics)

2. Maximum RF average output power among production units

Mode		Maximum Average power(dBm)
2.4GHz WLAN	802.11b	16.5
	802.11g	16
	802.11n-HT20	15.9
5GHz WLAN	802.11a	14.3

3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
2.4GHz WLAN	2412.0	2.50	16.50	19.000	0.079	79.433	0.016	1.000
5GHz WLAN	5180.0	4.50	14.30	18.800	0.076	75.858	0.015	1.000

Note: For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.