

裁切线 _____ 压痕线 _____ V槽线 _____ 半穿刀 _____	辅助线 _____ 牙 刀 _____ 画 线 _____
■ 外表面视图	□ 内表面视图

版本	变更日期	变更描述	结构工程	设计者
A01	2024/06/03	初始发行	段斯蓝	庄慧宇
A02	2024/06/19	P1/P7增加钥匙, P11改参数	段斯蓝	庄慧宇

[illegible]

Preface

Thank you for purchasing UGREEN products. For optimum operation, please read this manual carefully before use.

Cautions

- The product is compatible with official MagSafe cases from Apple or magnetic cases from UGREEN. Using other cases may affect magnetic charging.
- Do not place metal objects (such as paper clips, coins) or magnetic cards in the wireless charging area to avoid abnormal charging.

Recharging Your Power Bank



Tips

- Before initial use, please fully charge the product.
- It is recommended to use a charger of 5V 30W or higher for the fastest charging experience.

Charging Your Devices

Wireless Charging

① For MagSafe-compatible iPhones (iPhone 12 models or later): snap and charge.



② For other phones that support wireless charging: Adjust the position of the phone to align it with the wireless charging area of the product.




Place the phone on the wireless charging area and the product will automatically start charging. If it does not charge, please re-align the phone.

After charging is complete and the device is removed, the product will automatically power off.

Wired Charging



③ For MagSafe-compatible iPhones (iPhone 12 models or later): snap and charge.



Specifications

USB-C Input	5V=3A/9V=3A/20V=2.5A/15V=2A
USB-C Output	5V=2.4A/9V=3A/9V=3A/15V=2A/20V=1.5A/20V=1A
Wireless Charging Output	15W Max
Battery Type	Acetate Tricore Lithium-Ion Battery
Cell Capacity	3600mAh (2 x 5000mAh)
Rated Energy	12.96Wh (7.250000Wh)
Rated Power	6000mAh (TPP 9.2-44)
Battery Charging, United Voltage	4.2V±5%
Dimensions	110.9×96.9×14.0 (mm) (4.4×3.8×0.8 inch)
Charging Time	About 2.5 hours (with 5V 30W charger)
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	0°C~32°C (32°F~122°F)
Package Contents	1 x Power Bank, 1 x Charging Cable, 1 x User Manual

The data are measured by UGREEN lab but may vary based on specific circumstances.

This product features overvoltage protection. Under full load, if the internal temperature of the product reaches the preset protection value, the output power will be automatically reduced.

● Battery Indicator

- 0% ~ 25% (50% Flashing)
- 26% ~ 50%
- 51% ~ 75%
- 76% ~ 100%

● Magnetic Wireless Charging Indicator

- Magnetic wireless charging function is enabled
- Flashing: Metal foreign object detected/overtemperature

Warnings

If the battery has been accidentally swallowed or placed inside any part of the body, please seek medical attention immediately.

If you need to discard/burn, please recycle or dispose of them properly according to local laws and regulations.

Please store this product in a dry place, at room temperature.

Notice: The pictures in this manual are for illustration purposes only. Actual products may differ due to product updates or upgrades. Please refer to the actual product.

WARNING

- Do not expose the product to excessive temperature or areas that may become hot, such as vehicles, sun exposure, heaters, microwave ovens, ovens, etc.; otherwise, it may cause an explosion.
- When using a power adapter to charge the product, please ensure that it is a CC-certified and meets the standard requirements.
- Do not use uncerified or incompatible power adapters and charging cables, as doing so may cause fire, explosion, or other hazards.
- Do not store the product in a non-ventilated space for a long time, such as a hallway, as the confined space may cause fire or other dangers.
- Please dispose of this product according to local laws and regulations rather than as household waste. Improper disposal may result in an explosion.
- Do not use this product during thunderstorms to avoid product failure or risk of electric shock.
- During use, the temperature of the product will be slightly higher than room temperature, which is normal. It is recommended not to contact it for more than 10s.
- This product has a built-in battery. Do not disassemble, hit, crush, or throw it into fire.
- Discontinue use immediately if the battery is severely swollen.
- Do not use in a high-temperature environment.
- Do not use the battery if it is immersed in water!
- The battery is hazardous. Please keep the product out of the reach of children.

-7-
-8-
-9-
-10-
-11-
-12-

备注:

1. 材质：80G白牛皮
2. 印刷颜色：1C
3. 成型尺寸：60x105mm
4. 展开尺寸：420x105mm
5. 尺寸公差：±1 mm
6. 印刷偏位：<=0.5 mm
7. 套印偏位：<=0.35 mm
8. 成型工艺：风琴折
9. 所有成品及辅料符合欧盟包装指令94/62/EC，美国TPCH，欧盟REACH
10. 印刷油墨（成品）矿物油含量需满足MOSH(C15-C36)小于0.1%；MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%

SELECT			V							SCALE	UGREEN 绿联 深圳市绿联科技股份有限公司			
Dim TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	1:1				
0~6	0.05	0.05	0.10						0.20	SHEET 1/1	物料名称: PB761 说明书			
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20					
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	UNIT mm	产品名称	料号	项目工程师	核准
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30					
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50					
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80				王帅兵	庄慧宇
DRAFT TOLERANCE			± 0.20°		CRITICAL DIM. MARK				*					

裁切线 _____ 压痕线 _____ V槽线 _____ 半穿刀 _____	辅助线 _____ 牙 刀 _____ 画 线 _____
☒ 外表面视图	☐ 内表面视图

无线充移动电源

[illegible]

备注:

1. 材质：80g白牛皮纸
2. 表面处理：/
3. 印刷颜色：1C
4. 成型尺寸：60x80mm
5. 展开尺寸：540x80mm
6. 尺寸公差：±0.5 mm
7. 印刷偏位：≤0.5 mm
8. 套印偏位：≤0.35 mm
9. 成型工艺：风琴折
10. 所有成品及辅料符合欧盟包装指令94/62/EC，美国TPCH，欧盟REACH
11. 印刷油墨（成品）矿物油含量需满足MOSH(C15-C36)小于0.1%；
MOAH (1-7芳香环) 小于0.1%；MOAH (3-7芳香环) 小于0.0001%

SELECT			V							SCALE 1:1	UGREEN 绿联 深圳市绿联科技股份有限公司			
Dim TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL					
0~6	0.05	0.05	0.10						0.20	SHEET 1/1	物料名称: (外贸说明卡N1) 无线充移动电源			
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20					
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	UNIT mm	产品名称	料号	项目工程师	核准
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30					
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50					
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80				/	何艳芳
DRAFT TOLERANCE			± 0.20°		CRITICAL DIM. MARK			*						