



FCC Test Report

APPLICANT : Weifang GoerTek Electronics Co.,Ltd.
EQUIPMENT : SRH-S1
BRAND NAME : SONY
MODEL NAME : SRH-S1
FCC ID : SZGSRHS1
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Jun. 02, 2024 ~ Jul. 05, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT.....	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer.....	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	6
1.6. Test Location	7
1.7. Test Software	7
1.8. Applicable Standards.....	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System.....	10
2.3. Support Unit used in test configuration and system.....	10
2.4. EUT Operation Test Setup	10
3. TEST RESULT	11
3.1. Test of AC Conducted Emission Measurement.....	11
3.2. Test of Radiated Emission Measurement.....	15
4. LIST OF MEASURING EQUIPMENT.....	20
5. MEASUREMENT UNCERTAINTY.....	21



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC420222	Rev. 01	Initial issue of report	Jul. 15, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 7.05 dB at 0.187 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 5.03 dB at 54.25 MHz

Conformity Assessment Condition:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1. Applicant

Weifang GoerTek Electronics Co.,Ltd.

Gaoxin 2 Road,Free Trade Zone,Weifang,Shandong,261205,P.R.China

1.2. Manufacturer

Sony Corporation

1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	SRH-S1
Brand Name	SONY
Model Name	SRH-S1
FCC ID	SZGSRHS1
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11a/ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE nRF
SN	Conduction: VHZJD2DVT21008 Radiation: VHZJD2DVT21008
HW Version	R2
SW Version	V3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	802.11b/g/n/ac/ax: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac/ax: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz 802.11a/ax: 5925 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz nRF: 2400 MHz ~ 2483.5 MHz
Rx Frequency	802.11b/g/n/ac/ax: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac/ax: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz; 5725 MHz ~ 5850 MHz 802.11a/ax: 5925 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz nRF: 2400 MHz ~ 2483.5 MHz
Antenna Type	WLAN : FPC Antenna Bluetooth : FPC Antenna nRF : FPC Antenna
Type of Modulation	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK nRF : GFSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH07-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	210616
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: Bluetooth Link + nRF Link + (With one Controller) + (With one Ring) + WLAN(2.4G) Link + Xhomeapp on + Camera on + MIC on + Battery + USB Cable 1 (Charging from Adapter)
	Mode 2: Bluetooth Link + nRF Idle + (With one Controller) Controller charging by Dock + (With one Ring) Ring charging by Dock + WLAN(5G) Link + Xhomeapp on + Loudspeaker + Run Color Bar + USB Cable 3 Connect Dock and Notebook + Battery +USB Cable 1(Charging from Dock) USB Cable 2 (Connect Dock and Adapter)
	Mode 3: Bluetooth Link + nRF Idle + WLAN(5G Band IV) Link + Run Color Bar With PC + (With one Controller) Controller charging by Dock + Xhomeapp on + USB Cable 3 (Connect Dock and NB) + USB Cable 1(Charging from Dock) + (With one Ring) Ring charging by Dock + Loudspeaker + Data Link with Notebook (Notebook to EUT) + USB Cable 2 (Connect Dock and Adapter)
	Mode 4: Bluetooth Link + nRF Idle + (With one Controller) Controller charging by Dock + (With one Ring) Ring charging by Dock + WLAN(6G) Link + Xhomeapp on + Loudspeaker + Run Color Bar + USB Cable 3 (Connect Dock and Notebook) + Data Link with NB (EUT to NB) + Battery + USB Cable 1(Charging from Dock) + USB Cable 2 (Connect Dock and Adapter)
	Mode 5: Bluetooth Idle + nRF Idle + WLAN(6G) Link + Play music + (With one Controller) + Xhomeapp on + USB Cable 3 (Connect EUT and NB) + (With one Ring) + Loudspeaker + Data Link with NB (NB to EUT) + Battery
	Mode 6: Bluetooth Idle + nRF Link + WLAN Idle + Play music + (With one Controller) + USB Cable 3 (Connect EUT and NB) + (With one Ring) + Data Link with NB (EUT to NB) + Battery

Radiated Emissions	Mode 1: Bluetooth Link + nRF Link + (With one Controller) + (With one Ring) + WLAN(2.4G) Link + Xhome app on + Camera on + MIC on + Battery + USB Cable 1 (Charging from Adapter) Mode 2: Bluetooth Link + nRF Idle + (With one Controller) Controller charging by Dock + (With one Ring) Ring charging by Dock + WLAN(5G) Link + Xhomeapp on + Loudspeaker + Run Color Bar + USB Cable 3 (Connect Dock and NB) + Battery +USB Cable 1(Charging from Dock) USB Cable 2 (Connect Dock and Adapter) Mode 3: Bluetooth Link + nRF Idle + (With one Controller) Controller charging by Dock + (With one Ring) Ring charging by Dock + WLAN(6G) Link + Xhomeapp on + Loudspeaker + Run Color Bar + USB Cable 3 (Connect Dock and NB) + Data Link with NB (EUT to NB) +Battery + USB Cable 1(Charging from Dock) + USB Cable 2 (Connect Dock and Adapter) Mode 4: Bluetooth Link + nRF Idle + (With one Controller) Controller charging by Dock + (With one Ring) Ring charging by Dock + WLAN(6G) Link + Xhomeapp on + Loudspeaker + Run Color Bar + USB Cable 3 (Connect Dock and NB) + Data Link with NB (EUT to NB) + Battery + USB Cable 1(Charging from Dock) + USB Cable 2 (Connect Dock and Adapter) Mode 5: Bluetooth Idle + nRF Idle + (With one Controller) + (With one Ring) + WLAN(5G Band IV) Link + Xhomeapp on + Loudspeaker + Play music +USB Cable 3(Connect EUT and NB)+ Data Link with NB (NB to EUT) + Battery Mode 6: Bluetooth Idle + nRF Link + (With one Controller) + (With one Ring) + WLAN Idle + Run Color Bar + USB Cable 3 (Connect EUT and NB) + Data Link with NB (EUT to NB) + Battery Mode 7: Bluetooth Idle + nRF Idle + (With one Controller) + (With one Ring) + WLAN Idle + Battery + Earphone
Remark: 1. The worst case of AC is mode 5; only the test data of this mode is reported. 2. The worst case of RE is mode 3; only the test data of this mode is reported. 3. Data Link with NB means data application transferred mode between EUT and Notebook.	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A
2.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A
3.	Notebook	Lenovo	V130-15IKB005	N/A	Unshielded AC I/P cable 1.8m
4.	Vector Signal Generator	R&S	SMBV100A	258305	N/A
5.	Hard DISK	WD	C6B	N/A	N/A
6.	Type-C Earphone	MOTO	LYEJ02LM	Unshielded AC I/P cable 1.0m	N/A
7.	AC Adapter	tianyin	TPD-71B120250CU01	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was attached to the Bluetooth earphone, controller, ring or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Execute “Music Player” or run color bar.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	24.2~25.6°C
		Relative Humidity :	37~39%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : FCC IC-QP LISN-060105-L 2024 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.169	56.12	-8.87	64.99	45.60	0.10	10.42	QP
2	0.169	37.42	-17.57	54.99	26.90	0.10	10.42	Average
3 *	0.187	57.10	-7.05	64.15	46.60	0.09	10.41	QP
4	0.187	41.60	-12.55	54.15	31.10	0.09	10.41	Average
5	0.200	54.99	-8.63	63.62	44.50	0.08	10.41	QP
6	0.200	38.69	-14.93	53.62	28.20	0.08	10.41	Average
7	0.256	47.35	-14.21	61.56	36.90	0.09	10.36	QP
8	0.256	31.65	-19.91	51.56	21.20	0.09	10.36	Average
9	0.518	40.70	-15.30	56.00	30.60	-0.11	10.21	QP
10	0.518	27.00	-19.00	46.00	16.90	-0.11	10.21	Average
11	2.869	40.10	-15.90	56.00	30.20	-0.17	10.07	QP
12	2.869	22.40	-23.60	46.00	12.50	-0.17	10.07	Average



Test Engineer :	Amos Zhang	Temperature :	24.2~25.6°C
		Relative Humidity :	37~39%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC IC-QP LISN-060105-N 2024 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.162	53.84	-11.50	65.34	43.30	0.12	10.42	QP
2	0.162	34.44	-20.90	55.34	23.90	0.12	10.42	Average
3 *	0.187	55.24	-8.91	64.15	44.70	0.13	10.41	QP
4	0.187	40.84	-13.31	54.15	30.30	0.13	10.41	Average
5	0.211	49.00	-14.18	63.18	38.51	0.09	10.40	QP
6	0.211	30.80	-22.38	53.18	20.31	0.09	10.40	Average
7	0.252	49.15	-12.54	61.69	38.80	-0.02	10.37	QP
8	0.252	32.25	-19.44	51.69	21.90	-0.02	10.37	Average
9	0.486	40.28	-15.95	56.23	30.20	-0.15	10.23	QP
10	0.486	27.58	-18.65	46.23	17.50	-0.15	10.23	Average
11	2.962	36.66	-19.34	56.00	26.80	-0.21	10.07	QP
12	2.962	23.16	-22.84	46.00	13.30	-0.21	10.07	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.


3.2.4. Test Setup of Radiated Emission


For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission




Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr 18, 2024	Jun. 29, 2024 ~Jul. 05, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Jun. 29, 2024 ~Jul. 05, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Apr 18, 2024	Jun. 29, 2024 ~Jul. 05, 2024	Apr 17, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Jun. 29, 2024 ~Jul. 05, 2024	Oct. 10, 2024	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 11, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Oct. 10, 2024	Radiation (03CH07-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz~44G,MAX 30dB	Oct. 11, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Oct. 10, 2024	Radiation (03CH07-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz~1GHz	Aug. 19, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Aug. 18, 2024	Radiation (03CH07-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Dec. 21, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Dec. 20, 2024	Radiation (03CH07-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 15, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Oct. 14, 2024	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	413741	9KHz~1GHz	Jan. 04, 2024	Jun. 02, 2024 ~Jul. 01, 2024	Jan. 03, 2025	Radiation (03CH07-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz~18Ghz	Oct. 11, 2023	Jun. 02, 2024 ~Jul. 01, 2024	Oct. 10, 2024	Radiation (03CH07-KS)
Amplifier	EM	EM18G40GGA	060851	18~40GHz	Jan. 03, 2024	Jun. 02, 2024 ~Jul. 01, 2024	Jan. 02, 2025	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Jun. 02, 2024 ~Jul. 01, 2024	NCR	Radiation (03CH07-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Jun. 02, 2024 ~Jul. 01, 2024	NCR	Radiation (03CH07-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Jun. 02, 2024 ~Jul. 01, 2024	NCR	Radiation (03CH07-KS)

NCR: No Calibration Required

5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.84dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.06dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.16dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.28dB
--	--------

----- THE END -----