



## TEST REPORT

REGULATION :

FCC Part 1.1310

Applicant	Testing Laboratory
JVC KENWOOD Corporation 1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan Tel.: +81 45 939 6254 Fax.: +81 45 939 6261	Intertek Japan K. K. Kashima Laboratory URL: <a href="http://www.japan.intertek-etlsemko.com">http://www.japan.intertek-etlsemko.com</a> 3-2 Sunayama, Kamisu, Ibaraki 314-0255 Japan Tel. +81 479 40 1097

Equipment type	UHF DIGITAL TRANSCEIVER
Trademark	KENWOOD
Model(s)	NX-840H-K2 , NX-840-M2
Serial No.	1
FCC ID	K44452701
Test Result	Complied
Report Number	14040209JKA-001
Report issue date	May 27, 2014

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Approved by

Hideaki Kosemura

[Assistant Manager]

Tested by

Koichi Wagatsuma

[Engineer]

## TABLE OF CONTENTS

---

	Page
SECTION 1. INFORMATION	3
SECTION 2. TEST DATA	4
SECTION 3. LIST OF MEASURING INSTRUMENTS	6

---

## SECTION 1. INFORMATION

### APPLICANT

Company	JVC KENWOOD Corporation
Address	1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan
Contact Person	Tamaki Shimamura Manager, Communications Equipment Division

### MANUFACTURER

Company	JVC KENWOOD Corporation
Address	1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan

### EQUIPMENT UNDER TEST

Model No.	NX-840H-K2 , NX-840-M2	
Serial No.	1	
Frequency range	406.1 to 470 MHz	
Maximum Power Rating	45	W
Duty cycle	50	%
Collector Current, A	15.0	amps (Maximum)
Collector Voltage, Vdc	13.6	Vdc
Supply Voltage, Vdc	13.6	Vdc

### DATE OF TEST AND TEST ENGINEER

Date of Issue	May 19, 2014
Test Engineer	Koichi Wagatsuma
Test Location	Kashima Immunity Test Room

### Revision Summary

Revised Date	Section	Description of Changes

## SECTION 2. TEST DATA

The EUT was placed inside an semi anechoic chamber at height of 0.8 m to simulate being mounted on a vehicle. The isotropic probe was placed a distance of 0.4 m from the EUT and power density was measured at 0.2 m increments from 0.2 m to 2.0 m with the peak value from each location being recorded in the corresponding data tables.

The general population limit was applied to all measurements.

The EUT is a PTT radio for mobile application with a peak power of 45 W. By allowing for an operational 50 % factor the power was reduced to 22.5 W for testing purposes yet transmitted continuously during the test. A 0 dBd antenna was utilized for testing.

### Measurement Result

406.15 MHz

Probe Height (m)	Peak Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
0.2	0.003	0.27	Pass
0.4	0.055	0.27	Pass
0.6	0.041	0.27	Pass
0.8	0.189	0.27	Pass
1.0	0.254	0.27	Pass
1.2	0.225	0.27	Pass
1.4	0.225	0.27	Pass
1.6	0.216	0.27	Pass
1.8	0.106	0.27	Pass
2.0	0.051	0.27	Pass

438.05 MHz

Probe Height (m)	Peak Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
0.2	0.018	0.29	Pass
0.4	0.037	0.29	Pass
0.6	0.045	0.29	Pass
0.8	0.163	0.29	Pass
1.0	0.225	0.29	Pass
1.2	0.176	0.29	Pass
1.4	0.181	0.29	Pass
1.6	0.141	0.29	Pass
1.8	0.067	0.29	Pass
2.0	0.027	0.29	Pass

469.95 MHz

Probe Height (m)	Peak Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
0.2	0.019	0.31	Pass
0.4	0.015	0.31	Pass
0.6	0.032	0.31	Pass
0.8	0.118	0.31	Pass
1.0	0.107	0.31	Pass
1.2	0.104	0.31	Pass
1.4	0.146	0.31	Pass
1.6	0.108	0.31	Pass
1.8	0.050	0.31	Pass
2.0	0.025	0.31	Pass

### SECTION 3. LIST OF MEASURING INSTRUMENTS

Instrument	Model No.	Serial No.	Manufacturer	Cal Date	Cal Due Date
Power Supply	GZV4000	90290931	Daiichi denpa kogyo	N/A	N/A
Digital Multi Meter	8846A	9642018	FLUKE	2013/5/31	2014/5/31
Fleld Probe	HI 6005	00130667	ETS Lindgren	2014/4/2	2015/4/30