



CERTIFICATION TEST REPORT

Report Number. : 4790632299-E5V4

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-A546V

FCC ID : A3LSMA546V

EUT Description : GSM/WCDMA/LTE 5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax
and NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
2023-02-03

Prepared by:
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2023-01-17	Initial issue	Dexter(Hyunsik) Yun
V2	2023-01-25	Updated to address TCB's question	Dexter(Hyunsik) Yun
V3	2023-01-30	Updated to address TCB's question	Dexter(Hyunsik) Yun
V4	2023-02-03	Updated to address TCB's question	Dexter(Hyunsik) Yun

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. DECISION RULES AND MEASUREMENT UNCERTAINTY	7
4.1. METROLOGICAL TRACEABILITY.....	7
4.2. SAMPLE CALCULATION.....	7
4.3. MEASUREMENT UNCERTAINTY	7
4.4. DECISION RULES.....	7
5. EQUIPMENT UNDER TEST	8
5.1. EUT DESCRIPTION.....	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE	9
5.5. DESCRIPTION OF TEST SETUP.....	9
6. TEST AND MEASUREMENT EQUIPMENT	11
7. TEST RESULTS SUMMARY	12
8. MEASUREMENT METHODS	13
9. ANTENNA PORT TEST RESULTS	14
9.1. ON TIME AND DUTY CYCLE	14
9.2. 20 dB BANDWIDTH	15
9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	15
9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	15
9.3. HOPPING FREQUENCY SEPARATION.....	17
9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	18
9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	18
9.4. NUMBER OF HOPPING CHANNELS	19
9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	20
9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	21
9.5. AVERAGE TIME OF OCCUPANCY.....	22
9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION	23
9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	25
9.6. OUTPUT POWER.....	27
9.6.1. BASIC DATA RATE GFSK MODULATION.....	27

9.6.2.	ENHANCED DATA RATE $\pi/4$ -DPSK MODULATION	27
9.6.3.	ENHANCED DATA RATE 8PSK MODULATION	27
9.6.4.	OUTPUT POWER PLOTS.....	28
9.7.	AVERAGE POWER	30
9.7.1.	BASIC DATA RATE GFSK MODULATION.....	30
9.7.2.	ENHANCED DATA RATE $\pi/4$ -DQPSK MODULATION	30
9.7.3.	ENHANCED DATA RATE 8PSK MODULATION	30
9.8.	CONDUCTED SPURIOUS EMISSIONS	31
9.8.1.	BLUETOOTH BASIC DATA RATE GFSK MODULATION	32
9.8.2.	BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION.....	34
10.	RADIATED TEST RESULTS	36
10.1.	TRANSMITTER ABOVE 1 GHz	38
10.1.1.	BLUETOOTH BASIC DATA RATE GFSK MODULATION	38
10.1.2.	BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION	45
10.2.	WORST CASE BELOW 1 GHz	52
11.	AC POWER LINE CONDUCTED EMISSIONS	53
11.1.	AC Power Line.....	54

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC

MODEL: SM-A546V

SERIAL NUMBER: R3CTA0AXZDA (CONDUCTED);
R3CTA0AXPBY (RADIATED);

DATE TESTED: 2022-12-05 ~ 2023-01-17;

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



Seokhwan Hong
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Dexter(Hyunsik) Yun
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1(3m semi-anechoic chamber)
☒	Chamber 2(3m semi-anechoic chamber)
☒	Chamber 3(3m semi-anechoic chamber)
☐	Chamber 4(3m Full-anechoic chamber)
☐	Chamber 5(3m Full-anechoic chamber)

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

$$\begin{aligned} \text{AC Corrected Reading (dBuV)} &= \text{Measured Voltage (dBuV)} + \text{Extension Cord} \\ &\text{Loss (dB)} + \text{Cable Loss (dB)} \\ 44.72 \text{ dBuV} &= 34.72 \text{ dBuV} + 9.9 \text{ dB} + 0.1 \text{ dB} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.80 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.92 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.06 dB
Radiated Disturbance, 18 GHz to 40 GHz	6.02 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULES

Decision rule for statement(s) of conformity is based on Procedure 2, Clause 4.4.3 in IEC Guide 115:2021.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC.
This test report addresses the DSS(BT) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Peak	15.760	37.670
		Average	14.749	29.847
	Enhanced Pi/4-DPSK	Peak	14.800	30.200
		Average	12.696	18.604
	Enhanced 8PSK	Peak	15.260	33.574
		Average	12.701	18.625

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The internal antenna was Permanently attached.
Therefore this E.U.T Complies with the requirement of §15.203.

The radio utilizes an internal antennas, with ANT (SUB5_WiFi1+BT) maximum gain of -1.95 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37T7WW84Y9SEA	N/A
Data Cable	SAMSUNG	EP-DN980	GH39-02116A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A


TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests. Test software enable BT communications.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	2024-08-15
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	2024-08-15
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	2024-08-15
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	2023-10-06
Antenna, Horn, 18 GHz	ETS	3115	00167211	2024-08-04
Antenna, Horn, 18 GHz	ETS	3115	00161451	2024-08-21
Antenna, Horn, 18 GHz	ETS	3117	00168724	2024-08-04
Antenna, Horn, 18 GHz	ETS	3117	00168717	2024-08-21
Antenna, Horn, 40 GHz	ETS	3116C	00166155	2024-08-02
Preamplifier	ETS	3116C-PA	00168841	2023-08-04
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	80108-0004	N/A
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	110367-0003	N/A
Preamplifier, 1000 MHz	Sonoma	310N	341282	2023-08-02
Preamplifier, 1000 MHz	Sonoma	310N	351741	2023-08-02
Preamplifier, 1000 MHz	Sonoma	310N	370599	2023-08-02
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	2023-08-02
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	2023-08-01
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	2023-08-01
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	2023-08-03
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	2023-08-01
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9030B	MY60070693	2023-01-18
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9040B	MY60080268	2023-01-19
Average Power Sensor	Agilent / HP	U2000	MY54270007	2023-08-03
Average Power Sensor	Agilent / HP	U2000	MY54260010	2023-08-03
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	2023-08-02
Power Splitter	MINI-CIRCUITS	WA1534	UL003	2024-01-09
Power Splitter	MINI-CIRCUITS	WA1534	UL004	2024-01-09
Attenuator	PASTERNAK	PE7087-10	A009	2023-08-03
Attenuator	PASTERNAK	PE7087-10	A001	2023-08-03
Attenuator	PASTERNAK	PE7087-10	A008	2023-08-03
Attenuator	PASTERNAK	PE7004-10	2	2023-08-01
EMI Test Receive, 40 GHz	R&S	ESU40	100439	2023-08-02
EMI Test Receive, 40 GHz	R&S	ESU40	100457	2023-07-29
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	2023-08-02
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	2023-08-01
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	2023-08-01
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	2023-08-02
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	2023-08-01
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	2023-08-01
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	2023-08-02
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	2023-08-01
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	2023-08-01
LISN	R&S	ENV-216	101837	2023-08-04
Termination	WEINSCHEL	M1406A	T09	2023-08-03
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247(d)	Band Edge / Conducted Spurious Emission	-20 dBc	Conducted	Complies
15.247 (b)(1)	TX conducted output power	< 21 dBm		Complies
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		Complies
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Complies
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 8 dBm		Complies
15.207(a)	AC Power Line conducted emissions	Section 11	Power Line conducted	Complies
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m(Av)	Radiated	Complies

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW : ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION : ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS : ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY : ANSI C63.10, Section 7.8.4

OUTPUT POWER : ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.6, 7.8.8

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 6.

Out-of-band EMISSIONS IN RESTRICTED BANDS : ANSI C63.10, Section 6.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS



Mode	On time [msec]	Period [msec]	Duty Cycle [%]	Duty Cycle Correction Factor[dB]	1/T Minimum VBW [kHz]
2 400 ~ 2 483.5 MHz Band					
BDR	2.893	3.750	77.147	1.127	0.346
EDR	2.902	3.749	77.407	1.112	0.345

9.2. 20 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. The sweep time is coupled.


RESULTS

9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]
0	2 402	866.0
39	2 441	874.6
78	2 480	934.0
Worst		934.0

9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	20 dB Bandwidth [kHz]
0	2 402	1 212.0
39	2 441	1 208.0
78	2 480	1 213.0
Worst		1 213.0



9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. The VBW is set to $\text{VBW} \geq \text{RBW}$. The sweep time is coupled.

RESULTS

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. The analyzer is set to Max Hold.


RESULTS

Normal Mode: All Channels Observed


9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION




100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3




30MHz SPAN, SEGMENT 2 OF 3




30MHz SPAN, SEGMENT 3 OF 3


9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION




100 MHz Span



30MHz SPAN, SEGMENT 1 OF 3



30MHz SPAN, SEGMENT 2 OF 3



30MHz SPAN, SEGMENT 3 OF 3

9.5. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.


The average time of occupancy in the specified 3.16 second period (79 channels * 0.4 s) is equal to $10 * (\# \text{ of pulses in } 3.16 \text{ s}) * \text{pulse width}$.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to $10 * (\# \text{ of pulses in } 0.8 \text{ s}) * \text{pulse width}$.


RESULTS

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION


DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.387	32	0.124	0.4	-0.276
DH3	1.644	17	0.279	0.4	-0.121
DH5	2.891	13	0.376	0.4	-0.024
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.387	8	0.031	0.4	-0.369
DH3	1.644	4.25	0.070	0.4	-0.330
DH5	2.891	3.25	0.094	0.4	-0.306




PULSE WIDTH – DH1




NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – DH1



PULSE WIDTH – DH3



NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – DH3




PULSE WIDTH – DH5



NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – DH5

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION


DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Normal					
DH1	0.400	32	0.128	0.4	-0.272
DH3	1.650	16	0.264	0.4	-0.136
DH5	2.902	11	0.319	0.4	-0.081
DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK AFH					
DH1	0.400	8	0.032	0.4	-0.368
DH3	1.650	4	0.066	0.4	-0.334
DH5	2.902	2.75	0.080	0.4	-0.320




PULSE WIDTH – 3-DH1




NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – 3-DH1



PULSE WIDTH – 3-DH3



NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – 3-DH3



PULSE WIDTH – 3-DH5



NUMBER OF PULSES IN 3.16 SECOND
OBSERVATION PERIOD – 3-DH5

9.6. OUTPUT POWER

LIMITS

§15.247 (b) (1)

The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	14.73	21.00	-6.27
39	2 441	15.76		-5.24
78	2 480	15.33		-5.67
Worst		15.76		-5.24

9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION


Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	14.40	21.00	-6.60
39	2 441	14.80		-6.20
78	2 480	13.96		-7.04
Worst		14.80		-6.20


9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Peak Output Power [dBm]	Limit [dBm]	Margin [dB]
0	2 402	14.87	21.00	-6.13
39	2 441	15.26		-5.74
78	2 480	14.40		-6.60
Worst		15.26		-5.74

9.6.4. OUTPUT POWER PLOTS

PEAK OUTPUT POWER





9.7. AVERAGE POWER

LIMITS

None; for reporting purposes only

TEST PROCEDURE

Measurements perform using a wideband gated RF power meter.
The cable assembly insertion loss was entered as an offset in the power meter to allow for direct reading of power.

RESULTS

9.7.1. BASIC DATA RATE GFSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	14.726	29.689
39	2 441	14.569	28.635
78	2 480	14.749	29.847

9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	12.696	18.604
39	2 441	11.595	14.438
78	2 480	11.631	14.558

9.7.3. ENHANCED DATA RATE 8PSK MODULATION

Channel	Frequency [MHz]	Average Output Power [dBm]	Average Output Power [mW]
0	2 402	12.701	18.625
39	2 441	11.600	14.454
78	2 480	11.639	14.585

9.8. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Limit = -20 dBc

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.







The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

The band-edges at 2.4 and 2.4835 GHz are investigated with the transmitter set to the normal hopping mode.


RESULTS

9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

SPURIOUS EMISSIONS, NON-HOPPING




SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON




9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

SPURIOUS EMISSIONS, NON-HOPPING



SPURIOUS BANDEDGE EMISSIONS WITH HOPPING ON



10. RADIATED TEST RESULTS

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	162.0125 ~	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	167.17	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	167.72 ~ 173.2	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	240 ~ 285	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	322 ~ 335.4	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	399.90 ~ 410	3345.8 ~ 3358		
		608 ~ 614	3600 ~ 4400		
		960 ~ 1240			

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements. (Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.)

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1/T (on time) for average measurement.

$$\text{GFSK} = 1/T = 1 / 0.00290\text{s} = 345\text{Hz}.$$

The minimum VBW was 347Hz, but test receiver(ESU40) couldn't set value 347Hz. Due to this reason, testing VBW was set to 500Hz(Worst cases).

The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.


Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open are test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

10.1. TRANSMITTER ABOVE 1 GHz

10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.77	Pk	31.7	-19.7	52.77	-	-	74	-21.23	72	101	H
2	* 2.36829	43.48	Pk	31.7	-19.7	55.48	-	-	74	-18.52	72	101	H
3	* 2.39	30.41	VA1T	31.7	-19.7	42.41	54	-11.59	-	-	72	101	H
4	* 2.32118	31.09	VA1T	31.6	-19.6	43.09	54	-10.91	-	-	72	101	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL RESULT




Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.56	PK	31.7	-19.7	51.56	-	-	74	-22.44	358	125	V
2	* 2.35851	44.2	PK	31.6	-19.6	56.2	-	-	74	-17.8	358	125	V
3	* 2.39	30.48	VA1T	31.7	-19.7	42.48	54	-11.52	-	-	358	125	V
4	* 2.382	30.99	VA1T	31.7	-19.6	43.09	54	-10.91	-	-	358	125	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
Pk - Peak detector
VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00218957	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	60.35	Pk	32.9	-24.7	68.55	-	-	74	-5.45	80	133	H
2	* 2.4836	61.65	Pk	32.9	-24.7	69.85	-	-	74	-4.15	80	133	H
3	* 2.4835	30.55	VA1T	32.9	-24.7	38.75	54	-15.25	-	-	80	133	H
4	* 2.48373	31.48	VA1T	32.9	-24.7	39.68	54	-14.32	-	-	80	133	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00218957	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	50.77	Pk	32.9	-24.7	58.97	-	-	74	-15.03	291	102	V
2	* 2.4836	51.26	Pk	32.9	-24.7	59.46	-	-	74	-14.54	291	102	V
3	* 2.4835	30.26	VA1T	32.9	-24.7	38.46	54	-15.54	-	-	291	102	V
4	2.53572	30.94	VA1T	32.9	-24.6	39.24	54	-14.76	-	-	291	102	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector


VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

0 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0021895 7	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80364	42.31	PKFH	34.6	-29.9	47.01	-	-	74	-26.99	152	108	H
* 4.80396	35.59	VA1T	34.6	-29.9	40.29	54	-13.71	-	-	152	108	H
* 4.80384	41.28	PKFH	34.6	-29.9	45.98	-	-	74	-28.02	191	346	V
* 4.80382	34.48	VA1T	34.6	-29.9	39.18	54	-14.82	-	-	191	346	V
7.20622	34.13	PKFH	36.1	-25.6	44.63	-	-	74	-29.37	0	100	H
7.19771	32.91	PKFH	36.1	-25.7	43.31	-	-	74	-30.69	0	100	V
9.60161	31.21	PKFH	37.3	-21.8	46.71	-	-	74	-27.29	289	102	H
9.6096	32.14	PKFH	37.3	-21.8	47.64	-	-	74	-26.36	39	104	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

39 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0016872_4	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88178	39.91	PKFH	34	-27.6	46.31	-	-	74	-27.69	150	118	H
* 4.88206	33.04	VA1T	34	-27.6	39.44	54	-14.56	-	-	150	118	H
* 4.88175	39.21	PKFH	34	-27.6	45.61	-	-	74	-28.39	199	362	V
* 4.88198	31.41	VA1T	34	-27.6	37.81	54	-16.19	-	-	199	362	V
* 7.32411	34.35	PKFH	35.7	-24.4	45.65	-	-	74	-28.35	0	100	H
* 7.32494	33.5	PKFH	35.7	-24.4	44.8	-	-	74	-29.2	360	100	V
9.76473	31.85	PKFH	37.1	-21	47.95	-	-	74	-26.05	0	100	H
9.76302	30.92	PKFH	37.1	-21	47.02	-	-	74	-26.98	360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

78 CHANNEL RESULTS



HORIZONTAL



VERTICAL

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_0016872 4	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.95971	37.21	PKFH	34	-27	44.21	-	-	74	-29.79	154	111	H
* 4.95995	29.39	VA1T	34	-27	36.39	54	-17.61	-	-	154	111	H
* 4.95959	37.2	PKFH	34	-27	44.2	-	-	74	-29.8	194	313	V
* 4.95997	28.78	VA1T	34	-27	35.78	54	-18.22	-	-	194	313	V
* 7.43704	33.61	PKFH	35.7	-23.7	45.61	-	-	74	-28.39	125	100	H
* 7.4398	22.7	VA1T	35.7	-23.7	34.7	54	-19.3	-	-	125	100	H
* 7.43997	35.27	PKFH	35.7	-23.7	47.27	-	-	74	-26.73	127	100	V
* 7.44024	24.16	VA1T	35.7	-23.7	36.16	54	-17.84	-	-	127	100	V
9.92058	32.42	PKFH	37.3	-21.1	48.62	-	-	74	-25.38	176	113	H
9.9224	31.21	PKFH	37.3	-21.1	47.41	-	-	74	-26.59	300	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band


PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

BANDEDGE (0 CHANNEL)

HORIZONTAL RESULT



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.17	PK	31.7	-19.7	53.17	-	-	74	-20.83	73	100	H
2	* 2.34697	43.75	PK	31.6	-19.6	55.75	-	-	74	-18.25	73	100	H
3	* 2.39	30.37	VA1T	31.7	-19.7	42.37	54	-11.63	-	-	73	100	H
4	* 2.36158	30.92	VA1T	31.6	-19.5	43.02	54	-10.98	-	-	73	100	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B=1/T_{on}$ where: T_{on} is transmit duration

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	42.69	PK	31.7	-19.7	54.69	-	-	74	-19.31	358	125	V
2	* 2.37553	43.21	PK	31.7	-19.6	55.31	-	-	74	-18.69	358	125	V
3	* 2.39	30.39	VA1T	31.7	-19.7	42.39	54	-11.61	-	-	358	125	V
4	* 2.3859	31.1	VA1T	31.7	-19.6	43.2	54	-10.8	-	-	358	125	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B = 1/T_{on}$ where: T_{on} is transmit duration

BANDEDGE (78 CHANNEL)

HORIZONTAL RESULT



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00218957	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	60.62	Pk	32.9	-24.7	68.82	-	-	74	-5.18	76	136	H
2	* 2.48354	61.33	Pk	32.9	-24.7	69.53	-	-	74	-4.47	76	136	H
3	* 2.4835	31.17	VA1T	32.9	-24.7	39.37	54	-14.63	-	-	76	136	H
4	2.55655	31.25	VA1T	32.9	-24.6	39.55	54	-14.45	-	-	76	136	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

VA1T - FHSS: Linear Voltage Average $V_B = 1/T_{on}$ where: T_{on} is transmit duration

VERTICAL RESULT



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00218957	10dB_ATT[dB]	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	42.06	PK	32.9	-24.7	50.26	-	-	74	-23.74	215	363	V
2	* 2.48358	57.45	PK	32.9	-24.7	65.65	-	-	74	-8.35	215	363	V
3	* 2.4835	30.72	VA1T	32.9	-24.7	38.92	54	-15.08	-	-	215	363	V
4	2.55705	31.12	VA1T	32.9	-24.6	39.42	54	-14.58	-	-	215	363	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector


VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

HARMONICS AND SPURIOUS EMISSIONS

0 CHANNEL RESULTS



HORIZONTAL



VERTICAL


Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.80528	34.58	PKFH	34	-27.7	40.88	-	-	74	-33.12	0	100	H
* 4.80451	35.51	PKFH	34	-27.7	41.81	-	-	74	-32.19	0	100	V
7.20707	33.32	PKFH	35.7	-25.1	43.92	-	-	74	-30.08	0	100	H
7.20689	33.55	PKFH	35.7	-25	44.25	-	-	74	-29.75	0	100	V
9.61014	31.74	PKFH	36.9	-21.2	47.44	-	-	74	-26.56	0	100	H
9.60896	20.47	PKFH	36.9	-21.3	36.07	-	-	74	-37.93	0	100	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

39 CHANNEL RESULTS



HORIZONTAL




VERTICAL

Radiated Emissions


Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.88264	35.7	PKFH	34	-27.6	42.1	-	-	74	-31.9	0	100	H
* 4.8836	35	PKFH	34	-27.6	41.4	-	-	74	-32.6	0	100	V
* 7.3242	33.69	PKFH	35.7	-24.4	44.99	-	-	74	-29.01	0	100	H
* 7.32152	34.39	PKFH	35.7	-24.5	45.59	-	-	74	-28.41	0	100	V
9.76515	30.49	PKFH	37.1	-21	46.59	-	-	74	-27.41	0	100	H
9.76347	31.01	PKFH	37.1	-21	47.11	-	-	74	-26.89	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

78 CHANNEL RESULTS



HORIZONTAL



VERTICAL


Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	3117_00168724	3GHz_HP[dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 4.95834	34.36	PKFH	34	-27	41.36	-	-	74	-32.64	0	100	H
* 4.9601	35.29	PKFH	34	-27	42.29	-	-	74	-31.71	0	100	V
* 7.44245	33.53	PKFH	35.7	-23.7	45.53	-	-	74	-28.47	0	100	H
* 7.44199	32.93	PKFH	35.7	-23.7	44.93	-	-	74	-29.07	0	100	V
9.92063	30.63	PKFH	37.3	-21.1	46.83	-	-	74	-27.17	0	100	H
9.92149	30.66	PKFH	37.3	-21.1	46.86	-	-	74	-27.14	0	100	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PKFH FHSS/BT RB=100k for Frequencies<1GHz / RB=1MHz for Frequencies>1GHz, VB=3 x RB, Peak

10.2. WORST CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



HORIZONTAL



VERTICAL

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163_749	Below 1G[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	QPK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	77.918	40.26	Pk	12.5	-30.8	0	21.96	40	-18.04	0-360	100	H
3	181.223	43.51	Pk	15.4	-29.8	0	29.11	43.52	-14.41	0-360	100	H
5	385.117	34.86	Pk	21.1	-28.5	0	27.46	46.02	-18.56	0-360	300	H
2	39.797	43.19	Pk	18.5	-31.3	0	30.39	40	-9.61	0-360	100	V
4	94.408	45.2	Pk	16.4	-30.7	0	30.9	43.52	-12.62	0-360	100	V
6	888.062	33.85	Pk	27.8	-25.8	0	35.85	46.02	-10.17	0-360	100	V

Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10:2013.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

11.1. AC Power Line

LINE 1 RESULTS



Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
1	.153	40.37	Pk	9.8	.1	50.27	65.84	-15.57	-	-
2	.153	25.75	Av	9.8	.1	35.65	-	-	55.84	-20.19
3	.201	36.29	Pk	9.8	.2	46.29	63.57	-17.28	-	-
4	.207	19.9	Av	9.8	.2	29.9	-	-	53.32	-23.42
5	.252	30.39	Pk	9.6	.2	40.19	61.69	-21.5	-	-
6	.255	16.62	Av	9.6	.2	26.42	-	-	51.59	-25.17
7	.468	33.51	Pk	9.9	.2	43.61	56.55	-12.94	-	-
8	.471	20.53	Av	9.9	.2	30.63	-	-	46.5	-15.87
9	1.908	28.53	Pk	9.7	.3	38.53	56	-17.47	-	-
10	1.926	11.47	Av	9.7	.3	21.47	-	-	46	-24.53
11	11.412	32.8	Pk	9.9	.3	43	60	-17	-	-
12	11.415	19.16	Av	9.9	.3	29.36	-	-	50	-20.64

Pk - Peak detector

Av - Average detection

LINE 2 RESULTS



Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_N[dB]	CABLELOS S(dB)	Corrected Reading (dB(uVolts))	CFR 47 FCC PART 15 Class B QP	Margin (dB)	CFR 47 FCC PART 15 Class B AV	Margin (dB)
13	.156	40.59	Pk	9.8	.1	50.49	65.67	-15.18	-	-
14	.156	22.04	Av	9.8	.1	31.94	-	-	55.67	-23.73
15	.21	36.37	Pk	9.8	.2	46.37	63.21	-16.84	-	-
16	.21	19.59	Av	9.8	.2	29.59	-	-	53.21	-23.62
17	.225	34.84	Pk	9.7	.2	44.74	62.63	-17.89	-	-
18	.255	12.7	Av	9.6	.2	22.5	-	-	51.59	-29.09
19	.435	34.85	Pk	9.9	.2	44.95	57.16	-12.21	-	-
20	.465	21.05	Av	9.9	.2	31.15	-	-	46.6	-15.45
21	1.902	23.68	Pk	9.7	.3	33.68	56	-22.32	-	-
22	1.932	10.23	Av	9.7	.3	20.23	-	-	46	-25.77
23	11.331	29.1	Pk	9.9	.3	39.3	60	-20.7	-	-
24	11.34	18.78	Av	9.9	.3	28.98	-	-	50	-21.02

Pk - Peak detector

Av - Average detection

END OF TEST REPORT