

**FCC ID: 2ATQ9-E95A****Portable device**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT:

| Modulation                | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|---------------------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| EDR mode (GFSK)           | 2.402               | -0.913                 | 0.81                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39023            | 3.00                    | YES                |
|                           | 2.441               | -0.999                 | 0.79                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39338            | 3.00                    | YES                |
|                           | 2.480               | -0.072                 | 0.98                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39651            | 3.00                    | YES                |
| EDR mode ( $\pi$ /4DQPSK) | 2.402               | 0.864                  | 1.22                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39023            | 3.00                    | YES                |
|                           | 2.441               | 0.744                  | 1.19                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39338            | 3.00                    | YES                |
|                           | 2.480               | -0.285                 | 0.94                  | 0±1                 | 1.00                    | 1.26                   | <5            | 0.39651            | 3.00                    | YES                |
|                           |                     |                        |                       |                     |                         |                        |               |                    |                         |                    |
|                           |                     |                        |                       |                     |                         |                        |               |                    |                         |                    |
|                           |                     |                        |                       |                     |                         |                        |               |                    |                         |                    |

**Conclusion:**

For the max result :  $0.39651 \leq \text{FCC Limit } 3.0$  for 1g SAR.