



Label location

Label sample:

90.00 mm



BLUETTI

150.00 mm

FCC ID: 2AYT3-EP500

Portable Power Station
Model No.: EP500
Battery Capacity: 5120Wh, 51.2VDC, 100Ah

Input
AC: 100-120VAC, 50/60Hz, 15A MAX
DC: 55-145VDC, 20A MAX

Output
AC × 4: 100-120VAC, 50/60Hz, 2000W Total
Aviation Sockets × 1: 12VDC, 30A
USB-A × 1: 5VDC, 2A
USB-A × 1: 5VDC, 1A
USB-A × 2: 5VDC, 2A; 9VDC, 2A; 12VDC, 1.5A
USB-C × 1: 5-15VDC, 3A; 20VDC, 5A
Cigarette Lighter Socket × 1: 12VDC, 10A
DC 5521 × 2: 12VDC, 10A Total
(DC 5521 and Cigarette Lighter 10A Total)
Wireless Charging × 2: 5/7.5/10/15W Total

Discharge Temperature: -20-40°C
Charging Temperature: 0-40°C
Working Humidity: 10%-90%

WARNING:

1. Please disposal the product in accordance with local laws;
2. Do not disassemble, pierce, electric shock the product, or burn it in fire.

FC This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



SHENZHEN POWEROAK NEWENER CO.LTD MADE IN CHINA P/N: 17.0301.0877-01A1