

Appendix B

Highest Test Plots

Table of Contents

1. 2.4G Head-worn 0mm SAR 3

1. 2.4G Head-worn 0mm SAR

Date: 16.01.2025

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24122303-1E

Serial: S:24122303-010

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used: $f = 2480\text{ MHz}$; $\sigma = 1.787\text{ S/m}$; $\epsilon_r = 40.21$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95) @ 2480 MHz; Calibrated: 29.04.2024
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/bootom side DH5 2480/Area Scan (14x24x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Maximum value of SAR (measured) = 0.531 W/kg

Configuration/bootom side DH5 2480/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.792 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 0.683 W/kg

SAR(1 g) = 0.325 W/kg; SAR(10 g) = 0.147 W/kg

Smallest distance from peaks to all points 3 dB below = 8.9 mm

Ratio of SAR at M2 to SAR at M1 = 48.5%

Maximum value of SAR (measured) = 0.549 W/kg



Date: 16.01.2025

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24122303-1E

Serial: S:24122303-010

Communication System: UID 0, Bluetooth (0); Communication System Band: BLE; Frequency: 2480 MHz;Communication System PAR: 0 dB; PMF: 1.12202e-005
Medium parameters used: $f = 2478 \text{ MHz}$; $\sigma = 1.787 \text{ S/m}$; $\epsilon_r = 40.21$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ConvF(7.95, 7.95, 7.95) @ 2480 MHz; Calibrated: 29.04.2024
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP.1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/Bottom side SRD 2478/Area Scan (14x24x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (measured) = 0.226 W/kg

Configuration/Bottom side SRD 2478/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 1.312 V/m; Power Drift = 0.15 dB
Peak SAR (extrapolated) = 0.292 W/kg
SAR(1 g) = 0.141 W/kg; SAR(10 g) = 0.064 W/kg
Smallest distance from peaks to all points 3 dB below = 8.2 mm
Ratio of SAR at M2 to SAR at M1 = 50.6%
Maximum value of SAR (measured) = 0.231 W/kg

