RF Exposure evaluation

Product Description: Axel Bass Boost Bluetooth® Headphone

Model Number: 100165-001B FCC ID: 2AGR4-100165

IC: 21530-100165

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \leq 3.0$ for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation

According to the follow transmitter output power (Pt) formula:

Pt = (E x d) 2/ (30 x gt)

Pt=transmitter output power in watts gt=numeric gain of the transmitting antenna (unitess)

E=electric field strength in V/m

d=measurement distance in meters (m)

According to the formula described above:

Emax=95.26dBuv/m=0.058V/m, d=3m, g_t=1

 P_{t} = (E x d) 2 / ($30 \times g_{t}$) =(**0.058**x3) 2 / (30x1)=**0.0010092**W=**1.01**mW

The result is rounded to one decimal place for comparison

Worse case is as below: [2402MHz -1.01mW output power]

 $(1.01 \text{mW} / 5 \text{mm})^* [\sqrt{2.402} (\text{GHz})] = 0.31 < 3.0 \text{ for } 1 - \text{g SAR}$

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer FCC test report.

According to Clause 2.5.1 of RSS-102 Issue 5 SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance4,5

Frequency(MHz)	At separation distance of ≤5 mm
2450	4 mW

According to the follow transmitter output power (Pt) formula:

 P_{MAX} =0.06dBm

Antenna gain=0dBi

 P_{EIRP} =0.06+0=0.06dBm=1.01mW <4mW

Then SAR evaluation is not required

NOTE: For the maximum power, you can refer IC test report.