

Shenzhen CTL Testing Technology Co., Ltd. Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

Т	EST REPORT	
Report Reference No	CTL1909098011-WF08	
Compiled by: (position+printed name+signature)	Happy Guo (File administrators)	Happy Guo
Tested by: (position+printed name+signature)	Nice Nong (Test Engineer)	Nice Nong
Approved by: (position+printed name+signature)	Ivan Xie (Manager)	Than Nie
Product Name	Master Roam T6	
Model/Type reference:	Т6	
List Model(s)	N/A	
Trade Mark	Master Roam	
FCC ID	2AU4T-T6	
Applicant's name:	Shanghai TUGE Data Technolog	ies Co., Ltd.
Address of applicant	Building C, No.888, Huanhu West Pudong New District, Shanghai, C	2 nd Road, Nanhui New Town, hina.
Test Firm:	Shenzhen CTL Testing Technolo	ogy Co., Ltd.
Address of Test Firm	Floor 1-A, Baisha Technology P Nanshan District, Shenzhen, China	ark, No.3011, Shahexi Road, a 518055
Test specification Standard	FCC CFR Title 47 Part 2, Part 27 EIA/TIA 603-D: 2010 KDB 971168 D01	
TRF Originator	Shenzhen CTL Testing Technology	/ Co., Ltd.
Master TRF	Dated 2011-01	
Date of receipt of test item:	Sep. 30, 2019	
Date of sampling:	Sep. 30, 2019	
Date of Test Date:	Sep. 30, 2019-Nov. 07, 2019	
Data of Issue	Nov. 08, 2019	
Result	Pass	
Shenzhen CTL Testing Technolog	y Co., Ltd. All rights reserved.	

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. ·	C	TI 1000008011-WE08	Nov. 08, 2019
			Date of issue
Equipment under Test	:	Master Roam T6	
Model /Type	<	Т6	
Listed Models		N/A	
Applicant	:	Shanghai TUGE Data Techr	nologies Co., Ltd.
Address	:	Building C, No.888, Huanhu V Pudong New District, Shangh	West 2 nd Road, Nanhui New Town, nai, China
Manufacturer	:	Hui Zhou fortuneship techr	nology Company Limited
Address	:	NO.86, Hechang 7th West Ro Development District, Huizho P.R.China (Phase II plant)	oad, Zhong Kai Hi-tech ou City, Guangdong Province,

Test result	Pass *	
rootroount		

*In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

V1.0

** Modified History **

Revisions	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2019-11-08	CTL1909098011-WF08	Tracy Qi
	-			1
			-	· · · ·









Table of Contents

Page

1. SUN	MMARY	5
11		-
1.1.		
1.2.		5
1.3.	I EST FACILITY	б
1.4.	STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
2. GEN	IERAL INFORMATION	7
2.1.	ENVIRONMENTAL CONDITIONS	7
2.2.	GENERAL DESCRIPTION OF EUT	7
2.3.	DESCRIPTION OF TEST MODES	7
2.4.	EQUIPMENTS USED DURING THE TEST	7
2.5.	Related Submittal(s) / Grant (s)	8
2.6.	Modifications	8
3. TES	T CONDITIONS AND RESULTS	9
3.1.	Output Power	9
3.2.	Peak-to-Average Ratio (PAR)	
3.3.	Occupied Bandwidth and Emission Bandwidth	
3.4.	BAND EDGE COMPLIANCE	14
3.5.	SPURIOUS EMISSION	
3.6.	FREQUENCY STABILITY UNDER TEMPERATURE & VOLTAGE VARIATIONS	
4. TES	T SETUP PHOTOS OF THE EUT	20
5. EXT	ERNAL AND INTERNAL PHOTOS OF THE EUT	21







1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

FCC Part 27 : MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES

TIA/EIA 603 D June 2010:Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

FCC Part 2: FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

KDB971168 D01: v02r02 MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

ANSI C63.10: 2013: American National Standard for Testing Unlicensed Wireless Devices

ANSI C63.4: 2014: –American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz Range of 9 kHz to 40GHz

1.2. Test Description

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 27.50(d)(4)	Pass
Peak-to-Average Ratio	Part 27.50(d)(4)	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 27.53(h)	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 27.53(h)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 27.53(h)	Pass
Out of band emission, Band Edge	Part 2.1051 Part 27.53(h)	Pass
Frequency stability	Part 2.1055 Part 27.54	Pass

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd. Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9518B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9518B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

rereatter the best measur	earter the best measurement capability for CTL laboratory is reported.						
Test	Range	Measurement Uncertainty	Notes				
Radiated Emission	30~1000MHz	4.10dB	(1)				
Radiated Emission Above 1GHz		4.32dB	(1)				
Conducted Disturbance	0.15~30MHz	3.20dB	(1)				

Hereafter the best measurement capability for CTL laboratory is reported:

 This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	Master Roam T6
Model/Type reference:	Т6
Power supply:	DC 3.8V from battery
Hardware version:	ET612-MB-V0.2
Software version:	Android 7.0
LTE	
Operation Band:	FDD-LTE: Band 2/4/5/7/12/17 TDD-LTE: Band 38/41
Modulation Type:	QPSK, 16QAM
Release Version:	Release 9
Category:	Cat 4
Antenna type:	FPC antenna
Antenna gain:	3dBi

Note: For more details, refer to the user's manual of the EUT. Note1: This report only reports band 17.

2.3. Description of Test Modes

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2019/05/20	2020/05/19
Bilog Antenna	Sunol Sciences Corp.	JB1	A061714	2019/05/20	2020/05/19
EMI Test Receiver	R&S	ESCI	103710	2019/05/20	2020/05/19
Spectrum Analyzer	Agilent	E4407B	MY41440676	2019/05/20	2020/05/19
Spectrum Analyzer	Agilent	N9020	US46220290	2019/05/20	2020/05/19
Spectrum Analyzer	Keysight	N9020A	MY53420874	2019/05/20	2020/05/19
Controller	EM Electronics	Controller EM 1000	N/A	2019/05/20	2020/05/19
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2019/05/20	2020/05/19

Horn Antenna	Sunol Sciences Corp.	DRH-118	A062014	2019/05/20	2020/05/19
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2019/05/20	2020/05/19
Amplifier	Agilent	8349B	3008A02306	2019/05/20	2020/05/19
Amplifier	Agilent	8447D	2944A10176	2019/05/20	2020/05/19
Temperature/Humi dity Meter	Gangxing	CTH-608	02	2019/05/20	2020/05/19
Wideband Radio Communication Tester	R&S	CMW500	101814	2019/05/20	2020/05/19
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2019/05/20	2020/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2019/05/20	2020/05/19
RF Cable	HUBER+SUHN ER	RG214	N/A	2019/05/20	2020/05/19
Climate Chamber	ESPEC	EL-10KA	A20120523	2019/05/20	2020/05/19
SIGNAL GENERATOR	Agilent	E4421B	US40051744	2019/05/20	2020/05/19
Directional Coupler	Agilent	87300B	3116A03638	2019/05/20	2020/05/19
Power Sensor	Agilent	U2021XA	MY5365004	2019/05/20	2020/05/19
Power Meter	Agilent	U2531A	TW53323507	2019/05/20	2020/05/19

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with of the Part 27 and RSS-130 Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.



3. TEST CONDITIONS AND RESULTS

3.1. Output Power

LIMIT

FCC: 3 Watts ERP

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Power Measurement:

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- c) EUT Communicate with CMW500 then selects a channel for testing.
- d) Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- a) The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b) The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c) The output of the test antenna shall be connected to the measuring receiver.

- d) The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e) The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g) The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h) The maximum signal level detected by the measuring receiver shall be noted.
- i) The transmitter shall be replaced by a substitution antenna.
- j) The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k) The substitution antenna shall be connected to a calibrated signal generator.
- I) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m) The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n) The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o) The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p) The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q) Test site anechoic chamber refer to ANSI C63.4.

TEST RESULTS

Conducted Measurement: See Appendix A.

Radiated Measurement:

Remark:

V1.0

- 1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 17; recorded worst case for each Channel Bandwidth of LTE FDD Band 17.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Ag}(dB)+G_{a}(dBi)$

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
706.5	-15.26	2.38	8.23	2.15	36.70	25.14	34.77	12.36	V
710	-14.16	2.40	8.29	2.15	36.70	26.28	34.77	12.15	V
713.5	-15.63	2.43	8.28	2.15	36.70	24.77	34.77	12.21	V

LTE FDD Band 17_Channel Bandwidth 5MHz_QPSK

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
709	-15.26	2.38	8.23	2.15	36.70	22.14	25.14	12.53	V
710	-14.16	2.40	8.29	2.15	36.70	22.23	26.28	12.34	V
711	-15.63	2.43	8.28	2.15	36.70	22.41	24.77	12.39	V

LTE FDD Band 17_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
706.5	-15.26	2.38	8.23	2.15	36.70	25.14	34.77	12.48	V
710	-14.16	2.40	8.29	2.15	36.70	26.28	34.77	12.56	V
713.5	-15.63	2.43	8.28	2.15	36.70	24.77	34.77	12.31	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
709	-15.26	2.38	8.23	2.15	36.70	25.14	34.77	12.06	V
710	-14.16	2.40	8.29	2.15	36.70	26.28	34.77	12.14	V
711	-15.63	2.43	8.28	2.15	36.70	24.77	34.77	12.27	V

3.2. Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- 2. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- 3. Set the number of counts to a value that stabilizes the measured CCDF curve;
- 4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,

2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.

5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

See Appendix B.

3.3. Occupied Bandwidth and Emission Bandwidth

<u>LIMIT</u>

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded.

Set RBW was set to about 1% of emission BW, VBW≥3 times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

See Appendix C.

LIMIT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P) dB$

TEST CONFIGURATION



TEST PROCEDURE

- 1. The transmitter output port was connected to base station.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
- 3. Set EUT at maximum power through base station.
- 4. Select lowest and highest channels for each band and different modulation.
- 5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

See Appendix D.



3.5. Spurious Emission

LIMIT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P) dB$

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Spurious Measurement:

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- c. EUT Communicate with CMW500 then selects a channel for testing.
- d. Add a correction factor to the display of spectrum, and then test.
- e. The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to10th harmonic.

Radiated Spurious Measurement:

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- I. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for Part 22 and 1MHz for Part 24. The frequency range was checked up to 10th harmonic.
- r. Test site anechoic chamber refer to ANSI C63.

TEST RESULTS

Conducted Measurement: See Appendix E.



Radiated Measurement:

Remark:

- 1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 12; recorded worst case for each Channel Bandwidth of LTE FDD Band 12.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Ag}(dB)+G_{a}(dBi)$

LTE FDD Band 17_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	Correction (dB)	P _{Ag} (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
706.5	-15.26	2.38	8.23	2.15	36.70	25.14	34.77	9.63	V
710.0	-14.81	2.40	8.29	2.15	36.70	25.63	34.77	9.14	V
713.5	-15.45	2.43	8.28	2.15	36.70	24.95	34.77	9.82	V

LTE FDD Band 17_Channel Bandwidth 10MHz_QPSK

Frequency	P _{Mea}	P _{cl}	Ga	Correction	P_{Aq}	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	Antenna	(dB)	(dB)	(dBm)	(dBm)	(dB)	
			Gain(dB)						
709.0	-14.98	2.38	8.23	2.15	36.70	25.42	34.77	9.35	V
710.0	-14.93	2.40	8.29	2.15	36.70	25.51	34.77	9.26	V
711.0	-15.03	2.43	8.28	2.15	36.70	25.37	34.77	9.40	V

LTE FDD Band 17_Channel Bandwidth 5MHz_16QAM

Frequency	P _{Mea}	P _{cl}	Ga	Correction	P _{Ag}	ERP	Limit	Margin	Polarization
(MHZ)	(dBm)	(dB)	Antenna Coin(dP)	(dB)	(dB)	(dBm)	(dBm)	(dB)	
706.5	-15.16	2.38	8.23	2.15	36.70	25.24	34.77	9.53	V
710.0	-15.26	2.40	8.29	2.15	36.70	25.18	34.77	9.59	V
713.5	-15.03	2.43	8.28	2.15	36.70	25.37	34.77	9.40	V

LTE FDD Band 17_Channel Bandwidth 10MHz_16QAM

Frequency	P _{Mea}	P _{cl}	Ga	Correction	P _{Ag}	ERP	Limit	Margin	Polarization
(MHz)	(dBm)	(dB)	Antenna	(dB)	(dB)	(dBm)	(dBm)	(dB)	
		100	Gain(dB)						
709.0	-15.07	2.38	8.23	2.15	36.70	25.33	34.77	9.44	V
710.0	-15.02	2.40	8.29	2.15	36.70	25.42	34.77	9.35	V
711.0	-15.12	2.43	8.28	2.15	36.70	25.28	34.77	9.49	V

3.6. Frequency Stability under Temperature & Voltage Variations

LIMIT

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

TEST CONFIGURATION



Variable Power Supply

TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Frequency Stability under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- 2. Subject the EUT to overnight soak at -30 °C.
- 3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE Band 17, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10 °C increments from -30 °C to +50 °C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
- 5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6. Subject the EUT to overnight soak at +50°C.
- 7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements

9. At all temperature levels hold the temperature to +/- 0.5° C during the measurement procedure. Frequency Stability under Voltage Variations:

Set chamber temperature to 20° C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation (±15%) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark:

1. We tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 17; recorded worst case.

LTE Band 17, 5MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Frequency	/ error (Hz)	Frequency	error (ppm)	Limit
(V)	QPSK	16QAM	QPSK	16QAM	(ppm)
4.37	1.62	9.03	0.00228	0.01272	2.50
3.80	-1.74	5.19	-0.00245	0.00731	2.50
3.23	8.85	0.63	0.01246	0.00089	2.50

Frequency Error vs Temperature

Temperature	Frequency	error (Hz)	Frequency	error (ppm)	Limit
(°C)	QPSK	16QAM	QPSK	16QAM	(ppm)
-30°	-1.43	4.74	-0.00201	0.00668	2.50
-20°	1.98	-9.45	0.00279	-0.01331	2.50
-10°	4.08	-7.49	0.00575	-0.01055	2.50
0°	4.40	-3.33	0.00620	-0.00469	2.50
10°	0.42	0.39	0.00059	0.00055	2.50
20°	0.30	-6.05	0.00042	-0.00852	2.50
30°	0.80	3.23	0.00113	0.00455	2.50
40°	-5.04	7.89	-0.00710	0.01111	2.50
50°	-5.07	8.85	-0.00714	0.01246	2.50







4. Test Setup Photos of the EUT











5. External and Internal Photos of the EUT

Reference to the test report No. CTL1909098011-WF01





