

**FCC ID: 2ARWY-Y40**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

| Modulation    | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| GFSK          | 2.402               | 2.004                  | 1.59                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.61847            | 3.00                    | YES                |
|               | 2.441               | 1.64                   | 1.46                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49524            | 3.00                    | YES                |
|               | 2.480               | 1.633                  | 1.46                  | 1±1                 | 2.00                    | 1.58                   | <5            | 0.49918            | 3.00                    | YES                |
| $\pi$ /4DQPSK | 2.402               | 2.76                   | 1.89                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.61847            | 3.00                    | YES                |
|               | 2.441               | 2.35                   | 1.72                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.62347            | 3.00                    | YES                |
|               | 2.480               | 2.336                  | 1.71                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.62843            | 3.00                    | YES                |
| 8DQPSK        | 2.402               | 3.012                  | 2.00                  | 3±1                 | 4.00                    | 2.51                   | <5            | 0.77860            | 3.00                    | YES                |
|               | 2.441               | 2.623                  | 1.83                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.62347            | 3.00                    | YES                |
|               | 2.480               | 2.565                  | 1.81                  | 2±1                 | 3.00                    | 2.00                   | <5            | 0.62843            | 3.00                    | YES                |

**Conclusion:**

For the max result :  $0.77860 \leq \text{FCC Limit } 3.0$  for 1g SAR.