

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10



FCC TEST REPORT

(Part 15, Subpart C)

| | |
|------------|---|
| Applicant: | Thundercomm Technology Co., Ltd. |
| Address: | No. 107, Middle Datagu Road, Xiantao Street, Yubei District, Chongqing, China, 401122 |



| | |
|---------------------------|---|
| Manufacturer or Supplier: | Thundercomm Technology Co., Ltd. |
| Address: | No. 107, Middle Datagu Road, Xiantao Street, Yubei District, Chongqing, China, 401122 |
| Product: | Edge AI Station |
| Brand Name: | Thundercomm |
| Model Name: | EB5S |
| FCC ID: | 2AOHHEB5S |
| Date of tests: | Sep. 09, 2023 ~ Oct. 31, 2023 |

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

| | |
|--|--|
| Prepared by Simon Wang Engineer / Mobile Department | Approved by Luke Lu Manager / Mobile Department |
|  Date: Oct. 31, 2023 |  Date: Oct. 31, 2023 |

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

| | |
|--|-----------|
| RELEASE CONTROL RECORD | 3 |
| 1 SUMMARY OF TEST RESULTS..... | 4 |
| 1.1 MEASUREMENT UNCERTAINTY | 5 |
| 2 GENERAL INFORMATION | 6 |
| 2.1 GENERAL DESCRIPTION OF EUT | 6 |
| 2.2 DESCRIPTION OF TEST MODES | 8 |
| 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST | 9 |
| 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... | 9 |
| 2.3 DUTY CYCLE OF TEST SIGNAL | 12 |
| 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS | 13 |
| 2.5 DESCRIPTION OF SUPPORT UNITS | 13 |
| 3 TEST TYPES AND RESULTS..... | 14 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 14 |
| 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT | 14 |
| 3.1.2 TEST INSTRUMENTS..... | 14 |
| 3.1.3 TEST PROCEDURES | 15 |
| 3.1.4 DEVIATION FROM TEST STANDARD | 15 |
| 3.1.5 TEST SETUP | 16 |
| 3.1.6 EUT OPERATING CONDITIONS | 16 |
| 3.1.7 TEST RESULTS | 17 |
| 3.2 RADIATED EMISSION MEASUREMENT | 19 |
| 3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT | 19 |
| 3.2.2 TEST INSTRUMENTS..... | 20 |
| 3.2.3 TEST PROCEDURES | 21 |
| 3.2.4 DEVIATION FROM TEST STANDARD | 21 |
| 3.2.5 TEST SETUP | 22 |
| 3.2.6 EUT OPERATING CONDITIONS | 23 |
| 3.2.7 TEST RESULTS | 24 |
| 4 PHOTOGRAPHS OF THE TEST CONFIGURATION | 55 |
| 5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB56 | |



**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

RELEASE CONTROL RECORD

| ISSUE NO. | REASON FOR CHANGE | DATE ISSUED |
|-------------------|--------------------------|--------------------|
| W7L-P23070010RF10 | Original release | Oct. 31, 2023 |



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) | | |
|---|----------------------------------|------------|
| STANDARD SECTION | TEST TYPE AND LIMIT | RESULT |
| 15.207 | AC Power Conducted Emission | Compliance |
| 15.205 15.209 | Radiated Emissions | Compliance |
| 15.247(d) | Out of band Emission Measurement | See Note |
| 15.247(a)(2) | 6dB bandwidth | See Note |
| 15.247(b) | Conducted Output power | See Note |
| 15.247(e) | Power Spectral Density | See Note |
| 15.203 | Antenna Requirement | Compliance |

NOTE: Refer to Module report SZ22110114W03/ SZ22110114W03-1/ SZ22110114W03-2, FCC ID: 2AOHHTURBOXC865C. The verify results of conducted power are similar or lower, so this report the power table are not updated.



1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| MEASUREMENT | UNCERTAINTY |
|-----------------------------------|-----------------------|
| AC Power Conducted emissions | $\pm 2.70\text{dB}$ |
| Radiated emissions (9KHz~30MHz) | $\pm 2.68\text{dB}$ |
| Radiated emissions (30MHz~1GHz) | $\pm 4.98\text{dB}$ |
| Radiated emissions (1GHz ~6GHz) | $\pm 4.70\text{dB}$ |
| Radiated emissions (6GHz ~18GHz) | $\pm 4.60\text{dB}$ |
| Radiated emissions (18GHz ~40GHz) | $\pm 4.12\text{dB}$ |
| Conducted emissions | $\pm 4.01\text{dB}$ |
| Occupied Channel Bandwidth | $\pm 43.58\text{KHz}$ |
| Conducted Output power | $\pm 2.06\text{dB}$ |
| Power Spectral Density | $\pm 0.85\text{ dB}$ |

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|--------------------------------|---|
| PRODUCT | Edge AI Station |
| BRAND NAME | Thundercomm |
| MODEL NAME | EB5S |
| NOMINAL VOLTAGE | 19Vdc(adapter) |
| MODULATION | DSSS, OFDM, OFDMA |
| TRANSMISSION RATE | 802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n20: up to 144.4 Mbps 802.11n40: up to 300 Mbps 802.11ax20: up to 286.8Mbps 802.11ax40: up to 573.5Mbps 802.11ax 20 (RU26/52/106/242): up to 286.8Mbps 802.11ax 40 (RU26/52/106/242/484): up to 573.5Mbps |
| OPERATING FREQUENCY | 2412-2462MHz for 11b/g/n(HT20/40) /ax(HE20/40) 2412-2462MHz for ax(20M RU26/52/106/242)/ax (40M RU26/52/106/242/484) |
| MAX. OUTPUT POWER | WLAN: 480.52mW (Maximum) RU WLAN: 729.46mW (Maximum) |
| ANTENNA TYPE | ANT 0: Fixed External Antenna with -2.04dBi gain for WIFI ANT 1: Fixed External Antenna with -2.04dBi gain for WIFI |
| HW VERSION | Turbox EB5S-IO-BOARD V03 |
| SW VERSION | R.5S.LA.2.20231030 |
| I/O PORTS | Refer to user's manual |
| CABLE SUPPLIED | N/A |



**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function for B/G mode, and a MIMO function for N20/N40/AX20/AX40 mode. Physically, the EUT provides two transmitters and two receivers.

| MODULATION MODE | TX/RX FUNCTION |
|---------------------------------------|----------------|
| 802.11b | 2TX /2RX |
| 802.11g | 2TX /2RX |
| 802.11n (20MHz) | 2TX /2RX |
| 802.11ax (20MHz) | 2TX /2RX |
| 802.11n (40MHz) | 2TX /2RX |
| 802.11ax (40MHz) | 2TX /2RX |
| 802.11ax (20MHz RU 26/52/106/242) | 2TX /2RX |
| 802.11ax (40MHz RU 26/52/106/242/484) | 2TX /2RX |

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.
4. According to KDB 662911 D01, the directional gain = $G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the maximum antenna gain in dBi, N_{ANT} is the number of outputs. Directional gain = $-2.04\text{dBi} + 10\log(2) = 0.97\text{dBi} < 6\text{dBi}$, so the power limit needn't to be reduced.

List of Accessory:

| ACCESSORIES | BRAND | MANUFACTURER | MODEL | SPECIFICATION |
|-------------|---------|------------------------------------|----------------|---|
| AC Adapter | Huntkey | Shenzhen Huntkey Electric Co. Ltd. | HKA09019047-6U | I/P: 100-240Vac, 1.5A, O/P: 19Vdc, 3.15A |



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11ax20 (HE20), 802.11ax20 (RU 26/52/106/242):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 1 | 2412 MHz | 7 | 2442 MHz |
| 2 | 2417 MHz | 8 | 2447 MHz |
| 3 | 2422 MHz | 9 | 2452 MHz |
| 4 | 2427 MHz | 10 | 2457 MHz |
| 5 | 2432 MHz | 11 | 2462 MHz |
| 6 | 2437 MHz | | |

7 channels are provided for 802.11n (HT40), 802.11ax40 (HE40), 802.11ax40 (RU 26/52/106/242/484):

| CHANNEL | FREQUENCY | CHANNEL | FREQUENCY |
|---------|-----------|---------|-----------|
| 3 | 2422 MHz | 7 | 2442 MHz |
| 4 | 2427 MHz | 8 | 2447 MHz |
| 5 | 2432 MHz | 9 | 2452 MHz |
| 6 | 2437 MHz | | |



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

| EUT CONFIGURE MODE | APPLICABLE TO | | | | MODE |
|--------------------------|---------------|-------|-----|------|------|
| | RE<1G | RE≥1G | PLC | APCM | |
| - | √ | √ | √ | - | - |

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|--------------|----------------------|-------------------|------------|---------------------|
| 802.11n HT20 | 1 to 11 | 1 | OFDM | MCS0 |

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|---------------------|-------------------|----------------|------------|------------------|
| 802.11b | 1 to 11 | 1, 6, 11 | DSSS | 1.0 |
| 802.11g | 1 to 11 | 1, 6, 11 | OFDM | 6.0 |
| 802.11n HT20 | 1 to 11 | 1, 6, 11 | OFDM | MCS0 |
| 802.11ax HE20 | 1 to 11 | 1, 6, 11 | OFDM | MCS0 |
| 802.11n HT40 | 3 to 9 | 3,6,9 | OFDM | MCS0 |
| 802.11ax HE40 | 3 to 9 | 3,6,9 | OFDM | MCS0 |
| 802.11ax 20 (RU 26) | 1 to 11 | 1, 11 | OFDMA | MCS0 |

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

| MODE | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION | DATA RATE (Mbps) |
|--------------|-------------------|----------------|------------|------------------|
| 802.11n HT20 | 1 to 11 | 1 | OFDM | MCS0 |



TEST CONDITION:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | TEST VOLTAGE | TESTED BY |
|------------------|--------------------------|-------------------|-----------|
| RE<1G | 23deg. C, 70%RH | DC 19V By Adapter | Jace Hu |
| RE≥1G | 23deg. C, 70%RH | DC 19V By Adapter | Jace Hu |
| PLC | 25deg. C, 52%RH | DC 19V By Adapter | Carl Xie |



Test Report No.: W7L-P23070010RF10

2.3 DUTY CYCLE OF TEST SIGNAL

Refer to Module report SZ22110114W03/ SZ22110114W03-1/ SZ22110114W03-2.



2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|-----|---------|--------|---------------|------------|--------|
| 1 | Desktop | Lenovo | M73 SFF | PC04GRQV | N/A |
| 2 | Desktop | Lenovo | M73 SFF | PC06CS27 | N/A |
| 3 | Laptop | Lenovo | Thinkpad T450 | PC-049PT1 | N/A |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| 1 | AC Line: Unshielded, Detachable 1.5m |
| 2 | AC Line: Unshielded, Detachable 1.5m |
| 3 | USB Line: Unshielded, Detachable 1.5m |



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

| FREQUENCY OF EMISSION (MHz) | CONDUCTED LIMIT (dB μ V) | |
|-----------------------------|------------------------------|----------|
| | Quasi-peak | Average |
| 0.15 ~ 0.5 | 66 to 56 | 56 to 46 |
| 0.5 ~ 5 | 56 | 46 |
| 5 ~ 30 | 60 | 50 |

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|-----------------------|---------------|-----------|------------|-----------|-----------|
| EMI Test Receiver | Rohde&Schwarz | ESR3 | 102749 | Feb.25,22 | Feb.24,24 |
| ELEKTRA test software | Rohde&Schwarz | ELEKTRA | NA | N/A | N/A |
| LISN network | Rohde&Schwarz | ENV216 | 102640 | Feb.17,22 | Feb.16,24 |
| CABLE | Rohde&Schwarz | W61.01 | N/A | Apr.28,23 | Oct.27,23 |
| CABLE | Rohde&Schwarz | W61.01 | N/A | Oct.27,23 | Apr.26,24 |
| CABLE | Rohde&Schwarz | W601 | N/A | Apr.28,23 | Oct.27,23 |
| CABLE | Rohde&Schwarz | W601 | N/A | Oct.27,23 | Apr.26,24 |

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 6 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

| Frequency Range | 150KHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9 kHz |
|-----------------|----------------|--|---------------------------------------|
| Input Power | 120Vac, 60Hz | Environmental Conditions | 26deg. C, 51%RH |
| Tested By | Carl Xie | | |

| Re | Frequency [MHz] | QPK Level [dBuV] | QPK Limit [dBuV] | QPK Margin [dB] | CAV Level [dBuV] | CAV: AVG Limit [dBuV] | CAV Margin [dB] | Correction [dB] | Line | Meas. BW [kHz] |
|----|-----------------|------------------|------------------|-----------------|------------------|-----------------------|-----------------|-----------------|------|----------------|
| 1 | 0.150 | 60.99 | 66.00 | 5.01 | 39.92 | 56.00 | 16.08 | 12.57 | L1 | 9.000 |
| 1 | 0.375 | 37.66 | 58.39 | 20.73 | 20.87 | 48.39 | 27.51 | 11.77 | L1 | 9.000 |
| 1 | 0.866 | 16.91 | 56.00 | 39.09 | 5.59 | 46.00 | 40.41 | 11.75 | L1 | 9.000 |
| 1 | 2.405 | 14.13 | 56.00 | 41.87 | 1.89 | 46.00 | 44.11 | 11.77 | L1 | 9.000 |
| 1 | 4.254 | 18.26 | 56.00 | 37.74 | 8.05 | 46.00 | 37.95 | 11.79 | L1 | 9.000 |
| 1 | 10.140 | 40.63 | 60.00 | 19.37 | 27.24 | 50.00 | 22.76 | 11.83 | L1 | 9.000 |

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






| | | | |
|-----------------|----------------|--|---------------------------------------|
| Frequency Range | 150KHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9 kHz |
| Input Power | 120Vac, 60Hz | Environmental Conditions | 26deg. C, 51%RH |
| Tested By | Carl Xie | | |

| Rg | Frequency [MHz] | QPK Level [dBuV] | QPK Limit [dBuV] | QPK Margin [dB] | CAV Level [dBuV] | CAV: AVG Limit [dBuV] | CAV Margin [dB] | Correction [dB] | Line | Meas. BW [kHz] |
|----|-----------------|------------------|------------------|-----------------|------------------|-----------------------|-----------------|-----------------|------|----------------|
| 1 | 0.150 | 60.40 | 66.00 | 5.60 | 39.29 | 56.00 | 16.71 | 12.13 | N | 9.000 |
| 1 | 0.375 | 38.36 | 58.39 | 20.03 | 20.05 | 48.39 | 28.34 | 12.83 | N | 9.000 |
| 1 | 1.131 | 14.80 | 56.00 | 41.20 | 6.19 | 46.00 | 39.81 | 12.74 | N | 9.000 |
| 1 | 2.265 | 18.35 | 56.00 | 37.65 | 8.12 | 46.00 | 37.88 | 12.74 | N | 9.000 |
| 1 | 4.254 | 24.54 | 56.00 | 31.46 | 13.52 | 46.00 | 32.48 | 12.76 | N | 9.000 |
| 1 | 9.987 | 41.11 | 60.00 | 18.89 | 28.23 | 50.00 | 21.77 | 12.79 | N | 9.000 |

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

| FREQUENCIES (MHz) | FIELD STRENGTH (microvolts/meter) | MEASUREMENT DISTANCE (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

| Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|------------------------------------|------------------------------|------------------|-----------------------|-----------|-----------|
| Pre-Amplifier | R&S | SCU18F1 | 100815 | Aug.30,22 | Aug.29,24 |
| Pre-Amplifier | R&S | SCU08F1 | 101028 | Sep.16,22 | Sep.15,24 |
| Signal Generator | R&S | SMB100A | 182185 | Feb.16,22 | Feb.15,24 |
| 3m Fully-anechoic Chamber | TDK | 9m*6m*6m | HRSW-SZ-EMC-01Chamber | Nov.25,22 | Nov.24,25 |
| 3m Semi-anechoic Chamber | TDK | 9m*6m*6m | HRSW-SZ-EMC-02Chamber | Nov.25,22 | Nov.24,25 |
| EMI TEST Receiver | R&S | ESW44 | 101973 | Feb.25,22 | Feb.24,24 |
| Bilog Antenna | SCHWARZBECK | VULB 9163 | 1264 | Feb.28,22 | Feb.27,24 |
| Horn Antenna | ETS-LINDGREN | 3117 | 227836 | Aug.22,22 | Aug.21,24 |
| Horn Antenna (18GHz-40GHz) | Steatite Q-par Antennas | QMS 00880 | 23486 | Feb.23,22 | Feb.22,24 |
| Horn Antenna | Steatite Q-par Antennas | QMS 00208 | 23485 | Aug.22,22 | Aug.21,24 |
| Loop Antenna | SCHWARZ | HFH2-Z2/Z2E | 100976 | Feb.23,22 | Feb.22,24 |
| WIDEBANDRADIO COMMUNICATION TESTER | R&S | CMW500 | 169399 | Jun.27,22 | Jun.26,24 |
| Test Software | ELEKTRA | ELEKTRA4.32 | N/A | N/A | N/A |
| Open Switch and Control Unit | R&S | OSP220 | 101964 | N/A | N/A |
| DC Source | HYELEC | HY3010B | 551016 | Aug.31,22 | Aug.30,24 |
| Hygrothermograph | DELI | 20210528 | SZ014 | Sep.06,22 | Sep.05,24 |
| 6DB attenuator | Tonscend Technology Co., Ltd | N/A | 23062787 | N/A | N/A |
| PC | LENOVO | E14 | HRSW0024 | N/A | N/A |
| TMC-AMI18843A(CABLE) | R&S | HF290-NMNM-7.00M | N/A | N/A | N/A |
| TMC-AMI18843A(CABLE) | R&S | HF290-NMNM-4.00M | N/A | N/A | N/A |
| CABLE | R&S | W13.02 | N/A | Apr.28,23 | Oct.27,23 |
| CABLE | R&S | W13.02 | N/A | Oct.27,23 | Apr.26,24 |
| CABLE | R&S | W12.14 | N/A | Apr.28,23 | Oct.27,23 |
| CABLE | R&S | W12.14 | N/A | Oct.27,23 | Apr.26,24 |

- NOTE:**
1. The calibration interval of the above test instruments is 6 months or 24months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation




BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed it on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

802.11n (20MHz):


| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
|-----------------|--------------|-------------------|-----------------|
| FREQUENCY RANGE | 30MHz ~ 1GHz | | |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | QPK Level [dBμV/m] | QPK Limit [dBμV/m] | QPK Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] | Meas. BW [kHz] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|----------------|
| 1 | 40.767 | 23.75 | 40.00 | 16.25 | -10.96 | H | 0.8 | 2 | 120.000 |
| 1 | 86.212 | 28.17 | 40.00 | 11.83 | -15.27 | H | 86.9 | 2 | 120.000 |
| 1 | 102.411 | 27.93 | 43.50 | 15.57 | -12.14 | H | 86.9 | 2 | 120.000 |
| 1 | 135.488 | 22.67 | 43.50 | 20.83 | -15.61 | H | 224.4 | 2 | 120.000 |
| 1 | 244.516 | 25.56 | 46.00 | 20.44 | -9.16 | H | 5 | 1 | 120.000 |
| 1 | 375.708 | 20.08 | 46.00 | 25.92 | -5.51 | H | 273 | 1 | 120.000 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.





BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10


| | | | |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz | | |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | QPK Level [dBμV/m] | QPK Limit [dBμV/m] | QPK Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] | Meas. BW [kHz] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|----------------|
| 1 | 32.765 | 30.13 | 40.00 | 9.87 | -13.24 | V | 359 | 1 | 120.000 |
| 1 | 57.306 | 21.62 | 40.00 | 18.38 | -11.38 | V | 273 | 1 | 120.000 |
| 1 | 88.000 | 21.10 | 40.00 | 18.90 | -14.72 | V | 134.4 | 1 | 120.000 |
| 1 | 165.897 | 17.84 | 43.50 | 25.66 | -14.24 | V | 359 | 1 | 120.000 |
| 1 | 243.885 | 22.70 | 46.00 | 23.30 | -9.18 | V | 86.9 | 2 | 120.000 |
| 1 | 497.928 | 22.28 | 46.00 | 23.72 | -4.57 | V | 226.7 | 2 | 120.000 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.



**ABOVE 1GHz WORST-CASE DATA:**

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

802.11b:

| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Peak (PK) |
|-----------------|--------------|-------------------|--------------|
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,386.500 | 46.92 | 74.00 | 27.08 | 7.08 | H | 79.8 | 2 |
| 1 | 2,390.000 | 46.20 | 74.00 | 27.80 | 7.08 | H | 79.8 | 2 |
| 1 | 2,411.000 | 98.47 | | | 7.17 | H | 79.8 | 2 |

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.500 | 33.83 | 54.00 | 20.17 | 7.08 | H | 5 | 1 |
| 1 | 2,390.000 | 33.36 | 54.00 | 20.64 | 7.08 | H | 5 | 1 |
| 1 | 2,411.500 | 93.92 | | | 7.17 | H | 206.4 | 2 |



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.000 | 38.52 | 54.00 | 15.48 | 7.08 | V | 1 | 1 |
| 1 | 2,390.000 | 37.59 | 54.00 | 16.41 | 7.08 | V | 1 | 1 |
| 1 | 2,413.000 | 104.11 | | | 7.19 | V | 1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.500 | 50.55 | 74.00 | 23.45 | 7.08 | V | 359.1 | 1 |
| 1 | 2,390.000 | 49.86 | 74.00 | 24.14 | 7.08 | V | 1 | 1 |
| 1 | 2,411.000 | 108.09 | | | 7.17 | V | 220.8 | 2 |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2412MHz: Fundamental frequency.



**BUREAU
VERITAS**


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
|-----------------|--------------|-------------------|--------------|
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.53 | 74.00 | 23.47 | 39.88 | 54.00 | 14.12 | 15.25 | H | 88.9 | 1 |
| 2 | 7,311.000 | 57.49 | 74.00 | 16.51 | 45.83 | 54.00 | 8.17 | 21.10 | H | 88.9 | 1 |






**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 51.14 | 74.00 | 22.86 | 39.74 | 54.00 | 14.26 | 15.25 | V | 271 | 2 |
| 2 | 7,311.000 | 57.26 | 74.00 | 16.74 | 45.62 | 54.00 | 8.38 | 21.10 | V | 1 | 2 |



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2437MHz: Fundamental frequency.



**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

| | | | |
|------------------------|---------------|--------------------------|--------------|
| CHANNEL | TX Channel 11 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,461.000 | 93.75 | | | 7.40 | H | 119.1 | 2 |
| 2 | 2,483.500 | 32.32 | 54.00 | 21.68 | 7.36 | H | 355 | 2 |
| 2 | 2,487.000 | 32.92 | 54.00 | 21.08 | 7.36 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.000 | 94.45 | | | 7.39 | H | 151.4 | 2 |
| 2 | 2,483.500 | 45.80 | 74.00 | 28.20 | 7.36 | H | 139.2 | 1 |
| 2 | 2,486.500 | 46.94 | 74.00 | 27.06 | 7.36 | H | 66.2 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,461.000 | 104.63 | | | 7.40 | V | 355.4 | 1 |
| 2 | 2,483.500 | 37.12 | 54.00 | 16.88 | 7.36 | V | 0.9 | 2 |
| 2 | 2,486.500 | 38.51 | 54.00 | 15.49 | 7.36 | V | 0.9 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.000 | 109.11 | | | 7.39 | V | 13.4 | 2 |
| 2 | 2,483.500 | 50.13 | 74.00 | 23.87 | 7.36 | V | 359.1 | 1 |
| 2 | 2,486.000 | 51.37 | 74.00 | 22.63 | 7.36 | V | 359.1 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2462MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

802.11g

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 33.91 | 54.00 | 20.09 | 7.08 | H | 359 | 1 |
| 1 | 2,390.000 | 34.26 | 54.00 | 19.74 | 7.08 | H | 359 | 1 |
| 1 | 2,418.000 | 80.12 | | | 7.23 | H | 359 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 54.10 | 74.00 | 19.90 | 7.08 | H | 282.6 | 1 |
| 1 | 2,390.000 | 54.43 | 74.00 | 19.57 | 7.08 | H | 5 | 1 |
| 1 | 2,409.000 | 99.01 | | | 7.15 | H | 219.6 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 44.30 | 54.00 | 9.70 | 7.08 | V | 359.1 | 1 |
| 1 | 2,390.000 | 45.26 | 54.00 | 8.74 | 7.08 | V | 359.1 | 1 |
| 1 | 2,408.500 | 97.72 | | | 7.14 | V | 359.1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 60.47 | 74.00 | 13.53 | 7.08 | V | 359 | 1 |
| 1 | 2,390.000 | 60.47 | 74.00 | 13.53 | 7.08 | V | 359 | 1 |
| 1 | 2,408.500 | 109.45 | | | 7.14 | V | 219.6 | 2 |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2412MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
|-----------------|--------------|-------------------|--------------|
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 51.08 | 74.00 | 22.92 | 39.85 | 54.00 | 14.15 | 15.25 | H | 35.5 | 2 |
| 2 | 7,311.000 | 57.02 | 74.00 | 16.98 | 45.87 | 54.00 | 8.13 | 21.10 | H | 359 | 2 |






**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 51.23 | 74.00 | 22.77 | 39.78 | 54.00 | 14.22 | 15.25 | V | 17.1 | 2 |
| 2 | 7,311.000 | 57.55 | 74.00 | 16.45 | 45.77 | 54.00 | 8.23 | 21.10 | V | 0.9 | 2 |



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2437MHz: Fundamental frequency.
- For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

| | | | |
|-----------------|---------------|-------------------|--------------|
| CHANNEL | TX Channel 11 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,467.000 | 88.02 | | | 7.37 | H | 355 | 2 |
| 2 | 2,483.500 | 33.76 | 54.00 | 20.24 | 7.36 | H | 355 | 2 |
| 2 | 2,484.000 | 33.56 | 54.00 | 20.44 | 7.36 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,464.500 | 96.66 | | | 7.38 | H | 149.1 | 2 |
| 2 | 2,483.500 | 50.81 | 74.00 | 23.19 | 7.36 | H | 220.8 | 2 |
| 2 | 2,484.000 | 51.57 | 74.00 | 22.43 | 7.36 | H | 220.8 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,460.000 | 97.68 | | | 7.40 | V | 1 | 1 |
| 2 | 2,483.500 | 43.32 | 54.00 | 10.68 | 7.36 | V | 1 | 1 |
| 2 | 2,484.000 | 42.93 | 54.00 | 11.07 | 7.36 | V | 1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,461.000 | 110.84 | | | 7.40 | V | 11.4 | 2 |
| 2 | 2,483.500 | 63.01 | 74.00 | 10.99 | 7.36 | V | 1 | 2 |
| 2 | 2,485.000 | 60.68 | 74.00 | 13.32 | 7.36 | V | 1 | 2 |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2462MHz: Fundamental frequency.



802.11n (20MHz)

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 41.48 | 54.00 | 12.52 | 7.08 | H | 355 | 2 |
| 1 | 2,390.000 | 42.01 | 54.00 | 11.99 | 7.08 | H | 355 | 2 |
| 1 | 2,415.500 | 94.83 | | | 7.21 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.000 | 57.43 | 74.00 | 16.57 | 7.08 | H | 355 | 2 |
| 1 | 2,390.000 | 58.65 | 74.00 | 15.35 | 7.08 | H | 355 | 2 |
| 1 | 2,416.500 | 107.60 | | | 7.22 | H | 355 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 45.86 | 54.00 | 8.14 | 7.08 | V | 359.1 | 1 |
| 1 | 2,390.000 | 47.37 | 54.00 | 6.63 | 7.08 | V | 359.1 | 1 |
| 1 | 2,414.000 | 99.98 | | | 7.20 | V | 1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.000 | 59.06 | 74.00 | 14.94 | 7.08 | V | 144 | 1 |
| 1 | 2,390.000 | 61.32 | 74.00 | 12.68 | 7.08 | V | 144 | 1 |
| 1 | 2,413.500 | 111.87 | | | 7.19 | V | 359.1 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2412MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.68 | 74.00 | 23.32 | 40.06 | 54.00 | 13.94 | 15.25 | H | 1 | 2 |
| 2 | 7,311.000 | 56.76 | 74.00 | 17.24 | 45.85 | 54.00 | 8.15 | 21.10 | H | 34.3 | 2 |






**BUREAU
VERITAS**

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.04 | 74.00 | 23.96 | 39.92 | 54.00 | 14.08 | 15.25 | V | 339.4 | 1 |
| 2 | 7,311.000 | 58.39 | 74.00 | 15.61 | 45.85 | 54.00 | 8.15 | 21.10 | V | 1 | 2 |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2437MHz: Fundamental frequency.



| | | | |
|-----------------|---------------|-------------------|--------------|
| CHANNEL | TX Channel 11 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,460.000 | 87.54 | | | 7.40 | H | 355 | 2 |
| 2 | 2,483.500 | 37.67 | 54.00 | 16.33 | 7.36 | H | 355 | 2 |
| 2 | 2,484.000 | 37.09 | 54.00 | 16.91 | 7.36 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,460.000 | 108.12 | | | 7.40 | H | 291.3 | 2 |
| 2 | 2,483.500 | 51.27 | 74.00 | 22.73 | 7.36 | H | 219.6 | 2 |
| 2 | 2,484.000 | 52.33 | 74.00 | 21.67 | 7.36 | H | 219.6 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.000 | 100.56 | | | 7.39 | V | 1 | 2 |
| 2 | 2,483.500 | 44.43 | 54.00 | 9.57 | 7.36 | V | 1 | 2 |
| 2 | 2,484.000 | 43.96 | 54.00 | 10.04 | 7.36 | V | 1 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.000 | 112.93 | | | 7.39 | V | 10.7 | 2 |
| 2 | 2,483.500 | 62.57 | 74.00 | 11.43 | 7.36 | V | 359.1 | 1 |
| 2 | 2,484.500 | 60.15 | 74.00 | 13.85 | 7.36 | V | 10.7 | 2 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2462MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

802.11n (40MHz)

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 3 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,389.000 | 36.12 | 54.00 | 17.88 | 7.08 | H | 359 | 2 |
| 3 | 2,390.000 | 36.46 | 54.00 | 17.54 | 7.08 | H | 359 | 2 |
| 3 | 2,419.500 | 82.22 | | | 7.25 | H | 1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,389.000 | 56.97 | 74.00 | 17.03 | 7.08 | H | 216.9 | 1 |
| 3 | 2,390.000 | 57.44 | 74.00 | 16.56 | 7.08 | H | 216.9 | 1 |
| 3 | 2,417.000 | 104.25 | | | 7.22 | H | 216.9 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,389.000 | 44.72 | 54.00 | 9.28 | 7.08 | V | 5.6 | 1 |
| 3 | 2,390.000 | 46.82 | 54.00 | 7.18 | 7.08 | V | 5.6 | 1 |
| 3 | 2,424.000 | 96.17 | | | 7.29 | V | 1 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,388.000 | 59.98 | 74.00 | 14.02 | 7.08 | V | 141.5 | 1 |
| 3 | 2,390.000 | 61.29 | 74.00 | 12.71 | 7.08 | V | 350.6 | 1 |
| 3 | 2,432.500 | 108.50 | | | 7.34 | V | 359.1 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2422MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 51.00 | 74.00 | 23.00 | 39.88 | 54.00 | 14.12 | 15.25 | H | 248.3 | 2 |
| 2 | 7,311.000 | 56.77 | 74.00 | 17.23 | 45.87 | 54.00 | 8.13 | 21.10 | H | 1 | 2 |






BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 51.20 | 74.00 | 22.80 | 39.83 | 54.00 | 14.17 | 15.25 | V | 359 | 2 |
| 2 | 7,311.000 | 56.62 | 74.00 | 17.38 | 45.81 | 54.00 | 8.19 | 21.10 | V | 0.9 | 2 |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2437MHz: Fundamental frequency.



| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 9 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,461.000 | 92.20 | | | 7.40 | H | 5 | 1 |
| 4 | 2,483.500 | 37.13 | 54.00 | 16.87 | 7.36 | H | 355 | 2 |
| 4 | 2,485.000 | 38.35 | 54.00 | 15.65 | 7.36 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,448.000 | 104.16 | | | 7.44 | H | 291.3 | 2 |
| 4 | 2,483.500 | 60.54 | 74.00 | 13.46 | 7.36 | H | 144.3 | 2 |
| 4 | 2,486.000 | 58.76 | 74.00 | 15.24 | 7.36 | H | 214.6 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,442.000 | 96.52 | | | 7.40 | V | 359.1 | 1 |
| 4 | 2,483.500 | 46.55 | 54.00 | 7.45 | 7.36 | V | 1 | 2 |
| 4 | 2,484.500 | 45.36 | 54.00 | 8.64 | 7.36 | V | 1 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,462.000 | 107.80 | | | 7.39 | V | 359 | 2 |
| 4 | 2,483.500 | 61.89 | 74.00 | 12.11 | 7.36 | V | 359 | 2 |
| 4 | 2,484.500 | 59.19 | 74.00 | 14.81 | 7.36 | V | 8.2 | 2 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2452MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

802.11ax (20MHz)

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.000 | 33.13 | 54.00 | 20.87 | 7.08 | H | 359 | 2 |
| 1 | 2,390.000 | 34.51 | 54.00 | 19.49 | 7.08 | H | 359 | 2 |
| 1 | 2,420.000 | 82.38 | | | 7.25 | H | 359 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.500 | 54.99 | 74.00 | 19.01 | 7.08 | H | 355.6 | 2 |
| 1 | 2,390.000 | 54.43 | 74.00 | 19.57 | 7.08 | H | 355.6 | 2 |
| 1 | 2,409.500 | 106.98 | | | 7.15 | H | 197.8 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.000 | 39.26 | 54.00 | 14.74 | 7.08 | V | 359.1 | 1 |
| 1 | 2,390.000 | 43.62 | 54.00 | 10.38 | 7.08 | V | 359.1 | 1 |
| 1 | 2,413.500 | 96.68 | | | 7.19 | V | 359.1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.500 | 57.81 | 74.00 | 16.19 | 7.08 | V | 218.5 | 2 |
| 1 | 2,390.000 | 59.23 | 74.00 | 14.77 | 7.08 | V | 1 | 1 |
| 1 | 2,413.500 | 111.05 | | | 7.19 | V | 359.1 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2412MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 52.19 | 74.00 | 21.81 | 40.04 | 54.00 | 13.96 | 15.25 | H | 88.9 | 1 |
| 2 | 7,311.000 | 56.23 | 74.00 | 17.77 | 45.70 | 54.00 | 8.30 | 21.10 | H | 323.2 | 1 |






BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.57 | 74.00 | 23.43 | 39.90 | 54.00 | 14.10 | 15.25 | V | 271.1 | 2 |
| 2 | 7,311.000 | 56.01 | 74.00 | 17.99 | 45.77 | 54.00 | 8.23 | 21.10 | V | 36.7 | 2 |



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2437MHz: Fundamental frequency.



| | | | |
|-----------------|---------------|-------------------|--------------|
| CHANNEL | TX Channel 11 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,460.000 | 93.11 | | | 7.40 | H | 101.2 | 2 |
| 2 | 2,483.500 | 36.93 | 54.00 | 17.07 | 7.36 | H | 355.6 | 2 |
| 2 | 2,485.000 | 36.14 | 54.00 | 17.86 | 7.36 | H | 355.6 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,457.500 | 107.30 | | | 7.41 | H | 270.7 | 1 |
| 2 | 2,483.500 | 50.73 | 74.00 | 23.27 | 7.36 | H | 218.5 | 2 |
| 2 | 2,486.500 | 50.19 | 74.00 | 23.81 | 7.36 | H | 218.5 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.500 | 97.74 | | | 7.39 | V | 359 | 2 |
| 2 | 2,483.500 | 44.37 | 54.00 | 9.63 | 7.36 | V | 359 | 2 |
| 2 | 2,484.500 | 43.20 | 54.00 | 10.80 | 7.36 | V | 359 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,463.000 | 112.39 | | | 7.39 | V | 359 | 2 |
| 2 | 2,483.500 | 63.01 | 74.00 | 10.99 | 7.36 | V | 5.7 | 1 |
| 2 | 2,484.000 | 62.63 | 74.00 | 11.37 | 7.36 | V | 359 | 2 |

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
2. 2462MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

802.11ax (40MHz)

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 3 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,388.000 | 34.59 | 54.00 | 19.41 | 7.08 | H | 359 | 2 |
| 3 | 2,390.000 | 35.33 | 54.00 | 18.67 | 7.08 | H | 359 | 2 |
| 3 | 2,420.000 | 80.66 | | | 7.25 | H | 359.1 | 1 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,389.000 | 53.53 | 74.00 | 20.47 | 7.08 | H | 215.7 | 1 |
| 3 | 2,390.000 | 55.22 | 74.00 | 18.78 | 7.08 | H | 215.7 | 1 |
| 3 | 2,408.000 | 104.45 | | | 7.14 | H | 215.7 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,388.500 | 40.23 | 54.00 | 13.77 | 7.08 | V | 359 | 1 |
| 3 | 2,390.000 | 43.41 | 54.00 | 10.59 | 7.08 | V | 5 | 1 |
| 3 | 2,423.500 | 94.57 | | | 7.28 | V | 0.9 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 3 | 2,388.500 | 55.64 | 74.00 | 18.36 | 7.08 | V | 357.3 | 1 |
| 3 | 2,390.000 | 56.93 | 74.00 | 17.07 | 7.08 | V | 359 | 1 |
| 3 | 2,432.000 | 109.34 | | | 7.34 | V | 359 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2422MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: W7L-P23070010RF10

Worst case harmonic:

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 52.39 | 74.00 | 21.61 | 39.89 | 54.00 | 14.11 | 15.25 | H | 34.3 | 2 |
| 2 | 7,311.000 | 57.01 | 74.00 | 16.99 | 46.18 | 54.00 | 7.82 | 21.10 | H | 0.9 | 2 |






BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 52.08 | 74.00 | 21.92 | 39.96 | 54.00 | 14.04 | 15.25 | V | 269.8 | 2 |
| 2 | 7,311.000 | 57.32 | 74.00 | 16.68 | 45.73 | 54.00 | 8.27 | 21.10 | V | 359 | 2 |



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2437MHz: Fundamental frequency.



| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 9 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,461.000 | 90.48 | | | 7.40 | H | 5 | 1 |
| 4 | 2,483.500 | 34.98 | 54.00 | 19.02 | 7.36 | H | 359.1 | 1 |
| 4 | 2,486.500 | 36.51 | 54.00 | 17.49 | 7.36 | H | 355 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,449.000 | 105.33 | | | 7.44 | H | 290.2 | 2 |
| 4 | 2,483.500 | 57.74 | 74.00 | 16.26 | 7.36 | H | 143 | 2 |
| 4 | 2,486.500 | 56.49 | 74.00 | 17.51 | 7.36 | H | 218.1 | 1 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,442.000 | 94.80 | | | 7.40 | V | 359.1 | 1 |
| 4 | 2,483.500 | 44.85 | 54.00 | 9.15 | 7.36 | V | 0.9 | 2 |
| 4 | 2,484.000 | 44.89 | 54.00 | 9.11 | 7.36 | V | 0.9 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 4 | 2,462.500 | 109.33 | | | 7.39 | V | 7 | 2 |
| 4 | 2,483.500 | 63.67 | 74.00 | 10.33 | 7.36 | V | 1 | 1 |
| 4 | 2,484.500 | 63.74 | 74.00 | 10.26 | 7.36 | V | 0.9 | 2 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2452MHz: Fundamental frequency.

BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

2.4G WIFI-RU**802.11ax (20MHz) (RU26):**

| | | | |
|------------------------|--------------|--------------------------|--------------|
| CHANNEL | TX Channel 1 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.325 | 34.35 | 54.00 | 19.65 | 9.30 | H | 359 | 2 |
| 1 | 2,390.000 | 34.47 | 54.00 | 19.53 | 9.30 | H | 359 | 2 |
| 1 | 2,403.575 | 98.21 | | | 9.37 | H | 359 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.800 | 55.69 | 74.00 | 18.31 | 9.30 | H | 140.6 | 1 |
| 1 | 2,390.000 | 56.98 | 74.00 | 17.02 | 9.30 | H | 140.6 | 1 |
| 1 | 2,403.580 | 110.44 | | | 9.37 | H | 18.7 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,389.800 | 34.99 | 54.00 | 19.01 | 9.30 | V | 359 | 2 |
| 1 | 2,390.000 | 35.16 | 54.00 | 18.84 | 9.30 | V | 359 | 2 |
| 1 | 2,403.575 | 99.28 | | | 9.37 | V | 359 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 1 | 2,388.850 | 54.83 | 74.00 | 19.17 | 9.29 | V | 43.8 | 1 |
| 1 | 2,390.000 | 57.83 | 74.00 | 16.17 | 9.30 | V | 43.8 | 1 |
| 1 | 2,404.050 | 111.42 | | | 9.37 | V | 359 | 2 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2412MHz: Fundamental frequency.



BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10


Worst case harmonic:

802.11ax (20MHz) (RU26):

| | | | |
|-----------------|--------------|-------------------|--------------|
| CHANNEL | TX Channel 6 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.69 | 74.00 | 23.31 | 40.16 | 54.00 | 13.84 | 15.25 | H | 1 | 1 |
| 2 | 7,311.000 | 57.27 | 74.00 | 16.73 | 45.90 | 54.00 | 8.10 | 21.10 | H | 359 | 2 |






BUREAU
VERITAS

Test Report No.: W7L-P23070010RF10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 4,874.000 | 50.09 | 74.00 | 23.91 | 39.78 | 54.00 | 14.22 | 15.25 | V | 359.1 | 1 |
| 2 | 7,311.000 | 56.92 | 74.00 | 17.08 | 46.01 | 54.00 | 7.99 | 21.10 | V | 269.8 | 2 |



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2437MHz: Fundamental frequency.



| | | | |
|-----------------|---------------|-------------------|--------------|
| CHANNEL | TX Channel 11 | DETECTOR FUNCTION | Peak (PK) |
| FREQUENCY RANGE | 1GHz ~ 25GHz | | Average (AV) |

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,470.360 | 96.96 | | | 9.30 | H | 355 | 2 |
| 2 | 2,483.500 | 33.64 | 54.00 | 20.36 | 9.31 | H | 68.9 | 2 |
| 2 | 2,484.160 | 33.61 | 54.00 | 20.39 | 9.31 | H | 68.9 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,470.360 | 110.46 | | | 9.30 | H | 355 | 2 |
| 2 | 2,483.500 | 63.93 | 74.00 | 10.07 | 9.31 | H | 23.7 | 2 |
| 2 | 2,483.920 | 63.41 | 74.00 | 10.59 | 9.31 | H | 2.2 | 2 |

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| Rg | Frequency [MHz] | AVG Level [dBμV/m] | AVG Limit [dBμV/m] | AVG Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,470.480 | 99.34 | | | 9.30 | V | 1 | 2 |
| 2 | 2,483.500 | 34.65 | 54.00 | 19.35 | 9.31 | V | 1.8 | 2 |
| 2 | 2,483.800 | 34.63 | 54.00 | 19.37 | 9.31 | V | 17 | 2 |

| Rg | Frequency [MHz] | PK+ Level [dBμV/m] | PK+ Limit [dBμV/m] | PK+ Margin [dB] | Correction [dB] | Polarization | Azimuth [deg] | Antenna Height [m] |
|----|-----------------|--------------------|--------------------|-----------------|-----------------|--------------|---------------|--------------------|
| 2 | 2,470.480 | 112.90 | | | 9.30 | V | 23.6 | 2 |
| 2 | 2,483.500 | 60.03 | 74.00 | 13.97 | 9.31 | V | 1 | 1 |
| 2 | 2,484.760 | 59.54 | 74.00 | 14.46 | 9.31 | V | 291.2 | 1 |

REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission Level.
- 2462MHz: Fundamental frequency.



Test Report No.: W7L-P23070010RF10

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: W7L-P23070010RF10

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---