

FCC SAR

Measurement and Test Report

For

Hyundai Corporation

25, Yulgok-ro 2-Gil, Jongno-gu, Seoul, South Korea

FCC ID: RQQHLT-FSL500B

Test Standards:	FCC Part 2.1093 ANSI / IEEE C95.1 :2005 ANSI / IEEE C95.3 :2002 <u>IEEE 1528 :2013</u>
Product Description:	<u>4G Smart Phone</u>
Tested Model:	<u>L500C</u>
Report No.:	<u>STR16108015H</u>
Tested Date:	<u>2016-10-17 to 2016-10-21</u>
Issued Date:	<u>2016-10-22</u>
Tested By:	<u>Lucy Wei / Engineer</u> <i>Lucy Wei</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u> <i>Silin Chen</i>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u> <i>Jandy So</i>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. General Information	3
1.1 Product Description for Equipment Under Test (EUT).....	3
1.2 Test Standards	6
1.3 Test Methodology	6
1.4 Test Facility	6
2. Summary of Test Results	7
3. Specific Absorption Rate (SAR).....	8
3.1 Introduction.....	8
3.2 SAR Definition	8
4. SAR Measurement System.....	9
4.1 The Measurement System	9
4.2 Probe	9
4.3 Probe Calibration Process.....	11
4.4 Phantom	12
4.5 Device Holder	12
4.6 Test Equipment List.....	13
5. Tissue Simulating Liquids.....	14
5.1 Composition of Tissue Simulating Liquid.....	14
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	15
5.3 Tissue Calibration Result.....	16
6. SAR Measurement Evaluation	17
6.1 Purpose of System Performance Check.....	17
6.2 System Setup	17
6.3 Validation Results.....	18
7. EUT Testing Position	19
7.1 Define Two Imaginary Lines on The Handset.....	19
7.2 Cheek Position	20
7.3 Tilted Position.....	20
7.4 Body Worn Position	21
7.5 EUT Antenna Position	21
7.6 EUT Testing Position.....	22
8. SAR Measurement Procedures	23
8.1 Measurement Procedures	23
8.2 Spatial Peak SAR Evaluation	23
8.3 Area & Zoom Scan Procedures	24
8.4 Volume Scan Procedures.....	24
8.5 SAR Averaged Methods	24
8.6 Power Drift Monitoring	24
9. SAR Test Result	25
9.1 Conducted RF Output Power	25
9.2 Test Results for Standalone SAR Test.....	41
9.3 Simultaneous Multi-band Transmission SAR Analysis	48
10. Measurement Uncertainty	54
10.1 Uncertainty for EUT SAR Test.....	54
10.2 Uncertainty for System Performance Check.....	55
Annex A. Plots of System Performance Check	57
Annex B. Plots of SAR Measurement	69
Annex C. EUT Photos	106
Annex D. Test Setup Photos	108
Annex E. Calibration Certificate.....	113

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Hyundai Corporation
Address of applicant: 25, Yulgok-ro 2-Gil, Jongno-gu, Seoul, South Korea

Manufacturer: Shenzhen Fortuneship Technology Co., Ltd.
Address of manufacturer: Room 701-716, 7th Floor, Kanghesheng Building, No.1
ChuangSheng Road, Nanshan District, Shenzhen,
Guangdong, P. R. China

General Description of EUT:	
Product Name:	4G Smart Phone
Brand Name:	/
Model No.:	L500C
Adding Model(s):	/
Hardware Version:	WW816 V0.6
Software Version:	Android 6.0
Rated Voltage:	DC 3.7V
Battery Capacity:	2200mAh
Device Category:	Portable Device
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.14dBm, GSM1900: 29.93dBm EDGE850: 26.53dBm, EDGE1900: 25.10dBm
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -2.0dBi; GSM1900: -1.6dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.93dBm, WCDMA Band 5: 22.94dBm,
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: -1.6dBi, WCDMA Band 5: -2.0dBi,
4G	
Support Networks:	FDD-LTE
Support Band:	FDD-LTE Band 2, 7
Uplink Frequency:	FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 7: Tx: 2500-2570MHz
Downlink Frequency:	FDD-LTE Band 2: Rx: 1930-1990MHz, FDD-LTE Band 7: Rx: 2620-2690MHz,
RF Output Power:	FDD-LTE Band 2: 24.02dBm, FDD-LTE Band 7: 24.07dBm,
Type of Modulation:	QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	FDD-LTE Band 2: -1.6dBi, FDD-LTE Band 7: -1.0dBi,
WIFI	
Support Standards:	802.11b, 802.11g, 802.11n

Frequency Range:	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
RF Output Power:	12.17dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11/7
Channel Separation:	5MHz
Antenna Type:	Integral Antenna
Antenna Gain:	-1.0dBi
Bluetooth	
Bluetooth Version:	V4.0
Frequency Range:	2402-2480MHz
RF Output Power:	0.894dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Antenna Type:	Integral Antenna
Antenna Gain:	-1.0dBi

1.2 Test Standards

The following report is prepared on behalf of the Hyundai Corporation in accordance with FCC 47 CFR Part 2.1093, ANSI/IEEE C95.1-2005, ANSI / IEEE C95.3 :2002, IEEE 1528-2013, KDB 447498 D01 v06, KDB 648474 D04 v01r03, KDB 248227 D01 v02r02, KDB 941225 D01 v03r01, KDB 941225 D05 v02r05 ,KDB 941225 D06 v02r01, and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Head SAR	Body-worn (10mm Gap)	Hotspot (10mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	
GSM	0.292	0.756	0.736	1.6
WCDMA	0.484	0.593	0.834	1.6
FDD-LTE	0.512	0.773	0.773	1.6
WLAN 2.4G	0.523	0.114	0.114	1.6
Simultaneous Transmission	1.035	0.870	0.855	1.6

Remark:

*The highest reported SAR values for head, body-worn accessory, wireless router(hotspot), and simultaneous transmission conditions are **0.523W/kg, 0.773W/kg, 0.834W/kg, and 1.035W/kg** respectively.*

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedure specified in IEEE 1528-2013 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.


4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE5 SN 09/13 EP168 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Probe Length: 330 mm
- Length of Individual Dipoles: 4.5 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter : 5 mm
- Distance between dipoles / probe extremity: 2.7mm

- Probe linearity: <0.25 dB
 - Axial Isotropy: <0.25 dB
 - Spherical Isotropy: <0.50 dB
 - Calibration range: 700 to 3000MHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annex technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

l = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	SATIMO	SSE5	SN 09/13 EP168	2016-06-01	2017-05-31
835MHz Dipole	SATIMO	SID835	SN 47/12 DIP 0G835-204	2016-03-20	2017-03-19
1900MHz Dipole	SATIMO	SID1900	SN 47/12 DIP 1G900-207	2016-03-20	2017-03-19
2450MHz Dipole	SATIMO	SID2450	SN 13/15 DIP 2G450-364	2016-03-20	2017-03-19
Dielectric Probe Kit	SATIMO	SCLMP	SN 47/12 OCPG49	2016-03-20	2017-03-19
SAM Phantom	SATIMO	SAM	SN/ 47/12 SAM95	N/A	N/A
MULTIMETER	KEITHLEY	Keithley 2000	4006367	2016-06-04	2017-06-03
Signal Generator	Rohde & Schwarz	SMR20	100047	2016-06-04	2017-06-03
Universal Tester	Rohde & Schwarz	CMU200	112012	2016-06-04	2017-06-03
Network Analyzer	HP	8753C	2901A00831	2016-06-04	2017-06-03
Directional Couplers	Agilent	778D	20160	2016-06-04	2017-06-03


5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head SAR



Liquid Height for Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Triton (%)	HEC (%)	Preventol (%)	DGBE (%)
Head						
835	35.34	0.98	0.00	0.00	63.68	0.00
1800	55.19	0.66	30.35	0.00	0.00	13.80
2450	55.44	0.32	30.50	0.00	0.00	13.74
Body						
835	52.87	1.07	0.00	0.00	46.10	0.00
1800	70.81	0.52	20.01	0.00	0.00	8.65
2450	55.44	0.32	30.50	0.00	0.00	13.74

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Head		Body	
	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3	0.80	61.9
300	0.87	45.3	0.92	58.2
450	0.87	43.5	0.94	56.7
750	0.89	41.9	0.96	55.5
835	0.90	41.5	0.97	55.2
900	0.97	41.5	1.05	55.0
915	0.98	41.5	1.06	55.0
1450	1.20	40.5	1.30	54.0
1610	1.29	40.3	1.40	53.8
1800-2000	1.40	40.0	1.52	53.3
2450	1.80	39.2	1.95	52.7
3000	2.40	38.5	2.73	52.0
5800	5.27	35.3	6.00	48.2

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Head Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
835	21.2	0.87	0.90	-3.33	41.11	41.50	-0.94	± 5	2016-10-17
1900	21.3	1.38	1.40	-1.43	38.56	40.00	-3.60	± 5	2016-10-17
2450	21.3	1.74	1.80	-3.33	38.15	39.20	-2.68	± 5	2016-10-17

Body Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
835	21.2	0.95	0.97	-2.06	54.85	55.20	-0.63	± 5	2016-10-17
1900	21.3	1.50	1.52	-1.32	52.42	53.30	-1.65	± 5	2016-10-17
2450	21.3	1.91	1.95	-2.05	52.01	52.70	-1.31	± 5	2016-10-17


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835 MHz and 1900 MHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance
MHz	(W/kg)	(W/kg)	(W/kg)	(%)
Head				
835	9.67	2.41	9.64	-0.31
1900	39.58	9.91	39.64	0.15
2450	53.69	13.45	53.8	0.20
Body				
835	9.38	2.35	9.4	0.21
1900	39.10	9.78	39.12	0.05
2450	50.41	12.59	50.36	-0.10

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Define Two Imaginary Lines on The Handset

- (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Illustration for Handset Vertical and Horizontal Reference Lines

7.2 Cheek Position

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 7.2).




Illustration for Cheek Position

7.3 Tilted Position

(a) To position the device in the “cheek” position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 7.3).




Illustration for Tilted Position

7.4 Body Worn Position

- To position the device parallel to the phantom surface with either keypad up or down.
- To adjust the device parallel to the flat phantom.
- To adjust the distance between the device surface and the flat phantom to 10mm.





Illustration for Body Worn Position

7.5 EUT Antenna Position



Block Diagram for EUT Antenna Position

7.6 EUT Testing Position

Head/Body-worn/Hotspot mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Head SAR tests				
Antennas	Right Cheek	Left Cheek	Right Tilted	Left Tilted
WWAN	Yes	Yes	Yes	Yes
WLAN	Yes	Yes	Yes	Yes

Hotspot SAR tests, Test distance: 10mm						
Antennas	Front	Back	Right Side	Left Side	Top Side	Bottom Side
WWAN	Yes	Yes	No	Yes	No	Yes
WLAN	Yes	Yes	Yes	No	Yes	No

Body-worn SAR tests		
Antennas	Front	Back
WWAN	Yes	Yes
WLAN	Yes	Yes

Remark:

1. Referring to KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test separation distances is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex E demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

GSM - Burst Average Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
GSM	32.09	32.08	31.93	29.86	29.27	28.58
GPRS (1 slot)	32.14	32.12	32.05	29.93	29.39	28.73
GPRS (2 slots)	31.58	31.6	31.5	29.1	28.74	28.24
GPRS (3 slots)	29.95	30.01	29.9	26.96	26.9	26.76
GPRS (4 slots)	28.87	28.99	28.86	25.67	25.69	25.71
EDGE (1 slot)	26.53	26.13	25.72	24.67	25.1	25.08
EDGE (2 slots)	25.53	25.07	24.6	23.52	24	24.17
EDGE (3 slots)	23.44	22.93	22.41	21.44	21.92	22.18
EDGE (4 slots)	22.21	21.74	21.18	20.22	20.71	20.87

GSM - Source-Based Time-Average Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
GSM	23.09	23.08	22.93	20.86	20.27	19.58
GPRS (1 slot)	23.14	23.12	23.05	20.93	20.39	19.73
GPRS (2 slots)	25.58	25.60	25.50	23.10	22.74	22.24
GPRS (3 slots)	25.70	25.76	25.65	22.71	22.65	22.51
GPRS (4 slots)	25.87	25.99	25.86	22.67	22.69	22.71
EDGE (1 slot)	17.53	17.13	16.72	15.67	16.10	16.08
EDGE (2 slots)	19.53	19.07	18.60	17.52	18.00	18.17
EDGE (3 slots)	19.19	18.68	18.16	17.19	17.67	17.93
EDGE (4 slots)	19.21	18.74	18.18	17.22	17.71	17.87

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Duty cycle factor = 9 dB for 1 Tx slot, 6 dB for 2 Tx slots, 4.25 dB for 3 Tx slots, 3 dB for 4 Tx slots

Remark:

1. For Head SAR testing, GSM should be evaluated, therefore the EUT was set in GSM for GSM850 and GSM1900 due to its highest source-based time-average power.
2. For Body SAR testing, GPRS should be evaluated, therefore the EUT was set in GPRS (4TX slots) for GSM850 and GPRS (2TX slots) for GSM1900 due to its highest source-based time-average power.
3. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
4. The DUT do not support DTM function.

WCDMA - Average Power (dBm)						
Band	WCDMA Band II			WCDMA Band V		
Channel	9262	9400	9538	4132	4182	4233
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.6	846.6
RMC 12.2k	22.69	22.8	22.93	22.94	22.87	22.92
HSDPA Subtest-1	21.66	21.76	21.81	21.84	21.63	21.7
HSDPA Subtest-2	21.56	21.67	21.72	21.73	21.57	21.72
HSDPA Subtest-3	21.43	21.59	21.71	21.61	21.47	21.67
HSDPA Subtest-4	21.38	21.55	21.64	21.66	21.39	21.58
HSUPA Subtest-1	21.54	21.64	21.78	21.75	21.71	21.61
HSUPA Subtest-2	21.53	21.63	21.69	21.74	21.68	21.54
HSUPA Subtest-3	21.47	21.57	21.51	21.68	21.54	21.49
HSUPA Subtest-4	21.35	21.49	21.53	21.65	21.41	21.48
HSUPA Subtest-5	21.34	21.41	21.44	21.52	21.37	21.31

Remark:

1. For Head SAR, per KDB 941225 D01 v03, RMC 12.2kbps setting is used to evaluate SAR. If AMR 12.2kbps power is < 1/4 dB higher than RMC, SAR tests with AMR 12.2kbps can be excluded.
2. For Body SAR, per KDB 941225 D01 v03, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA subset-1 output power is < 1/4 dB higher than RMC, and SAR with RMC 12.2kbps setting is $\leq 1.2\text{W/kg}$, HSDPA SAR evaluation can be excluded

FDD-LTE Band 2:

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.99	
		1	3	24.01	
		1	5	23.99	
		3	0	23.91	
		3	2	23.94	
		3	3	23.91	
		6	0	23.15	
	MCH	1	0	23.31	
		1	3	23.36	
		1	5	23.31	
		3	0	23.26	
		3	2	23.24	
		3	3	23.26	
		6	0	22.44	
	HCH	1	0	23.12	
		1	3	22.88	
		1	5	22.84	
		3	0	23.04	
		3	2	22.91	
		3	3	22.85	
		6	0	22.26	
16QAM	LCH	1	0	22.99	
		1	3	23.08	
		1	5	23.00	
		3	0	22.94	
		3	2	22.91	
		3	3	22.91	
		6	0	21.99	
	MCH	1	0	22.46	
		1	3	22.56	
		1	5	22.45	
		3	0	22.14	
		3	2	22.15	
		3	3	22.16	
		6	0	21.27	
	HCH	1	0	22.33	
		1	3	22.27	

		1	5	22.21	
		3	0	22.18	
		3	2	22.08	
		3	3	22.05	
		6	0	21.42	

Channel Bandwidth: 3 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.55	
		1	7	23.83	
		1	14	23.82	
		8	0	23.22	
		8	4	23.18	
		8	7	23.17	
		15	0	23.09	
	MCH	1	0	23.30	
		1	7	23.35	
		1	14	23.28	
		8	0	22.46	
		8	4	22.44	
		8	7	22.42	
		15	0	22.38	
	HCH	1	0	23.32	
		1	7	22.88	
		1	14	22.58	
		8	0	22.45	
		8	4	22.27	
		8	7	22.13	
		15	0	22.31	
16QAM	LCH	1	0	23.14	
		1	7	23.18	
		1	14	23.07	
		8	0	22.14	
		8	4	22.13	
		8	7	22.09	
		15	0	21.96	
	MCH	1	0	22.41	
		1	7	22.47	
		1	14	22.37	
		8	0	21.40	
		8	4	21.40	
		8	7	21.35	

	HCH	15	0	21.30	
		1	0	22.38	
		1	7	22.33	
		1	14	22.05	
		8	0	21.29	
		8	4	21.29	
		8	7	21.28	
		15	0	21.24	

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.86	
		1	12	23.43	
		1	24	23.68	
		12	0	22.87	
		12	6	22.72	
		12	13	22.77	
		25	0	22.79	
	MCH	1	0	23.48	
		1	12	23.43	
		1	24	23.34	
		12	0	22.44	
		12	6	22.42	
		12	13	22.39	
		25	0	22.34	
	HCH	1	0	23.42	
		1	12	22.89	
		1	24	22.66	
		12	0	22.30	
		12	6	22.19	
		12	13	21.96	
		25	0	22.27	
16QAM	LCH	1	0	23.23	
		1	12	22.82	
		1	24	23.08	
		12	0	22.02	
		12	6	21.89	
		12	13	21.94	
		25	0	21.86	
	MCH	1	0	22.61	
		1	12	22.61	
		1	24	22.45	

		12	0	21.48	
		12	6	21.47	
		12	13	21.44	
		25	0	21.32	
	HCH	1	0	22.17	
		1	12	21.96	
		1	24	21.71	
		12	0	21.28	
		12	6	21.29	
		12	13	21.12	
		25	0	21.26	

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.39	
		1	24	23.18	
		1	49	23.11	
		25	0	22.63	
		25	12	22.45	
		25	25	22.44	
		50	0	22.55	
	MCH	1	0	23.50	
		1	24	23.32	
		1	49	22.56	
		25	0	22.40	
		25	12	22.36	
		25	25	22.30	
		50	0	22.35	
	HCH	1	0	23.17	
		1	24	23.29	
		1	49	22.02	
		25	0	22.17	
		25	12	22.23	
		25	25	22.21	
		50	0	22.20	
16QAM	LCH	1	0	22.72	
		1	24	22.50	
		1	49	22.45	
		25	0	21.65	
		25	12	21.51	
		25	25	21.50	
		50	0	21.59	

	MCH	1	0	22.63	
		1	24	22.47	
		1	49	22.03	
		25	0	21.40	
		25	12	21.32	
		25	25	21.25	
		50	0	21.32	
	HCH	1	0	22.41	
		1	24	22.43	
		1	49	21.53	
		25	0	21.19	
		25	12	21.22	
		25	25	21.27	
		50	0	21.24	

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.48	
		1	37	23.18	
		1	74	23.55	
		37	0	22.49	
		37	18	22.40	
		37	38	22.59	
		75	0	22.50	
	MCH	1	0	23.59	
		1	37	23.24	
		1	74	22.52	
		37	0	22.66	
		37	18	22.58	
		37	38	22.35	
		75	0	22.60	
	HCH	1	0	23.22	
		1	37	23.34	
		1	74	22.21	
		37	0	22.30	
		37	18	22.33	
		37	38	22.37	
		75	0	22.40	
16QAM	LCH	1	0	22.82	
		1	37	22.49	
		1	74	22.89	
		37	0	21.54	

		37	18	21.45	
		37	38	21.59	
		75	0	21.56	
	MCH	1	0	22.74	
		1	37	22.55	
		1	74	21.95	
		37	0	21.55	
		37	18	21.45	
		37	38	21.38	
		75	0	21.50	
	HCH	1	0	22.34	
		1	37	22.45	
		1	74	21.59	
		37	0	21.28	
		37	18	21.28	
		37	38	21.38	
		75	0	21.32	

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	24.02	
		1	49	23.33	
		1	99	23.83	
		50	0	22.45	
		50	25	22.47	
		50	50	22.76	
		100	0	22.62	
	MCH	1	0	23.82	
		1	49	23.31	
		1	99	22.63	
		50	0	22.54	
		50	25	22.37	
		50	50	22.19	
		100	0	22.41	
	HCH	1	0	22.88	
		1	49	23.27	
		1	99	22.26	
		50	0	22.16	
		50	25	22.20	
		50	50	22.28	
		100	0	22.21	
16QAM	LCH	1	0	22.83	

		1	49	22.53	
		1	99	22.94	
		50	0	21.46	
		50	25	21.46	
		50	50	21.78	
		100	0	21.62	
	MCH	1	0	22.90	
		1	49	22.54	
		1	99	21.96	
		50	0	21.50	
		50	25	21.32	
		50	50	21.24	
		100	0	21.39	
	HCH	1	0	22.24	
		1	49	22.45	
		1	99	21.71	
		50	0	21.20	
		50	25	21.24	
		50	50	21.31	
		100	0	21.20	

FDD-LTE Band 7:

Channel Bandwidth: 5 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	22.27	
		1	12	21.82	
		1	24	21.73	
		12	0	20.97	
		12	6	20.77	
		12	13	20.67	
		25	0	20.78	
	MCH	1	0	21.91	
		1	12	22.08	
		1	24	22.55	
		12	0	20.98	
		12	6	21.07	
		12	13	21.22	
		25	0	21.10	
	HCH	1	0	22.83	
		1	12	23.69	
		1	24	23.80	
		12	0	22.07	
		12	6	22.51	
		12	13	22.94	
		25	0	22.52	
16QAM	LCH	1	0	21.39	
		1	12	20.91	
		1	24	20.80	
		12	0	20.01	
		12	6	19.79	
		12	13	19.71	
		25	0	19.84	
	MCH	1	0	21.00	
		1	12	21.19	
		1	24	21.53	
		12	0	20.06	
		12	6	20.16	
		12	13	20.29	
		25	0	20.19	
	HCH	1	0	21.87	
		1	12	22.71	

		1	24	23.43	
		12	0	21.06	
		12	6	21.52	
		12	13	21.91	
		25	0	21.46	

Channel Bandwidth: 10 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	21.98	
		1	24	21.78	
		1	49	21.63	
		25	0	20.93	
		25	12	20.78	
		25	25	20.70	
		50	0	20.82	
	MCH	1	0	21.75	
		1	24	21.91	
		1	49	22.07	
		25	0	20.90	
		25	12	20.94	
		25	25	21.02	
		50	0	20.98	
	HCH	1	0	23.57	
		1	24	24.05	
		1	49	23.39	
		25	0	22.74	
		25	12	22.93	
		25	25	23.09	
		50	0	22.86	
16QAM	LCH	1	0	21.16	
		1	24	21.00	
		1	49	20.81	
		25	0	19.70	
		25	12	20.90	
		25	25	20.55	
		50	0	21.57	
	MCH	1	0	20.97	
		1	24	21.09	
		1	49	21.25	
		25	0	20.00	
		25	12	20.05	
		25	25	20.12	

	HCH	50	0	20.09	
		1	0	22.65	
		1	24	23.06	
		1	49	23.25	
		25	0	21.65	
		25	12	21.84	
		25	25	21.96	
		50	0	21.83	

Channel Bandwidth: 15 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	22.16	
		1	37	21.84	
		1	74	21.61	
		37	0	21.06	
		37	18	20.88	
		37	38	20.82	
		75	0	20.96	
	MCH	1	0	21.77	
		1	37	21.94	
		1	74	22.20	
		37	0	20.97	
		37	18	21.01	
		37	38	21.14	
		75	0	21.09	
	HCH	1	0	23.26	
		1	37	24.03	
		1	74	23.54	
		37	0	22.70	
		37	18	23.02	
		37	38	23.37	
		75	0	23.00	
16QAM	LCH	1	0	21.35	
		1	37	21.06	
		1	74	20.77	
		37	0	20.04	
		37	18	19.86	
		37	38	19.76	
		75	0	19.94	
	MCH	1	0	20.96	
		1	37	21.21	
		1	74	21.30	

		37	0	19.95	
		37	18	20.01	
		37	38	20.13	
		75	0	20.10	
	HCH	1	0	22.18	
		1	37	22.96	
		1	74	23.31	
		37	0	21.57	
		37	18	21.85	
		37	38	22.17	
		75	0	21.84	

Channel Bandwidth: 20 MHz					
Modulation	Channel	RB Configuration		Average Power [dBm]	
		Size	Offset		
QPSK	LCH	1	0	23.08	
		1	49	22.87	
		1	99	22.80	
		50	0	22.02	
		50	25	21.99	
		50	50	21.92	
		100	0	21.92	
	MCH	1	0	23.03	
		1	49	23.01	
		1	99	22.06	
		50	0	21.66	
		50	25	20.53	
		50	50	21.07	
		100	0	21.38	
	HCH	1	0	24.07	
		1	49	24.04	
		1	99	23.57	
		50	0	23.05	
		50	25	23.14	
		50	50	23.17	
		100	0	23.05	
16QAM	LCH	1	0	22.19	
		1	49	22.25	
		1	99	22.07	
		50	0	21.17	
		50	25	21.16	
		50	50	21.10	
		100	0	21.02	

	MCH	1	0	20.90	
		1	49	21.37	
		1	99	20.97	
		50	0	21.66	
		50	25	21.29	
		50	50	21.54	
		100	0	21.00	
	HCH	1	0	22.88	
		1	49	23.03	
		1	99	23.08	
		50	0	21.94	
		50	25	21.99	
		50	50	22.05	
		100	0	21.99	

Remark:

1. Per KDB941225 D05 v02r05, Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.8 When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
2. Per KDB941225 D05 v02r05, the procedures required for 1 RB allocation in section 4.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in sections 4.2.1 and 4.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB941225 D05 v02r05, For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in sections 4.2.1, 5.2.2 and 4.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

WLAN - Maximum Average Power				
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)
802.11b	1Mbps	CH 01	2412	12.17
		CH 06	2437	10.27
		CH 11	2462	10.74
802.11g	54Mbps	CH 01	2412	7.9
		CH 06	2437	7.33
		CH 11	2462	8.99
802.11n (20MHz)	MCS7	CH 01	2412	7.52
		CH 06	2437	7.13
		CH 11	2462	8.57
802.11n (40MHz)	MCS7	CH 03	2422	8.07
		CH 06	2437	6.79
		CH 09	2452	7.02

Remark:

1. Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion
2. Per KDB 248227 D01 v02r02, if 11g and 11n average output power is higher than 1/4 dB higher than 11b mode, SAR will be verified.
3. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4 dB higher than those measured at the lowest data rate. For 802.11n mode, SAR test according to the highest power channel with correspondence data rates.

Bluetooth - Maximum Average Power		
Test Mode	Data Rate	Average Power(dBm)
GFSK	1Mbps	0.894
Pi/4 QDPSK	2Mbps	-0.266
8DPSK	3Mbps	-0.246

Bluetooth - Maximum Average Power				
Test Mode	Data Rate	Channel	Frequency (MHz)	Average Power (dBm)
BLE	1Mbps	CH 00	2402	-8.024
		CH 19	2440	-10.27
		CH 39	2480	-9.217

Remark:

Bluetooth maximum output power is 0.894dBm, and Maximum Tune-Up output power is 1.0dBm. Per KDB 447498 D01 V06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
1.0	1.26	5	2.402	0.39	3

The exclusion thresholds is $0.39 < 3$, therefore, the RF exposure evaluation is not required.

9.2 Test Results for Standalone SAR Test

Head SAR

GSM850 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
1.	GSM	Right Cheek	128	824.2	32.09	32.5	1.0990	0.2057	0.2261
2.	GSM	Right Tilted	128	824.2	32.09	32.5	1.0990	0.1193	0.1311
3.	GSM	Left Cheek	128	824.2	32.09	32.5	1.0990	0.1986	0.2183
4.	GSM	Left Tilted	128	824.2	32.09	32.5	1.0990	0.0933	0.1025

GSM1900 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
5.	GSM	Right Cheek	512	1850.2	29.86	30.0	1.0328	0.1504	0.1553
6.	GSM	Right Tilted	512	1850.2	29.86	30.0	1.0328	0.1132	0.1169
7.	GSM	Left Cheek	512	1850.2	29.86	30.0	1.0328	0.1751	0.1808
8.	GSM	Left Tilted	512	1850.2	29.86	30.0	1.0328	0.1233	0.1273

GPRS850 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
9.	GPRS_4TX	Right Cheek	190	836.6	28.99	29.0	1.0023	0.2223	0.2228
10.	GPRS_4TX	Right Tilted	190	836.6	28.99	29.0	1.0023	0.1212	0.1215
11.	GPRS_4TX	Left Cheek	190	836.6	28.99	29.0	1.0023	0.2913	0.2920
12.	GPRS_4TX	Left Tilted	190	836.6	28.99	29.0	1.0023	0.1467	0.1470

GPRS1900 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	M Hz					
13.	GPRS_2TX	Right Cheek	512	1850.2	29.1	29.5	1.0965	0.0408	0.0447
14.	GPRS_2TX	Right Tilted	512	1850.2	29.1	29.5	1.0965	0.0321	0.0352
15.	GPRS_2TX	Left Cheek	512	1850.2	29.1	29.5	1.0965	0.0471	0.0516
16.	GPRS_2TX	Left Tilted	512	1850.2	29.1	29.5	1.0965	0.0357	0.0391

WCDMA Band 2 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
17.	RMC	Right Cheek	9538	1907.6	22.93	23.0	1.0162	0.2428	0.2467
18.	RMC	Right Tilted	9538	1907.6	22.93	23.0	1.0162	0.1654	0.1681
19.	RMC	Left Cheek	9538	1907.6	22.93	23.0	1.0162	0.4762	0.4839
20.	RMC	Left Tilted	9538	1907.6	22.93	23.0	1.0162	0.2432	0.2472

WCDMA Band 5 – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
21.	RMC	Right Cheek	4132	826.4	22.94	23.0	1.0139	0.1723	0.1747
22.	RMC	Right Tilted	4132	826.4	22.94	23.0	1.0139	0.1137	0.1153
23.	RMC	Left Cheek	4132	826.4	22.94	23.0	1.0139	0.1697	0.1721
24.	RMC	Left Tilted	4132	826.4	22.94	23.0	1.0139	0.0972	0.0986

LTE Band 2– Head SAR Test								
Plot No.	Mode	Test Position Head	Freque ncy	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
25.	RMC QPSK 20MHz 1RB	Right Cheek	1860.0	24.02	24.5	1.1169	0.3850	0.4300
26.	RMC QPSK 20MHz 1RB	Right Tilted	1860.0	24.02	24.5	1.1169	0.2018	0.2254
27.	RMC QPSK 20MHz 1RB	Left Cheek	1860.0	24.02	24.5	1.1169	0.4588	0.5124
28.	RMC QPSK 20MHz 1RB	Left Tilted	1860.0	24.02	24.5	1.1169	0.2214	0.2473
29.	RMC QPSK 20MHz 50%RB	Right Cheek	1860.0	22.76	23.0	1.0568	0.2973	0.3142
30.	RMC QPSK 20MHz 50%RB	Right Tilted	1860.0	22.76	23.0	1.0568	0.1192	0.1260
31.	RMC QPSK 20MHz 50%RB	Left Cheek	1860.0	22.76	23.0	1.0568	0.3692	0.3902
32.	RMC QPSK 20MHz 50%RB	Left Tilted	1860.0	22.76	23.0	1.0568	0.1436	0.1518

LTE Band 7– Head SAR Test								
Plot No.	Mode	Test Position Head	Frequency	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth		MHz					
33.	RMC QPSK 20MHz 1RB	Right Cheek	2560.0	24.07	24.5	1.1041	0.0840	0.0927
34.	RMC QPSK 20MHz 1RB	Right Tilted	2560.0	24.07	24.5	1.1041	0.0436	0.0481
35.	RMC QPSK 20MHz 1RB	Left Cheek	2560.0	24.07	24.5	1.1041	0.1828	0.2018
36.	RMC QPSK 20MHz 1RB	Left Tilted	2560.0	24.07	24.5	1.1041	0.1022	0.1128
37.	RMC QPSK 20MHz 50%RB	Right Cheek	2560.0	23.17	23.5	1.0789	0.0642	0.0693
38.	RMC QPSK 20MHz 50%RB	Right Tilted	2560.0	23.17	23.5	1.0789	0.0356	0.0384
39.	RMC QPSK 20MHz 50%RB	Left Cheek	2560.0	23.17	23.5	1.0789	0.1186	0.1280
40.	RMC QPSK 20MHz 50%RB	Left Tilted	2560.0	23.17	23.5	1.0789	0.0754	0.0814

WLAN 2.4GHz – Head SAR Test									
Plot No.	Mode	Test Position Head	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
41.	802.11b	Right Cheek	01	2412	12.17	12.5	1.0789	0.2202	0.2376
42.	802.11b	Right Tilted	01	2412	12.17	12.5	1.0789	0.1143	0.1233
43.	802.11b	Left Cheek	01	2412	12.17	12.5	1.0789	0.4847	0.5230
44.	802.11b	Left Tilted	01	2412	12.17	12.5	1.0789	0.2956	0.3189

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Body-worn SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
45.	GSM	Back	128	824.2	32.09	32.5	1.0990	0.4250	0.4671
46.	GSM	Front	128	824.2	32.09	32.5	1.0990	0.2379	0.2615

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
47.	GSM	Back	512	1850.2	29.86	30.0	1.0328	0.7002	0.7231
48.	GSM	Front	512	1850.2	29.86	30.0	1.0328	0.7319	0.7559

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
57	RMC 12.2k	Back Side	9538	1907.6	22.93	23.0	1.0162	0.5837	0.5932
58	RMC 12.2k	Front Side	9538	1907.6	22.93	23.0	1.0162	0.4435	0.4507

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
63	RMC 12.2k	Back Side	4132	826.4	22.94	23.0	1.0139	0.2988	0.3030
64	RMC 12.2k	Front Side	4132	826.4	22.94	23.0	1.0139	0.2220	0.2251

LTE Band 2–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Freque ncy	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
67	RMC QPSK 20MHz 1RB	Back Side	1860.0	24.02	24.5	1.1169	0.6297	0.7033
68	RMC QPSK 20MHz 1RB	Front Side	1860.0	24.02	24.5	1.1169	0.5034	0.5622
71	RMC QPSK 20MHz 50%RB	Back Side	1860.0	22.76	23.0	1.0568	0.5017	0.5302
72	RMC QPSK 20MHz 50%RB	Front Side	1860.0	22.76	23.0	1.0568	0.4222	0.4462

LTE Band 7–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
75	RMC QPSK 20MHz 1RB	Back Side	2560.0	24.07	24.5	1.1041	0.6999	0.7727
76	RMC QPSK 20MHz 1RB	Front Side	2560.0	24.07	24.5	1.1041	0.1052	0.1161
79	RMC QPSK 20MHz 50%RB	Back Side	2560.0	23.17	23.5	1.0789	0.5272	0.5688
80	RMC QPSK 20MHz 50%RB	Front Side	2560.0	23.17	23.5	1.0789	0.0823	0.0888

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
83	802.11b	Back Side	01	2412	12.17	12.5	1.0789	0.0759	0.0819
84	802.11b	Front Side	01	2412	12.17	12.5	1.0789	0.1055	0.1138

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Hotspot SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
49.	GPRS_4TX	Back Side	190	836.6	28.99	29.0	1.0023	0.3394	0.3402
50.	GPRS_4TX	Front Side	190	836.6	28.99	29.0	1.0023	0.4673	0.4684
51.	GPRS_4TX	Bottom side	190	836.6	28.99	29.0	1.0023	0.1643	0.1647
52.	GPRS_4TX	Left side	190	836.6	28.99	29.0	1.0023	0.1256	0.1259

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
53.	GPRS_2TX	Back Side	512	1850.2	29.1	29.5	1.0965	0.6708	0.7355
54.	GPRS_2TX	Front Side	512	1850.2	29.1	29.5	1.0965	0.4903	0.5376
55.	GPRS_2TX	Bottom side	512	1850.2	29.1	29.5	1.0965	0.5774	0.6331
56.	GPRS_2TX	Left side	512	1850.2	29.1	29.5	1.0965	0.3322	0.3643

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
57.	RMC 12.2k	Back Side	9538	1907.6	22.93	23.0	1.0162	0.5837	0.5932
58.	RMC 12.2k	Front Side	9538	1907.6	22.93	23.0	1.0162	0.4435	0.4507
59.	RMC 12.2k	Bottom side	9538	1907.6	22.93	23.0	1.0162	0.8210	0.8343
60.	RMC 12.2k	Bottom side	9262	1852.4	22.69	23.0	1.0740	0.5045	0.5418
61.	RMC 12.2k	Bottom side	9400	1880.0	22.8	23.0	1.0471	0.6818	0.7139
62.	RMC 12.2k	Left side	9538	1907.6	22.93	23.0	1.0162	0.3358	0.3413

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
63.	RMC 12.2k	Back Side	4132	826.4	22.94	23.0	1.0139	0.2988	0.3030
64.	RMC 12.2k	Front Side	4132	826.4	22.94	23.0	1.0139	0.2220	0.2251
65.	RMC 12.2k	Bottom side	4132	826.4	22.94	23.0	1.0139	0.1028	0.1042
66.	RMC 12.2k	Left side	4132	826.4	22.94	23.0	1.0139	0.1262	0.1280

LTE Band 2–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
67.	RMC QPSK 20MHz 1RB	Back Side	1860.0	24.02	24.5	1.1169	0.6297	0.7033
68.	RMC QPSK 20MHz 1RB	Front Side	1860.0	24.02	24.5	1.1169	0.5034	0.5622
69.	RMC QPSK 20MHz 1RB	Bottom side	1860.0	24.02	24.5	1.1169	0.6002	0.6703
70.	RMC QPSK 20MHz 1RB	Left side	1860.0	24.02	24.5	1.1169	0.2732	0.3051
71.	RMC QPSK 20MHz 50%RB	Back Side	1860.0	22.76	23.0	1.0568	0.5017	0.5302
72.	RMC QPSK 20MHz 50%RB	Front Side	1860.0	22.76	23.0	1.0568	0.4222	0.4462
73.	RMC QPSK 20MHz 50%RB	Bottom side	1860.0	22.76	23.0	1.0568	0.4638	0.4902
74.	RMC QPSK 20MHz 50%RB	Left side	1860.0	22.76	23.0	1.0568	0.1933	0.2043

LTE Band 7–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
75.	RMC QPSK 20MHz 1RB	Back Side	2560.0	24.07	24.5	1.1041	0.6999	0.7727
76.	RMC QPSK 20MHz 1RB	Front Side	2560.0	24.07	24.5	1.1041	0.1052	0.1161
77.	RMC QPSK 20MHz 1RB	Bottom side	2560.0	24.07	24.5	1.1041	0.5796	0.6399
78.	RMC QPSK 20MHz 1RB	Left side	2560.0	24.07	24.5	1.1041	0.2933	0.3238
79.	RMC QPSK 20MHz 50%RB	Back Side	2560.0	23.17	23.5	1.0789	0.5272	0.5688
80.	RMC QPSK 20MHz 50%RB	Front Side	2560.0	23.17	23.5	1.0789	0.0823	0.0888
81.	RMC QPSK 20MHz 50%RB	Bottom side	2560.0	23.17	23.5	1.0789	0.4828	0.5209
82.	RMC QPSK 20MHz 50%RB	Left side	2560.0	23.17	23.5	1.0789	0.2103	0.2269

WLAN 2.4GHz –Body SAR Test									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Max. Tune-up power (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
83.	802.11b	Back Side	01	2412	12.17	12.5	1.0789	0.0759	0.0819
84.	802.11b	Front Side	01	2412	12.17	12.5	1.0789	0.1055	0.1138
85.	802.11b	Right side	01	2412	12.17	12.5	1.0789	0.0268	0.0289
86.	802.11b	Top Side	01	2412	12.17	12.5	1.0789	0.0290	0.0313

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

9.3 Simultaneous Multi-band Transmission SAR Analysis

List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Head SAR	Body-worn SAR	Hotspot SAR
1	GSM(Voice) + WLAN(Data)	Yes	Yes	-
2	GPRS/ EDGE(Data) + WLAN(Data)	-	-	Yes
3	WCDMA (Voice)+ WLAN(Data)	Yes	Yes	-
4	HSDPA(Data) + WLAN(Data)	-	-	Yes
5	HSUPA(Data) + WLAN(Data)	-	-	Yes
6	LTE(Data) + WLAN(Data)	-	-	Yes
7	GSM(Voice) + Bluetooth(Data)	Yes	Yes	-
8	GPRS/ EDGE(Data) + Bluetooth(Data)	-	-	Yes
9	WCDMA(Voice) + Bluetooth(Data)	Yes	Yes	-
10	HSDPA(Data)+ Bluetooth(Data)	-	-	Yes
11	HSUPA(Data) + Bluetooth(Data)	-	-	Yes
12	LTE(Data) + Bluetooth(Data)	-	-	Yes

Remark:

- GSM and WCDMA share the same antenna, and cannot transmit simultaneously.
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
- According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}/x] \text{ W/kg}$$
for test separation distances $\leq 50 \text{ mm}$;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	X	SAR(1g) 5mm	SAR(1g) 10mm
1.0	1.26	5/10	2.402	7.5	0.0521	0.0260

- The maximum SAR summation is calculated based on the same configuration and test position.

Head SAR

WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.2261	0.2376	0.4637
Right Tilted	GSM850	0.1311	0.1233	0.2544
Left Cheek	GSM850	0.2183	0.5230	0.7413
Left Tilted	GSM850	0.1025	0.3189	0.4214
Right Cheek	GSM1900	0.1553	0.2376	0.3929
Right Tilted	GSM1900	0.1169	0.1233	0.2402
Left Cheek	GSM1900	0.1808	0.5230	0.7038
Left Tilted	GSM1900	0.1273	0.3189	0.4462
Right Cheek	GPRS850	0.2228	0.2376	0.4604
Right Tilted	GPRS850	0.1215	0.1233	0.2448
Left Cheek	GPRS850	0.2920	0.5230	0.815
Left Tilted	GPRS850	0.1470	0.3189	0.4659
Right Cheek	GPRS1900	0.0447	0.2376	0.2823
Right Tilted	GPRS1900	0.0352	0.1233	0.1585
Left Cheek	GPRS1900	0.0516	0.5230	0.5746
Left Tilted	GPRS1900	0.0391	0.3189	0.358
Right Cheek	WCDMA Band 2	0.2467	0.2376	0.4843
Right Tilted	WCDMA Band 2	0.1681	0.1233	0.2914
Left Cheek	WCDMA Band 2	0.4839	0.5230	1.0069
Left Tilted	WCDMA Band 2	0.2472	0.3189	0.5661
Right Cheek	WCDMA Band 5	0.1747	0.2376	0.4123
Right Tilted	WCDMA Band 5	0.1153	0.1233	0.2386
Left Cheek	WCDMA Band 5	0.1721	0.5230	0.6951
Left Tilted	WCDMA Band 5	0.0986	0.3189	0.4175
Right Cheek	LTE Band 2	0.4300	0.2376	0.6676
Right Tilted	LTE Band 2	0.2254	0.1233	0.3487
Left Cheek	LTE Band 2	0.5124	0.5230	1.0354
Left Tilted	LTE Band 2	0.2473	0.3189	0.5662
Right Cheek	LTE Band 7	0.0927	0.2376	0.3303
Right Tilted	LTE Band 7	0.0481	0.1233	0.1714
Left Cheek	LTE Band 7	0.2018	0.5230	0.7248
Left Tilted	LTE Band 7	0.1128	0.3189	0.4317

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850	0.2261	0.0521	0.2782
Right Tilted	GSM850	0.1311	0.0521	0.1832
Left Cheek	GSM850	0.2183	0.0521	0.2704
Left Tilted	GSM850	0.1025	0.0521	0.1546
Right Cheek	GSM1900	0.1553	0.0521	0.2074
Right Tilted	GSM1900	0.1169	0.0521	0.169
Left Cheek	GSM1900	0.1808	0.0521	0.2329
Left Tilted	GSM1900	0.1273	0.0521	0.1794
Right Cheek	GPRS850	0.2228	0.0521	0.2749
Right Tilted	GPRS850	0.1215	0.0521	0.1736
Left Cheek	GPRS850	0.2920	0.0521	0.3441
Left Tilted	GPRS850	0.1470	0.0521	0.1991
Right Cheek	GPRS1900	0.0447	0.0521	0.0968
Right Tilted	GPRS1900	0.0352	0.0521	0.0873
Left Cheek	GPRS1900	0.0516	0.0521	0.1037
Left Tilted	GPRS1900	0.0391	0.0521	0.0912
Right Cheek	WCDMA Band 2	0.2467	0.0521	0.2988
Right Tilted	WCDMA Band 2	0.1681	0.0521	0.2202
Left Cheek	WCDMA Band 2	0.4839	0.0521	0.536
Left Tilted	WCDMA Band 2	0.2472	0.0521	0.2993
Right Cheek	WCDMA Band 5	0.1747	0.0521	0.2268
Right Tilted	WCDMA Band 5	0.1153	0.0521	0.1674
Left Cheek	WCDMA Band 5	0.1721	0.0521	0.2242
Left Tilted	WCDMA Band 5	0.0986	0.0521	0.1507
Right Cheek	LTE Band 2	0.4300	0.0521	0.4821
Right Tilted	LTE Band 2	0.2254	0.0521	0.2775
Left Cheek	LTE Band 2	0.5124	0.0521	0.5645
Left Tilted	LTE Band 2	0.2473	0.0521	0.2994
Right Cheek	LTE Band 7	0.0927	0.0521	0.1448
Right Tilted	LTE Band 7	0.0481	0.0521	0.1002
Left Cheek	LTE Band 7	0.2018	0.0521	0.2539
Left Tilted	LTE Band 7	0.1128	0.0521	0.1649

Body-worn SAR
WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.4671	0.0819	0.549
Front	GSM850	0.2615	0.1138	0.3753
Back	GSM1900	0.7231	0.0819	0.805
Front	GSM1900	0.7559	0.1138	0.8697
Back	WCDMA Band 2	0.5932	0.0819	0.6751
Front	WCDMA Band 2	0.4507	0.1138	0.5645
Back	WCDMA Band 5	0.3030	0.0819	0.3849
Front	WCDMA Band 5	0.2251	0.1138	0.3389
Back	LTE Band 2	0.7033	0.0819	0.7852
Front	LTE Band 2	0.5622	0.1138	0.676
Back	LTE Band 7	0.7727	0.0819	0.8546
Front	LTE Band 7	0.1161	0.1138	0.2299

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.4671	0.0260	0.4931
Front	GSM850	0.2615	0.0260	0.2875
Back	GSM1900	0.7231	0.0260	0.7491
Front	GSM1900	0.7559	0.0260	0.7819
Back	WCDMA Band 2	0.5932	0.0260	0.6192
Front	WCDMA Band 2	0.4507	0.0260	0.4767
Back	WCDMA Band 5	0.3030	0.0260	0.329
Front	WCDMA Band 5	0.2251	0.0260	0.2511
Back	LTE Band 2	0.7033	0.0260	0.7293
Front	LTE Band 2	0.5622	0.0260	0.5882
Back	LTE Band 7	0.7727	0.0260	0.7987
Front	LTE Band 7	0.1161	0.0260	0.1421

Hotspot SAR
WWAN and WLAN

	WWAN		WLAN	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.3402	0.0819	0.4221
Front	GSM850	0.4684	0.1138	0.5822
Top side	GSM850	--	0.0313	0.0313
Bottom side	GSM850	0.1647	--	0.1647
Right side	GSM850	--	0.0289	0.0289
Left side	GSM850	0.1259	--	0.1259
Back	GSM1900	0.7355	0.0819	0.8174
Front	GSM1900	0.5376	0.1138	0.6514
Top side	GSM1900	--	0.0313	0.0313
Bottom side	GSM1900	0.6331	--	0.6331
Right side	GSM1900	--	0.0289	0.0289
Left side	GSM1900	0.3643	--	0.3643
Back	WCDMA Band 2	0.5932	0.0819	0.6751
Front	WCDMA Band 2	0.4507	0.1138	0.5645
Top side	WCDMA Band 2	--	0.0313	0.0313
Bottom side	WCDMA Band 2	0.8343	--	0.8343
Right side	WCDMA Band 2	--	0.0289	0.0289
Left side	WCDMA Band 2	0.3413	--	0.3413
Back	WCDMA Band 5	0.3030	0.0819	0.3849
Front	WCDMA Band 5	0.2251	0.1138	0.3389
Top side	WCDMA Band 5	--	0.0313	0.0313
Bottom side	WCDMA Band 5	0.1042	--	0.1042
Right side	WCDMA Band 5	--	0.0289	0.0289
Left side	WCDMA Band 5	0.1280	--	0.1280
Back	LTE Band 2	0.7033	0.0819	0.7852
Front	LTE Band 2	0.5622	0.1138	0.676
Top side	LTE Band 2	--	0.0313	0.0313
Bottom side	LTE Band 2	0.6703	--	0.6703
Right side	LTE Band 2	--	0.0289	0.0289
Left side	LTE Band 2	0.3051	--	0.3051
Back	LTE Band 7	0.7727	0.0819	0.8546
Front	LTE Band 7	0.1161	0.1138	0.2299
Top side	LTE Band 7	--	0.0313	0.0313
Bottom side	LTE Band 7	0.6399	--	0.6399
Right side	LTE Band 7	--	0.0289	0.0289
Left side	LTE Band 7	0.3238	--	0.3238

WWAN and Bluetooth

	WWAN		Bluetooth	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM850	0.3402	0.0260	0.3662
Front	GSM850	0.4684	0.0260	0.4944
Top side	GSM850	--	0.0260	0.0260
Bottom side	GSM850	0.1647	--	0.1647
Right side	GSM850	--	0.0260	0.0260
Left side	GSM850	0.1259	--	0.1259
Back	GSM1900	0.7355	0.0260	0.7615
Front	GSM1900	0.5376	0.0260	0.5636
Top side	GSM1900	--	0.0260	0.0260
Bottom side	GSM1900	0.6331	--	0.6331
Right side	GSM1900	--	0.0260	0.0260
Left side	GSM1900	0.3643	--	0.3643
Back	WCDMA Band 2	0.5932	0.0260	0.6192
Front	WCDMA Band 2	0.4507	0.0260	0.4767
Top side	WCDMA Band 2	--	0.0260	0.0260
Bottom side	WCDMA Band 2	0.8343	--	0.8343
Right side	WCDMA Band 2	--	0.0260	0.0260
Left side	WCDMA Band 2	0.3413	--	0.3413
Back	WCDMA Band 5	0.3030	0.0260	0.329
Front	WCDMA Band 5	0.2251	0.0260	0.2511
Top side	WCDMA Band 5	--	0.0260	0.0260
Bottom side	WCDMA Band 5	0.1042	--	0.1042
Right side	WCDMA Band 5	--	0.0260	0.0260
Left side	WCDMA Band 5	0.1280	--	0.1280
Back	LTE Band 2	0.7033	0.0260	0.7293
Front	LTE Band 2	0.5622	0.0260	0.5882
Top side	LTE Band 2	--	0.0260	0.0260
Bottom side	LTE Band 2	0.6703	--	0.6703
Right side	LTE Band 2	--	0.0260	0.0260
Left side	LTE Band 2	0.3051	--	0.3051
Back	LTE Band 7	0.7727	0.0260	0.7987
Front	LTE Band 7	0.1161	0.0260	0.1421
Top side	LTE Band 7	--	0.0260	0.0260
Bottom side	LTE Band 7	0.6399	--	0.6399
Right side	LTE Band 7	--	0.0260	0.0260
Left side	LTE Band 7	0.3238	--	0.3238

10. Measurement Uncertainty

10.1 Uncertainty for EUT SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ - %)	10g Ui (+ - %)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Test Sample Related									
Test sample positioning	E.4.2	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	E.2.9	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
SAR scaling	E6.5	0.0	R	$\sqrt{3}$	1	1	0.0	0.0	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E3.2	1.9	R	$\sqrt{3}$	1	0.84	1.10	0.90	∞
Liquid conductivity - deviation	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞

from target value										
Liquid conductivity measurement uncertainty	-	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	∞
Liquid permittivity - deviation from target value		E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	∞
Liquid permittivity measurement uncertainty	-	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	∞
Combined Standard Uncertainty				RSS				12.98	12.53	
Expanded Uncertainty (95% Confidence interval)				K=2				25.32	24.43	

10.2 Uncertainty for System Performance Check

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+ - %)	10g Ui (+ - %)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_Cp)^{1/2}$	$(1_Cp)^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	E.2.5	0	R	$\sqrt{3}$	0	0	0.0	0.0	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	E.6.1	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max.	E.5.2	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞

SAR Evaluation									
Dipole									
Dipole axis to liquid Distance	8,E.4.2	1.00	N	$\sqrt{3}$	1	1	0.58	0.58	N-1
Input power and SAR drift measurement	8,6.6.2	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
Deviation of experimental dipole from numerical dipole	E.6.4	5.5	R	$\sqrt{3}$	1	1	3.20	3.20	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	2.0	R	$\sqrt{3}$	1	0.84	1.10	1.10	∞
Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	
Liquid permittivity - deviation from target value	E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	M
Combined Standard Uncertainty			RSS				12.00	11.50	
Expanded Uncertainty (95% Confidence interval)			K=2				23.39	22.43	

Annex A. Plots of System Performance Check

MEASUREMENT 1

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 7 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	0.038437
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.129489
SAR 1g (W/Kg)	2.411253

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.4900	1.8942	1.4811	1.3541	1.1123	1.0539



3D screen shot	Hot spot position
	

MEASUREMENT 2

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.022540
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	7.174526
SAR 1g (W/Kg)	9.913214

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2354	6.8400	5.0121	4.1189	3.0522	2.8424



3D screen shot	Hot spot position
	

MEASUREMENT 3

For Head Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.64; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	38.153660
Conductivity (S/m)	1.740236
Power Variation (%)	1.141452
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	8.020427
SAR 1g (W/Kg)	13.452457

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	14.1034	12.0012	10.2624	7.4715	5.9022	4.5114



3D screen shot	Hot spot position
	

MEASUREMENT 4

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.901472
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.028956
SAR 1g (W/Kg)	2.354211

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.5789	1.1300	0.8795	0.5940	0.5011	0.5100



3D screen shot	Hot spot position
	

MEASUREMENT 5

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	0.541872
Ambient Temperature	21.1
Liquid Temperature	21.3






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.134651
SAR 1g (W/Kg)	9.781550

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2031	6.43001	4.9011	4.5325	3.1201	2.5024



3D screen shot	Hot spot position
	

MEASUREMENT 6

For Body Liquid

Type: Validation measurement (Fast, 75.00 %)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 21 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	52.010212
Conductivity (S/m)	1.910255
Power Variation (%)	1.369745
Ambient Temperature	21.1
Liquid Temperature	21.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	7.119522
SAR 1g (W/Kg)	12.592360

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	13.3911	11.7951	9.2945	8.5400	6.3712	4.6225



3D screen shot	Hot spot position
	

Annex B. Plots of SAR Measurement

<u>TYPE</u>	<u>BAND</u>	<u>PARAMETERS</u>
Phone	GSM850	<u>Measurement 1:</u> Right Head with Cheek device position on Low Channel in GSM mode
Phone	GSM1900	<u>Measurement 7:</u> Left Head with Cheek device position on Low Channel in GSM mode
Phone	GPRS850_4TX	<u>Measurement 11:</u> Left Head with Cheek device position on Middle Channel in GPRS mode
Phone	GPRS1900_2TX	<u>Measurement 15:</u> Left Head with Cheek device position on Low Channel in GPRS mode
Phone	WCDMA1900_RMC	<u>Measurement 19:</u> Left Head with Cheek device position on High Channel in WCDMA mode
Phone	WCDMA850_RMC	<u>Measurement 21:</u> Right Head with Cheek device position on Low Channel in WCDMA mode
Phone	LTE Band 2_RMC	<u>Measurement 27:</u> Left Head with Cheek device position on Low Channel in LTE QPSK 20MHz 1RB mode
Phone	LTE Band 7_RMC	<u>Measurement 35:</u> Left Head with Cheek device position on High Channel in LTE QPSK 20MHz 1RB mode
Phone	WiFi_802.11b	<u>Measurement 43:</u> Left Head with Cheek device position on Low Channel in 802.11b mode
Phone	GSM850	<u>Measurement 45:</u> Flat Plane with Back(Body-worn) device position on Low Channel in GSM mode
Phone	GSM1900	<u>Measurement 48:</u> Flat Plane with Front(Body-worn) device position on Low Channel in GSM mode
Phone	GPRS850_4TX	<u>Measurement 50:</u> Flat Plane with Front device position on Middle Channel in GPRS mode
Phone	GPRS1900_2TX	<u>Measurement 53:</u> Flat Plane with Back device position on Low Channel in GPRS mode
Phone	WCDMA1900_RMC	<u>Measurement 59:</u> Flat Plane with Bottom side device position on High Channel in WCDMA mode
Phone	WCDMA850_RMC	<u>Measurement 63:</u> Flat Plane with Back device position on Low Channel in WCDMA mode
Phone	LTE Band 2_RMC	<u>Measurement 67:</u> Flat Plane with Back device position on Low Channel in LTE QPSK 20MHz 1RB mode
Phone	LTE Band 7_RMC	<u>Measurement 75:</u> Flat Plane with Back device position on High Channel in LTE QPSK 20MHz 1RB mode
Phone	WiFi_802.11b	<u>Measurement 84:</u> Flat Plane with Front side device position on Low Channel in 802.11b mode
<i>Remark: SAR plot is showed the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.</i>		

MEASUREMENT 1

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 11 minutes 48 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	824.200000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.144536
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-50.00, Y=-40.00

SAR 10g (W/Kg)	0.179085
SAR 1g (W/Kg)	0.205710



MEASUREMENT 7

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 11 minutes 48 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.442440
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-56.00, Y=-58.00

SAR 10g (W/Kg)	0.109206
SAR 1g (W/Kg)	0.175072



MEASUREMENT 11

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 11 minutes 48 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	GPRS850_4TX
Channels	Middle
Signal	Duty Cycle: 1:2


B. SAR Measurement Results


Frequency (MHz)	836.600000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.903833
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-56.00, Y=-32.00

SAR 10g (W/Kg)	0.247500
SAR 1g (W/Kg)	0.291301



3D screen shot	Hot spot position
	

MEASUREMENT 15

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	GPRS1900_2TX
Channels	Low
Signal	Duty Cycle: 1:4



B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.536272
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-55.00, Y=-49.00

SAR 10g (W/Kg)	0.029477
SAR 1g (W/Kg)	0.047051



MEASUREMENT 19

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	WCDMA1900_RMC
Channels	High
Signal	Duty Cycle 1:1


B. SAR Measurement Results



Frequency (MHz)	1907.600000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.524540
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-55.00, Y=-56.00

SAR 10g (W/Kg)	0.292956
SAR 1g (W/Kg)	0.476193



3D screen shot	Hot spot position
	

MEASUREMENT 21

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.93; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Right head
Device Position	Cheek
Band	WCDMA850_RMC
Channels	Low
Signal	Duty Cycle 1:1


B. SAR Measurement Results


Frequency (MHz)	826.400000
Relative Permittivity (real part)	41.110245
Conductivity (S/m)	0.871245
Power Variation (%)	1.342427
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-50.00, Y=-40.00

SAR 10g (W/Kg)	0.152029
SAR 1g (W/Kg)	0.172257



3D screen shot	Hot spot position
	

MEASUREMENT 27

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.35; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	LTE Band 2_RMC
Channels	QPSK, 20MHz, 1RB, Low
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	1860.000000
Relative Permittivity (real part)	38.560124
Conductivity (S/m)	1.380369
Power Variation (%)	1.743564
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-56.00, Y=-57.00

SAR 10g (W/Kg)	0.267391
SAR 1g (W/Kg)	0.458786



MEASUREMENT 35

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.64; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	LTE Band 7_RMC
Channels	QPSK, 20MHz, 1RB, High
Signal	Duty Cycle 1:1


B. SAR Measurement Results



Frequency (MHz)	2560.000000
Relative Permittivity (real part)	38.153660
Conductivity (S/m)	1.740236
Power Variation (%)	0.924535
Ambient Temperature	21.1
Liquid Temperature	21.2



Maximum location: X=-47.00, Y=-49.00

SAR 10g (W/Kg)	0.096035
SAR 1g (W/Kg)	0.182815



3D screen shot	Hot spot position
	

MEASUREMENT 43

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.64; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Left head
Device Position	Cheek
Band	WiFi_802.11b
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results


Frequency (MHz)	2412.000000
Relative Permittivity (real part)	38.153660
Conductivity (S/m)	1.740236
Power Variation (%)	3.234772
Ambient Temperature	21.1
Liquid Temperature	21.2





Maximum location: X=-12.00, Y=18.00

SAR 10g (W/Kg)	0.220412
SAR 1g (W/Kg)	0.484708

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.5427	0.2460	0.1079	0.0501



3D screen shot	Hot spot position
	

MEASUREMENT 45

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back(Body-worn)
Band	GSM850
Channels	Low
Signal	TDMA (Crest factor: 8.0)

B. SAR Measurement Results


Frequency (MHz)	824.200000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.901472
Ambient Temperature	21.1
Liquid Temperature	21.3




Maximum location: X=14.00, Y=-36.00

SAR 10g (W/Kg)	0.318123
SAR 1g (W/Kg)	0.424969

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.4023	0.2907	0.2274	0.1959



3D screen shot	Hot spot position
	

MEASUREMENT 48

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Front(Body-worn)
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)



B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	1.474622
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=0.00, Y=23.00

SAR 10g (W/Kg)	0.409825
SAR 1g (W/Kg)	0.731871



MEASUREMENT 50

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Front
Band	GPRS850_4TX
Channels	Middle
Signal	Duty Cycle: 1:2



B. SAR Measurement Results

Frequency (MHz)	836.600000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	0.901472
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=15.00, Y=-23.00

SAR 10g (W/Kg)	0.356782
SAR 1g (W/Kg)	0.467343



MEASUREMENT 53

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat plane
Device Position	Back
Band	GPRS1900_2TX
Channels	Low
Signal	Duty Cycle: 1:4

B. SAR Measurement Results


Frequency (MHz)	1850.200000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	2.483762
Ambient Temperature	21.1
Liquid Temperature	21.3





Maximum location: X=-6.00, Y=-10.00

SAR 10g (W/Kg)	0.402785
SAR 1g (W/Kg)	0.670806

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.7065	0.4394	0.2715	0.1682



3D screen shot	Hot spot position
	

MEASUREMENT 59

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Bottom
Band	WCDMA1900_RMC
Channels	High
Signal	Duty Cycle 1:1

B. SAR Measurement Results


Frequency (MHz)	1907.600000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	1.847552
Ambient Temperature	21.1
Liquid Temperature	21.3





Maximum location: X=9.00, Y=-10.00

SAR 10g (W/Kg)	0.444790
SAR 1g (W/Kg)	0.820999

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.0000	0.9161	0.5727	0.3575	0.2252



3D screen shot	Hot spot position
	

MEASUREMENT 63

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 7.13; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back
Band	WCDMA850_RMC
Channels	Low
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	826.400000
Relative Permittivity (real part)	54.851214
Conductivity (S/m)	0.951454
Power Variation (%)	2.341234
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=18.00, Y=-32.00

SAR 10g (W/Kg)	0.236626
SAR 1g (W/Kg)	0.298786



MEASUREMENT 67

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 6.55; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 2_RMC
Channels	QPSK, 20MHz, 1RB, Low
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	1860.000000
Relative Permittivity (real part)	52.420415
Conductivity (S/m)	1.501966
Power Variation (%)	1.523573
Ambient Temperature	21.1
Liquid Temperature	21.3



Maximum location: X=-15.00, Y=-10.00

SAR 10g (W/Kg)	0.391245
SAR 1g (W/Kg)	0.629744



MEASUREMENT 75

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 7_RMC
Channels	QPSK, 20MHz, 1RB, High
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	2560.000000
Relative Permittivity (real part)	52.010212
Conductivity (S/m)	1.910255
Power Variation (%)	3.672346
Ambient Temperature	21.1
Liquid Temperature	21.2



Maximum location: X=-5.00, Y=17.00

SAR 10g (W/Kg)	0.326245
SAR 1g (W/Kg)	0.699895



MEASUREMENT 84

Type: Phone measurement (Complete)

Date of measurement: 10/17/2016

Measurement duration: 12 minutes 3 seconds


E-field Probe: SSE5 - SN 09/13 EP168; ConvF: 5.80; Calibrated: 06/01/2016

A. Experimental conditions

Area Scan	sam_direct_droit2_surf8mm.txt
Phantom	Flat Plane
Device Position	Front
Band	WiFi_802.11b
Channels	Low
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative Permittivity (real part)	52.010212
Conductivity (S/m)	1.910255
Power Variation (%)	2.492743
Ambient Temperature	21.1
Liquid Temperature	21.2



Maximum location: X=13.00, Y=-8.00

SAR 10g (W/Kg)	0.052066
SAR 1g (W/Kg)	0.105465



Annex C. EUT Photos

EUT View Front



EUT View Back



Antenna View




Annex D. Test Setup Photos


Head Exposure Conditions

Cheek




Tilt



Cheek**Tilt**

Body-worn & Hotspot mode Exposure Conditions

Body Front




Body Back



Hotspot Exposure Conditions

Body Left



Body Right



Body Top



Body Bottom



Annex E. Calibration Certificate

Please refer to the exhibit for the calibration certificate

******* END OF REPORT *******