



TEST REPORT

FCC ID: 2AXYP-OSW-851H

Product: Smart Watch

Model No.: OSW-851H

Trade Mark: oraimo

Report No.: WSCT-A2LA-R&E240700029A-LE

Issued Date: 23 July 2024

Issued for:

ORAIMO TECHNOLOGY LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT HONGKONG

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B, Baoshi Science & Technology Park, Baoshi Road,
Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755-26996192
FAX: +86-755-86376605



Note: The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. This report must not be used by the client to claim product certification, approval, or any agency of the U.S. Government.



TABLE OF CONTENTS

1. Test Certification	3
2. Test Result Summary	4
3. EUT Description	5
4. Genera Information	6
4.1. TEST ENVIRONMENT AND MODE	6
4.2. DESCRIPTION OF SUPPORT UNITS	6
5. Facilities and Accreditations	7
5.1. FACILITIES	7
5.2. ACCREDITATIONS	7
5.3. MEASUREMENT UNCERTAINTY	8
5.4. MEASUREMENT INSTRUMENTS	9
6. Test Results and Measurement Data	10
6.1. ANTENNA REQUIREMENT	10
6.2. CONDUCTED EMISSION	11
6.3. CONDUCTED OUTPUT POWER	14
6.4. EMISSION BANDWIDTH	16
6.5. POWER SPECTRAL DENSITY	21
6.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT	23
6.7. RADIATED SPURIOUS EMISSION MEASUREMENT	37



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

1. Test Certification

Product: Smart Watch
Model No.: OSW-851H
Trade Mark: oraimo
Applicant: ORAIMO TECHNOLOGY LIMITED
FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer: Jiangsu Saibo Yuhua Technology Co.,Ltd
Building 8(D) of Yancheng High-Tech Zone Intelligent
Terminal Industrial Park, P.R.China.
Date of Test: 03 July 2024 to 23 July 2024
Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen)Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:

Wang Xiang

(Wang Xiang)

Checked By:

Chen Xu

(Chen Xu)

Approved By:

Liu Fuxin

(Liu Fuxin)

Date:

23 July 2024

世标检测认证股份
World Standardization Certification & Testing Group (Shenzhen) Co., Ltd.ADD: Building A-B, Baoshi Science & Technology Park, Baoshi Road, Baoan District, Shenzhen, Guangdong, China
TEL: 0086-755-26996192 26996053 FAX: 0086-755-86376605 E-mail: fengbing.wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.



3. EUT Description

Product Name:	Smart Watch
Model :	OSW-851H
Trade Mark:	oraimo
Operation Frequency:	BLE1M:2402MHz~2480MHz BLE2M: 2404MHz~2478MHz
Channel Separation:	2MHz
Number of Channel:	40
Modulation Technology:	GFSK
Antenna Type:	Integral Antenna
Antenna Gain:	-1.05dBi
Operating Voltage	Li-ion Battery: 552125 Voltage: 3.8V Rated Capacity: 350mAh Limited Charge Voltage: 4.35V
Remark:	N/A.

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
...	...	...	...	...	...	...	...
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz
Remark: Channel 0, 19 & 39 have been tested.							



4. Genera Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Adapter	XCU32	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



5. Facilities and Accreditations

5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group(Shenzhen) CO., LTD**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

CNAS - Registration Number: L3732

China National Accreditation Service for Conformity Assessment, The test firm Registration Number: L3732

FCC - Designation Number: CN1303

World Standardization Certification & Testing Group(Shenzhen) CO., LTD. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Designation Number: CN1303.

A2LA - Certificate Number: 5768.01

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number: 5768.01



5.3.Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Power Spectral Density	$\pm 3.2\text{dB}$
2	Duty Cycle and Tx-Sequence and Tx-Gap	$\pm 1\%$
3	Medium Utilisation Factor	$\pm 1.3\%$
4	Occupied Channel Bandwidth	$\pm 2.4\%$
5	Transmitter Unwanted Emission in the out-of Band	$\pm 1.3\%$
6	Transmitter Unwanted Emissions in the Spurious Domain	$\pm 2.5\%$
7	Receiver Spurious Emissions	$\pm 2.5\%$
8	Conducted Emission Test	$\pm 3.2\text{dB}$
9	RF power, conducted	$\pm 0.16\text{dB}$
10	Spurious emissions, conducted	$\pm 0.21\text{dB}$
11	All emissions, radiated(<1GHz)	$\pm 4.7\text{dB}$
12	All emissions, radiated(>1GHz)	$\pm 4.7\text{dB}$
13	Temperature	$\pm 0.5^{\circ}\text{C}$
14	Humidity	$\pm 2.0\%$



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com**5.4.MEASUREMENT INSTRUMENTS**


NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
Test software	--	EZ-EMC	CON-03A	-	-
Test software	--	MTS8310	-	-	-
EMI Test Receiver	R&S	ESCI	100005	11/05/2023	11/04/2024
LISN	AFJ	LS16	16010222119	11/05/2023	11/04/2024
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2023	11/04/2024
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	11/05/2023	11/04/2024
Coaxial cable	Megalon	LMR400	N/A	11/05/2023	11/04/2024
GPIO cable	Megalon	GPIO	N/A	11/05/2023	11/04/2024
Spectrum Analyzer	R&S	FSU	100114	11/05/2023	11/04/2024
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2023	11/04/2024
Pre-Amplifier	CDSI	PAP-1G18-38	--	11/05/2023	11/04/2024
Bi-log Antenna	SCHWARZBECK	VULB9168	01488	7/29/2023	7/28/2024
9*6*6 Anechoic	--	--	--	11/05/2023	11/04/2024
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	11/05/2023	11/04/2024
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	11/05/2023	11/04/2024
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	11/05/2023	11/04/2024
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	11/05/2023	11/04/2024
Loop Antenna	EMCO	6502	00042960	11/05/2023	11/04/2024
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	11/05/2023	11/04/2024
Power meter	Anritsu	ML2487A	6K00003613	11/05/2023	11/04/2024
Power sensor	Anritsu	MX248XD	--	11/05/2023	11/04/2024
Spectrum Analyzer	Keysight	N9010B	MY60241089	11/05/2023	11/04/2024



6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Bluetooth antenna is a Integral Antenna. it meets the standards, and the best case gain of the antenna is -1.05dBi.	



6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.10:2014		
Frequency Range:	150 kHz to 30 MHz		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limits:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
Test Setup:	Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Mode:	Charging + Transmitting Mode		
Test Procedure:	1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2014 on conducted measurement.		
Test Result:	N/A		




6.2.2. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)

The worst mode is BLE 2M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	0.4290	7.64	20.55	28.19	47.27	-19.08	AVG
2	0.4470	14.58	20.54	35.12	56.93	-21.81	QP
3	0.6090	13.20	20.53	33.73	56.00	-22.27	QP
4	0.6809	0.72	20.54	21.26	46.00	-24.74	AVG
5	0.7440	11.40	20.56	31.96	56.00	-24.04	QP
6	0.8025	-2.38	20.58	18.20	46.00	-27.80	AVG
7	0.8970	8.91	20.63	29.54	56.00	-26.46	QP
8	1.2030	-2.59	20.66	18.07	46.00	-27.93	AVG
9	2.1840	0.17	20.61	20.78	46.00	-25.22	AVG
10	2.6745	12.36	20.60	32.96	56.00	-23.04	QP
11	2.6745	-0.52	20.60	20.08	46.00	-25.92	AVG
12	3.5430	7.70	20.59	28.29	56.00	-27.71	QP



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,

Please Contact with WSCT
www.wsct-cert.com**Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)**

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4335	2.77	20.55	23.32	47.19	-23.87	AVG
2 *	0.4380	16.45	20.55	37.00	57.10	-20.10	QP
3	0.5550	12.76	20.52	33.28	56.00	-22.72	QP
4	0.6450	-3.83	20.53	16.70	46.00	-29.30	AVG
5	0.6630	12.73	20.53	33.26	56.00	-22.74	QP
6	0.8160	9.82	20.59	30.41	56.00	-25.59	QP
7	0.8205	-3.61	20.59	16.98	46.00	-29.02	AVG
8	2.1660	-0.91	20.61	19.70	46.00	-26.30	AVG
9	2.2065	11.73	20.61	32.34	56.00	-23.66	QP
10	2.6790	-1.25	20.60	19.35	46.00	-26.65	AVG
11	2.7195	10.74	20.60	31.34	56.00	-24.66	QP
12	4.5870	-6.35	20.58	14.23	46.00	-31.77	AVG

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Lisc factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)


Q.P. = Quasi-Peak AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.



6.3. Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074
Limit:	30dBm
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04. 2. Set spectrum analyzer as following: a) Set the RBW $\geq$ DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.
Test Result:	PASS



6.3.2. Test Data

BLE 1M			
Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	4.70	30.00	PASS
Middle	5.09	30.00	PASS
Highest	3.92	30.00	PASS

BLE 2M			
Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	4.91	30.00	PASS
Middle	5.20	30.00	PASS
Highest	4.19	30.00	PASS

Test plots as follows:



6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS



6.4.2. Test data

BLE 1M

Test channel	6dB Emission Bandwidth (kHz)		
	BT LE mode	Limit	Result
Lowest	0.650	>500k	PASS
Middle	0.631	>500k	
Highest	0.650	>500k	

BLE 2M

Test channel	6dB Emission Bandwidth (kHz)		
	BT LE mode	Limit	Result
Lowest	1.077	>500k	PASS
Middle	0.942	>500k	
Highest	0.908	>500k	

Test plots as follows:




Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01


For Question,
Please Contact with WSCT
www.wsct-cert.com

Test Graphs

-6dB Bandwidth BLE 1M 2402MHz





-6dB Bandwidth BLE 1M 2440MHz





Report No.: WSCT-A2LA-R&E240700029A-LE



Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com**-6dB Bandwidth BLE 1M 2480MHz****-6dB Bandwidth BLE 2M 2404MHz**



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com**-6dB Bandwidth BLE 2M 2440MHz****-6dB Bandwidth BLE 2M 2478MHz**



6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW) 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS



6.5.2. Test data

Test channel	Power Spectral Density (dBm/3kHz)		
	BLE 1M	Limit	Result
Lowest	-10.20	8 dBm/3kHz	PASS
Middle	-10.62	8 dBm/3kHz	
Highest	-11.35	8 dBm/3kHz	

Test channel	Power Spectral Density (dBm/3kHz)		
	BLE 2M	Limit	Result
Lowest	-10.99	8 dBm/3kHz	PASS
Middle	-11.83	8 dBm/3kHz	
Highest	-11.35	8 dBm/3kHz	

Test plots as follows:




Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01


For Question,
Please Contact with WSCT
www.wsct-cert.com

Test Graphs

PSD BLE 1M 2402MHz



PSD BLE 1M 2440MHz






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

PSD BLE 1M 2480MHz



PSD BLE 2M 2404MHz






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

PSD BLE 2M 2440MHz



PSD BLE 2M 2478MHz





6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01


For Question,
Please Contact with WSCT
www.wsct-cert.com

Test Data


Band Edge

Test Graphs

Band Edge BLE 1M 2402MHz Ref



Band Edge BLE 1M 2402MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Band Edge BLE 1M 2480MHz Ref



Band Edge BLE 1M 2480MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Band Edge BLE 2M 2404MHz Ref



Band Edge BLE 2M 2404MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Band Edge BLE 2M 2478MHz Ref



Band Edge BLE 2M 2478MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE
Conducted RF Spurious Emission

Certificate #5768.01


For Question,
Please Contact with WSCT
www.wsct-cert.com

Test Graphs

Tx. Spurious BLE 1M 2402MHz Ref



Tx. Spurious BLE 1M 2402MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Tx. Spurious BLE 1M 2440MHz Ref



Tx. Spurious BLE 1M 2440MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Tx. Spurious BLE 1M 2480MHz Ref



Tx. Spurious BLE 1M 2480MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Tx. Spurious BLE 2M 2404MHz Ref



Tx. Spurious BLE 2M 2404MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Tx. Spurious BLE 2M 2440MHz Ref



Tx. Spurious BLE 2M 2440MHz Emission






Report No.: WSCT-A2LA-R&E240700029A-LE


Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Tx. Spurious BLE 2M 2478MHz Ref



Tx. Spurious BLE 2M 2478MHz Emission







6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209			
Test Method:	ANSI C63.10:2014			
Frequency Range:	9 kHz to 25 GHz			
Measurement Distance:	3 m			
Antenna Polarization:	Horizontal & Vertical			
Operation mode:	Refer to item 4.1			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz
	30MHz-1GHz	Quasi-peak	100KHz	300KHz
	Above 1GHz	Peak	1MHz	3MHz
Limit:				Remark
				Quasi-peak Value
				Quasi-peak Value
				Quasi-peak Value
				Peak Value
Test setup:				Average Value
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	
	0.009-0.490	2400/F(KHz)	300	
	0.490-1.705	24000/F(KHz)	30	
	1.705-30	30	30	
Test setup:	30-88	100	3	
	88-216	150	3	
	216-960	200	3	
	Above 960	500	3	
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
Test setup:	Above 1GHz	500	3	Average
		5000	3	Peak
For radiated emissions below 30MHz				
Distance = 3m EUT Turn table Ground Plane Computer Pre-Amplifier Receiver				
30MHz to 1GHz				



Above 1GHz

**Test Procedure:**

- For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.1 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.



	2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 4.1 for details
Test results:	PASS

Note: Freq. = Emission frequency in MHz
 Reading level (dBμV) = Receiver reading
 Corr. Factor (dB) = Attenuation factor + Cable loss
 Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)
 Limit (dBμV) = Limit stated in standard
 Margin (dB) = Level (dBμV) – Limits (dBμV)






6.7.2. Test Data(Worst case)

Please refer to following diagram for individual
Below 1GHz

The worst mode is BLE 2M

Horizontal:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		30.0000	28.81	-2.60	26.21	40.00	-13.79	QP
2		37.1550	27.03	-1.85	25.18	40.00	-14.82	QP
3		56.9912	27.09	-2.62	24.47	40.00	-15.53	QP
4		153.7385	25.95	-1.48	24.47	43.50	-19.03	QP
5		863.0562	26.66	7.03	33.69	46.00	-12.31	QP
6		993.0114	25.93	8.55	34.48	54.00	-19.52	QP




Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
ct-cert.com

Vertical:

80.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		30.0000	31.93	-2.60	29.33	40.00	-10.67	QP
2	*	38.0783	34.18	-1.69	32.49	40.00	-7.51	QP
3		42.6000	29.43	-1.80	27.63	40.00	-12.37	QP
4		101.6443	30.29	-5.47	24.82	43.50	-18.68	QP
5		884.5029	26.87	7.36	34.23	46.00	-11.77	QP
6		958.7943	26.82	8.20	35.02	46.00	-10.98	QP

Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) - Limits (dBuV)





Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com


Above 1GHz(The worst mode is BLE 2M)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious above 18G is noise only, do not show on the report.

Low channel: 2402MHz

Horizontal:


**Susputed Data List**

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1960.0000	45.45	2.11	43.34	74	-28.55	72.6	Horizontal	PK	Pass
1	1960.0000	31.96	2.11	29.85	54	-22.04	72.6	Horizontal	AV	Pass
2	2435.6250	49.05	7.69	41.36	74	-24.95	84.6	Horizontal	PK	Pass
2	2435.6250	37.5	7.69	29.81	54	-16.5	84.6	Horizontal	AV	Pass
3	5718.1250	56.77	21.31	35.46	74	-17.23	0	Horizontal	PK	Pass
3	5718.1250	48.19	21.31	26.88	54	-5.81	0	Horizontal	AV	Pass
4	8304.0000	42.15	37.12	5.03	74	-31.85	360.1	Horizontal	PK	Pass
4	8304.0000	34.39	37.12	-2.73	54	-19.61	360.1	Horizontal	AV	Pass
5	11082.0000	46.54	39.43	7.11	74	-27.46	360.1	Horizontal	PK	Pass
5	11082.0000	39.4	39.43	-0.03	54	-14.6	360.1	Horizontal	AV	Pass
6	17911.5000	53.33	45.91	7.42	74	-20.67	10.6	Horizontal	PK	Pass
6	17911.5000	46.2	45.91	0.29	54	-7.8	10.6	Horizontal	AV	Pass



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
ct-cert.com

Suspected Data List


NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1768.1250	45.5	0.73	44.77	74	-28.5	3.5	Vertical	PK	Pass
1	1768.1250	30.63	0.73	29.9	54	-23.37	3.5	Vertical	AV	Pass
2	3401.8750	53.98	9.35	44.63	74	-20.02	53.5	Vertical	PK	Pass
2	3401.8750	37.7	9.35	28.35	54	-16.3	53.5	Vertical	AV	Pass
3	5639.3750	57.23	20.99	36.24	74	-16.77	122.8	Vertical	PK	Pass
3	5639.3750	47.42	20.99	26.43	54	-6.58	122.8	Vertical	AV	Pass
4	9628.5000	43.95	37.84	6.11	74	-30.05	351.1	Vertical	PK	Pass
4	9628.5000	36.02	37.84	-1.82	54	-17.98	351.1	Vertical	AV	Pass
5	13860.0000	49.86	41.14	8.72	74	-24.14	121.2	Vertical	PK	Pass
5	13860.0000	42.14	41.14	1	54	-11.86	121.2	Vertical	AV	Pass
6	17977.5000	54.32	46.35	7.97	74	-19.68	331.6	Vertical	PK	Pass
6	17977.5000	47.06	46.35	0.71	54	-6.94	331.6	Vertical	AV	Pass



Report No.: WSCT-A2LA-R&E240700029A-LE
Middle channel: 2440MHz
Horizontal:

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com



Suspected Data List


NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2446.2500	46.86	7.73	39.13	74	-27.14	231.7	Horizontal	PK	Pass
1	2446.2500	37.81	7.73	30.08	54	-16.19	231.7	Horizontal	AV	Pass
2	3505.0000	55.76	9.67	46.09	74	-18.24	91.8	Horizontal	PK	Pass
2	3505.0000	37.76	9.67	28.09	54	-16.24	91.8	Horizontal	AV	Pass
3	5968.7500	57.18	21.84	35.34	74	-16.82	85.8	Horizontal	PK	Pass
3	5968.7500	47.5	21.84	25.66	54	-6.5	85.8	Horizontal	AV	Pass
4	10290.0000	44.26	38.51	5.75	74	-29.74	72.2	Horizontal	PK	Pass
4	10290.0000	37.2	38.51	-1.31	54	-16.8	72.2	Horizontal	AV	Pass
5	13932.0000	50.11	41.32	8.79	74	-23.89	1	Horizontal	PK	Pass
5	13932.0000	42.38	41.32	1.06	54	-11.62	1	Horizontal	AV	Pass
6	17877.0000	53.52	45.68	7.84	74	-20.48	322	Horizontal	PK	Pass
6	17877.0000	45.98	45.68	0.3	54	-8.02	322	Horizontal	AV	Pass



Report No.: WSCT-A2LA-R&E240700029A-LE
Vertical:

Certificate #5768.01

For Question,
Please Contact with WSCT
ct-cert.com



Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	1956.2500	49.72	2.08	47.64	74	-24.28	359.5	Vertical	PK	Pass
1	1956.2500	32.32	2.08	30.24	54	-21.68	359.5	Vertical	AV	Pass
2	3875.6250	50.94	11.53	39.41	74	-23.06	358.8	Vertical	PK	Pass
2	3875.6250	41.48	11.53	29.95	54	-12.52	358.8	Vertical	AV	Pass
3	5683.7500	57.85	21.2	36.65	74	-16.15	268.6	Vertical	PK	Pass
3	5683.7500	47.99	21.2	26.79	54	-6.01	268.6	Vertical	AV	Pass
4	10519.5000	45.1	38.83	6.27	74	-28.9	339.9	Vertical	PK	Pass
4	10519.5000	37.9	38.83	-0.93	54	-16.1	339.9	Vertical	AV	Pass
5	14022.0000	50.03	41.47	8.56	74	-23.97	176.2	Vertical	PK	Pass
5	14022.0000	42.56	41.47	1.09	54	-11.44	176.2	Vertical	AV	Pass
6	17910.0000	53.59	45.9	7.69	74	-20.41	0.5	Vertical	PK	Pass
6	17910.0000	46.26	45.9	0.36	54	-7.74	0.5	Vertical	AV	Pass






Report No.: WSCT-A2LA-R&E240700029A-LE

High channel: 2480MHz

Horizontal:

Certificate #5768.01

For Question,
Please Contact with WSCT
www.wsct-cert.com

Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2438.7500	48.79	7.7	41.09	74	-25.21	0	Horizontal	PK	Pass
1	2438.7500	38.44	7.7	30.74	54	-15.56	0	Horizontal	AV	Pass
2	3418.7500	55.99	9.46	46.53	74	-18.01	35.6	Horizontal	PK	Pass
2	3418.7500	37.45	9.46	27.99	54	-16.55	35.6	Horizontal	AV	Pass
3	5669.3750	58.11	21.14	36.97	74	-15.89	0	Horizontal	PK	Pass
3	5669.3750	47.92	21.14	26.78	54	-6.08	0	Horizontal	AV	Pass
4	9739.5000	44.4	37.92	6.48	74	-29.6	226.5	Horizontal	PK	Pass
4	9739.5000	36.42	37.92	-1.5	54	-17.58	226.5	Horizontal	AV	Pass
5	14134.5000	50	41.33	8.67	74	-24	0.7	Horizontal	PK	Pass
5	14134.5000	42.63	41.33	1.3	54	-11.37	0.7	Horizontal	AV	Pass
6	17956.5000	53.55	46.21	7.34	74	-20.45	310.2	Horizontal	PK	Pass
6	17956.5000	46.77	46.21	0.56	54	-7.23	310.2	Horizontal	AV	Pass



Report No.: WSCT-A2LA-R&E240700029A-LE

Certificate #5768.01

For Question,
Please Contact with WSCT
ct-cert.com

Suspected Data List

NO.	Freq. [MHz]	Reading [dB(uV)]	Factor [dB]	Level [dB(uV)]	Limit [dB]	Margin [dB]	Deg [°]	Polarity	Trace	Verdict
1	2438.7500	48.32	7.7	40.62	74	-25.68	350	Vertical	PK	Pass
1	2438.7500	38.52	7.7	30.82	54	-15.48	350	Vertical	AV	Pass
2	3502.5000	51.19	9.67	41.52	74	-22.81	284.4	Vertical	PK	Pass
2	3502.5000	38.13	9.67	28.46	54	-15.87	284.4	Vertical	AV	Pass
3	5513.7500	56.85	20.27	36.58	74	-17.15	85.9	Vertical	PK	Pass
3	5513.7500	46.53	20.27	26.26	54	-7.47	85.9	Vertical	AV	Pass
4	9325.5000	43.6	37.63	5.97	74	-30.4	35.1	Vertical	PK	Pass
4	9325.5000	34.95	37.63	-2.68	54	-19.05	35.1	Vertical	AV	Pass
5	12304.5000	47.74	38.69	9.05	74	-26.26	360	Vertical	PK	Pass
5	12304.5000	39.57	38.69	0.88	54	-14.43	360	Vertical	AV	Pass
6	17971.5000	54.5	46.31	8.19	74	-19.5	44.7	Vertical	PK	Pass
6	17971.5000	46.98	46.31	0.67	54	-7.02	44.7	Vertical	AV	Pass

Note:

1. All emissions not reported were more than 20dB below the specified limit or in the noise floor.
2. Emission Level= Reading Level+Probe Factor +Cable Loss.
3. Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

*****END OF REPORT*****