



M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com info@mflom.com (480) 926-3100, FAX: 926-3598

Date: September 3, 2004

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Rexon Technology Corporation
Equipment: RHP-520
FCC ID: I7ORHP-520
FCC Rules: 87

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

David E. Lee,
Compliance Test Manager

enclosure(s)
cc: Applicant
DEL/del



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com info@mflom.com (480) 926-3100, FAX: 926-3598

Transmitter Certification

of

FCC ID: I7ORHP-520

Model: RHP-520

to

Federal Communications Commission

Rule Part(s) 87

Date of report: September 3, 2004

On the Behalf of the Applicant:

Rexon Technology Corporation
Taichung Export Processing Zone
11-3, Chien-Kuo Road, Tantz, Taichung,
Taiwan, ROC

At the Request of:

Check #0036772

Edmo Distributors Inc.
5505 E. Rutter Ave.
Spokane, WA 99212

Attention of:

Tim Gump

Supervised by:

A handwritten signature in black ink, appearing to read "D. Lee", with a horizontal line underneath.

David E. Lee,
Compliance Test Manager

List of Exhibits

(FCC **Certification** (Transmitters) - Revised 9/28/98)

Applicant: Rexon Technology Corporation
Taichung Export Processing Zone
11-3,Chien-Kuo Road, Tantz, Taichung,
Taiwan, ROC

FCC ID: I7ORHP-520

By Applicant:

1. Letter of Authorization
2. Confidentiality Request: 0.457 And 0.459
3. Identification Drawings, 2.1033(c)(11)
 - Label
 - Location of Label
 - Compliance Statement
 - Location of Compliance Statement
4. Photographs, 2.1033(c)(12)
5. Documentation: 2.1033(c)
 - (3) User Manual
 - (9) Tune Up Info
 - (10) Schematic Diagram
 - (10) Circuit Description
 - Block Diagram
 - Parts List
 - Active Devices
6. SAR Attestation

By M.F.A. Inc.:

- A. Testimonial & Statement of Certification

The Applicant has been cautioned as to the following:**15.21 Information to the User.**

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

<u>Rule</u>	<u>Description</u>	<u>Page</u>
	Test Report	1
2.1033(c)(14)	Rule Summary	2
	Standard Test Conditions and Engineering Practices	3
2.1033(c)	General Information Required	5
2.1046(a)	Carrier Output Power (Conducted)	8
2.1046(a)	ERP Carrier Power (Radiated)	10
2.1051	Unwanted Emissions (Transmitter Conducted)	12
2.1053(a)	Field Strength of Spurious Radiation	15
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	19
2.1047(a)	Audio Frequency Response	23
2.1047(b)	Modulation Limiting	25
2.1055(a)(1)	Frequency Stability (Temperature Variation)	27
2.1055(b)(1)	Frequency Stability (Voltage Variation)	29
2.202(g)	Necessary Bandwidth and Emission Bandwidth	31

Page Number

1 of 31.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a)

Test Report

b) Laboratory:

(FCC: 31040/SIT)
(Canada: IC 2044)M. Flom Associates, Inc.
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

c) Report Number:

d0490008

d) Client:

Edmo Distributors Inc.
5505 E. Rutter Ave.
Spokane, WA 99212

e) Identification:

RHP-520
FCC ID: I7ORHP-520
EUT Description: Airband COM/NAV with WX

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:

September 3, 2004

EUT Received:

August 20, 2004

h, j, k):

As indicated in individual tests.

i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



David E. Lee, Lab Manager

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

Page Number

2 of 31.

Sub-part

2.1033(c)(14):**Test and Measurement Data**

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 – Domestic Public Fixed Radio Services
- ☐ 22 – Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 – International Fixed Public Radiocommunication services
- ☐ 24 – Personal Communications Services
- ☐ 74 Subpart H - Low Power Auxiliary Stations
- ☐ 80 – Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radio Beacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☒ 87 – Aviation Services
- ☐ 90 – Private Land Mobile Radio Services
- ☐ 94 – Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 – Fixed Microwave Services

**Standard Test Conditions
and
Engineering Practices**

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2001, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Frequencies 118.000MHz, 121.500MHz and 136.975MHz were used for conducted emissions. For radiated emissions 127.000MHz was used in place of 121.500MHz to avoid interference on this distress frequency.


Measurement results, unless otherwise noted, are worst-case measurements.



A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 – 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**



NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at <http://ts.nist.gov/mra> under the 'Asia' category."

Page Number

5 of 31.

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to Part 87

Sub-part 2.1033**(c)(1): Name and Address of Applicant:**

Rexon Technology Corporation
Taichung Export Processing Zone
11-3,Chien-Kuo Road, Tantz, Taichung,
Taiwan, ROC

Manufacturer:

Applicant

(c)(2): FCC ID:

I7ORHP-520

Model Number:

RHP-520

(c)(3): Instruction Manual(s):

Please see attached exhibits

(c)(4): Type of Emission:

6K00A3E

(c)(5): Frequency Range, MHz:

118 to 136.975

(c)(6): Power Rating, Watts: X Switchable Variable

5W PEP , 1W PEP

 N/A**(c)(7): Maximum Power Rating, Watts:**

10W

DUT Results:Passes X Fails

Page Number

6 of 31.

Information for Push-To-Talk Devices

Type and number of antenna to be used for this device:

One, ¼ wave whip

Maximum antenna gain for antenna indicated above:

0dBi

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?

No – Restricted Duty Cycle (<50%)

Other hardware or operating restrictions that could limit a person's RF Exposure:

Time out timer

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:

No

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?

1.5cm

Can device access wire-line services to make phone calls, either directly or through an operator?

No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?

Yes – in manual

Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:

In manual

Page Number

7 of 31.

Subpart 2.1033 (continued)

(c)(8): Voltages & currents in all elements in final RF stage, including final transistor or solid-state device:

Collector Current, A	=	1.0 Hi Pwr, 0.6 Lo Pwr
Collector Voltage, Vdc	=	12.0
Supply Voltage, Vdc	=	12.0

(c)(9): **Tune-Up Procedure:**

Please see attached exhibits

(c)(10): **Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please see attached exhibits

(c)(11): **Label Information:**

Please see attached exhibits

(c)(12): **Photographs:**

Please see attached exhibits

(c)(13): **Digital Modulation Description:**

☐ Attached Exhibits
☒ N/A

(c)(14): **Test and Measurement Data:**

Follows

Page Number 8 of 31.

Name of Test: Carrier Output Power (Conducted)


Specification: 47 CFR 2.1046(a)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

Measurement Procedure

- A) The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an RF Power Meter.
- B) Measurement accuracy is $\pm 3\%$.

Transmitter Test Set-Up: RF Power Output



Asset	Description	s/n		
(1)	Coaxial Attenuator			
X	i00231/2 PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
	i00122/3 NARDA 766 (10 dB)	7802 or 7802A	NCR	
(2)	Power Meters			
X	i00020 HP 8901A Power Mode	2105A01087	12 mo	Apr-04
(3)	Frequency Counter			
X	i00020 HP 8901A Frequency Mode	2105A01087	12 mo	Apr-04

Page Number

9 of 31.

Measurement Results
(Worst case)

Frequency of Carrier, MHz = 136.975, 121.500, 118.000
Ambient Temperature = 23°C ± 3°C

Power Setting		RF Power, Watts
High	36.99	5.0
Low	30.00	1.0

Performed by:

David E. Lee,
Compliance Test Manager

Page Number 10 of 31.

Name of Test: ERP Carrier Power (Radiated)

Specification: TIA/EIA 603A (Substitution Method)


Measurement Procedure

Definition

The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

Method of Measurement:

- A) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



- B) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.
- C) Repeat step B) for seven additional readings at 45° interval positions of the turntable.
- D) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.
- E) Calculate the average radiated output power from the readings in step C) and D) by the following:

$$\text{average radiated power} = 10 \log_{10} S 10(\text{LVL} - \text{LOSS})/10 \text{ (dBm)}$$

Page Number

11 of 31.

Test Equipment

Asset	Description	s/n	Cycle	Last Cal
Transducer				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-03
X i00089	April 2001 200MHz-1GHz	001500	12 mo.	Sep-03
X i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Jan-04
Amplifier				
X i00028	HP 8449A	2749A00121	12 mo.	May-04
Spectrum Analyzer				
X i00029	HP 8563E	3213A00104	12 mo.	May-04
X i00033	HP 85462A	3625A00357	12 mo.	Sep-03
Substitution Generator				
X i00067	HP 8920A Communication TS	3345U01242	12 mo.	Oct-03
i00207	HP 8753D Network Analyzer	3410A08514	12 mo.	Jul-04

Measurement Results

	118.000000 MHz		127.000000 MHz		136.975000 MHz	
	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db	LVL, dbm	Path Loss, db
0°	9.4	3.9	23.6	5.8	21.0	3.3
45°	9.1		23.7		20.6	
90°	9.3		23.7		20.9	
135°	9.2		23.5		20.9	
180°	9.2		23.2		20.7	
225°	9.2		23.2		20.5	
270°	9.1		23.5		21.1	
315°	9.2		23.7		20.6	

	118.000 MHz	127.000 MHz	136.975 MHz
Av. Radiated Power:	13.11dbm	29.31dbm	24.09dbm

Performed by:


Samir Mahmoud
Test Technician

Page Number 12 of 31.

Name of Test: Unwanted Emissions (Transmitter Conducted)


Specification: 47 CFR 2.1051

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

Measurement Procedure

- A) The emissions were measured for the worst case as follows:
- 1). within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - 2). from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
- B) The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.

Transmitter Test Set-Up: Spurious Emission



Asset	Description	s/n		
(1) Audio Oscillator/Generator				
X	i00017	HP 8903A Audio Analyzer	2216A01753	12 mo
	i00002	HP 3336B Synthesizer / Level Gen.	1931A01465	12 mo
(2) Coaxial Attenuator				
X	i00231/2	PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR
	i0012/3	NARDA 766 (10 dB)	7802 or 7802A	NCR
(3) Filters; Notch, HP, LP, BP				
X	i00126	Eagle TNF-1 Notch Filter	100-250	NCR
	i00125	Eagle TNF-1 Notch Filter	50-60	NCR
	i00124	Eagle TNF-1 Notch Filter	250-850	NCR
(4) Spectrum Analyzer				
X	i00048	HP 8566B Spectrum Analyzer	2511A01467	12 mo
	i00029	HP 8563E Spectrum Analyzer	3213A00104	12 mo

Page Number 13 of 31.

Name of Test: Unwanted Emissions (Transmitter Conducted)


Measurement Results
(Worst Case)

Summary:

Frequency of carrier, MHz	=	136.975, 121.500, 118.000
Spectrum Searched, GHz	=	0 to 10 x F_c
Maximum Response, Hz	=	1410
All Other Emissions	=	= 20 dB Below Limit
Limit(s), dBc		$-(43 + 10 \times \log P) = -50$ (5 Watts)

Tabulated Results follow:

Performed by:


David E. Lee,
Compliance Test Manager

Page Number 14 of 31.

Name of Test: Unwanted Emissions (Transmitter Conducted)

Measurement Results

State: High Power

Ambient Temperature: 23°C ± 3°C

Frequency Tuned, MHz	Frequency Emission, MHz	Level, dBm	Level, dBc	Margin, dB
118.000000	54.320000	-31.7	-66.7	-18.7
118.000000	59.110000	-26.3	-61.3	-13.3
121.500000	60.870000	-33.1	-68.1	-20.1
136.975000	68.620000	-32.2	-67.2	-19.2
121.500000	100.580000	-29.5	-64.5	-16.5
136.975000	115.870000	-33.8	-68.8	-20.8
118.000000	139.520000	-30.3	-65.3	-17.3
121.500000	143.040000	-30.5	-65.5	-17.5
118.000000	172.420000	-31.3	-66.3	-18.3
118.000000	177.200000	-25.5	-60.5	-12.5
121.500000	182.540000	-33.8	-68.8	-20.8
118.000000	235.999000	-27.3	-62.3	-14.3
121.500000	243.001000	-25.2	-60.2	-12.2
136.975000	273.944000	-31.5	-66.5	-18.5
118.000000	353.992000	-27.4	-62.4	-14.4
121.500000	364.500000	-26.8	-61.8	-13.8
136.975000	410.923000	-31.1	-66.1	-18.1
118.000000	471.990000	-32.1	-67.1	-19.1
121.500000	486.005000	-32.6	-67.6	-19.6
136.975000	547.892000	-36.8	-71.8	-23.8
118.000000	589.990000	-41.0	-76.0	-28.0
121.500000	607.512000	-41.0	-76.0	-28.0
136.975000	684.884000	-40.1	-75.1	-27.1
118.000000	708.406000	-44.2	-79.2	-31.2
121.500000	728.999000	-43.9	-78.9	-30.9
136.975000	821.470000	-44.0	-79.0	-31.0
118.000000	825.950000	-43.9	-78.9	-30.9
121.500000	850.591000	-42.6	-77.6	-29.6
118.000000	944.171000	-44.7	-79.7	-31.7
136.975000	958.446000	-43.8	-78.8	-30.8
121.500000	972.445000	-44.1	-79.1	-31.1
118.000000	1062.281000	-43.6	-78.6	-30.6
121.500000	1093.523000	-43.8	-78.8	-30.8
136.975000	1095.690000	-44.0	-79.0	-31.0
118.000000	1180.325000	-43.8	-78.8	-30.8
121.500000	1214.843000	-44.2	-79.2	-31.2
136.975000	1232.591000	-43.4	-78.4	-30.4
118.000000	1297.527000	-44.3	-79.3	-31.3
121.500000	1336.686000	-43.3	-78.3	-30.3
136.975000	1369.967000	-43.9	-78.9	-30.9

Page Number 15 of 31.

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)

Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917


Measurement Procedure

Definition:

Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.


Method of Measurement:

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth = 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load that is placed on the turntable. The RF cable to this load should be of minimum length.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Page Number

17 of 31.

Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =

$$10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I)}$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment

Asset	Description	s/n	Cycle	Last Cal
Transducer				
	i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo. Sep-03
X	i00089	Apriel 2001 200MHz-1GHz	001500	12 mo. Sep-03
X	i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo. Jan-04
Amplifier				
X	i00028	HP 8449A	2749A00121	12 mo. May-04
Spectrum Analyzer				
X	i00029	HP 8563E	3213A00104	12 mo. May-04
X	i00033	HP 85462A	3625A00357	12 mo. Sep-03
Substitution Generator				
X	i00067	HP 8920A Communication TS	3345U01242	12 mo. Oct-03
	i00207	HP 8753D Network Analyzer	3410A08514	12 mo. Jul-04
Microphone, Antenna Port, and Cabling				
Microphone	N	Cable Length	N/A	Meters
Antenna Port Terminated	<u>Y</u>	Load	<u>N/A</u>	Antenna Gain <u>Unity</u>
All Ports Terminated by Load	<u>Y</u>	Peripheral	<u>None</u>	

Page Number 18 of 31.

Reported in Watts ERP for Part 87 Reports Only

Name of Test: Radiated Spurious Emissions

Measurement Results

Ambient Temperature: 23°C ± 3°C

g0480130: 2004-Aug-24 Tue 16:01:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C

Frequency Tuned, MHz	Frequency Emission, MHz	Meter, dBuV/m	CF, dB	ERP, dBm	ERP, Watts
108.000000	129.700000	17.95	14.71	-64.7	<1nW
127.000000	148.700000	15.26	15.47	-66.6	<1nW
136.975000	158.675000	13.25	15.54	-68.6	<1nW
108.000000	259.400000	11.56	22.64	-63.2	<1nW
127.000000	297.400000	9.06	29.83	-58.5	1.41nW
136.975000	317.350000	8.02	20.19	-69.2	<1nW
108.000000	389.093800	12.55	22.36	-62.5	<1nW
127.000000	446.100000	8.59	23.73	-65.1	<1nW
136.975000	476.025000	7.42	24.37	-65.6	<1nW
108.000000	518.762500	5.63	26.09	-65.7	<1nW
127.000000	594.538000	1.66	30.67	-65	<1nW
136.975000	634.700000	8.15	31.75	-57.5	1.75nW
108.000000	648.450000	3.33	32.05	-62	<1nW
127.000000	743.488000	6.5	32.78	-58.1	1.55nW
136.975000	793.375000	6.03	32.42	-58.9	1.29nW

Performed by:



David E. Lee,
Compliance Test Manager

Page Number 19 of 31.

Name of Test: Emission Masks (Occupied Bandwidth)


Specification: 47 CFR 2.1049(c)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

Measurement Procedure

- A) The EUT and test equipment were set up as shown below
- B) For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
- C) For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
- D) The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

Transmitter Test Set-Up: Occupied Bandwidth




Asset	Description	s/n		
(1) Audio Oscillator/Generator				
X i00017	HP 8903A Modulation Meter	2216A01753	12 mo	Nov-04
(2) Coaxial Attenuator				
X i00231/2	PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
i00123	NARDA 766 (10 dB)	7802A	NCR	
(3) Interface				
X i00021	HP 8954A Transceiver Interface	2146A00159	NCR	
(4) Spectrum Analyzer				
X i00048	HP 8566B Spectrum Analyzer	2511A01467	12 mo	Jul-04
i00029	HP 8563E Spectrum Analyzer	3213A00104	12 mo	May-04

Page Number.

20 of 31.


Name of Test: Emission Masks (Occupied Bandwidth)
g0470134: 2004-Aug-26 Thu 15:53:00
STATE: 2:High Power



POWER:
MODULATION:

HIGH
VOICE: 2500 Hz SINE WAVE
MASK: FCC, 87.139, AM, 25kHz BW

Performed by:


David E. Lee,
Compliance Test Manager

Page Number 21 of 31.


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g0480139: 2004-Aug-26 Thu 12:18:00

State: 1:Low Power

Ambient Temperature: 23°C ± 3°C



Power:

LOW

Modulation:

VOICE: 2500 Hz SINE WAVE
[10.5dB in-line attenuation]

Performed by:

David E. Lee,
Compliance Test Manager

Page Number

22 of 31.

Name of Test:


Emission Masks (Occupied Bandwidth)

Measurement Results

g0480138: 2004-Aug-26 Thu 12:13:00

State: 2: High Power

Ambient Temperature: 23°C ± 3°C




Power:

HIGH

Modulation:

VOICE: 2500 Hz SINE WAVE
[10.5dB in-line attenuation]

Performed by:


David E. Lee,
Compliance Test Manager

Page Number 23 of 31.

Name of Test: Audio Frequency Response


Specification: 47 CFR 2.1047(a)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

Measurement Procedure

- A) The EUT and test equipment were set up as shown below.
- B) The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
- C) With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
- D) The response in dB relative to 1 kHz was measured, using the HP 8901A Modulation Meter.

Transmitter Test Set-Up: Audio Frequency Response



Asset	Description (as applicable)	s/n		
(1)	Audio Oscillator			
X	i00017 HP 8903A	2216A01753	12 mo	Nov-03
(2)	Coaxial Attenuator			
X	i00231/2 PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
(3)	Modulation Analyzer			
X	i00020 HP 8901A	2105A01087	12 mo	Apr-04
(4)	Audio Analyzer			
X	i00017 HP 8903A	2216A01753	12 mo	Nov-03

Page Number 24 of 31.


Name of Test: Audio Frequency Response

Measurement Results

g0480105: 2004-Aug-26 Thu 16:31:00

State: 0:General

Ambient Temperature: 23°C ± 3°C



Frequency of Maximum Audio Response, Hz = 1410

Additional points:

Frequency, Hz	Level, dB
300	- 3.34
20000	- 10.28
30000	- 10.96
50000	- 10.65

Performed by:

David E. Lee,
Compliance Test Manager

Page Number 25 of 31.

Name of Test: Modulation Limiting


Specification: 47 CFR 2.1047(b)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

Measurement Procedure

- A) The signal generator was connected to the input of the EUT as shown below.
- B) The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
- C) The input level was varied from 30% modulation to at least 20 dB higher than the saturation point.
- D) Measurements were performed for both negative and positive modulation and the respective results were recorded.

Transmitter Test Set-Up: Modulation Limiting



Asset	Description (as applicable)	s/n		
(1)	Audio Oscillator			
X	i00017 HP 8903A	2216A01753	12 mo	Nov-03
(2)	Coaxial Attenuator			
X	i00231/2 PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
(3)	Modulation Analyzer			
X	i00020 HP 8901A	2105A01087	12 mo	Apr-04
(4)	Audio Analyzer			
X	i00017 HP 8903A	2216A01753	12 mo	Nov-03

Page Number 26 of 31.

Name of Test: Modulation Limiting

Measurement Results

State: Ambient Temperature: 23°C ± 3°C

Device is Amplitude Modulated

Absolute	Scale Relative, dB	300 k	1 k	2.5 k
-70	-35	2.3%	3.6%	3.4
-65	-30	3.2	5.2	4.6
-60	-25	4.5	8.1	7.9
-55	-15	7.5	13.2	13.1
-50	-10	11.6	21.7	21.8
-45	-5	18.6	35.3	35.7
-40	0	33.6	50%	54.8
-35	+5	52.9	78.4	78.3
-30	+10	75.4	94.2	94.5
-25	+15	92.7	99.4	99.4
-20	+20	98.5	99.8	99.8
-15	+25	98.3	99.8	99.9

Performed by:



David E. Lee,
Compliance Test Manager

Page Number 27 of 31.

Name of Test: Frequency Stability (Temperature Variation)


Specification: 47 CFR 2.1055(a)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Measurement Procedure

- A) The EUT and test equipment were set up as shown on the following page.
- B) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
- C) With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
- D) The temperature tests were performed for the worst case.

Transmitter Test Set-Up: Temperature Variation



Asset	Description	s/n		
(1) Temperature, Humidity, Vibration				
X i00027	Tenney Temp. Chamber	9083-765-234	NCR	
(2) Coaxial Attenuator				
X i00231/2	PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
i00122/3	NARDA 766 (10 dB)	7802 or 7802A	NCR	
(3) RF Power				
X i00067	HP 8920A Communications TS	3345U01242	12 mo	Oct-03
(4) Frequency Counter				
X i00067	HP 8920A Communications TS	3345U01242	12 mo	Oct-03

Page Number 28 of 31.


Name of Test: Frequency Stability (Temperature Variation)

Measurement Results


g0480106: 2004-Aug-27 Fri 07:59:17

State: 0:General

Ambient Temperature: 23°C ± 3°C



Performed by:


David E. Lee,
Compliance Test Manager

Page Number 29 of 31.

Name of Test: Frequency Stability (Voltage Variation)


Specification: 47 CFR 2.1055(d)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Measurement Procedure

- A) The EUT was placed in a temperature chamber (if required) at $25 \pm 5^\circ\text{C}$ and connected as shown below.
- B) The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- C) The variation in frequency was measured for the worst case.

Transmitter Test Set-Up: Voltage Variation



Asset	Description	s/n		
(1) Temperature, Humidity, Vibration				
i00027	Tenney Temp. Chamber	9083-765-234	NCR	
(2) Coaxial Attenuator				
X i00231/2	PASTERNAK PE7021-30 (30 dB)	231 or 232	NCR	
i00122/3	NARDA 766 (10 dB)	7802 or 7802A	NCR	
(3) RF Power				
X i00067	HP 8920A Communications TS	3345U01242	12 mo	Oct-03
(4) Frequency Counter				
X i00067	HP 8920A Communications TS	3345U01242	12 mo	Oct-03

Page Number

30 of 31.

Results: Frequency Stability (Voltage Variation)

State: High Power, 121.500MHz

Ambient Temperature: 23°C ± 3°C

Limit, ppm = 10
 Limit, Hz = 1215
 Battery End Point (Voltage) = 7.7

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	10.71	121.500000	0	0.00
100	12.6	121.500000	0	0.00
115	14.49	121.500010	10	0.08
61	7.7	121.499980	-20	-0.16

Performed by:



David E. Lee,
Compliance Test Manager

Page Number 31 of 31.

Name of Test: Necessary Bandwidth and Emission Bandwidth


Specification: 47 CFR 2.202(g)

Modulation = 6K00A3E

Necessary Bandwidth Calculation:

Maximum Modulation (M), kHz	3.0
Maximum Deviation (D), kHz	= N/A
Constant Factor (K)	= 2
Necessary Bandwidth (B_N), kHz	= 6.0

Performed by:


David E. Lee,
Compliance Test Manager

END OF TEST REPORT

**Testimonial
and
Statement of Certification**

This is to Certify:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



David E. Lee,
Compliance Test Manager