Remark	Description	Editor	Date

正面

封底

ERO1X PRO Mesh Extender

High-quality WiFi 6 mesh extender, designed to elevate your surfing experience to the highest level. This powerful extender seamlessly expands your network coverage, ensuring fast and reliable connectivity throughout your home. With easy setup and robust performance, it guarantees a smooth and interruption-free online experience, whether you're streaming, gaming, or working from home. Say goodbye to dead zones and buffering, and embrace the future of top-tier WiFi with our exceptional WiFi 6 mesh extender.

1G LAN Ports | MU-MIMO | Easy & Quick Installation | WiFi 6 AX | Whole-Home Mesh Wi-Fi

Package Contents:

Extender ERO1X PRO | Power Adapter | LAN Cable | Quick Installation Guide

LED Indicators:

Stable - Booting up/gateway without Internet
Blinking - connection problem to gateway

Stable - Ready for Adoption
Blinking - Adoption in Progress

Stable - Connected to Internet
Blinking - Weak WiFi signal, Improve location

封面

ERO1X PRO

Quick Installation Guide

反面

Connect the Hardware

Follow these steps only after you have placed your home gateway and adopted it in the HomePass® by Plume app.

1. Connect the supplied power adapter to the ERO1X PRO and a power outlet.
2. Turn on the router by pressing the power button.
3. On the HomePass® by Plume app in Home page, scroll down to the Adapt section.
4. Tap the ⋮ to open the Options Menu.
5. Tap on Add a pod.
6. Tap on Other setup options...
7. You can choose to 'Scan a QR code' or 'Enter a serial number' to add the device. The QR code and serial number are located on the right side of the device.
8. Click 'Next,' and the device will be added. All WiFi configurations will adopt from your home router, creating one mesh Wireless Network (SSID).



Back Panel



FCC Regulations:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
This device has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiated radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.
However, there is no guarantee that interference will not occur in a particular installation if this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the
following measures:
- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Note:
Caution: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

RF Exposure Information

This device meets the government's requirements for exposure to radio waves.
This device is designed and manufactured not to exceed the emission limits for exposure to radio frequency (RF) energy set by the Federal Communications Commission of the U.S. Government.

This device complies with FCC radiation exposure limits set forth for an uncontrolled environment.
In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antenna shall not be less than 22 cm during normal operation.

折痕线，无需印刷

NOTES(技术要求)：

1.Dimension after folding(折叠后尺寸)：150*150mm
2.Print colour(印刷颜色):4Colour printing (四色印刷).
3.Material(材质)：128g copperplate paper(128g 铜版纸).
4.Coating(表面处理)：Varnishing(双面过光油)
5.Binding process(装订工艺)：Paper folding(折页)——对折
6.Output lpi(输出网线)：200 lpi.
7.Tolerance(公差)：L(长)*W(宽):±1mm.
8.Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards.
(原材料及后处理工艺均能满足我司《环保技术标准》要求).

DIM \ TOL±				
RANGE	C1	C2	C3	C4
0~6	0.1	0.1	0.15	0.2
6~30	0.2	0.3	0.4	0.5
30~80	0.25	0.5	0.9	1.2
80~180	0.3	0.8	1.2	1.5
180~315	0.5	1.3	1.8	3
315~500	0.7	1.5	2.5	4
500~800	0.9	1.8	3	5
ANG.TOL±	0°~30°/0.1°		30°~60°/0.3°	60°~90°/0.5°

CUSTOMER: Heights			T&W 同维 SHENZHEN GONGJIN ELECTRONICS CO., LTD.			
TITLE: QUICK INSTALLATION GUIDE		MODEL: ERO1X PRO			PART NO: 614000005390	
UNIT'S	mm	VER:	V01	DRAW	郭海涛	DATE: 20231011
MAT'L	/	SCALE	N/A	CHECK	赵 柳	
FINISH	/	SHEET	1/1	PDE	N/A	