

Test Report

Verified code: 826245

Report No.: E20230828994601-8

Customer: Lumi United Technology Co., Ltd

Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District,
Nanshan District, Shenzhen, China

Sample Name: Motion and Light Sensor P2

Sample Model: ML-S03D

Receive Sample Date: Aug.28,2023

Test Date: Aug.30,2023 ~ Sep.05,2023

Reference Document: 47 CFR, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices

Test Result: Pass

Prepared by: Chen Xiacong
Chen Xiacong

Reviewed by: Jiang Tao
Jiang Tao

Approved by: Xiao Liang
Xiao Liang

GRG METROLOGY & TEST GROUP CO., LTD.

Issued Date: 2023-11-21

GRG METROLOGY & TEST GROUP CO., LTD.

Address: No.163,Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1. GENERAL DESCRIPTION OF EUT..... 5

1.1 APPLICANT 5

1.2 MANUFACTURER..... 5

1.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST 5

2. LABORATORY..... 6

2.1 LABORATORY 6

2.2 ACCREDITATIONS 6

3. LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE 7

4. CALCULATION METHOD 8

5. ESTIMATION RESULT 9

5.1 MEASUREMENT RESULTS 9

6. CONCLUSION 10

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E20230828994601-8	Original Issue	2023-11-02

----- The following blanks -----

1. GENERAL DESCRIPTION OF EUT

1.1 APPLICANT

Name: Lumi United Technology Co., Ltd

Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China

1.2 MANUFACTURER

Name: Lumi United Technology Co., Ltd

Address: B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China

1.3 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Motion and Light Sensor P2

Model No.: ML-S03D

Adding Model: ML-S03E

Models Difference: ML-S03E & ML-S03D have the same technical construction including circuit diagram, PCB LAYOUT, hardware version and software version identical, except sales area and packaging are different.

Trade Name: Aqara

FCC ID: 2AKIT-MLS03

Power supply: DC 3V power supplied by battery

Frequency Band: 2402MHz-2480MHz for BLE, 2405MHz-2480MHz for Thread

Transmit Power: BLE for 1Mbps:9.82dBm, BLE for 2Mbps:9.81dBm, Thread: 8.26dBm

Modulation type: GFSK for BLE, O-QPSK for Thread

Antenna Specification: BLE&Thread:PIFA antenna with 0.95dBi gain (Max)

Temperature Range: -10 °C ~ 55 °C

Hardware Version: X3

Software Version: 0.0.0.1

Sample No: E20230828994601-0001, E20230828994601-0002

Note 1: This report is made solely on the basis of such data and/or information. We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

Note 2: All the tests were performed on the model ML-S03D.

2. LABORATORY

2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of GRG METROLOGY & TEST GROUP CO., LTD.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District
Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

2.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to GB/T 27025(ISO/IEC 17025:2017)

USA A2LA(Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada ISED (Company Number: 24897, CAB identifier:CN0069)

USA FCC (Registration Number: 759402, Designation Number:CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,

<http://www.grgtest.com>

----- The following blanks -----

3. LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

General

According to the KDB 447498 D04 Interim General RF Exposure Guidance v01, General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table 4.1 to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE 4.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2 f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2 R^2$
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

For mobile devices that are not exempt per Table 4.1 at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than $ERP_{20\text{cm}}$ in Formula (4.1).

Formula (4.1):

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

4. CALCULATION METHOD

Predication of MPE limit at a given distance

$EIRP(dBm) = \text{Maximum Tune-up Output power (dBm)} + \text{Maximum antenna gain(dBi)}$

$ERP(dBm) = EIRP(dBm) - 2.15$

R=minimum distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, $d=20\text{cm}$, as well as the maximum gain of the used as following information, the RF power ERP can be obtained.

Table 1 Antenna Specification

Mode	Antenna type	Internal Identification	Maximum antenna gain
BLE 1M	PIFA antenna	Antenna 1	0.95dBi
BLE 2M	PIFA antenna	Antenna 1	0.95dBi
Thread	PIFA antenna	Antenna 1	0.95dBi

Table 2 Transmit Power

Mode	Maximum Output Power (dBm)	Maximum Tune-up Output power (dBm)
BLE 1M	9.82	9.00 ± 1.00
BLE 2M	9.81	9.00 ± 1.00
Thread	8.26	8.00 ± 1.00

----- The following blanks -----

5. ESTIMATION RESULT

5.1 MEASUREMENT RESULTS

STANDALONE MPE

Mode	Frequency (MHz)	Tune-up Output power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	ERP (dBm)	ERP (W)	Threshold ERP(W)
BLE 1M	2402- 2480	10.00	0.95	10.95	8.80	0.008	0.768
BLE 2M	2402- 2480	10.00	0.95	10.95	8.80	0.008	0.768
Thread	2405-0475	9.00	0.95	9.95	7.80	0.006	0.768

Remark:

1. RF Exposure use distance is 20cm from manufacturer declaration of user manual.
2. Threshold $ERP(W) = 19.2R^2(W) = 19.2 \times 0.2 \times 0.2(W) = 0.768(W)$.
3. The BLE and Thread do not support simultaneous transmission
4. $ERP(dBm) = EIRP(dBm) - 2.15$

----- The following blanks -----

6. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of Report -----