


FCC SAR TEST REPORT

FCC ID : A4RGD2WG
Equipment : Wireless Device
Model Name : GD2WG
Applicant : Google LLC
1600 Amphitheatre Parkway, Mountain
View, California, 94043 USA
Standard : FCC 47 CFR Part 2 (2.1093)

The product was received on May 18, 2023 and testing was started from Jun. 05, 2023 and completed on Jun. 09, 2023. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. EMC & Wireless Communications Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	6
4. RF Exposure Limits.....	8
4.1 Uncontrolled Environment.....	8
4.2 Controlled Environment.....	8
5. Specific Absorption Rate (SAR).....	9
5.1 Introduction	9
5.2 SAR Definition.....	9
6. System Description and Setup	10
6.1 Test Site Location.....	10
6.2 E-Field Probe	11
6.3 Data Acquisition Electronics (DAE)	11
6.4 Phantom.....	12
6.5 Device Holder.....	13
7. Measurement Procedures	14
7.1 Spatial Peak SAR Evaluation.....	14
7.2 Power Reference Measurement.....	15
7.3 Area Scan	15
7.4 Zoom Scan.....	16
7.5 Volume Scan Procedures.....	17
7.6 Power Drift Monitoring.....	17
8. Test Equipment List.....	18
9. System Verification	19
9.1 Tissue Verification	19
9.2 System Performance Check Results.....	20
10. UMTS/LTE Output Power (Unit: dBm)	21
11. WiFi/Bluetooth Output Power (Unit: dBm)	41
12. SAR Test Results	43
12.1 Head SAR	44
12.2 Extremity SAR.....	47
13. Simultaneous Transmission Analysis.....	50
13.1 Head Exposure Conditions	50
13.2 Extremity Exposure Conditions	50
14. Uncertainty Assessment	51
15. References.....	51
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA351307	01	Initial issue of report	Jun. 26, 2023
FA351307	02	Update section11	Jul. 03, 2023

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) for Google LLC, Wireless Device, GD2WG, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary		Highest Simultaneous Transmission 1g SAR (W/kg)	Highest Simultaneous Transmission 10g SAR (W/kg)
			Head (Separation 10mm)	Extremity (Separation 0mm)		
			1g SAR (W/kg)	10g SAR (W/kg)		
Licensed	WCDMA	WCDMA II	0.29	0.13	0.34	0.55
		WCDMA IV	0.23	0.14		
		WCDMA V	<0.01	0.45		
	LTE	LTE Band 12 / 17	<0.01	0.50		
		LTE Band 13	<0.01	0.42		
		LTE Band 2 / 25	0.28	0.10		
		LTE Band 5 / 26	<0.01	0.47		
		LTE Band 4 / 66	0.23	0.10		
		LTE Band 71	<0.01	0.48		
DTS	WLAN	2.4GHz WLAN	0.01	0.03	0.29	0.53
DSS	2.4GHz Band	Bluetooth	0.05	0.05	0.34	0.55
Date of Testing:			2023/06/05 ~ 2023/06/09			

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Head 1g SAR, 4.0 W/kg for Extremity 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang
Report Producer: Daisy Peng

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Wireless Device
Model Name	GD2WG
FCC ID	A4RGD2WG
S / N	35201RTJWN0CXJ
Wireless Technology and Frequency Range	WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	RMC 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM WLAN: 802.11b/g/n HT20 Bluetooth BR/EDR/LE
Remark: 1. There are four strap materials in SAR testing. The Strap 1 perform full SAR testing and Strap 2/3/4 spot check worst case from full SAR testing. 2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously. 3. According to KDB 447498 D01 section6.2, transmitters that are built-in within a wrist devices typically operate in speaker mode for voice communication, with the device worn on the wrist and positioned next to the mouth. Next to the mouth exposure requires 1 -g SAR and the wrist-worn condition requires 10-g extremity SAR. When SAR evaluation is required, next to the mouth use is evaluated with the front of the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium.	

3.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05												
FCC ID			A4RGD2WG									
Equipment Name			Wireless Device									
Operating Frequency Range of each LTE transmission band			LTE Band 2: 1850 MHz ~ 1910 MHz									
			LTE Band 4: 1710 MHz ~ 1755 MHz									
			LTE Band 5: 824 MHz ~ 849 MHz									
			LTE Band 12: 699 MHz ~ 716 MHz									
			LTE Band 13: 777 MHz ~ 787 MHz									
			LTE Band 17: 704 MHz ~ 716 MHz									
			LTE Band 25: 1850 MHz ~ 1915 MHz									
			LTE Band 26: 814 MHz ~ 849 MHz									
			LTE Band 66: 1710 MHz ~ 1780 MHz									
			LTE Band 71: 663 MHz ~ 698 MHz									
Channel Bandwidth			LTE Band 2:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 4:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 13: 5MHz, 10MHz									
			LTE Band 17: 5MHz, 10MHz									
			LTE Band 25:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz									
			LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 71: 5MHz, 10MHz, 15MHz, 20MHz									
uplink modulations used			QPSK / 16QAM									
LTE Voice / Data requirements			Voice and Data only									
LTE MPR permanently built-in by design			Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3									
			Modulation		Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	
					1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz		
			QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1		
			16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1		
			16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2		
			64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2		
			64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3		
			256 QAM	≥ 1						≤ 5		
LTE A-MPR			In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)									
Spectrum plots for RB configuration			A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.									
Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745

LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)				
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)					
L	23205		779.5		23230		782					
M	23230		782									
H	23255		784.5									
LTE Band 17												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)					
L	23755		706.5		23780		709					
M	23790		710		23790		710					
H	23825		713.5		23800		711					
LTE Band 25												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26047	1850.7	26055	1851.5	26065	1852.5	26090	1855	26115	1857.5	26140	1860
M	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880
H	26683	1914.3	26675	1913.5	26665	1912.5	26640	1910	26615	1907.5	26590	1905
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5		
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5		
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5		
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770
LTE Band 71												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	133147	665.5	133172	668	133197	670.5	133222	673				
M	133297	680.5	133297	680.5	133297	680.5	133297	680.5				
H	133447	695.5	133422	693	133397	690.5	133372	688				

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	SAR16-HY
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	SAR17-HY

6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.




Fig 5.1 Photo of DAE

6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				



7.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit ⁽²⁾	D750V3	1012	Aug. 18, 2021	Aug. 16, 2023
SPEAG	835MHz System Validation Kit ⁽²⁾	D835V2	499	Aug. 18, 2021	Aug. 16, 2023
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 21, 2022	Nov. 20, 2023
SPEAG	1900MHz System Validation Kit ⁽²⁾	D1900V2	5d041	Aug. 19, 2021	Aug. 17, 2023
SPEAG	2450MHz System Validation Kit	D2450V2	929	Nov. 21, 2022	Nov. 20, 2023
SPEAG	Data Acquisition Electronics	DAE4	1512	Mar. 20, 2023	Mar. 19, 2024
SPEAG	Dosimetric E-Field Probe	EX3DV4	3728	Mar. 22, 2023	Mar. 21, 2024
Testo	Hygro meter	608-H1	45196600	Nov. 02, 2022	Nov. 01, 2023
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Oct. 31, 2022	Oct. 30, 2023
Keysight	Wireless Communication Test Set	E5515C	MY50266977	May. 15, 2023	May. 14, 2024
R&S	BT Base Station	CBT32	101136	Oct. 25, 2022	Oct. 24, 2023
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Oct. 12, 2022	Oct. 11, 2023
Keysight	ENA Network Analyzer	E5071C	MY46104758	Sep. 22, 2022	Sep. 21, 2023
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 28, 2022	Sep. 27, 2023
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3796	Jan. 13, 2023	Jan. 12, 2024
Anritsu	Power Meter	ML2495A	1419002	Aug. 16, 2022	Aug. 15, 2023
Anritsu	Power Meter	ML2495A	1804003	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Power Sensor	MA2411B	1911176	Aug. 16, 2022	Aug. 15, 2023
Anritsu	Power Sensor	MA2411B	1726150	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jul. 21, 2022	Jul. 20, 2023
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 10, 2023	Jan. 09, 2024
Mini-Circuits	Power Amplifier	ZVE-8G+	479102029	Sep. 15, 2022	Sep. 14, 2023
Mini-Circuits	Power Amplifier	ZHL-42W+	321501827	Sep. 15, 2022	Sep. 14, 2023
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	22.4	0.896	42.697	0.89	41.90	0.67	1.90	± 5	2023/6/9
835	22.4	0.919	42.401	0.90	41.50	2.11	2.17	± 5	2023/6/7
1750	22.5	1.368	40.771	1.37	40.10	-0.15	1.67	± 5	2023/6/8
1900	22.5	1.445	39.223	1.40	40.00	3.21	-1.94	± 5	2023/6/8
2450	22.3	1.781	40.339	1.80	39.20	-1.06	2.91	± 5	2023/6/5

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)	Test Site
2023/6/9	750	50	D750V3-1012	EX3DV4 - SN3728	DAE4 Sn1512	0.410	8.560	8.2	-4.21	0.268	5.560	5.36	-3.60	SAR05
2023/6/7	835	50	D835V2-499	EX3DV4 - SN3728	DAE4 Sn1512	0.496	9.680	9.92	2.48	0.321	6.280	6.42	2.23	SAR05
2023/6/8	1750	50	D1750V2-1068	EX3DV4 - SN3728	DAE4 Sn1512	1.740	36.700	34.8	-5.18	0.926	19.300	18.52	-4.04	SAR05
2023/6/8	1900	50	D1900V2-5d041	EX3DV4 - SN3728	DAE4 Sn1512	1.920	40.600	38.4	-5.42	0.999	21.100	19.98	-5.31	SAR05
2023/6/5	2450	50	D2450V2-929	EX3DV4 - SN3728	DAE4 Sn1512	2.450	52.400	49	-6.49	1.150	24.700	23	-6.88	SAR05




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. UMTS/LTE Output Power (Unit: dBm)

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<WCDMA>													
Band		WCDMA II_Ant 0			Tune-up Limit (dBm)	WCDMA IV_Ant 0			Tune-up Limit (dBm)	WCDMA V_Ant 1			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	RMC 12.2Kbps	22.81	22.70	22.57	24.50	22.60	22.55	22.58	24.50	23.33	23.21	22.91	24.50
3GPP Rel 6	HSDPA Subtest-1	22.74	22.75	22.76	24.50	22.58	22.54	22.53	24.50	23.00	22.96	22.94	24.50
3GPP Rel 6	HSDPA Subtest-2	22.71	22.72	22.76	24.50	22.53	22.53	22.52	24.50	23.00	22.95	22.98	24.50
3GPP Rel 6	HSDPA Subtest-3	22.67	22.76	22.31	24.00	22.52	22.05	22.21	24.00	22.52	22.44	22.52	24.00
3GPP Rel 6	HSDPA Subtest-4	22.64	22.73	22.31	24.00	22.53	22.03	22.30	24.00	22.50	22.44	22.48	24.00
3GPP Rel 8	DC-HSDPA Subtest-1	22.72	22.72	22.78	24.50	22.50	22.59	22.51	24.50	22.94	23.05	22.88	24.50
3GPP Rel 8	DC-HSDPA Subtest-2	22.64	22.75	22.79	24.50	22.51	22.55	22.54	24.50	22.96	22.94	22.95	24.50
3GPP Rel 8	DC-HSDPA Subtest-3	22.71	22.76	22.35	24.00	22.47	22.06	22.16	24.00	22.48	22.45	22.52	24.00
3GPP Rel 8	DC-HSDPA Subtest-4	22.64	22.69	22.24	24.00	22.49	22.02	22.28	24.00	22.46	22.50	22.42	24.00
3GPP Rel 6	HSUPA Subtest-1	22.54	22.51	22.56	24.50	22.52	22.58	22.54	24.50	22.51	22.55	22.57	24.50
3GPP Rel 6	HSUPA Subtest-2	20.94	20.92	20.92	22.50	20.86	20.80	20.82	22.50	20.91	20.87	20.94	22.50
3GPP Rel 6	HSUPA Subtest-3	21.94	21.93	21.97	23.50	21.80	21.71	21.79	23.50	21.93	22.01	21.89	23.50
3GPP Rel 6	HSUPA Subtest-4	20.94	20.88	20.94	22.50	20.91	20.84	20.81	22.50	20.92	21.00	20.98	22.50
3GPP Rel 6	HSUPA Subtest-5	22.80	22.78	22.74	24.50	22.50	22.53	22.52	24.50	23.00	22.93	22.97	24.50

<LTE Conducted Power>**General Note:**

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B5/B12/B17/B26/B71 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 4/5/17 SAR test was covered by Band 66/26/12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band



<LTE Band 2 Ant 0>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				18700	18900	19100	
Frequency (MHz)				1860	1880	1900	
20	QPSK	1	0	22.81	22.54	22.61	24.5
20	QPSK	1	49	22.74	22.75	22.76	
20	QPSK	1	99	22.73	22.51	22.67	
20	QPSK	50	0	22.39	21.87	22.06	23.5
20	QPSK	50	24	22.49	22.04	22.40	
20	QPSK	50	50	22.37	21.74	21.99	
20	QPSK	100	0	22.06	21.59	21.83	23.5
20	16QAM	1	0	22.60	22.01	22.32	
20	16QAM	1	13	22.54	22.06	22.27	
20	16QAM	1	26	22.62	22.15	22.46	23.5
20	16QAM	12	0	22.33	21.84	22.05	
20	16QAM	12	7	22.38	21.94	22.28	
20	16QAM	12	15	22.51	21.96	22.20	22.5
20	16QAM	27	0	21.47	20.95	21.16	
Channel				18675	18900	19125	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1880	1902.5	
15	QPSK	1	0	22.80	22.52	22.61	
15	QPSK	1	37	22.69	22.73	22.72	24.5
15	QPSK	1	74	22.67	22.54	22.57	
15	QPSK	36	0	22.37	21.78	22.02	23.5
15	QPSK	36	20	22.49	21.96	22.36	
15	QPSK	36	39	22.30	21.69	21.93	
15	QPSK	75	0	22.03	21.53	21.77	23.5
15	16QAM	1	0	22.57	21.95	22.24	
15	16QAM	1	13	22.50	21.98	22.21	
15	16QAM	1	26	22.60	22.11	22.42	23.5
15	16QAM	12	0	22.24	21.80	21.97	
15	16QAM	12	7	22.29	21.94	22.26	
15	16QAM	12	15	22.47	21.93	22.20	22.5
15	16QAM	27	0	21.46	20.95	21.14	
Channel				18650	18900	19150	Tune-up limit (dBm)
Frequency (MHz)				1855	1880	1905	
10	QPSK	1	0	22.78	22.57	22.58	
10	QPSK	1	25	22.74	22.73	22.76	24.5
10	QPSK	1	49	22.66	22.52	22.67	
10	QPSK	25	0	22.38	21.77	21.99	23.5
10	QPSK	25	12	22.49	21.95	22.32	
10	QPSK	25	25	22.32	21.70	21.90	
10	QPSK	50	0	21.99	21.50	21.74	23.5
10	16QAM	1	0	22.57	21.93	22.29	
10	16QAM	1	13	22.52	21.99	22.19	
10	16QAM	1	26	22.54	22.06	22.36	23.5
10	16QAM	12	0	22.26	21.74	22.00	
10	16QAM	12	7	22.36	21.89	22.18	
10	16QAM	12	15	22.42	21.87	22.10	22.5
10	16QAM	27	0	21.43	20.87	21.06	
Channel				18625	18900	19175	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1880	1907.5	
5	QPSK	1	0	22.77	22.56	22.60	
5	QPSK	1	12	22.65	22.71	22.71	24.5



FCC SAR TEST REPORT

Report No. : FA351307

5	QPSK	1	24	22.64	22.59	22.62	
5	QPSK	12	0	22.30	21.86	21.98	23.5
5	QPSK	12	7	22.41	22.01	22.38	
5	QPSK	12	13	22.32	21.71	21.89	
5	QPSK	25	0	22.03	21.54	21.83	
5	16QAM	1	0	22.54	21.96	22.32	23.5
5	16QAM	1	12	22.47	22.00	22.27	
5	16QAM	1	24	22.53	22.12	22.37	
5	16QAM	12	0	22.29	21.82	21.96	23.5
5	16QAM	12	7	22.30	21.87	22.25	
5	16QAM	12	13	22.49	21.88	22.16	
5	16QAM	25	0	21.38	20.95	21.08	22.5
Channel				18615	18900	19185	Tune-up limit (dBm)
Frequency (MHz)				1851.5	1880	1908.5	
3	QPSK	1	0	22.80	22.55	22.53	24.5
3	QPSK	1	8	22.74	22.68	22.74	
3	QPSK	1	14	22.65	22.51	22.65	
3	QPSK	8	0	22.30	21.87	22.06	23.5
3	QPSK	8	4	22.43	21.99	22.30	
3	QPSK	8	7	22.34	21.71	21.94	
3	QPSK	15	0	21.98	21.59	21.83	
3	16QAM	1	0	22.52	21.97	22.23	23.5
3	16QAM	1	8	22.44	22.03	22.18	
3	16QAM	1	14	22.57	22.13	22.44	
3	16QAM	8	0	22.23	21.78	21.98	23.5
3	16QAM	8	4	22.34	21.91	22.27	
3	16QAM	8	7	22.47	21.88	22.20	
3	16QAM	15	0	21.47	20.85	21.07	22.5
Channel				18607	18900	19193	Tune-up limit (dBm)
Frequency (MHz)				1850.7	1880	1909.3	
1.4	QPSK	1	0	22.77	22.56	22.54	24.5
1.4	QPSK	1	3	22.70	22.71	22.73	
1.4	QPSK	1	5	22.64	22.57	22.58	
1.4	QPSK	3	0	22.74	22.56	22.58	
1.4	QPSK	3	1	22.61	22.68	22.70	
1.4	QPSK	3	3	22.64	22.54	22.54	
1.4	QPSK	6	0	22.33	21.81	22.01	23.5
1.4	16QAM	1	0	22.55	22.01	22.26	23.5
1.4	16QAM	1	3	22.45	21.98	22.22	
1.4	16QAM	1	5	22.60	22.15	22.42	
1.4	16QAM	3	0	22.53	21.98	22.24	
1.4	16QAM	3	1	22.40	21.88	22.18	
1.4	16QAM	3	3	22.56	22.13	22.37	
1.4	16QAM	6	0	22.25	21.75	21.99	22.5



<LTE Band 4 Ant 0>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20050	20175	20300	
Frequency (MHz)				1720	1732.5	1745	
20	QPSK	1	0	22.70	22.70	22.96	24.5
20	QPSK	1	49	22.72	22.81	22.94	
20	QPSK	1	99	22.70	22.67	22.82	
20	QPSK	50	0	22.10	22.06	22.40	23.5
20	QPSK	50	24	21.97	21.99	22.20	
20	QPSK	50	50	22.02	22.04	22.29	
20	QPSK	100	0	21.94	21.86	22.00	23.5
20	16QAM	1	0	21.94	22.01	22.24	
20	16QAM	1	13	22.11	22.13	22.45	
20	16QAM	1	26	22.08	22.18	22.50	23.5
20	16QAM	12	0	21.95	21.99	22.23	
20	16QAM	12	7	21.98	21.97	22.16	
20	16QAM	12	15	22.06	22.10	22.36	22.5
20	16QAM	27	0	21.08	21.08	21.21	
Channel				20025	20175	20325	Tune-up limit (dBm)
Frequency (MHz)				1717.5	1732.5	1747.5	
15	QPSK	1	0	22.67	22.62	22.95	
15	QPSK	1	37	22.71	22.71	22.85	24.5
15	QPSK	1	74	22.69	22.62	22.79	
15	QPSK	36	0	22.07	22.01	22.33	23.5
15	QPSK	36	20	21.93	21.95	22.18	
15	QPSK	36	39	21.98	22.02	22.24	
15	QPSK	75	0	21.92	21.81	21.94	23.5
15	16QAM	1	0	21.85	22.01	22.19	
15	16QAM	1	13	22.04	22.10	22.40	
15	16QAM	1	26	22.04	22.13	22.43	23.5
15	16QAM	12	0	21.88	21.95	22.14	
15	16QAM	12	7	21.92	21.88	22.15	
15	16QAM	12	15	22.03	22.03	22.33	22.5
15	16QAM	27	0	21.05	21.05	21.16	
Channel				20000	20175	20350	Tune-up limit (dBm)
Frequency (MHz)				1715	1732.5	1750	
10	QPSK	1	0	22.69	22.70	22.94	
10	QPSK	1	25	22.70	22.71	22.89	24.5
10	QPSK	1	49	22.70	22.64	22.74	
10	QPSK	25	0	22.01	22.00	22.37	23.5
10	QPSK	25	12	21.89	21.96	22.16	
10	QPSK	25	25	22.02	21.94	22.22	
10	QPSK	50	0	21.92	21.76	21.94	23.5
10	16QAM	1	0	21.94	21.96	22.22	
10	16QAM	1	13	22.01	22.09	22.41	
10	16QAM	1	26	22.08	22.09	22.48	23.5
10	16QAM	12	0	21.94	21.99	22.17	
10	16QAM	12	7	21.98	21.96	22.15	
10	16QAM	12	15	21.98	22.07	22.34	22.5
10	16QAM	27	0	21.05	21.01	21.19	
Channel				19975	20175	20375	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1732.5	1752.5	
5	QPSK	1	0	22.60	22.62	22.94	
5	QPSK	1	12	22.70	22.75	22.89	24.5



FCC SAR TEST REPORT

Report No. : FA351307

5	QPSK	1	24	22.67	22.61	22.76	23.5
5	QPSK	12	0	22.07	22.01	22.38	
5	QPSK	12	7	21.92	21.94	22.19	
5	QPSK	12	13	21.94	22.01	22.23	
5	QPSK	25	0	21.84	21.81	21.90	
5	16QAM	1	0	21.94	21.93	22.17	23.5
5	16QAM	1	12	22.07	22.13	22.41	
5	16QAM	1	24	21.99	22.12	22.43	
5	16QAM	12	0	21.92	21.92	22.13	23.5
5	16QAM	12	7	21.89	21.88	22.09	
5	16QAM	12	13	22.02	22.01	22.35	
5	16QAM	25	0	20.98	21.08	21.16	22.5
Channel				19965	20175	20385	Tune-up limit (dBm)
Frequency (MHz)				1711.5	1732.5	1753.5	
3	QPSK	1	0	22.70	22.65	22.90	24.5
3	QPSK	1	8	22.72	22.79	22.86	
3	QPSK	1	14	22.70	22.59	22.75	
3	QPSK	8	0	22.02	22.01	22.34	23.5
3	QPSK	8	4	21.93	21.92	22.18	
3	QPSK	8	7	21.99	22.00	22.24	
3	QPSK	15	0	21.91	21.82	21.96	
3	16QAM	1	0	21.87	22.01	22.16	23.5
3	16QAM	1	8	22.11	22.13	22.35	
3	16QAM	1	14	21.98	22.15	22.49	
3	16QAM	8	0	21.85	21.95	22.21	23.5
3	16QAM	8	4	21.96	21.91	22.10	
3	16QAM	8	7	21.98	22.05	22.29	
3	16QAM	15	0	20.98	21.04	21.11	22.5
Channel				19957	20175	20393	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1732.5	1754.3	
1.4	QPSK	1	0	22.63	22.67	22.89	24.5
1.4	QPSK	1	3	22.62	22.74	22.84	
1.4	QPSK	1	5	22.65	22.65	22.76	
1.4	QPSK	3	0	22.55	22.65	22.80	
1.4	QPSK	3	1	22.60	22.74	22.83	
1.4	QPSK	3	3	22.56	22.61	22.68	
1.4	QPSK	6	0	22.04	22.04	22.35	23.5
1.4	16QAM	1	0	21.92	22.00	22.15	23.5
1.4	16QAM	1	3	22.05	22.09	22.38	
1.4	16QAM	1	5	22.06	22.09	22.47	
1.4	16QAM	3	0	21.91	22.00	22.13	
1.4	16QAM	3	1	21.97	22.09	22.36	
1.4	16QAM	3	3	22.05	22.09	22.45	
1.4	16QAM	6	0	21.88	21.89	22.21	22.5



<LTE Band 5 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				20450	20525	20600	
Frequency (MHz)				829	836.5	844	
10	QPSK	1	0	23.49	23.26	23.38	24.5
10	QPSK	1	25	23.31	23.34	23.40	
10	QPSK	1	49	23.39	23.38	23.48	
10	QPSK	25	0	22.57	22.34	22.47	23.5
10	QPSK	25	12	22.49	22.31	22.34	
10	QPSK	25	25	22.71	22.46	22.55	
10	QPSK	50	0	22.50	22.39	22.56	23.5
10	16QAM	1	0	22.87	22.72	22.74	
10	16QAM	1	13	22.84	22.71	22.80	
10	16QAM	1	26	22.98	22.73	22.83	23.5
10	16QAM	12	0	22.47	22.33	22.49	
10	16QAM	12	7	22.50	22.36	22.41	
10	16QAM	12	15	22.43	22.41	22.46	22.5
10	16QAM	27	0	21.53	21.34	21.43	
Channel				20425	20525	20625	Tune-up limit (dBm)
Frequency (MHz)				826.5	836.5	846.5	
5	QPSK	1	0	23.45	23.23	23.31	
5	QPSK	1	12	23.31	23.26	23.34	24.5
5	QPSK	1	24	23.39	23.30	23.39	
5	QPSK	12	0	22.53	22.31	22.47	23.5
5	QPSK	12	7	22.39	22.30	22.33	
5	QPSK	12	13	22.64	22.45	22.46	
5	QPSK	25	0	22.41	22.34	22.53	23.5
5	16QAM	1	0	22.84	22.65	22.67	
5	16QAM	1	12	22.74	22.69	22.76	
5	16QAM	1	24	22.96	22.72	22.75	23.5
5	16QAM	12	0	22.43	22.25	22.45	
5	16QAM	12	7	22.48	22.32	22.38	
5	16QAM	12	13	22.36	22.39	22.40	22.5
5	16QAM	25	0	21.53	21.26	21.36	
Channel				20415	20525	20635	Tune-up limit (dBm)
Frequency (MHz)				825.5	836.5	847.5	
3	QPSK	1	0	23.42	23.21	23.30	
3	QPSK	1	8	23.31	23.30	23.32	24.5
3	QPSK	1	14	23.31	23.34	23.44	
3	QPSK	8	0	22.56	22.33	22.38	23.5
3	QPSK	8	4	22.48	22.29	22.34	
3	QPSK	8	7	22.61	22.45	22.46	
3	QPSK	15	0	22.46	22.29	22.49	23.5
3	16QAM	1	0	22.77	22.68	22.65	
3	16QAM	1	8	22.75	22.70	22.79	
3	16QAM	1	14	22.90	22.65	22.82	23.5
3	16QAM	8	0	22.47	22.23	22.39	
3	16QAM	8	4	22.41	22.31	22.32	
3	16QAM	8	7	22.33	22.37	22.36	22.5
3	16QAM	15	0	21.44	21.31	21.37	
Channel				20407	20525	20643	Tune-up limit (dBm)
Frequency (MHz)				824.7	836.5	848.3	
1.4	QPSK	1	0	23.41	23.23	23.32	
1.4	QPSK	1	3	23.23	23.34	23.32	24.5



FCC SAR TEST REPORT

Report No. : FA351307

1.4	QPSK	1	5	23.31	23.34	23.45	
1.4	QPSK	3	0	23.46	23.13	23.29	
1.4	QPSK	3	1	23.14	23.28	23.27	
1.4	QPSK	3	3	23.23	23.26	23.35	
1.4	QPSK	6	0	22.54	22.25	22.47	23.5
1.4	16QAM	1	0	22.87	22.69	22.66	23.5
1.4	16QAM	1	3	22.83	22.65	22.79	
1.4	16QAM	1	5	22.96	22.71	22.80	
1.4	16QAM	3	0	22.86	22.69	22.62	
1.4	16QAM	3	1	22.74	22.61	22.71	
1.4	16QAM	3	3	22.91	22.66	22.73	
1.4	16QAM	6	0	22.40	22.25	22.39	22.5

<LTE Band 12 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23060	23095	23130	
Frequency (MHz)				704	707.5	711	
10	QPSK	1	0	23.07	23.00	23.01	24.5
10	QPSK	1	25	22.71	22.74	22.79	
10	QPSK	1	49	23.04	22.87	22.94	
10	QPSK	25	0	21.93	21.81	21.78	23.5
10	QPSK	25	12	21.91	21.79	21.81	
10	QPSK	25	25	21.92	21.76	21.76	
10	QPSK	50	0	21.77	21.80	21.84	
10	16QAM	1	0	22.47	22.31	22.27	23.5
10	16QAM	1	13	22.29	22.18	22.23	
10	16QAM	1	26	22.20	22.10	22.16	
10	16QAM	12	0	21.86	21.81	21.86	23.5
10	16QAM	12	7	21.80	21.82	21.73	
10	16QAM	12	15	21.87	21.86	21.92	
10	16QAM	27	0	20.91	20.81	20.92	22.5
Channel				23035	23095	23155	Tune-up limit (dBm)
Frequency (MHz)				701.5	707.5	713.5	
5	QPSK	1	0	23.03	22.95	22.98	24.5
5	QPSK	1	12	22.63	22.66	22.74	
5	QPSK	1	24	22.94	22.78	22.86	
5	QPSK	12	0	21.92	21.79	21.77	23.5
5	QPSK	12	7	21.87	21.77	21.78	
5	QPSK	12	13	21.89	21.66	21.72	
5	QPSK	25	0	21.69	21.80	21.79	
5	16QAM	1	0	22.44	22.23	22.20	23.5
5	16QAM	1	12	22.22	22.12	22.15	
5	16QAM	1	24	22.13	22.09	22.11	
5	16QAM	12	0	21.81	21.71	21.83	23.5
5	16QAM	12	7	21.79	21.74	21.63	
5	16QAM	12	13	21.82	21.80	21.84	
5	16QAM	25	0	20.83	20.81	20.89	22.5
Channel				23025	23095	23165	Tune-up limit (dBm)
Frequency (MHz)				700.5	707.5	714.5	
3	QPSK	1	0	23.01	22.90	22.97	24.5
3	QPSK	1	8	22.62	22.72	22.70	
3	QPSK	1	14	22.94	22.86	22.87	
3	QPSK	8	0	21.92	21.73	21.77	23.5

3	QPSK	8	4	21.87	21.72	21.73	
3	QPSK	8	7	21.82	21.73	21.74	
3	QPSK	15	0	21.73	21.72	21.79	
3	16QAM	1	0	22.39	22.29	22.20	23.5
3	16QAM	1	8	22.27	22.11	22.19	
3	16QAM	1	14	22.15	22.05	22.09	
3	16QAM	8	0	21.81	21.76	21.85	23.5
3	16QAM	8	4	21.80	21.82	21.64	
3	16QAM	8	7	21.81	21.76	21.84	
3	16QAM	15	0	20.81	20.75	20.91	22.5
Channel				23017	23095	23173	Tune-up limit (dBm)
Frequency (MHz)				699.7	707.5	715.3	
1.4	QPSK	1	0	22.98	22.97	22.92	24.5
1.4	QPSK	1	3	22.65	22.69	22.78	
1.4	QPSK	1	5	23.01	22.80	22.90	
1.4	QPSK	3	0	22.98	22.89	22.86	
1.4	QPSK	3	1	22.61	22.69	22.71	
1.4	QPSK	3	3	22.96	22.79	22.83	
1.4	QPSK	6	0	21.87	21.80	21.71	23.5
1.4	16QAM	1	0	22.45	22.25	22.24	23.5
1.4	16QAM	1	3	22.23	22.18	22.13	
1.4	16QAM	1	5	22.18	22.08	22.14	
1.4	16QAM	3	0	22.40	22.22	22.24	
1.4	16QAM	3	1	22.18	22.15	22.05	
1.4	16QAM	3	3	22.12	22.03	22.12	
1.4	16QAM	6	0	21.82	21.73	21.82	22.5

<LTE Band 13 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23230			
Frequency (MHz)				782			
10	QPSK	1	0		23.19		24.5
10	QPSK	1	25		23.16		
10	QPSK	1	49		23.14		
10	QPSK	25	0		22.34		23.5
10	QPSK	25	12		22.20		
10	QPSK	25	25		22.12		
10	QPSK	50	0		22.18		23.5
10	16QAM	1	0		22.60		
10	16QAM	1	13		22.51		
10	16QAM	1	26		22.22		23.5
10	16QAM	12	0		22.26		
10	16QAM	12	7		22.28		
10	16QAM	12	15		22.24		22.5
10	16QAM	27	0		21.52		
Channel				23205	23230	23255	Tune-up limit (dBm)
Frequency (MHz)				779.5	782	784.5	
5	QPSK	1	0	23.13	23.12	23.14	24.5
5	QPSK	1	12	23.07	23.16	23.11	
5	QPSK	1	24	23.14	23.09	23.09	
5	QPSK	12	0	22.27	22.29	22.26	23.5
5	QPSK	12	7	22.16	22.20	22.15	
5	QPSK	12	13	22.04	22.10	22.05	

5	QPSK	25	0	22.11	22.11	22.18	
5	16QAM	1	0	22.57	22.60	22.53	23.5
5	16QAM	1	12	22.43	22.42	22.45	
5	16QAM	1	24	22.18	22.18	22.18	
5	16QAM	12	0	22.17	22.25	22.21	23.5
5	16QAM	12	7	22.27	22.23	22.25	
5	16QAM	12	13	22.17	22.14	22.21	
5	16QAM	25	0	21.56	21.51	21.55	22.5

<LTE Band 17 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				23780	23790	23800	
Frequency (MHz)				709	710	711	
10	QPSK	1	0	22.84	22.91	22.89	
10	QPSK	1	25	22.83	22.84	22.77	24.5
10	QPSK	1	49	22.81	22.88	22.76	
10	QPSK	25	0	21.86	21.87	21.95	
10	QPSK	25	12	21.77	21.82	21.83	23.5
10	QPSK	25	25	21.65	21.72	21.74	
10	QPSK	50	0	21.88	21.85	21.90	
10	16QAM	1	0	22.11	22.28	22.18	23.5
10	16QAM	1	13	22.02	22.11	22.15	
10	16QAM	1	26	22.12	22.09	22.04	
10	16QAM	12	0	21.70	21.81	21.78	23.5
10	16QAM	12	7	21.77	21.88	21.87	
10	16QAM	12	15	21.75	21.82	21.86	
10	16QAM	27	0	20.78	20.82	20.79	22.5
Channel				23755	23790	23825	Tune-up limit (dBm)
Frequency (MHz)				706.5	710	713.5	
5	QPSK	1	0	22.77	22.83	22.81	
5	QPSK	1	12	22.82	22.84	22.68	24.5
5	QPSK	1	24	22.76	22.86	22.70	
5	QPSK	12	0	21.86	21.84	21.94	
5	QPSK	12	7	21.73	21.73	21.81	23.5
5	QPSK	12	13	21.55	21.62	21.68	
5	QPSK	25	0	21.86	21.78	21.80	
5	16QAM	1	0	22.08	22.18	22.17	23.5
5	16QAM	1	12	21.99	22.10	22.11	
5	16QAM	1	24	22.07	22.06	21.96	
5	16QAM	12	0	21.64	21.80	21.76	23.5
5	16QAM	12	7	21.73	21.83	21.86	
5	16QAM	12	13	21.65	21.76	21.86	
5	16QAM	25	0	20.70	20.75	20.69	22.5



<LTE Band 25 Ant 0>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				26140	26340	26590	
Frequency (MHz)				1860	1880	1905	
20	QPSK	1	0	22.84	22.64	22.68	24.5
20	QPSK	1	49	22.80	22.67	22.76	
20	QPSK	1	99	22.81	22.78	22.82	
20	QPSK	50	0	21.91	21.63	21.69	23.5
20	QPSK	50	24	21.99	21.80	21.75	
20	QPSK	50	50	21.82	21.65	21.62	
20	QPSK	100	0	21.76	21.63	21.73	23.5
20	16QAM	1	0	22.13	21.93	21.97	
20	16QAM	1	13	21.98	21.88	21.85	
20	16QAM	1	26	22.09	21.87	21.95	23.5
20	16QAM	12	0	21.90	21.77	21.79	
20	16QAM	12	7	21.93	21.74	21.71	
20	16QAM	12	15	21.96	21.79	21.85	22.5
20	16QAM	27	0	20.97	20.71	20.71	
Channel				26115	26340	26615	Tune-up limit (dBm)
Frequency (MHz)				1857.5	1880	1907.5	
15	QPSK	1	0	22.77	22.58	22.63	
15	QPSK	1	37	22.72	22.65	22.72	24.5
15	QPSK	1	74	22.72	22.78	22.78	
15	QPSK	36	0	21.88	21.59	21.67	23.5
15	QPSK	36	20	21.96	21.77	21.69	
15	QPSK	36	39	21.74	21.57	21.55	
15	QPSK	75	0	21.71	21.58	21.72	23.5
15	16QAM	1	0	22.12	21.93	21.93	
15	16QAM	1	13	21.98	21.78	21.80	
15	16QAM	1	26	22.05	21.83	21.88	23.5
15	16QAM	12	0	21.83	21.72	21.72	
15	16QAM	12	7	21.90	21.65	21.63	
15	16QAM	12	15	21.95	21.69	21.75	22.5
15	16QAM	27	0	20.94	20.66	20.66	
Channel				26090	26340	26640	Tune-up limit (dBm)
Frequency (MHz)				1855	1880	1910	
10	QPSK	1	0	22.75	22.54	22.63	
10	QPSK	1	25	22.71	22.64	22.69	24.5
10	QPSK	1	49	22.81	22.78	22.79	
10	QPSK	25	0	21.81	21.58	21.59	23.5
10	QPSK	25	12	21.95	21.72	21.73	
10	QPSK	25	25	21.73	21.64	21.56	
10	QPSK	50	0	21.66	21.62	21.69	23.5
10	16QAM	1	0	22.08	21.90	21.95	
10	16QAM	1	13	21.89	21.86	21.85	
10	16QAM	1	26	22.05	21.82	21.95	23.5
10	16QAM	12	0	21.90	21.67	21.70	
10	16QAM	12	7	21.85	21.65	21.64	
10	16QAM	12	15	21.92	21.74	21.75	22.5
10	16QAM	27	0	20.96	20.67	20.71	
Channel				26065	26340	26665	Tune-up limit (dBm)
Frequency (MHz)				1852.5	1880	1912.5	
5	QPSK	1	0	22.80	22.56	22.66	
5	QPSK	1	12	22.72	22.66	22.72	24.5



FCC SAR TEST REPORT

Report No. : FA351307

5	QPSK	1	24	22.76	22.74	22.72	
5	QPSK	12	0	21.91	21.61	21.67	23.5
5	QPSK	12	7	21.89	21.70	21.75	
5	QPSK	12	13	21.75	21.63	21.54	
5	QPSK	25	0	21.75	21.63	21.68	
5	16QAM	1	0	22.03	21.86	21.96	23.5
5	16QAM	1	12	21.95	21.81	21.79	
5	16QAM	1	24	22.04	21.82	21.93	
5	16QAM	12	0	21.88	21.70	21.78	23.5
5	16QAM	12	7	21.88	21.69	21.70	
5	16QAM	12	13	21.95	21.79	21.84	
5	16QAM	25	0	20.96	20.63	20.71	22.5
Channel				26055	26340	26675	Tune-up limit (dBm)
Frequency (MHz)				1851.5	1880	1913.5	
3	QPSK	1	0	22.79	22.61	22.63	24.5
3	QPSK	1	8	22.73	22.65	22.70	
3	QPSK	1	14	22.79	22.73	22.75	
3	QPSK	8	0	21.81	21.59	21.60	23.5
3	QPSK	8	4	21.89	21.77	21.73	
3	QPSK	8	7	21.74	21.58	21.59	
3	QPSK	15	0	21.69	21.62	21.65	
3	16QAM	1	0	22.06	21.85	21.96	23.5
3	16QAM	1	8	21.98	21.81	21.85	
3	16QAM	1	14	22.07	21.79	21.90	
3	16QAM	8	0	21.87	21.68	21.76	23.5
3	16QAM	8	4	21.93	21.68	21.62	
3	16QAM	8	7	21.92	21.75	21.82	
3	16QAM	15	0	20.92	20.68	20.65	22.5
Channel				26047	26340	26683	Tune-up limit (dBm)
Frequency (MHz)				1850.7	1880	1914.3	
1.4	QPSK	1	0	22.81	22.57	22.59	24.5
1.4	QPSK	1	3	22.78	22.61	22.67	
1.4	QPSK	1	5	22.79	22.74	22.79	
1.4	QPSK	3	0	22.83	22.50	22.51	
1.4	QPSK	3	1	22.70	22.56	22.60	
1.4	QPSK	3	3	22.73	22.66	22.71	
1.4	QPSK	6	0	21.81	21.63	21.62	23.5
1.4	16QAM	1	0	22.11	21.91	21.90	23.5
1.4	16QAM	1	3	21.88	21.80	21.76	
1.4	16QAM	1	5	21.99	21.84	21.92	
1.4	16QAM	3	0	22.04	21.83	21.82	
1.4	16QAM	3	1	21.79	21.74	21.74	
1.4	16QAM	3	3	21.97	21.84	21.89	
1.4	16QAM	6	0	21.86	21.72	21.72	



<LTE Band 26 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				26765	26865	26965	
Frequency (MHz)				821.5	831.5	841.5	
15	QPSK	1	0	22.67	22.54	22.53	
15	QPSK	1	37	22.55	22.55	22.54	24.5
15	QPSK	1	74	22.51	22.50	22.58	
15	QPSK	36	0	21.56	21.55	21.58	
15	QPSK	36	20	21.67	21.60	21.53	23.5
15	QPSK	36	39	21.64	21.57	21.56	
15	QPSK	75	0	21.99	21.71	21.62	
15	16QAM	1	0	22.11	21.74	21.69	23.5
15	16QAM	1	13	21.76	21.59	21.55	
15	16QAM	1	26	21.89	21.63	21.56	
15	16QAM	12	0	21.62	21.38	21.37	23.5
15	16QAM	12	7	21.53	21.32	21.32	
15	16QAM	12	15	21.70	21.33	21.17	
15	16QAM	27	0	20.62	20.57	20.52	22.5
Channel				26740	26865	26990	Tune-up limit (dBm)
Frequency (MHz)				819	831.5	844	
10	QPSK	1	0	22.57	22.51	22.57	
10	QPSK	1	25	22.51	22.54	22.54	24.5
10	QPSK	1	49	22.52	22.57	22.53	
10	QPSK	25	0	21.52	21.55	21.50	
10	QPSK	25	12	21.66	21.54	21.56	23.5
10	QPSK	25	25	21.59	21.52	21.56	
10	QPSK	50	0	21.95	21.66	21.53	
10	16QAM	1	0	21.71	21.74	21.60	23.5
10	16QAM	1	13	21.73	21.57	21.55	
10	16QAM	1	26	21.84	21.59	21.55	
10	16QAM	12	0	21.62	21.29	21.33	23.5
10	16QAM	12	7	21.50	21.25	21.23	
10	16QAM	12	15	21.61	21.26	21.13	
10	16QAM	27	0	20.58	20.57	20.58	22.5
Channel				26715	26865	27015	Tune-up limit (dBm)
Frequency (MHz)				816.5	831.5	846.5	
5	QPSK	1	0	22.60	22.54	22.58	
5	QPSK	1	12	22.51	22.58	22.55	24.5
5	QPSK	1	24	22.51	22.54	22.52	
5	QPSK	12	0	21.53	21.55	21.54	
5	QPSK	12	7	21.62	21.57	21.51	23.5
5	QPSK	12	13	21.55	21.59	21.59	
5	QPSK	25	0	21.96	21.61	21.52	
5	16QAM	1	0	21.79	21.64	21.69	23.5
5	16QAM	1	12	21.73	21.56	21.50	
5	16QAM	1	24	21.89	21.53	21.56	
5	16QAM	12	0	21.61	21.32	21.28	23.5
5	16QAM	12	7	21.46	21.24	21.26	
5	16QAM	12	13	21.65	21.26	21.08	
5	16QAM	25	0	20.52	20.59	20.57	22.5
Channel				26705	26865	27025	Tune-up limit (dBm)
Frequency (MHz)				815.5	831.5	847.5	
3	QPSK	1	0	22.58	22.52	22.54	
3	QPSK	1	8	22.51	22.51	22.57	24.5



FCC SAR TEST REPORT

Report No. : FA351307

3	QPSK	1	14	22.51	22.55	22.58	23.5
3	QPSK	8	0	21.59	21.51	21.54	
3	QPSK	8	4	21.64	21.54	21.57	
3	QPSK	8	7	21.54	21.59	21.51	
3	QPSK	15	0	21.95	21.66	21.57	
3	16QAM	1	0	22.10	21.74	21.66	23.5
3	16QAM	1	8	21.71	21.50	21.53	
3	16QAM	1	14	21.82	21.55	21.54	
3	16QAM	8	0	21.54	21.35	21.33	23.5
3	16QAM	8	4	21.45	21.28	21.28	
3	16QAM	8	7	21.67	21.31	21.13	
3	16QAM	15	0	20.54	20.54	20.50	22.5
Channel				26697	26865	27033	Tune-up limit (dBm)
Frequency (MHz)				814.7	831.5	848.3	
1.4	QPSK	1	0	22.66	22.58	22.53	24.5
1.4	QPSK	1	3	22.55	22.52	22.59	
1.4	QPSK	1	5	22.59	22.54	22.56	
1.4	QPSK	3	0	22.61	22.50	22.53	
1.4	QPSK	3	1	22.54	22.50	22.58	
1.4	QPSK	3	3	22.50	22.55	22.56	
1.4	QPSK	6	0	21.59	21.55	21.51	23.5
1.4	16QAM	1	0	22.10	21.72	21.62	23.5
1.4	16QAM	1	3	21.76	21.58	21.53	
1.4	16QAM	1	5	21.82	21.57	21.58	
1.4	16QAM	3	0	21.73	21.73	21.69	
1.4	16QAM	3	1	21.71	21.57	21.56	
1.4	16QAM	3	3	21.86	21.58	21.56	
1.4	16QAM	6	0	21.54	21.35	21.27	22.5

<LTE Band 66 Ant 0>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				132072	132322	132572	
Frequency (MHz)				1720	1745	1770	
20	QPSK	1	0	23.23	22.84	23.16	24.5
20	QPSK	1	49	23.00	22.73	23.04	
20	QPSK	1	99	23.18	22.88	23.17	
20	QPSK	50	0	22.22	22.01	22.35	23.5
20	QPSK	50	24	22.44	22.03	22.34	
20	QPSK	50	50	22.30	22.09	22.40	
20	QPSK	100	0	22.34	21.95	22.21	23.5
20	16QAM	1	0	22.53	22.30	22.65	
20	16QAM	1	13	22.57	22.23	22.58	
20	16QAM	1	26	22.45	22.21	22.62	23.5
20	16QAM	12	0	22.34	22.05	22.41	
20	16QAM	12	7	22.34	22.07	22.46	
20	16QAM	12	15	22.48	22.22	22.46	22.5
20	16QAM	27	0	21.55	21.16	21.47	
Channel				132047	132322	132597	Tune-up limit (dBm)
Frequency (MHz)				1717.5	1745	1772.5	
15	QPSK	1	0	23.16	22.84	23.07	24.5
15	QPSK	1	37	22.96	22.67	22.98	
15	QPSK	1	74	23.13	22.83	23.15	
15	QPSK	36	0	22.14	21.93	22.34	23.5
15	QPSK	36	20	22.36	21.95	22.24	
15	QPSK	36	39	22.28	22.08	22.36	



FCC SAR TEST REPORT

Report No. : FA351307

15	QPSK	75	0	22.30	21.88	22.16	
15	16QAM	1	0	22.52	22.30	22.60	23.5
15	16QAM	1	13	22.48	22.14	22.57	
15	16QAM	1	26	22.36	22.20	22.56	
15	16QAM	12	0	22.25	22.01	22.39	23.5
15	16QAM	12	7	22.31	22.06	22.37	
15	16QAM	12	15	22.38	22.21	22.41	
15	16QAM	27	0	21.45	21.07	21.47	22.5
Channel				132022	132322	132622	Tune-up limit (dBm)
Frequency (MHz)				1715	1745	1775	
10	QPSK	1	0	23.21	22.82	23.09	24.5
10	QPSK	1	25	22.90	22.71	23.03	
10	QPSK	1	49	23.16	22.87	23.08	
10	QPSK	25	0	22.12	21.96	22.32	23.5
10	QPSK	25	12	22.42	21.93	22.32	
10	QPSK	25	25	22.20	22.02	22.36	
10	QPSK	50	0	22.29	21.88	22.12	23.5
10	16QAM	1	0	22.52	22.27	22.65	
10	16QAM	1	13	22.48	22.20	22.54	
10	16QAM	1	26	22.37	22.15	22.52	23.5
10	16QAM	12	0	22.31	22.05	22.36	
10	16QAM	12	7	22.28	21.97	22.40	
10	16QAM	12	15	22.38	22.20	22.42	22.5
10	16QAM	27	0	21.49	21.09	21.37	
Channel				131997	132322	132647	Tune-up limit (dBm)
Frequency (MHz)				1712.5	1745	1777.5	
5	QPSK	1	0	23.18	22.82	23.08	24.5
5	QPSK	1	12	22.98	22.66	23.04	
5	QPSK	1	24	23.12	22.86	23.13	
5	QPSK	12	0	22.17	21.94	22.30	23.5
5	QPSK	12	7	22.38	21.96	22.34	
5	QPSK	12	13	22.26	22.06	22.39	
5	QPSK	25	0	22.28	21.85	22.14	23.5
5	16QAM	1	0	22.43	22.26	22.57	
5	16QAM	1	12	22.49	22.13	22.48	
5	16QAM	1	24	22.39	22.18	22.56	23.5
5	16QAM	12	0	22.24	21.99	22.39	
5	16QAM	12	7	22.30	22.06	22.41	
5	16QAM	12	13	22.43	22.18	22.44	22.5
5	16QAM	25	0	21.52	21.09	21.40	
Channel				131987	132322	132657	Tune-up limit (dBm)
Frequency (MHz)				1711.5	1745	1778.5	
3	QPSK	1	0	23.18	22.81	23.06	24.5
3	QPSK	1	8	22.96	22.68	23.01	
3	QPSK	1	14	23.11	22.88	23.15	
3	QPSK	8	0	22.14	22.00	22.28	23.5
3	QPSK	8	4	22.36	21.98	22.34	
3	QPSK	8	7	22.29	22.08	22.40	
3	QPSK	15	0	22.33	21.93	22.18	23.5
3	16QAM	1	0	22.53	22.20	22.57	
3	16QAM	1	8	22.48	22.21	22.52	
3	16QAM	1	14	22.43	22.20	22.61	23.5
3	16QAM	8	0	22.30	21.96	22.34	
3	16QAM	8	4	22.25	21.98	22.37	
3	16QAM	8	7	22.38	22.20	22.42	22.5
3	16QAM	15	0	21.45	21.08	21.46	



FCC SAR TEST REPORT

Report No. : FA351307

Channel				131979	132322	132665	Tune-up limit (dBm)
Frequency (MHz)				1710.7	1745	1779.3	
1.4	QPSK	1	0	23.21	22.77	23.08	24.5
1.4	QPSK	1	3	23.00	22.69	22.94	
1.4	QPSK	1	5	23.08	22.80	23.07	
1.4	QPSK	3	0	23.21	22.76	23.07	
1.4	QPSK	3	1	22.97	22.69	22.95	
1.4	QPSK	3	3	23.13	22.79	23.14	
1.4	QPSK	6	0	22.22	22.01	22.29	23.5
1.4	16QAM	1	0	22.49	22.24	22.63	23.5
1.4	16QAM	1	3	22.50	22.17	22.48	
1.4	16QAM	1	5	22.45	22.20	22.58	
1.4	16QAM	3	0	22.50	22.30	22.65	
1.4	16QAM	3	1	22.55	22.16	22.52	
1.4	16QAM	3	3	22.40	22.11	22.52	
1.4	16QAM	6	0	22.25	21.97	22.41	22.5

<LTE Band 71 Ant 1>							
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)
Channel				133222	133322	133372	
Frequency (MHz)				673	683	688	24.5
20	QPSK	1	0	23.19	23.30	23.27	
20	QPSK	1	49	22.85	22.87	22.74	
20	QPSK	1	99	22.90	22.91	22.98	23.5
20	QPSK	50	0	22.07	22.20	22.19	
20	QPSK	50	24	21.96	22.14	22.13	
20	QPSK	50	50	21.91	22.06	21.97	
20	QPSK	100	0	21.95	22.06	21.98	23.5
20	16QAM	1	0	22.48	22.52	22.55	
20	16QAM	1	13	22.39	22.46	22.37	
20	16QAM	1	26	22.24	22.41	22.41	23.5
20	16QAM	12	0	22.11	22.19	22.16	
20	16QAM	12	7	22.10	22.15	22.09	
20	16QAM	12	15	22.16	22.17	22.13	22.5
20	16QAM	27	0	21.16	21.19	21.18	
Channel				133197	133297	133397	Tune-up limit (dBm)
Frequency (MHz)				670.5	680.5	690.5	
15	QPSK	1	0	23.11	23.20	23.25	24.5
15	QPSK	1	37	22.83	22.85	22.65	
15	QPSK	1	74	22.87	22.87	22.98	
15	QPSK	36	0	22.03	22.09	22.11	23.5
15	QPSK	36	20	21.96	22.13	22.12	
15	QPSK	36	39	21.91	21.99	21.94	
15	QPSK	75	0	21.85	21.96	21.95	
15	16QAM	1	0	22.45	22.52	22.48	23.5
15	16QAM	1	13	22.35	22.41	22.33	
15	16QAM	1	26	22.18	22.35	22.32	
15	16QAM	12	0	22.10	22.19	22.07	23.5
15	16QAM	12	7	22.10	22.07	22.09	
15	16QAM	12	15	22.09	22.14	22.06	
15	16QAM	27	0	21.08	21.10	21.08	22.5
Channel				133172	133272	133422	Tune-up limit (dBm)
Frequency (MHz)				668	678	693	
10	QPSK	1	0	23.14	23.27	23.20	24.5
10	QPSK	1	25	22.75	22.78	22.71	



FCC SAR TEST REPORT

Report No. : FA351307

10	QPSK	1	49	22.83	22.83	22.93	
10	QPSK	25	0	21.98	22.03	22.19	23.5
10	QPSK	25	12	21.86	22.08	22.09	
10	QPSK	25	25	21.90	22.00	21.89	
10	QPSK	50	0	21.89	21.96	21.97	
10	16QAM	1	0	22.47	22.52	22.47	23.5
10	16QAM	1	13	22.38	22.44	22.32	
10	16QAM	1	26	22.24	22.37	22.36	
10	16QAM	12	0	22.11	22.19	22.09	23.5
10	16QAM	12	7	22.08	22.06	22.06	
10	16QAM	12	15	22.14	22.10	22.13	
10	16QAM	27	0	21.06	21.10	21.17	22.5
Channel				133147	133247	133447	Tune-up limit (dBm)
Frequency (MHz)				665.5	675.5	695.5	
5	QPSK	1	0	23.16	23.28	23.17	24.5
5	QPSK	1	12	22.82	22.78	22.68	
5	QPSK	1	24	22.83	22.90	22.91	
5	QPSK	12	0	21.99	22.09	22.09	23.5
5	QPSK	12	7	21.86	22.06	22.09	
5	QPSK	12	13	21.83	22.04	21.88	
5	QPSK	25	0	21.87	21.98	21.94	
5	16QAM	1	0	22.40	22.43	22.51	23.5
5	16QAM	1	12	22.39	22.38	22.29	
5	16QAM	1	24	22.16	22.34	22.39	
5	16QAM	12	0	22.01	22.16	22.06	23.5
5	16QAM	12	7	22.03	22.07	22.01	
5	16QAM	12	13	22.06	22.13	22.10	
5	16QAM	25	0	21.13	21.12	21.17	22.5

11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, additional output power measurements were not necessary.
2. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
3. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
4. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
5. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. 18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.


	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	18.90	20.00	100.00
		6	2437	19.40	20.00	
		11	2462	19.50	20.00	
	802.11g 6Mbps	1	2412	18.50	19.00	98.07
		6	2437	18.70	19.00	
		11	2462	17.40	18.00	
	802.11n-HT20 MCS0	1	2412	18.60	19.00	97.50
		6	2437	18.70	19.00	
		11	2462	17.00	18.00	

<2.4GHz Bluetooth>

Bluetooth	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	BR / EDR 1Mbps	0	2402	18.53	19.00	76.80
		39	2441	19.28	20.00	
		78	2480	17.55	18.50	
	BR / EDR 2Mbps	0	2402	14.44	15.00	76.77
		39	2441	15.32	16.00	
		78	2480	14.20	14.50	
	BR / EDR 3Mbps	0	2402	14.56	15.00	77.07
		39	2441	15.45	16.00	
		78	2480	14.14	14.50	
	LE 1Mbps	0	2402	17.90	19.00	85.60
		19	2440	18.90	19.50	
		39	2480	16.40	17.50	
	LE 2Mbps	0	2402	18.10	19.00	57.57
		19	2440	19.10	19.50	
		39	2480	16.60	17.50	

General Note:

- For 2.4GHz Bluetooth SAR testing was selected BR/EDR 1Mbps due to its highest average power and duty cycle is 76.8% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



12. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
- 3.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B5/B12/B17/B26/B71 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 4/5/17 SAR test was covered by Band 66/26/12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
3. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
4. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

12.1 Head SAR

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	9262	1852.4	22.81	24.50	1.476	0.01	0.077	0.114
	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	9400	1880	22.70	24.50	1.514	0.09	0.063	0.095
	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	9538	1907.6	22.57	24.50	1.560	-0.03	0.065	0.101
01	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 2	9262	1852.4	22.81	24.50	1.476	-0.01	0.193	0.285
	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 3	9262	1852.4	22.81	24.50	1.476	0.02	0.084	0.124
	WCDMA II	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 4	9262	1852.4	22.81	24.50	1.476	0.05	0.132	0.195
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	1312	1712.4	22.60	24.50	1.549	0.08	0.069	0.107
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	1413	1732.6	22.55	24.50	1.567	0.05	0.073	0.114
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 1	1513	1752.6	22.58	24.50	1.556	0.04	0.060	0.093
02	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 2	1413	1732.6	22.55	24.50	1.567	-0.03	0.147	0.230
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 3	1413	1732.6	22.55	24.50	1.567	0.01	0.141	0.221
	WCDMA IV	RMC 12.2Kbps	Front	10mm	Ant 0	Strap 4	1413	1732.6	22.55	24.50	1.567	-0.07	0.041	0.064
	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 1	4132	826.4	23.33	24.50	1.309	0.14	< 0.001	< 0.001
03	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 1	4182	836.4	23.21	24.50	1.346	0	< 0.001	< 0.001
	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 1	4233	846.6	22.91	24.50	1.442	-0.08	< 0.001	< 0.001
	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 2	4132	826.4	23.33	24.50	1.309	0.12	< 0.001	< 0.001
	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 3	4132	826.4	23.33	24.50	1.309	-0.01	< 0.001	< 0.001
	WCDMA V	RMC 12.2Kbps	Front	10mm	Ant 1	Strap 4	4132	826.4	23.33	24.50	1.309	0.19	< 0.001	< 0.001

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
04	LTE Band 12	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 1	23095	707.5	23.00	24.50	1.413	-0.02	< 0.001	< 0.001
	LTE Band 12	10M	QPSK	25	0	Front	10mm	Ant 1	Strap 1	23095	707.5	21.81	23.50	1.476	0.08	< 0.001	< 0.001
	LTE Band 12	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 2	23095	707.5	23.00	24.50	1.413	0.03	< 0.001	< 0.001
	LTE Band 12	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 3	23095	707.5	23.00	24.50	1.413	0.15	< 0.001	< 0.001
	LTE Band 12	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 4	23095	707.5	23.00	24.50	1.413	-0.09	< 0.001	< 0.001
05	LTE Band 13	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 1	23230	782	23.19	24.50	1.352	0.13	< 0.001	< 0.001
	LTE Band 13	10M	QPSK	25	0	Front	10mm	Ant 1	Strap 1	23230	782	22.34	23.50	1.306	0.05	< 0.001	< 0.001
	LTE Band 13	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 2	23230	782	23.19	24.50	1.352	-0.11	< 0.001	< 0.001
	LTE Band 13	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 3	23230	782	23.19	24.50	1.352	-0.08	< 0.001	< 0.001
	LTE Band 13	10M	QPSK	1	0	Front	10mm	Ant 1	Strap 4	23230	782	23.19	24.50	1.352	0.09	< 0.001	< 0.001
	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	26140	1860	22.84	24.50	1.466	-0.07	0.117	0.171
	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	26340	1880	22.64	24.50	1.535	-0.03	0.110	0.169
	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	26590	1905	22.68	24.50	1.521	-0.01	0.105	0.160
	LTE Band 25	20M	QPSK	50	24	Front	10mm	Ant 0	Strap 1	26140	1860	21.99	23.50	1.416	0.08	0.086	0.122
06	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 2	26140	1860	22.84	24.50	1.466	-0.05	0.188	0.276
	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 4	26140	1860	22.84	24.50	1.466	0.04	0.060	0.088
	LTE Band 25	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 3	26140	1860	22.84	24.50	1.466	0.05	0.151	0.221
07	LTE Band 26	15M	QPSK	1	0	Front	10mm	Ant 1	Strap 1	26865	831.5	22.54	24.50	1.570	0.02	< 0.001	< 0.001
	LTE Band 26	15M	QPSK	36	20	Front	10mm	Ant 1	Strap 1	26865	831.5	21.60	23.50	1.549	-0.15	< 0.001	< 0.001
	LTE Band 26	15M	QPSK	1	0	Front	10mm	Ant 1	Strap 2	26865	831.5	22.54	24.50	1.570	-0.08	< 0.001	< 0.001
	LTE Band 26	15M	QPSK	1	0	Front	10mm	Ant 1	Strap 3	26865	831.5	22.54	24.50	1.570	0.04	< 0.001	< 0.001
	LTE Band 26	15M	QPSK	1	0	Front	10mm	Ant 1	Strap 4	26865	831.5	22.54	24.50	1.570	0.13	< 0.001	< 0.001
	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	132072	1720	23.23	24.50	1.340	0.03	0.081	0.109
	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	132322	1745	22.84	24.50	1.466	-0.02	0.067	0.098
	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 1	132572	1770	23.16	24.50	1.361	0.08	0.064	0.087
	LTE Band 66	20M	QPSK	50	24	Front	10mm	Ant 0	Strap 1	132072	1720	22.44	23.50	1.276	0.06	0.066	0.084
08	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 2	132072	1720	23.23	24.50	1.340	-0.09	0.174	0.233
	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 3	132072	1720	23.23	24.50	1.340	0.07	0.080	0.107
	LTE Band 66	20M	QPSK	1	0	Front	10mm	Ant 0	Strap 4	132072	1720	23.23	24.50	1.340	-0.01	0.037	0.050
09	LTE Band 71	20M	QPSK	1	0	Front	10mm	Ant 1	Strap 1	133322	683	23.30	24.50	1.318	0.08	< 0.001	< 0.001
	LTE Band 71	20M	QPSK	50	0	Front	10mm	Ant 1	Strap 1	133322	683	22.20	23.50	1.349	0.13	< 0.001	< 0.001
	LTE Band 71	20M	QPSK	1	0	Front	10mm	Ant 1	Strap 2	133322	683	23.30	24.50	1.318	-0.11	< 0.001	< 0.001
	LTE Band 71	20M	QPSK	1	0	Front	10mm	Ant 1	Strap 3	133322	683	23.30	24.50	1.318	0.09	< 0.001	< 0.001
	LTE Band 71	20M	QPSK	1	0	Front	10mm	Ant 1	Strap 4	133322	683	23.30	24.50	1.318	0.01	< 0.001	< 0.001

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 1	11	2462	19.50	20.00	1.122	100	1.000	-0.15	0.004	0.004
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 1	1	2412	18.90	20.00	1.288	100	1.000	0.01	0.002	0.003
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 1	6	2437	19.40	20.00	1.148	100	1.000	-0.19	0.002	0.002
10	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 2	11	2462	19.50	20.00	1.122	100	1.000	0	0.006	0.007
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 3	11	2462	19.50	20.00	1.122	100	1.000	-0.12	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 1	Strap 4	11	2462	19.50	20.00	1.122	100	1.000	-0.14	0.001	0.001

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 1	39	2441	19.28	20.00	1.180	76.8	1.085	0.18	0.032	0.041
	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 1	0	2402	18.53	19.00	1.114	76.8	1.085	-0.18	0.031	0.037
	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 1	78	2480	17.55	18.50	1.244	76.8	1.085	0.14	0.028	0.038
11	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 2	39	2441	19.28	20.00	1.180	76.8	1.085	0.08	0.041	0.052
	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 3	39	2441	19.28	20.00	1.180	76.8	1.085	0.13	0.036	0.046
	Bluetooth	1Mbps	Front	10mm	Ant 1	Strap 4	39	2441	19.28	20.00	1.180	76.8	1.085	-0.06	0.033	0.042

**12.2 Extremity SAR****<WCDMA SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	9262	1852.4	22.81	24.50	1.476	0.16	0.088	0.130
	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	9400	1880	22.70	24.50	1.514	0.08	0.074	0.112
	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	9538	1907.6	22.57	24.50	1.560	0	0.068	0.106
	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 2	9262	1852.4	22.81	24.50	1.476	-0.17	0.081	0.120
12	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 3	9262	1852.4	22.81	24.50	1.476	-0.05	0.091	0.134
	WCDMA II	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 4	9262	1852.4	22.81	24.50	1.476	0.06	0.076	0.112
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	1312	1712.4	22.60	24.50	1.549	0.13	0.036	0.056
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	1413	1732.6	22.55	24.50	1.567	0.09	0.045	0.071
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 1	1513	1752.6	22.58	24.50	1.556	-0.12	0.035	0.054
13	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 2	1413	1732.6	22.55	24.50	1.567	0.09	0.086	0.135
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 3	1413	1732.6	22.55	24.50	1.567	-0.07	0.083	0.130
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Ant 0	Strap 4	1413	1732.6	22.55	24.50	1.567	0.08	0.058	0.091
	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 1	4132	826.4	23.33	24.50	1.309	0.02	0.152	0.199
	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 1	4182	836.4	23.21	24.50	1.346	-0.05	0.178	0.240
	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 1	4233	846.6	22.91	24.50	1.442	0.01	0.166	0.239
14	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 2	4182	836.4	23.21	24.50	1.346	-0.01	0.337	0.454
	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 3	4182	836.4	23.21	24.50	1.346	0.03	0.209	0.281
	WCDMA V	RMC 12.2Kbps	Back	0mm	Ant 1	Strap 4	4182	836.4	23.21	24.50	1.346	-0.01	0.158	0.213

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 12	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 1	23095	707.5	23.00	24.50	1.413	-0.07	0.196	0.277
	LTE Band 12	10M	QPSK	25	0	Back	0mm	Ant 1	Strap 1	23095	707.5	21.81	23.50	1.476	0.09	0.145	0.214
	LTE Band 12	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 2	23095	707.5	23.00	24.50	1.413	0.03	0.197	0.278
15	LTE Band 12	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 3	23095	707.5	23.00	24.50	1.413	-0.1	0.351	0.496
	LTE Band 12	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 4	23095	707.5	23.00	24.50	1.413	-0.08	0.097	0.137
	LTE Band 13	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 1	23230	782	23.19	24.50	1.352	-0.13	0.159	0.215
	LTE Band 13	10M	QPSK	25	0	Back	0mm	Ant 1	Strap 1	23230	782	22.34	23.50	1.306	-0.01	0.136	0.178
	LTE Band 13	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 2	23230	782	23.19	24.50	1.352	0.08	0.197	0.266
16	LTE Band 13	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 3	23230	782	23.19	24.50	1.352	-0.06	0.313	0.423
	LTE Band 13	10M	QPSK	1	0	Back	0mm	Ant 1	Strap 4	23230	782	23.19	24.50	1.352	0.1	0.102	0.138
	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	26140	1860	22.84	24.50	1.466	-0.06	0.058	0.085
	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	26340	1880	22.64	24.50	1.535	-0.09	0.064	0.098
	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	26590	1905	22.68	24.50	1.521	0.03	0.052	0.079
	LTE Band 25	20M	QPSK	50	24	Back	0mm	Ant 0	Strap 1	26140	1860	21.99	23.50	1.416	-0.11	0.042	0.059
17	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 2	26340	1880	22.64	24.50	1.535	0.05	0.067	0.103
	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 3	26340	1880	22.64	24.50	1.535	-0.14	0.060	0.092
	LTE Band 25	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 4	26340	1880	22.64	24.50	1.535	0.08	0.054	0.083
	LTE Band 26	15M	QPSK	1	0	Back	0mm	Ant 1	Strap 1	26865	831.5	22.54	24.50	1.570	0.08	0.288	0.452
	LTE Band 26	15M	QPSK	36	20	Back	0mm	Ant 1	Strap 1	26865	831.5	21.60	23.50	1.549	0.16	0.231	0.358
	LTE Band 26	15M	QPSK	1	0	Back	0mm	Ant 1	Strap 2	26865	831.5	22.54	24.50	1.570	0.05	0.171	0.269
18	LTE Band 26	15M	QPSK	1	0	Back	0mm	Ant 1	Strap 3	26865	831.5	22.54	24.50	1.570	0.15	0.297	0.466
	LTE Band 26	15M	QPSK	1	0	Back	0mm	Ant 1	Strap 4	26865	831.5	22.54	24.50	1.570	-0.14	0.139	0.218
	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	132072	1720	23.23	24.50	1.340	0.07	0.063	0.084
	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	132322	1745	22.84	24.50	1.466	0.02	0.051	0.075
	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 1	132572	1770	23.16	24.50	1.361	0.06	0.051	0.069
	LTE Band 66	20M	QPSK	50	24	Back	0mm	Ant 0	Strap 1	132072	1720	22.44	23.50	1.276	-0.08	0.048	0.061
	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 2	132072	1720	23.23	24.50	1.340	0.03	0.072	0.096
19	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 3	132072	1720	23.23	24.50	1.340	0.03	0.073	0.098
	LTE Band 66	20M	QPSK	1	0	Back	0mm	Ant 0	Strap 4	132072	1720	23.23	24.50	1.340	-0.11	0.047	0.063
	LTE Band 71	20M	QPSK	1	0	Back	0mm	Ant 1	Strap 1	133322	683	23.30	24.50	1.318	0.08	0.240	0.316
	LTE Band 71	20M	QPSK	50	0	Back	0mm	Ant 1	Strap 1	133322	683	22.20	23.50	1.349	-0.09	0.190	0.256
	LTE Band 71	20M	QPSK	1	0	Back	0mm	Ant 1	Strap 2	133322	683	23.30	24.50	1.318	0.03	0.259	0.341
20	LTE Band 71	20M	QPSK	1	0	Back	0mm	Ant 1	Strap 3	133322	683	23.30	24.50	1.318	-0.15	0.365	0.481
	LTE Band 71	20M	QPSK	1	0	Back	0mm	Ant 1	Strap 4	133322	683	23.30	24.50	1.318	-0.01	0.153	0.202

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 1	11	2462	19.50	20.00	1.122	100	1.000	-0.05	0.024	0.027
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 1	1	2412	18.90	20.00	1.288	100	1.000	-0.12	0.015	0.019
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 1	6	2437	19.40	20.00	1.148	100	1.000	0.05	0.023	0.026
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 2	11	2462	19.50	20.00	1.122	100	1.000	0.01	0.025	0.028
21	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 3	11	2462	19.50	20.00	1.122	100	1.000	0.02	0.026	0.029
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 1	Strap 4	11	2462	19.50	20.00	1.122	100	1.000	0.08	0.019	0.021

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Strap	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 1	39	2441	19.28	20.00	1.180	76.8	1.085	0.06	0.025	0.032
	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 1	0	2402	18.53	19.00	1.114	76.8	1.085	0.18	0.021	0.025
	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 1	78	2480	17.55	18.50	1.244	76.8	1.085	0.07	0.023	0.031
	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 2	39	2441	19.28	20.00	1.180	76.8	1.085	0.14	0.028	0.036
22	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 3	39	2441	19.28	20.00	1.180	76.8	1.085	0.04	0.040	0.051
	Bluetooth	1Mbps	Back	0mm	Ant 1	Strap 4	39	2441	19.28	20.00	1.180	76.8	1.085	-0.16	0.026	0.033

13. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Head	Extremity
1.	WWAN + WLAN2.4GHz	Yes	Yes
2.	WWAN + Bluetooth	Yes	Yes

General Note:

- The worst case WLAN reported SAR for each configuration was used for SAR summation. Therefore, the following summations represent the absolute worst cases for simultaneous transmission.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation < 1.6W/kg.
 - $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

13.1 Head Exposure Conditions

Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)
	Maximum WWAN	WLAN2.4GHz Ant 1	Bluetooth Ant 1		
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
Front	0.285	0.007	0.052	0.292	0.337

13.2 Extremity Exposure Conditions

Exposure Position	1	2	3	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)
	Maximum WWAN	WLAN2.4GHz Ant 1	Bluetooth Ant 1		
	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)		
Back	0.496	0.029	0.051	0.525	0.547

Test Engineer : Bevis Chang and Lu Chen

14. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

15. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [8] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [9] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [10] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.