

## RF EXPOSURE EVALUATION

### 1. PRODUCT INFORMATION

<b>FCC ID</b>	2AKC6-AX3010
<b>Product Description</b>	Wireless USB Adapter
<b>Model Name</b>	AX3010, AX3008
<b>Frequency Band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Bluetooth: 2.402GHz ~ 2.480GHz <input type="checkbox"/> Others (NFC:13.56MHz)
<b>Device Category</b>	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others:
<b>Antenna Diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Antenna Gain</b>	2.4GWIFI: ANT 1: 1.34dBi; ANT 2: 2.11dBi 5GWIFI: Ant 1: 4.44dBi; Ant 2: 5.46dBi
<b>Minimum Assessment Distance</b>	5mm
<b>Evaluation Applied</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation
<b>Evaluation Result</b>	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

## 2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

Following FCC KDB 447498 D01 “General SAR test exclusion guidance” The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}]}{\leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}}$$
  - $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
  - Power and distance are rounded to the nearest mW and mm before calculation.
  - The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) (  $f(\text{MHz})/150$ )] mW, at 100MHz to 1500 MHz;
  - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)-10] mW at  $> 1500$  MHz and  $\leq 6$  GHz;
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances  $\leq 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by [agc01@agccert.com](mailto:agc01@agccert.com).

### 3. MEASUREMENT RESULT

Test Mode	Channel Frequency (MHz)	Max Output power (dBm)	Max Output power (mW)	Calculation Value (Note 1)	Limit Value
OFDM					
2.4G WLAN ANT 1	2422	6.48	4.446	1.384	3.0
5G WLAN ANT 2	5200	5.00	3.162	1.442	3.0
5G MIMO	5200	8.01	6.324	2.884	3.0
DSSS					
2.4G WLAN ANT 2	2412	6.13	4.102	1.274	3.0
OFDMA					
2.4G WLAN MIMO	2422	9.23	8.375	2.607	3.0
5G WLAN ANT 1	5210	5.49	3.540	1.616	3.0

Note 1: Calculation Value = [(max. power of channel, mW)/(min. test separation distance, mm)] · [√f(GHz)].

For example:  $6.324/5 \cdot \sqrt{5.200} = 2.884 \leq 3.0$

### 4. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.