

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-0599/20-08-04 MPE (FCC)

Certification numbers and labeling requirements	
FCC ID	2ASKB-HIRES55

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:

Alexander Hnatovskiy
 Lab Manager
 Radio Communications & EMC

Marco Scigliano
 Testing Manager
 Radio Communications & EMC

EUT technologies:

Technologies:	Max. power measured EIRP [dBm]	EIRP declared by customer
77 GHz VRD	16.14	18 dBm

NOTE: Test results taken from CTC Advanced report 1-0599/20-08-02

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	VRD	
Frequency (MHz)	77000	
PG Declared max power (EIRP)	19	dBm
R Distance	20	cm
S MPE limit for uncontrolled exposure	1	mW/cm ²
Calculated Power density:	0.0158	mW/cm ²
Calculated percentage of Limit:	1.58%	

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.