



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Phone
BRAND NAME : Motorola
MODEL NAME : XT2097-12
FCC ID : IHDT56ZJ2
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Dec. 07, 2020 and testing was completed on Dec. 30, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
1.9 Specification of Accessory.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	34
3.6 AC Conducted Emission Measurement.....	38
3.7 Antenna Requirements.....	40
4 LIST OF MEASURING EQUIPMENT	41
5 UNCERTAINTY OF EVALUATION	42
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR0D0715C	Rev. 01	Initial issue of report	Jan. 14, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.09 dB at 2389.950 & 2483.860 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 4.74 dB at 0.151 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago, IL60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago, IL60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Motorola
Model Name	XT2097-12
FCC ID	IHDT56ZJ2
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE FM Receiver, and GNSS
IMEI Code	Conducted: N/A Conduction: 354249350010638/354249350035635 Radiated: N/A
HW Version	DVT2
SW Version	QOJ30.26
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are three samples, please refer to the product equality declaration exhibit submitted. According to the difference, we choose the sample 2 to full test.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 21.27 dBm (0.1340 W) 802.11g : 22.70 dBm (0.1862 W) 802.11n HT20 : 22.72 dBm (0.1871 W)
Antenna Type / Gain	PIFA Antenna with gain -2.5 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Chenyang)	Model Name	MC-101
AC Adapter 1(EU)	Brand Name	Motorola (Chenyang)	Model Name	MC-102
AC Adapter 1(UK)	Brand Name	Motorola (Chenyang)	Model Name	MC-103
AC Adapter 1(AU)	Brand Name	Motorola (Chenyang)	Model Name	MC-105
AC Adapter 1(AR)	Brand Name	Motorola (Chenyang)	Model Name	MC-106
AC Adapter 1(BR)	Brand Name	Motorola (Chenyang)	Model Name	MC-107
AC Adapter 2(IN)	Brand Name	Motorola (Chenyang)	Model Name	MC-104
AC Adapter 3(US)	Brand Name	Motorola (Salcomp)	Model Name	MC-101
AC Adapter 3(EU)	Brand Name	Motorola (Salcomp)	Model Name	MC-102
AC Adapter 3(UK)	Brand Name	Motorola (Salcomp)	Model Name	MC-103
AC Adapter 3(AU)	Brand Name	Motorola (Salcomp)	Model Name	MC-105
AC Adapter 3(AR)	Brand Name	Motorola (Salcomp)	Model Name	MC-106
AC Adapter 3(CHILE)	Brand Name	Motorola (Salcomp)	Model Name	MC-109
AC Adapter 4(US)	Brand Name	Motorola (Aohai)	Model Name	MC-101
AC Adapter 4(EU)	Brand Name	Motorola (Aohai)	Model Name	MC-102
AC Adapter 4(UK)	Brand Name	Motorola (Aohai)	Model Name	SC-103
AC Adapter 4(AU)	Brand Name	Motorola (Aohai)	Model Name	SC-105
AC Adapter 4(AR)	Brand Name	Motorola (Aohai)	Model Name	MC-106
AC Adapter 5(BR)	Brand Name	Motorola (Flex)	Model Name	MC-107
AC Adapter 6(BR)	Brand Name	Motorola (Salcomp)	Model Name	MC-107
AC Adapter 7(UK)	Brand Name	Motorola (Chenyang)	Model Name	SC-43
AC Adapter 8(EU)	Brand Name	Motorola (Salom)	Model Name	SC-42
AC Adapter 8(US)	Brand Name	Motorola (Salom)	Model Name	SC-41
Battery 1	Brand Name	Motorola (Sunwoda)	Model Name	JK50
Battery 2	Brand Name	Motorola (ATL)	Model Name	JK50
Battery 3	Brand Name	Motorola (SCUD)	Model Name	JK50
Earphone 1	Brand Name	Motorola (NEW LEADER)	Model Name	NLD-EM313A-23SF
Earphone 2	Brand Name	Motorola(Ju wei)	Model Name	JWEP1185-ZN01H
USB Cable 1	Brand Name	Motorola (Washin)	Model Name	HX-ZN-04
USB Cable 2	Brand Name	Motorola (Ju wei)	Model Name	JWUB1472-ZN01H
USB Cable 3	Brand Name	Motorola (I SHENG)	Model Name	SC18C28955

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		




2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 2(Charging from Adapter 6) + Earphone 2 + Battery 2
Remark: For Radiated Test Cases, The tests were performed with Adapter 1, Earphone 1 and USB Cable 1	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.6 dB.

Offset(dB) = RF cable loss(dB).

= 5.6 (dB)

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Long Wu	Temperature :	21~25°C
		Relative Humidity :	51~54%


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11b	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	02
-------------	---------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11g	Test Channel :	09
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 30 DEC 2020 10:21:30

Channel Plot




Date: 30 DEC 2020 10:21:40

Spurious Emission 30MHz~3GHz



Date: 30 DEC 2020 10:21:54


Spurious Emission 2GHz~25GHz



Date: 30 DEC 2020 10:22:02




Test Mode :	802.11g	Test Channel :	10
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 28 DEC 2020 15:23:29

Channel Plot




Date: 28 DEC 2020 15:23:38

Spurious Emission 30MHz~3GHz



Date: 28 DEC 2020 15:23:51

Spurious Emission 2GHz~25GHz




Date: 28 DEC 2020 15:23:59




Test Mode : 802.11n HT20

Test Channel : 01


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz







Test Mode : 802.11n HT20

Test Channel : 02


100kHz PSD reference Level




Channel Plot



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----


100kHz PSD reference Level



Spurious Emission 30MHz~3GHz




Spurious Emission 2GHz~25GHz






Test Mode :	802.11n HT20	Test Channel :	08
-------------	--------------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	09
-------------	--------------	----------------	----





Test Mode :	802.11n HT20	Test Channel :	10
-------------	--------------	----------------	----






Test Mode : 802.11n HT20


Test Channel : 11

100kHz PSD reference Level




Date: 28 DEC 2020 15:38:29

Channel Plot




Date: 28 DEC 2020 15:38:35

Spurious Emission 30MHz~3GHz



Date: 28 DEC 2020 15:38:48

Spurious Emission 2GHz~25GHz



Date: 28 DEC 2020 15:38:56

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2020	Dec. 23, 2020~ Dec. 30, 2020	Nov. 01, 2021	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 13, 2020	Dec. 23, 2020~ Dec. 30, 2020	Jan. 12, 2021	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 13, 2020	Dec. 23, 2020~ Dec. 30, 2020	Jan. 12, 2021	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 17, 2020	Dec. 30, 2020	Oct. 16, 2021	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz	Apr. 14, 2020	Dec. 30, 2020	Apr. 13, 2021	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 01, 2020	Dec. 30, 2020	Oct. 31, 2021	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz~1GHz	May 29, 2020	Dec. 30, 2020	May 28, 2021	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 27, 2020	Dec. 30, 2020	Apr. 26, 2021	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	Dec. 30, 2020	Nov. 08, 2021	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Apr. 14, 2020	Dec. 30, 2020	Apr. 13, 2021	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Dec. 30, 2020	Jan. 07, 2021	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	1Ghz-18Ghz	Jan. 03, 2020	Dec. 30, 2020	Jan. 02, 2021	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2020	Dec. 30, 2020	Apr. 14, 2021	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 30, 2020	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 30, 2020	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 30, 2020	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 14, 2020	Dec. 28, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 17, 2020	Dec. 28, 2020	Oct. 16, 2021	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 27, 2020	Dec. 28, 2020	Oct. 26, 2021	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 17, 2020	Dec. 28, 2020	Oct. 16, 2021	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------



Appendix A. Conducted Test Results

Test Engineer:	Long Wu	Temperature:	21~25	°C
Test Date:	2020/12/23~2020/12/30	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.49	9.09	0.50	Pass
11b	1Mbps	1	6	2437	12.34	9.11	0.50	Pass
11b	1Mbps	1	11	2462	12.34	9.09	0.50	Pass
11g	6Mbps	1	1	2412	18.43	16.34	0.50	Pass
11g	6Mbps	1	2	2417	18.43	16.32	0.50	Pass
11g	6Mbps	1	6	2437	18.58	16.32	0.50	Pass
11g	6Mbps	1	9	2452	18.18	16.34	0.50	Pass
11g	6Mbps	1	10	2457	18.13	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.38	16.32	0.50	Pass
HT20	MCS0	1	1	2412	18.88	17.56	0.50	Pass
HT20	MCS0	1	2	2417	19.03	17.56	0.50	Pass
HT20	MCS0	1	6	2437	19.28	17.54	0.50	Pass
HT20	MCS0	1	8	2447	19.08	17.56	0.50	Pass
HT20	MCS0	1	9	2452	18.63	17.56	0.50	Pass
HT20	MCS0	1	10	2457	18.68	17.56	0.50	Pass
HT20	MCS0	1	11	2462	18.93	17.54	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	21.21	30.00	-2.50	18.71	36.00	Pass
11b	1Mbps	1	6	2437	21.27	30.00	-2.50	18.77	36.00	Pass
11b	1Mbps	1	11	2462	20.87	30.00	-2.50	18.37	36.00	Pass
11g	6Mbps	1	1	2412	22.05	30.00	-2.50	19.55	36.00	Pass
11g	6Mbps	1	2	2417	22.70	30.00	-2.50	20.20	36.00	Pass
11g	6Mbps	1	6	2437	22.29	30.00	-2.50	19.79	36.00	Pass
11g	6Mbps	1	9	2452	22.52	30.00	-2.50	20.02	36.00	Pass
11g	6Mbps	1	10	2457	21.74	30.00	-2.50	19.24	36.00	Pass
11g	6Mbps	1	11	2462	20.72	30.00	-2.50	18.22	36.00	Pass
HT20	MCS0	1	1	2412	20.92	30.00	-2.50	18.42	36.00	Pass
HT20	MCS0	1	2	2417	22.72	30.00	-2.50	20.22	36.00	Pass
HT20	MCS0	1	6	2437	22.45	30.00	-2.50	19.95	36.00	Pass
HT20	MCS0	1	8	2447	22.57	30.00	-2.50	20.07	36.00	Pass
HT20	MCS0	1	9	2452	22.42	30.00	-2.50	19.92	36.00	Pass
HT20	MCS0	1	10	2457	21.46	30.00	-2.50	18.96	36.00	Pass
HT20	MCS0	1	11	2462	20.70	30.00	-2.50	18.20	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)


2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	18.46
11b	1Mbps	1	6	2437	0.00	18.45
11b	1Mbps	1	11	2462	0.00	17.97
11g	6Mbps	1	1	2412	0.15	13.18
11g	6Mbps	1	2	2417	0.15	16.68
11g	6Mbps	1	6	2437	0.15	16.20
11g	6Mbps	1	9	2452	0.15	16.03
11g	6Mbps	1	10	2457	0.15	12.99
11g	6Mbps	1	11	2462	0.15	11.55
HT20	MCS0	1	1	2412	0.12	11.17
HT20	MCS0	1	2	2417	0.12	16.58
HT20	MCS0	1	6	2437	0.12	16.08
HT20	MCS0	1	8	2447	0.12	16.38
HT20	MCS0	1	9	2452	0.12	13.65
HT20	MCS0	1	10	2457	0.12	11.85
HT20	MCS0	1	11	2462	0.12	10.55

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-7.36	-2.50	8.00	Pass
11b	1Mbps	1	6	2437	-6.44	-2.50	8.00	Pass
11b	1Mbps	1	11	2462	-7.52	-2.50	8.00	Pass
11g	6Mbps	1	1	2412	-13.52	-2.50	8.00	Pass
11g	6Mbps	1	2	2417	-10.86	-2.50	8.00	Pass
11g	6Mbps	1	6	2437	-10.90	-2.50	8.00	Pass
11g	6Mbps	1	9	2452	-11.99	-2.50	8.00	Pass
11g	6Mbps	1	10	2457	-12.98	-2.50	8.00	Pass
11g	6Mbps	1	11	2462	-15.59	-2.50	8.00	Pass
HT20	MCS0	1	1	2412	-16.69	-2.50	8.00	Pass
HT20	MCS0	1	2	2417	-10.89	-2.50	8.00	Pass
HT20	MCS0	1	6	2437	-11.01	-2.50	8.00	Pass
HT20	MCS0	1	8	2447	-11.25	-2.50	8.00	Pass
HT20	MCS0	1	9	2452	-12.56	-2.50	8.00	Pass
HT20	MCS0	1	10	2457	-14.65	-2.50	8.00	Pass
HT20	MCS0	1	11	2462	-16.94	-2.50	8.00	Pass




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15C TWO-LISN-CN02-N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.154	54.47	-11.31	65.78	34.19	9.81	10.47	QP
2	0.154	41.57	-14.21	55.78	21.29	9.81	10.47	Average
3	0.168	46.87	-18.21	65.08	26.60	9.84	10.43	QP
4	0.168	32.37	-22.71	55.08	12.10	9.84	10.43	Average
5	0.197	46.86	-16.90	63.76	26.60	9.89	10.37	QP
6	0.197	33.76	-20.00	53.76	13.50	9.89	10.37	Average
7	0.211	47.14	-16.04	63.18	26.90	9.88	10.36	QP
8	0.211	32.84	-20.34	53.18	12.60	9.88	10.36	Average
9	17.109	38.46	-21.54	60.00	16.80	11.22	10.44	QP
10	17.109	29.46	-20.54	50.00	7.80	11.22	10.44	Average
11	19.635	40.09	-19.91	60.00	18.20	11.40	10.49	QP
12	19.635	30.49	-19.51	50.00	8.60	11.40	10.49	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2389.95	59.6	-14.4	74	52.08	33.5	7.47	33.45	110	111	P	H
		2389.95	50.91	-3.09	54	43.39	33.5	7.47	33.45	110	111	A	H
	*	2414	110.28	-	-	102.87	33.37	7.48	33.44	110	111	P	H
	*	2414	107.27	-	-	99.86	33.37	7.48	33.44	110	111	A	H
		2388.91	57.39	-16.61	74	49.87	33.5	7.47	33.45	391	82	P	V
		2389.95	48.95	-5.05	54	41.43	33.5	7.47	33.45	391	82	A	V
	*	2414	108.19	-	-	100.78	33.37	7.48	33.44	391	82	P	V
	*	2414	105.16	-	-	97.75	33.37	7.48	33.44	391	82	A	V
802.11b CH 11 2462MHz		2483.74	59.13	-14.87	74	52.15	32.86	7.55	33.43	104	118	P	H
		2483.5	50.71	-3.29	54	43.73	32.86	7.55	33.43	104	118	A	H
	*	2464	111.23	-	-	104.14	32.99	7.53	33.43	104	118	P	H
	*	2464	108.11	-	-	101.02	32.99	7.53	33.43	104	118	A	H
		2484.46	56.4	-17.6	74	49.42	32.86	7.55	33.43	294	64	P	V
		2483.5	46.5	-7.5	54	39.52	32.86	7.55	33.43	294	64	A	V
	*	2462	105.26	-	-	98.17	32.99	7.53	33.43	294	64	P	V
	*	2460	102.2	-	-	95.11	32.99	7.53	33.43	294	64	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	43.02	-30.98	74	59.06	34.84	10.84	61.72	300	0	P	H
		4824	41.55	-32.45	74	57.59	34.84	10.84	61.72	300	360	P	V
802.11b CH 06 2437MHz		4872	43.47	-30.53	74	59.46	34.83	10.89	61.71	300	0	P	H
		7308	47.82	-26.18	74	59.98	36.39	13.35	61.9	300	0	P	H
		4872	42.86	-31.14	74	58.85	34.83	10.89	61.71	300	360	P	V
		7308	49.98	-24.02	74	62.14	36.39	13.35	61.9	300	360	P	V
802.11b CH 11 2462MHz		4926	42.27	-31.73	74	58.23	34.82	10.93	61.71	300	0	P	H
		7386	50.87	-23.13	74	62.92	36.44	13.41	61.9	300	0	P	H
		4926	41.9	-32.1	74	57.86	34.82	10.93	61.71	300	360	P	V
		7386	53.36	-20.64	74	65.41	36.44	13.41	61.9	100	39	P	V
		7386	48.87	-5.13	54	60.92	36.44	13.41	61.9	100	39	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.95	63.37	-10.63	74	55.85	33.5	7.47	33.45	100	110	P	H
		2389.95	50.47	-3.53	54	42.95	33.5	7.47	33.45	100	110	A	H
	*	2408	107.54	-	-	100.13	33.37	7.48	33.44	100	110	P	H
	*	2418	99.21	-	-	91.8	33.37	7.48	33.44	100	110	A	H
		2389.95	58.79	-15.21	74	51.27	33.5	7.47	33.45	339	91	P	V
		2389.95	47.26	-6.74	54	39.74	33.5	7.47	33.45	339	91	A	V
	*	2408	103.2	-	-	95.79	33.37	7.48	33.44	339	91	P	V
	*	2418	93.62	-	-	86.21	33.37	7.48	33.44	339	91	A	V
802.11g CH 02 2417MHz		2389.95	59.18	-14.82	74	51.66	33.5	7.47	33.45	100	117	P	H
		2389.82	48.65	-5.35	54	41.13	33.5	7.47	33.45	100	117	A	H
	*	2424	110.72	-	-	103.42	33.24	7.5	33.44	100	117	P	H
	*	2424	102.7	-	-	95.4	33.24	7.5	33.44	100	117	A	H
		2374.35	56.12	-17.88	74	48.84	33.29	7.44	33.45	385	60	P	V
		2389.95	46.51	-7.49	54	38.99	33.5	7.47	33.45	385	60	A	V
	*	2424	107.2	-	-	99.9	33.24	7.5	33.44	385	60	P	V
	*	2422	99.45	-	-	92.15	33.24	7.5	33.44	385	60	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 09 2452MHz		2484.16	64.96	-9.04	74	57.98	32.86	7.55	33.43	110	124	P	H
		2483.5	50.65	-3.35	54	43.67	32.86	7.55	33.43	110	124	A	H
		2448	112.28	-	-	105.09	33.11	7.51	33.43	110	124	P	H
		2446	102.87	-	-	95.68	33.11	7.51	33.43	110	124	A	H
		2483.74	59.28	-14.72	74	52.3	32.86	7.55	33.43	332	74	P	V
		2483.56	46.97	-7.03	54	39.99	32.86	7.55	33.43	332	74	A	V
		2448	107.82	-	-	100.63	33.11	7.51	33.43	332	74	P	V
		2446	98.4	-	-	91.21	33.11	7.51	33.43	332	74	A	V
802.11g CH 10 2457MHz		2483.98	65.73	-8.27	74	58.75	32.86	7.55	33.43	113	113	P	H
		2483.86	50.91	-3.09	54	43.93	32.86	7.55	33.43	113	113	A	H
		2450	107.92	-	-	100.73	33.11	7.51	33.43	113	113	P	H
		2452	99.89	-	-	92.7	33.11	7.51	33.43	113	113	A	H
		2487.58	61.38	-12.62	74	54.51	32.73	7.56	33.42	321	92	P	V
		2483.5	47.15	-6.85	54	40.17	32.86	7.55	33.43	321	92	A	V
		2452	103.31	-	-	96.12	33.11	7.51	33.43	321	92	P	V
		2462	94.24	-	-	87.15	32.99	7.53	33.43	321	92	A	V
802.11g CH 11 2462MHz		2483.5	66.98	-7.02	74	60	32.86	7.55	33.43	106	112	P	H
		2483.5	50.73	-3.27	54	43.75	32.86	7.55	33.43	106	112	A	H
	*	2458	107.53	-	-	100.44	32.99	7.53	33.43	106	112	P	H
	*	2456	97.91	-	-	90.82	32.99	7.53	33.43	106	112	A	H
		2484.22	62.05	-11.95	74	55.07	32.86	7.55	33.43	368	72	P	V
		2483.5	47.28	-6.72	54	40.3	32.86	7.55	33.43	368	72	A	V
	*	2458	101.88	-	-	94.79	32.99	7.53	33.43	368	72	P	V
	*	2456	92.68	-	-	85.59	32.99	7.53	33.43	368	72	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	42.41	-31.59	74	58.45	34.84	10.84	61.72	300	0	P	H
		4824	41.6	-32.4	74	57.64	34.84	10.84	61.72	300	360	P	V
802.11g CH 02 2417MHz		4834	41.73	-32.27	74	57.76	34.83	10.86	61.72	300	0	P	H
		7251	49.48	-24.52	74	61.71	36.36	13.31	61.9	300	0	P	H
		4834	41.87	-32.13	74	57.9	34.83	10.86	61.72	300	360	P	V
		7251	53.19	-20.81	74	65.42	36.36	13.31	61.9	342	68	P	V
		7251	43.08	-10.92	54	55.31	36.36	13.31	61.9	342	68	A	V
802.11g CH 06 2437MHz		4872	41.34	-32.66	74	57.33	34.83	10.89	61.71	300	0	P	H
		7308	46.12	-27.88	74	58.28	36.39	13.35	61.9	300	0	P	H
		4872	42.02	-31.98	74	58.01	34.83	10.89	61.71	300	360	P	V
		7308	47.81	-26.19	74	59.97	36.39	13.35	61.9	300	360	P	V
802.11g CH 09 2452MHz		4904	44.11	-29.89	74	60.08	34.82	10.92	61.71	300	0	P	H
		7356	50.01	-23.99	74	62.11	36.42	13.38	61.9	300	0	P	H
		4904	49.89	-24.11	74	65.86	34.82	10.92	61.71	300	360	P	V
		7356	49.33	-24.67	74	61.43	36.42	13.38	61.9	300	360	P	V
802.11g CH 10 2457MHz		4914	40.87	-33.13	74	56.84	34.82	10.92	61.71	300	0	P	H
		7368	45.95	-28.05	74	58.02	36.43	13.4	61.9	300	0	P	H
		4914	41.23	-32.77	74	57.2	34.82	10.92	61.71	300	360	P	V
		7368	46	-28	74	58.07	36.43	13.4	61.9	300	360	P	V
802.11g CH 11 2462MHz		4926	41.86	-32.14	74	57.82	34.82	10.93	61.71	300	0	P	H
		7386	43.91	-30.09	74	55.96	36.44	13.41	61.9	300	0	P	H
		4926	42.96	-31.04	74	58.92	34.82	10.93	61.71	300	360	P	V
		7386	43.86	-30.14	74	55.91	36.44	13.41	61.9	300	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.3	65.63	-8.37	74	58.11	33.5	7.47	33.45	102	108	P	H
		2389.95	50.18	-3.82	54	42.66	33.5	7.47	33.45	102	108	A	H
	*	2416	105.32	-	-	97.91	33.37	7.48	33.44	102	108	P	H
	*	2418	97.38	-	-	89.97	33.37	7.48	33.44	102	108	A	H
		2389.82	59.81	-14.19	74	52.29	33.5	7.47	33.45	392	63	P	V
		2389.82	47.22	-6.78	54	39.7	33.5	7.47	33.45	392	63	A	V
	*	2416	101.73	-	-	94.32	33.37	7.48	33.44	392	63	P	V
	*	2418	93.75	-	-	86.34	33.37	7.48	33.44	392	63	A	V
802.11n HT20 CH 02 2417MHz		2389.17	61.36	-12.64	74	53.84	33.5	7.47	33.45	100	114	P	H
		2389.95	49.07	-4.93	54	41.55	33.5	7.47	33.45	100	114	A	H
		2422	109.98	-	-	102.68	33.24	7.5	33.44	100	114	P	H
		2422	101.93	-	-	94.63	33.24	7.5	33.44	100	114	A	H
		2355.63	56.52	-17.48	74	49.48	33.08	7.41	33.45	375	60	P	V
		2389.95	46.35	-7.65	54	38.83	33.5	7.47	33.45	375	60	A	V
		2426	107.36	-	-	100.06	33.24	7.5	33.44	375	60	P	V
		2426	99.52	-	-	92.22	33.24	7.5	33.44	375	60	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 09 2452MHz		2483.8	66.98	-7.02	74	60	32.86	7.55	33.43	161	124	P	H
		2483.56	49.44	-4.56	54	42.46	32.86	7.55	33.43	161	124	A	H
		2448	107.85	-	-	100.66	33.11	7.51	33.43	161	124	P	H
		2446	100.1	-	-	92.91	33.11	7.51	33.43	161	124	A	H
		2483.92	62.08	-11.92	74	55.1	32.86	7.55	33.43	330	76	P	V
		2483.5	46.73	-7.27	54	39.75	32.86	7.55	33.43	330	76	A	V
		2444	103.99	-	-	96.8	33.11	7.51	33.43	330	76	P	V
		2444	96.17	-	-	88.98	33.11	7.51	33.43	330	76	A	V
802.11n HT20 CH 10 2457MHz		2483.68	66.66	-7.34	74	59.68	32.86	7.55	33.43	111	115	P	H
		2483.62	49.66	-4.34	54	42.68	32.86	7.55	33.43	111	115	A	H
		2452	106.06	-	-	98.87	33.11	7.51	33.43	111	115	P	H
		2450	98.1	-	-	90.91	33.11	7.51	33.43	111	115	A	H
		2484.34	62.54	-11.46	74	55.56	32.86	7.55	33.43	319	100	P	V
		2483.86	47.09	-6.91	54	40.11	32.86	7.55	33.43	319	100	A	V
		2462	100.83	-	-	93.74	32.99	7.53	33.43	319	100	P	V
		2462	92.99	-	-	85.9	32.99	7.53	33.43	319	100	A	V
802.11n HT20 CH 11 2462MHz		2483.62	67.58	-6.42	74	60.6	32.86	7.55	33.43	107	112	P	H
		2483.5	50.88	-3.12	54	43.9	32.86	7.55	33.43	107	112	A	H
	*	2456	104.59	-	-	97.5	32.99	7.53	33.43	107	112	P	H
	*	2456	96.86	-	-	89.77	32.99	7.53	33.43	107	112	A	H
		2483.56	62.6	-11.4	74	55.62	32.86	7.55	33.43	367	86	P	V
		2483.5	48.25	-5.75	54	41.27	32.86	7.55	33.43	367	86	A	V
	*	2468	100.87	-	-	93.78	32.99	7.53	33.43	367	86	P	V
	*	2470	93.1	-	-	86.01	32.99	7.53	33.43	367	86	A	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	42.18	-31.82	74	58.22	34.84	10.84	61.72	300	0	P	H
		4824	41.97	-32.03	74	58.01	34.84	10.84	61.72	300	360	P	V
802.11n HT20 CH 02 2417MHz		4834	41.4	-32.6	74	57.43	34.83	10.86	61.72	300	0	P	H
		7251	48.57	-25.43	74	60.8	36.36	13.31	61.9	300	0	P	H
		4834	41.79	-32.21	74	57.82	34.83	10.86	61.72	300	360	P	V
		7251	53.07	-20.93	74	65.3	36.36	13.31	61.9	264	102	P	V
		7251	44.17	-9.83	54	56.4	36.36	13.31	61.9	264	102	A	V
802.11n HT20 CH 06 2437MHz		4872	41.56	-32.44	74	57.55	34.83	10.89	61.71	300	0	P	H
		7308	45.37	-28.63	74	57.53	36.39	13.35	61.9	300	0	P	H
		4872	43.09	-30.91	74	59.08	34.83	10.89	61.71	300	360	P	V
		7308	47.43	-26.57	74	59.59	36.39	13.35	61.9	300	360	P	V
802.11n HT20 CH 09 2452MHz		4902	42.77	-31.23	74	58.74	34.82	10.92	61.71	300	0	P	H
		7356	46.85	-27.15	74	58.95	36.42	13.38	61.9	300	0	P	H
		4902	42.73	-31.27	74	58.7	34.82	10.92	61.71	300	360	P	V
		7356	48.74	-25.26	74	60.84	36.42	13.38	61.9	300	360	P	V
802.11n HT20 CH 10 2457MHz		4914	40.85	-33.15	74	56.82	34.82	10.92	61.71	300	0	P	H
		7368	44.37	-29.63	74	56.44	36.43	13.4	61.9	300	0	P	H
		4914	41.13	-32.87	74	57.1	34.82	10.92	61.71	300	360	P	V
		7368	43.94	-30.06	74	56.01	36.43	13.4	61.9	300	360	P	V
802.11n HT20 CH 11 2462MHz		4926	41.69	-32.31	74	57.65	34.82	10.93	61.71	300	0	P	H
		7386	43.66	-30.34	74	55.71	36.44	13.41	61.9	300	0	P	H
		4926	41.96	-32.04	74	57.92	34.82	10.93	61.71	300	360	P	V
		7386	43.89	-30.11	74	55.94	36.44	13.41	61.9	300	360	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz WIFI 802.11 g. (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11 g LF		30.97	18.58	-21.42	40	26.03	24.57	1.26	33.28	-	-	P	H
		52.31	18.17	-21.83	40	35.8	13.9	1.63	33.16	-	-	P	H
		152.22	19.77	-23.73	43.5	33.21	16.98	2.78	33.2	-	-	P	H
		274.44	25.87	-20.13	46	35.89	19.4	3.73	33.15	-	-	P	H
		668.26	25.54	-20.46	46	25.71	26.57	5.82	32.56	-	-	P	H
		808.91	27.69	-18.31	46	25.19	28.39	6.39	32.28	100	0	P	H
		30	22.86	-17.14	40	29.82	25.1	1.24	33.3	-	-	P	V
		52.31	25.08	-14.92	40	42.71	13.9	1.63	33.16	100	0	P	V
		97.9	19.77	-23.73	43.5	34.75	15.84	2.24	33.06	-	-	P	V
		273.47	18.98	-27.02	46	28.93	19.47	3.73	33.15	-	-	P	V
		540.22	23.16	-22.84	46	25.6	25.13	5.23	32.8	-	-	P	V
		848.68	27.64	-18.36	46	24.01	29.28	6.55	32.2	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



For co-location:

2.4GHz 2400~2483.5MHz

WIFI 802.11g HT20 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g HT20 CH 10 2457MHz & Part 22H GSM 850		2483.86	64.85	-9.15	74	57.87	32.86	7.55	33.43	103	113	P	H
		2483.56	50.36	-3.64	54	43.38	32.86	7.55	33.43	103	113	A	H
	*	2452	108.7	-	-	101.51	33.11	7.51	33.43	103	113	P	H
	*	2454	99.1	-	-	92.01	32.99	7.53	33.43	103	113	A	H
		2483.5	58.54	-15.46	74	51.56	32.86	7.55	33.43	381	62	P	V
		2483.56	46.47	-7.53	54	39.49	32.86	7.55	33.43	381	62	A	V
	*	2452	103.56	-	-	96.37	33.11	7.51	33.43	381	62	P	V
	*	2450	94.99	-	-	87.8	33.11	7.51	33.43	381	62	A	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											

2.4GHz 2400~2483.5MHz

WIFI 802.11g HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g HT20 CH 10 2457MHz & Part 22H GSM 850		4914	42.56	-31.44	74	58.53	34.82	10.92	61.71	300	0	P	H
		7368	43.99	-30.01	74	56.06	36.43	13.4	61.9	300	0	P	H
		4914	42.61	-31.39	74	58.58	34.82	10.92	61.71	300	360	P	V
		7368	43.98	-30.02	74	56.05	36.43	13.4	61.9	300	360	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	96.50	1.399	0.715	0.75KHz
802.11n HT20	97.28	1.297	0.771	0.82KHz

802.11b





802.11g



802.11n HT20

