

## 2.2 OPERATIONAL DESCRIPTION

This device is a Wireless keyboard included wireless transmitter of keyboard and receiver. It is powered by Battery DC 6.0V.

This device is 1 channel with GFSK modulation.

The Receiver is USB interface and it is capable to receive signal from transmitter to control PC or notebook.

Another information please refer to users manual.

## 2.3 TEST MODES & EUT COMPONENTS DESCRIPTION

| EUT: Wireless keyboard, M/N: RK612A, RK612B |                             |
|---|-----------------------------|
| Test Mode                                   | Mode 1<br>Continue Transmit |
| Frequency                                   | 2420MHz                     |

## 2.4 SUMMARY OF TEST PROCEDURE AND TEST RESULTS

| Test Item          | Applied Standard Section                       | Test Result                 |
|--------------------|--|-----------------------------|
| Radistion Emission | 15.209, ANSI C63.4 Section 8                   | Pass (refer to section 3.7) |
| Peak Power Output  | 15.249(a), ANSI C63.4 Section 13<br>& Annex I  | Pass (refer to section 3.7) |
| Band Edge          | 15.249(d) , ANSI C63.4 Section 13<br>& Annex I | Pass (refer to section 4.6) |

## 2.5 CONFIGURATION OF THE TESTED SYSTEM

The FCC IDs/Types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards, which have grants) are:

### Non-Test Peripherals