

1/F., Building No. 1 Building, Agriculture Machinery Materials Co. Wushan Road, Shipai, Tianhe District, Guangzhou, China Telephone: +86 (0) 20 3848 1001 Fax: +86 (0) 20 3848 1006 kent_hsu@sgs.com

FEDERAL COMMUNICATIONS COMMISSION Registration number: 282399



Report No.: **03.04.0395EF-2** Page: 1 of 9 FCC ID: HAP91229R49

FCC TEST REPORT

Application No.	: 03.04.0395E		
Applicant	: Echo Toys Ltd		
FCC ID	: HAP91229T49		
Equipment under T Name Model	Yest (EUT): : Jimmy Neutron Ultra Orb : 91229		
Standards	: FCC PART 15, SUBPART B : 2002		
Date of Receipt	: 14 April 2003		
Date of Test	: 18 April 2003		
Date of Issue	: 21 April 2003		
Test Result :	PASS *		

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Kent Hsu Laboratory Manager SGS-CSTC Co.,Ltd.

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the SGS PRODUCT CERTIFICATION MARK. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

Member of the SGS Group (Société Générale de Surveillance)



2 Contents

		Page
1	COVER PAGE	1
2	CONTENTS	2
3	GENERAL INFORMATION	
	 3.1 CLIENT INFORMATION	
4	4.1 TEST RESULTS	
5	PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	



Report No.: **03.04.0395EF-2** Page: 3 of 9

3 General Information

3.1 Client Information

Applicant:	Echo Toys Ltd		
Address of Applicant:	Room 1108, Peninsula Centre 67 Mody Road, Tism Sha Tusi East,Kowloon, Hong Kong.		
Details of E.U.T.			
Product Name:	Jimmy Neutron Ultra Orb (Receiver Part)		
Model:	91229		
Power Supply:	9.6V DC Recycled Battery (6 x 'Ni-Cd AA' Size Batteries)		

3.3 Description of Support Units

The EUT was tested as an independent unit: a receiver for a 49MHz radio transmitter.

N/A-

3.4 Test Location

Power Cord:

3.2

All tests were performed at:-

SGS-CSTC Standards Technical Services Ltd., Guangzhou Safety & EMC Laboratory, 1/F, Building No. 1, Agriculture Machinery Materials Company Warehouse Ltd., Wushan Road Shipai, Tianhe District, Guangzhou, China. P.C. 510630.

Tel: +86 20 3848 1001 Fax: +86 20 3848 1006

3.5 Other Information Requested by the Customer

None.



3.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• NVLAP – Lab Code: 200611-0

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 2000611-0. Effective through February 2, 2003.

• ACA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

• VCCI

The 3m Semi-anechoic chamber and Shielded Room (11.5m x 4m x 4m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1599 and C-1706 respectively.

Date of Registration: February 28, 2003. Valid until May 30, 2005

 SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FINKO Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC

TESTING SERVICES and SAFETY TESTING SERVICES.

• CNAL – LAB Code: L0141

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of Testing Laboratories.

• FCC – Registration No.: 282399

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP, SGS-CSTC is an authorized test laboratory for the DoC process.



4 Test Results

4.1 Test Instruments

Test Equipment	Manufacturer	Model	Asset No.	Cal. Due Date
Temperature, Humidity & Barometer	Oregon Scientific	BA-888	EMC0003	25-07-2003
3m Semi- Anechoic Chamber	Frankonia	N/A	EMC0501	04-11-2003
EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	EMC0506	17-11-2003
Bilog Type Antenna	Schaffner Chase	CBL6143	EMC0519	01-12-2003
Coaxial cable	SGS	N/A	EMC0514	04-11-2003

4.2 E.U.T. Operation

Input voltage:

9.6V DC Recycled Battery (6 x 'Ni-Cd AA' Size Batteries)

Operating Environment:

Temperature:	24.0 °C
Humidity:	58 % RH
Atmospheric Pressure:	1012 mbar

EUT Operation:

Test the EUT in on mode.



4.3 Test Procedure & Measurement Data

4.3.1 Radiated Emissions

Test Requirement:	FCC Part15 B		
Test Method:	Based on FCC Part15 B Section 15.109		
Test Date:	18 April 2003		
Measurement Distance:	3m (Semi-Anechoic Chamber)		
Requirements:	Emissions shall not exceed:		
	40.0 dBµV/m between 30MHz & 88MHz		
	43.5 dBµV/m between 88MHz & 216MHz		
	46.0 dBµV/m between 216MHz & 960MHz		
	54.0 dBµV/m above 960MHz		
Detector:	Peak Scan (120kHz resolution bandwidth)		

Test Procedure: The procedure uesd was ANSI Standard C63.4-2000. Ansi Standard C63.4-2000 12.1.1.1 Superregenerative Receiver: A signal Generator was set to the unit under test operating frequency. An unmodulated continuous wave (CW) signal was radiated at the superregenerative receiver operating frequency to cohere the characteristi broadband emissions from the receiver. The receive was scanned from 30MHz to 1000MHz.When an emission was found,the table was roated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the horizontal and vertical polarities and the worst case emissions were reported.

Test Frequency (MHz)	Test Polarization	Test Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
107.560	Vertical	28.1	43.5	15.4
142.625	Vertical	25.6	46.0	20.4
160.685	Vertical	24.8	46.0	21.2
180.340	Vertical	27.6	46.0	18.4
374.345	Vertical	30.1	46.0	15.9
700.012	Vertical	28.9	46.0	17.1
107.560	Horizontal	27.2	43.5	16.3
141.128	Horizontal	25.6	43.5	17.9
184.082	Horizontal	28.3	43.5	15.2
225.632	Horizontal	26.3	46.0	19.7
281.780	Horizontal	32.5	46.0	13.5
345.635	Horizontal	26.6	46.0	19.4

The following measurements were performed on the EUT on 18 April 2003:

Test Results: The unit does meet the FCC Part 15 C requirements.