



FCC RF Test Report

APPLICANT : Sony Mobile Communications Inc.
EQUIPMENT : Wireless Headset
BRAND NAME : Sony
FCC ID : PY7-13007N
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Oct. 06, 2017 and testing was completed on Nov. 09, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL INC.****No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.****SPORTON INTERNATIONAL INC.**

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PY7-13007N

Page Number : 1 of 59

Report Issued Date : Jan. 12, 2018

Report Version : Rev. 04

Report Template No.: BU5-FR15CBT Version 2.0



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Descriptions of Test Mode	8
2.3 Test Mode.....	9
2.4 Connection Diagram of Test System.....	10
2.5 Support Unit used in test configuration and system	10
2.6 EUT Operation Test Setup	10
2.7 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 Hopping Channel Separation Measurement	14
3.3 Dwell Time Measurement.....	20
3.4 20dB and 99% Bandwidth Measurement	23
3.5 Output Power Measurement.....	34
3.6 Conducted Band Edges Measurement.....	35
3.7 Conducted Spurious Emission Measurement	42
3.8 Radiated Band Edges and Spurious Emission Measurement	52
3.9 Antenna Requirements.....	56
4 LIST OF MEASURING EQUIPMENT.....	57
5 UNCERTAINTY OF EVALUATION.....	59
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX D. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7O0620-01A	Rev. 01	Initial issue of report	Dec. 28, 2017
FR7O0620-01A	Rev. 02	Add accessories in section 2.5.	Jan. 09, 2018
FR7O0620-01A	Rev. 03	Add test panels description in section 2.2	Jan. 10, 2018
FR7O0620-01A	Rev. 04	Remove accessories in section 2.5.	Jan. 12, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.37 dB at 957.300 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Required	-
3.9	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-
Note: Not required means after assessing, test items are not necessary to carry out.					

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Peak Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	9.97 dBm	9.33 dBm	9.62 dBm
Ch39	2441MHz	10.17 dBm	9.64 dBm	9.84 dBm
Ch78	2480MHz	9.67 dBm	9.19 dBm	9.50 dBm

Channel	Frequency	Bluetooth RF Output Average Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	9.71 dBm	6.82 dBm	6.83 dBm
Ch39	2441MHz	10.01 dBm	7.47 dBm	7.48 dBm
Ch78	2480MHz	9.46 dBm	6.97 dBm	6.98 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report


2.3 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth 1Mbps GFSK / EDR 2Mbps $\pi/4$ -DQPSK / EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz for 1Mbps		
	Mode 2: CH39_2441 MHz for 1Mbps		
	Mode 3: CH78_2480 MHz for 1Mbps		
	Mode 4: CH00_2402 MHz for 2Mbps		
	Mode 5: CH39_2441 MHz for 2Mbps		
	Mode 6: CH78_2480 MHz for 2Mbps		
	Mode 7: CH00_2402 MHz for 3Mbps		
	Mode 8: CH39_2441 MHz for 3Mbps		
	Mode 9: CH78_2480 MHz for 3Mbps		

2.4 Connection Diagram of Test System

<Bluetooth Tx Mode >



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m

2.6 EUT Operation Test Setup

The RF test items utility, an engineering test program was programmed in order to make the EUT get into the engineering modes to contact with base station for continuous transmitting.



2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

Number of Hopping Channel Plot on Channel 00 - 78



Date: 7.NOV.2017 19:15:59



Date: 7.NOV.2017 19:17:48

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 7.NOV.2017 19:50:52


Channel Separation Plot on Channel 39 - 40



Date: 7.NOV.2017 19:59:05




Channel Separation Plot on Channel 77 - 78



Date: 7.NOV.2017 20:09:27

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 7.NOV.2017 20:17:31




Channel Separation Plot on Channel 39 - 40



Date: 7.NOV.2017 20:29:00


Channel Separation Plot on Channel 77 - 78



Date: 7.NOV.2017 20:36:48


<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 7.NOV.2017 20:44:20


Channel Separation Plot on Channel 39 - 40



Date: 7.NOV.2017 20:50:41



Channel Separation Plot on Channel 77 - 78



Date: 7.NOV.2017 20:56:04

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time


Please refer to Appendix A.

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Package Transfer Time Plot


<1Mbps>



Date: 2.NOV.2017 20:35:13




<2Mbps>



Date: 2.NOV.2017 20:36:44

<3Mbps>



Date: 2.NOV.2017 20:38:12

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 99% bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 7.NOV.2017 19:53:36


20 dB Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:00:21




20 dB Bandwidth Plot on Channel 78



Date: 7.NOV.2017 20:10:57

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 7.NOV.2017 20:18:56




20 dB Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:31:33

20 dB Bandwidth Plot on Channel 78




Date: 7.NOV.2017 20:37:57




<3Mbps>

20 dB Bandwidth Plot on Channel 00




Date: 7.NOV.2017 20:46:30

20 dB Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:52:12

20 dB Bandwidth Plot on Channel 78



Date: 7.NOV.2017 20:57:13




3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 7.NOV.2017 19:55:01




99% Occupied Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:01:27

99% Occupied Bandwidth Plot on Channel 78




Date: 7.NOV.2017 20:12:00




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 7.NOV.2017 20:20:12


99% Occupied Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:32:28




99% Occupied Bandwidth Plot on Channel 78



Date: 7.NOV.2017 20:38:53

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 7.NOV.2017 20:47:24




99% Occupied Bandwidth Plot on Channel 39



Date: 7.NOV.2017 20:53:20

99% Occupied Bandwidth Plot on Channel 78



Date: 7.NOV.2017 20:58:08

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup




3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 7.NOV.2017 19:55:34

High Band Edge Plot on Channel 78




Date: 7.NOV.2017 20:12:22




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 7.NOV.2017 20:20:34

High Band Edge Plot on Channel 78




Date: 7.NOV.2017 20:39:16




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 7.NOV.2017 20:47:52

High Band Edge Plot on Channel 78



Date: 7.NOV.2017 20:58:31




3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 7.NOV.2017 19:20:22

Hopping Mode High Band Edge Plot




Date: 7.NOV.2017 19:22:01




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 7.NOV.2017 19:25:13

Hopping Mode High Band Edge Plot




Date: 7.NOV.2017 19:26:18




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 7.NOV.2017 19:29:49

Hopping Mode High Band Edge Plot



Date: 7.NOV.2017 19:39:32

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure


1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




3.7.5 Test Result of Conducted Spurious Emission

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 19:56:37


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 19:56:59




1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:07:30


1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:07:52




1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:13:06


1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:13:28




2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:27:17


2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:27:39




2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:34:26


2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:34:48




2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:40:31


2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:40:53




3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:49:06


3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:49:28




3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 20:54:23


3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 20:54:45




3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 7.NOV.2017 21:01:00

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 7.NOV.2017 21:01:21



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1\text{GHz}$; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.76dB) derived from $20\log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.9 Antenna Requirements

3.9.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.9.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.9.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 26, 2017	Nov. 06, 2017~ Nov. 07, 2017	Sep. 25, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GHz z	Sep. 26, 2017	Nov. 06, 2017~ Nov. 07, 2017	Sep. 25, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz ~ 30GHz	Nov. 17, 2016	Nov. 06, 2017~ Nov. 07, 2017	Nov. 16, 2017	Conducted (TH05-HY)
Hygrometer	TECEP	DTM-303B	TP157151	N/A	Mar. 20, 2017	Nov. 06, 2017~ Nov. 07, 2017	Mar. 19, 2018	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21	1GHz~26GHz	Dec. 02, 2016	Nov. 06, 2017~ Nov. 07, 2017	Dec. 01, 2017	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Nov. 08, 2017~ Nov. 09, 2017	Oct. 19, 2018	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N 1D01N-06	35419&03	30MHz to 1GHz	Jan. 07, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 06, 2018	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 23, 2017	Nov. 08, 2017~ Nov. 09, 2017	Aug. 22, 2018	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 576	18GHz ~ 40GHz	Apr. 27, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 26, 2018	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 16, 2018	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 12, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 11, 2018	Radiation (03CH07-HY)
Amplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jul. 17, 2018	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590075	1GHz ~ 18GHz	Apr. 25, 2017	Nov. 08, 2017~ Nov. 09, 2017	Apr. 24, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Nov. 08, 2017~ Nov. 09, 2017	Mar. 13, 2018	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 30, 2017	Nov. 08, 2017~ Nov. 09, 2017	Oct. 29, 2018	Radiation (03CH07-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	HTC-2	1	N/A	Jun. 27, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jun. 26, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21	30MHz~1GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21+MY842 09521	1GHz~26GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21+MY842 09521	26GHz~40GHz	Jan. 03, 2017	Nov. 08, 2017~ Nov. 09, 2017	Jan. 02, 2018	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208 368	Control Ant Mast	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Test Software	Audix	E3	6.2009-8-2 4(sporton)	N/A	N/A	Nov. 08, 2017~ Nov. 09, 2017	N/A	Radiation (03CH07-HY)
Filter	Wainwright	WLKS1200-8S S	SN3	1.2G Low Pass	Nov. 22, 2016	Nov. 08, 2017~ Nov. 09, 2017	Nov. 21, 2017	Radiation (03CH07-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Nov. 22, 2016	Nov. 08, 2017~ Nov. 09, 2017	Nov. 21, 2017	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.70
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2017/11/7	Relative Humidity:	51~54	%

TEST RESULTS DATA***20dB and 99% Occupied Bandwidth and Hopping Channel Separation***

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.940	0.884	1.008	0.6267	Pass
DH	1Mbps	1	39	2441	0.936	0.884	1.002	0.6240	Pass
DH	1Mbps	1	78	2480	0.932	0.884	1.020	0.6213	Pass
2DH	2Mbps	1	0	2402	1.350	1.208	0.990	0.9000	Pass
2DH	2Mbps	1	39	2441	1.350	1.208	1.002	0.9000	Pass
2DH	2Mbps	1	78	2480	1.350	1.212	0.984	0.9000	Pass
3DH	3Mbps	1	0	2402	1.308	1.180	1.008	0.8720	Pass
3DH	3Mbps	1	39	2441	1.314	1.184	1.008	0.8760	Pass
3DH	3Mbps	1	78	2480	1.308	1.184	1.002	0.8720	Pass

TEST RESULTS DATA***Dwell Time***

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

TEST RESULTS DATA***Peak Power Table***

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	9.97	20.97	Pass
	39	1	10.17	20.97	Pass
	78	1	9.67	20.97	Pass
2DH1	0	1	9.33	20.97	Pass
	39	1	9.64	20.97	Pass
	78	1	9.19	20.97	Pass
3DH1	0	1	9.62	20.97	Pass
	39	1	9.84	20.97	Pass
	78	1	9.50	20.97	Pass

TEST RESULTS DATA***Average Power Table******(Reporting Only)***

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	9.71	5.16
	39	1	10.01	5.16
	78	1	9.46	5.16
2DH1	0	1	6.82	5.07
	39	1	7.47	5.07
	78	1	6.97	5.07
3DH1	0	1	6.83	5.07
	39	1	7.48	5.07
	78	1	6.98	5.07

TEST RESULTS DATA***Number of Hopping Frequency***

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Appendix B. Radiated Spurious Emission

Test Engineer :	Jessie Wang, James Chiu	Temperature :	21~23°C
		Relative Humidity :	52~56%

2.4GHz 2400~2483.5MHz

BT (1M) (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2382.03	47.12	-26.88	74	41.13	31.91	8.24	34.16	254	268	P	H
		2382.03	22.36	-31.64	54	-	-	-	-	-	-	A	H
	*	2402	95.17	-	-	89.17	31.95	8.24	34.19	254	268	P	H
	*	2402	70.41	-	-	-	-	-	-	-	-	A	H
													H
													H
		2382.24	49.41	-24.59	74	43.42	31.91	8.24	34.16	100	300	P	V
		2382.24	24.65	-29.35	54	-	-	-	-	-	-	A	V
	*	2402	102	-	-	96	31.95	8.24	34.19	100	300	P	V
	*	2402	77.24	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2338.84	48.47	-25.53	74	42.49	31.83	8.28	34.13	254	269	P	H
		2338.84	23.71	-30.29	54	-	-	-	-	-	-	A	H
	*	2441	95.47	-	-	89.36	32.08	8.27	34.24	254	269	P	H
	*	2441	70.71	-	-	-	-	-	-	-	-	A	H
		2483.9	47	-27	74	40.81	32.16	8.3	34.27	254	269	P	H
		2483.9	22.24	-31.76	54	-	-	-	-	-	-	A	H
		2325.82	47.21	-26.79	74	41.24	31.79	8.28	34.1	100	264	P	V
		2325.82	22.45	-31.55	54	-	-	-	-	-	-	A	V
	*	2441	101.07	-	-	94.96	32.08	8.27	34.24	100	264	P	V
	*	2441	76.31	-	-	-	-	-	-	-	-	A	V
		2490.55	47.53	-26.47	74	41.3	32.2	8.3	34.27	100	264	P	V
		2490.55	22.77	-31.23	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	95.34	-	-	89.15	32.16	8.3	34.27	300	271	P	H
	*	2480	70.58	-	-	-	-	-	-	-	-	A	H
		2494.4	47.62	-26.38	74	41.42	32.2	8.3	34.3	300	271	P	H
		2494.4	22.86	-31.14	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	100.75	-	-	94.56	32.16	8.3	34.27	100	304	P	V
	*	2480	75.99	-	-	-	-	-	-	-	-	A	V
		2485.16	47.46	-26.54	74	41.27	32.16	8.3	34.27	100	304	P	V
		2485.16	22.7	-31.3	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (1M) (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	41.41	-32.59	74	54.61	34.24	11.96	59.4	100	0	P	H
		4804	16.65	-37.35	54	-	-	-	-	-	-	A	H
													H
													H
		4804	42.64	-31.36	74	55.84	34.24	11.96	59.4	100	0	P	V
		4804	17.88	-36.12	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	42.89	-31.11	74	56.06	34.22	11.9	59.29	100	0	P	H
		4882	18.13	-35.87	54	-	-	-	-	-	-	A	H
		7323	47.83	-26.17	74	55.25	35.7	14.94	58.06	100	0	P	H
		7323	23.07	-30.93	54	-	-	-	-	-	-	A	H
		4882	46.43	-27.57	74	59.6	34.22	11.9	59.29	100	0	P	V
		4882	21.67	-32.33	54	-	-	-	-	-	-	A	V
		7323	49.96	-24.04	74	57.38	35.7	14.94	58.06	100	0	P	V
		7323	25.2	-28.8	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	42.18	-31.82	74	55.29	34.21	11.84	59.16	100	0	P	H
		4960	17.42	-36.58	54	-	-	-	-	-	-	A	H
		7440	47.7	-26.3	74	55.13	35.63	15.1	58.16	100	0	P	H
		7440	22.94	-31.06	54	-	-	-	-	-	-	A	H
		4960	43.5	-30.5	74	56.61	34.21	11.84	59.16	100	0	P	V
		4960	18.74	-35.26	54	-	-	-	-	-	-	A	V
		7440	49.03	-24.97	74	56.46	35.63	15.1	58.16	100	0	P	V
		7440	24.27	-29.73	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (2M) (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2372.475	47.36	-26.64	74	41.35	31.91	8.26	34.16	285	268	P	H
		2372.475	22.6	-31.4	54	-	-	-	-	-	-	A	H
	*	2402	95.32	-	-	89.32	31.95	8.24	34.19	285	268	P	H
	*	2402	70.56	-	-	-	-	-	-	-	-	A	H
													H
													H
		2382.345	48.19	-25.81	74	42.2	31.91	8.24	34.16	100	298	P	V
		2382.345	23.43	-30.57	54	-	-	-	-	-	-	A	V
	*	2402	101.12	-	-	95.12	31.95	8.24	34.19	100	298	P	V
	*	2402	76.36	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2369.92	47.41	-26.59	74	41.4	31.91	8.26	34.16	255	270	P	H
		2369.92	22.65	-31.35	54	-	-	-	-	-	-	A	H
	*	2441	94.67	-	-	88.56	32.08	8.27	34.24	255	270	P	H
	*	2441	69.91	-	-	-	-	-	-	-	-	A	H
		2484.18	46.67	-27.33	74	40.48	32.16	8.3	34.27	255	270	P	H
		2484.18	21.91	-32.09	54	-	-	-	-	-	-	A	H
		2313.08	47.26	-26.74	74	41.31	31.74	8.28	34.07	100	274	P	V
		2313.08	22.5	-31.5	54	-	-	-	-	-	-	A	V
	*	2441	100.34	-	-	94.23	32.08	8.27	34.24	100	274	P	V
	*	2441	75.58	-	-	-	-	-	-	-	-	A	V
		2498.32	46.98	-27.02	74	40.78	32.2	8.3	34.3	100	274	P	V
		2498.32	22.22	-31.78	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	94.53	-	-	88.34	32.16	8.3	34.27	300	254	P	H
	*	2480	69.77	-	-	-	-	-	-	-	-	A	H
		2491.04	47.08	-26.92	74	40.85	32.2	8.3	34.27	300	254	P	H
		2491.04	22.32	-31.68	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	99.73	-	-	93.54	32.16	8.3	34.27	100	296	P	V
	*	2480	74.97	-	-	-	-	-	-	-	-	A	V
		2483.96	47.56	-26.44	74	41.37	32.16	8.3	34.27	100	296	P	V
		2483.96	22.8	-31.2	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (2M) (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	41.85	-32.15	74	55.05	34.24	11.96	59.4	100	0	P	H
		4804	17.09	-36.91	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.83	-32.17	74	55.03	34.24	11.96	59.4	100	0	P	V
		4804	17.07	-36.93	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	43.35	-30.65	74	56.52	34.22	11.9	59.29	100	0	P	H
		4882	18.59	-35.41	54	-	-	-	-	-	-	A	H
		7323	44.39	-29.61	74	51.81	35.7	14.94	58.06	100	0	P	H
		7323	19.63	-34.37	54	-	-	-	-	-	-	A	H
		4882	44.45	-29.55	74	57.62	34.22	11.9	59.29	100	0	P	V
		4882	19.69	-34.31	54	-	-	-	-	-	-	A	V
		7323	48.4	-25.6	74	55.82	35.7	14.94	58.06	100	0	P	V
		7323	23.64	-30.36	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	41.55	-32.45	74	54.66	34.21	11.84	59.16	100	0	P	H
		4960	16.79	-37.21	54	-	-	-	-	-	-	A	H
		7440	44.2	-29.8	74	51.63	35.63	15.1	58.16	100	0	P	H
		7440	19.44	-34.56	54	-	-	-	-	-	-	A	H
		4960	42.09	-31.91	74	55.2	34.21	11.84	59.16	100	0	P	V
		4960	17.33	-36.67	54	-	-	-	-	-	-	A	V
		7440	47.17	-26.83	74	54.6	35.63	15.1	58.16	100	0	P	V
		7440	22.41	-31.59	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (3M) (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2358.93	47.65	-26.35	74	41.65	31.87	8.26	34.13	300	268	P	H
		2358.93	22.89	-31.11	54	-	-	-	-	-	-	A	H
	*	2402	94.34	-	-	88.34	31.95	8.24	34.19	300	268	P	H
	*	2402	69.58	-	-	-	-	-	-	-	-	A	H
													H
													H
		2382.03	48.72	-25.28	74	42.73	31.91	8.24	34.16	100	300	P	V
		2382.03	23.96	-30.04	54	-	-	-	-	-	-	A	V
	*	2402	101.16	-	-	95.16	31.95	8.24	34.19	100	300	P	V
	*	2402	76.4	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2331.56	47.32	-26.68	74	41.35	31.79	8.28	34.1	300	271	P	H
		2331.56	22.56	-31.44	54	-	-	-	-	-	-	A	H
	*	2441	94.61	-	-	88.5	32.08	8.27	34.24	300	271	P	H
	*	2441	69.85	-	-	-	-	-	-	-	-	A	H
		2492.23	47.51	-26.49	74	41.31	32.2	8.3	34.3	300	271	P	H
		2492.23	22.75	-31.25	54	-	-	-	-	-	-	A	H
		2324	47.45	-26.55	74	41.48	31.79	8.28	34.1	100	303	P	V
		2324	22.69	-31.31	54	-	-	-	-	-	-	A	V
	*	2441	100.64	-	-	94.53	32.08	8.27	34.24	100	303	P	V
	*	2441	75.88	-	-	-	-	-	-	-	-	A	V
		2494.96	46.86	-27.14	74	40.66	32.2	8.3	34.3	100	303	P	V
		2494.96	22.1	-31.9	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	95.8	-	-	89.61	32.16	8.3	34.27	300	254	P	H
	*	2480	71.04	-	-	-	-	-	-	-	-	A	H
		2495.28	46.65	-27.35	74	40.45	32.2	8.3	34.3	300	254	P	H
		2495.28	21.89	-32.11	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	100.17	-	-	93.98	32.16	8.3	34.27	100	303	P	V
	*	2480	75.41	-	-	-	-	-	-	-	-	A	V
		2484.4	47.76	-26.24	74	41.57	32.16	8.3	34.27	100	303	P	V
		2484.4	23	-31	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (3M) (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	41.21	-32.79	74	54.41	34.24	11.96	59.4	100	0	P	H
		4804	16.45	-37.55	54	-	-	-	-	-	-	A	H
													H
													H
		4804	43.21	-30.79	74	56.41	34.24	11.96	59.4	100	0	P	V
		4804	18.45	-35.55	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	43.37	-30.63	74	56.54	34.22	11.9	59.29	100	0	P	H
		4882	18.61	-35.39	54	-	-	-	-	-	-	A	H
		7323	44.71	-29.29	74	52.13	35.7	14.94	58.06	100	0	P	H
		7323	19.95	-34.05	54	-	-	-	-	-	-	A	H
		4882	45.32	-28.68	74	58.49	34.22	11.9	59.29	100	0	P	V
		4882	20.56	-33.44	54	-	-	-	-	-	-	A	V
		7323	48.38	-25.62	74	55.8	35.7	14.94	58.06	100	0	P	V
		7323	23.62	-30.38	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	41.39	-32.61	74	54.5	34.21	11.84	59.16	100	0	P	H
		4960	16.63	-37.37	54	-	-	-	-	-	-	A	H
		7440	45.12	-28.88	74	52.55	35.63	15.1	58.16	100	0	P	H
		7440	20.36	-33.64	54	-	-	-	-	-	-	A	H
		4960	43.06	-30.94	74	56.17	34.21	11.84	59.16	100	0	P	V
		4960	18.3	-35.7	54	-	-	-	-	-	-	A	V
		7440	46.84	-27.16	74	54.27	35.63	15.1	58.16	100	0	P	V
		7440	22.08	-31.92	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF		30.54	26.72	-13.28	40	32.17	24.2	1.71	31.36	-	-	P	H
		139.35	28.87	-14.63	43.5	40.8	17.25	2.34	31.52	-	-	P	H
		264.36	22.59	-23.41	46	31.28	19.38	3.28	31.35	-	-	P	H
		869.1	33.17	-12.83	46	29.36	29.08	5.27	30.54	-	-	P	H
		923	33.7	-12.3	46	29.53	29.36	5.33	30.52	-	-	P	H
		957.3	35.63	-10.37	46	29.88	30.86	5.4	30.51	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		30.54	27.13	-12.87	40	32.58	24.2	1.71	31.36	-	-	P	V
		117.75	19.93	-23.57	43.5	31.87	17.26	2.34	31.54	-	-	P	V
		254.37	21.86	-24.14	46	31.34	18.86	3.03	31.37	-	-	P	V
		885.9	33.16	-12.84	46	29.42	29	5.27	30.53	-	-	P	V
		944.7	34.2	-11.8	46	29.08	30.24	5.4	30.52	-	-	P	V
		958	35.03	-10.97	46	29.24	30.9	5.4	30.51	100	0	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)



Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots




Test Engineer :	Jessie Wang, James Chiu	Temperature :	21~23°C
		Relative Humidity :	52~56%




2.4GHz 2400~2483.5MHz



BT (1M) (Band Edge @ 3m)



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4FY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-4FY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL
	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT 00075962 HORIZONTAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT 00075962 VERTICAL



2.4GHz 2400~2483.5MHz
BT (1M) (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL




BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL




BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL



2.4GHz 2400~2483.5MHz
BT (2M) (Band Edge @ 3m)



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4FY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-4FY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL
	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	Left blank

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL
	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT 00075962 HORIZONTAL



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT: 00075962 VERTICAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT: 00075962 VERTICAL





2.4GHz 2400~2483.5MHz



BT (2M) (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL




BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL




BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-11Y Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-11Y Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL



2.4GHz 2400~2483.5MHz
BT (3M) (Band Edge @ 3m)



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-4FY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-4FY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 HORIZONTAL
	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 HORIZONTAL	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	 Site : 03CH07-HY Condition : PEAK 74 3m HF ANT 00075962 VERTICAL
Peak	 Site : 03CH07-HY Condition : PEAK BE 74 3m HF ANT 00075962 VERTICAL	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT 00075962 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT 00075962 HORIZONTAL



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH07-1FY Condition : PEAK_BE_74 3m HF ANT: 00075962 VERTICAL	 Site : 03CH07-1FY Condition : PEAK_74 3m HF ANT: 00075962 VERTICAL





2.4GHz 2400~2483.5MHz
BT (3M) (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 HORIZONTAL	 Site : 03CH07-1FY Condition : PEAK 74 3m SHF-EHF 131029 VERTICAL


Emission below 1GHz
2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH07-11V Condition : QP-3m LF-ANT-35419(6) HORIZONTAL	 Site : 03CH07-11V Condition : QP-3m LF-ANT-35419(6) VERTICAL


Appendix D. Duty Cycle Plots

<1Mbps>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:


1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

<2Mbps>

2DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:

- Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
- Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
- 2DH5 has the highest duty cycle worst case and is reported.

<3Mbps>

3DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

- Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78 \%$
- Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
- 3DH5** has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.89 \text{ ms} \times 20 \text{ channels} = 57.8 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.89 \text{ ms} \times 2 = 5.78 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.78 \text{ ms}/100\text{ms}) = -24.76 \text{ dB}$$