

American Telecommunications Certification Body Inc.
6731 Whittier Ave, McLean, VA 22101

June 1, 2001

RE: Axonn Corp.
FCC ID: FCC ID L2VAX550

I am in receipt of the response letter of May 31, 2001. The explanation provided is sufficient for my RF shielding question. I still have some concerns about data buffering. The big test for this is what would happen in an over-modulated condition.

- 1.) Please describe what effect if any will occur to the transmitted emission envelope with unusually high input signal levels. As an example, if the equipment is designed to accept a 1V p-p input data stream, what will happen if the input signal is increased to 10V p-p?
- 2.) Please describe what effect if any will occur to the transmitted emission envelope with unusually fast input data rates. As an example, if the maximum design data rate is 9600bps, what will happen if the serial input to the device is increased to 19,200bps?



William H. Graff
Examining Engineer
President and Director of Engineering
<mailto:whgraff@AmericanTCB.com>

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.