



RF TEST REPORT

Product Name: Hoteza Tablet

Model Name: HTZ1108A

FCC ID: 2BL9S-HTZ1108A

Issued For : Hoteza Limited

11 Meneou Avenue 7550 Kiti, Larnaca Cyprus

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street,
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT24L002RF12

Sample Received Date: Dec. 03, 2024

Date of Test: Dec. 03, 2024 ~ Dec. 26, 2024

Date of Issue: Dec. 26, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Hoteza Limited

Address: 11 Meneou Avenue 7550 Kiti, Larnaca Cyprus

Manufacturer: SHENZHEN PRETECH INDUSTRIAL CO., LTD

Address: 808, QIANCHENG COMMERCIAL CENTER, 5 HAICHENG ROAD,
MABU COMMUNITY, XIXIANG STREET, BAO'AN DISTRICT
SHENZHEN GUANGDONG CHINA

Product Name: Hoteza Tablet

Trademark: HOTEZA

Model Name: HTZ1108A

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.407, Subpart E ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





Table of Contents

Page

1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	13
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	14
3 . EMC EMISSION TEST	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT	19
4. POWER SPECTRAL DENSITY TEST	33
4.1 LIMIT	33
4.2 TEST PROCEDURE	33
4.3 DEVIATION FROM STANDARD	33
4.4 TEST SETUP	34
4.5 EUT OPERATION CONDITIONS	34
4.6 TEST RESULTS	34
5. BANDWIDTH MEASUREMENT	35
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	35
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	36
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	37
6. MAXIMUM CONDUCTED OUTPUT POWER	38
6.1 LIMIT	38
6.2 TEST PROCEDURE	38
6.3 DEVIATION FROM STANDARD	38
6.4 TEST SETUP	38
6.5 EUT OPERATION CONDITIONS	38
6.6 TEST RESULTS	38
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	39
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	39
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	39
8. ANTENNA REQUIREMENT	40



Table of Contents	Page
8.1 STANDARD REQUIREMENT	40
8.2 EUT ANTENNA	40
APPENDIX I - TEST RESULTS	41
DUTY CYCLE	41
MAXIMUM CONDUCTED OUTPUT POWER	63
-26DB BANDWIDTH	65
OCCUPIED CHANNEL BANDWIDTH	81
MAXIMUM POWER SPECTRAL DENSITY LEVEL	103
BAND EDGE	125
-6DB BANDWIDTH	140
APPENDIX II - MEASUREMENT PHOTOS	146
APPENDIX III - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	147



Revision History

Rev.	Issue Date	Contents
00	Dec. 26, 2024	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Part 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203/15.204	Antenna Requirement	PASS

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Registration number:	746540
Accreditation Certificate:	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$
9	Bandwidth	$\pm 10.40\text{KHz}$
10	PSD	$\pm 1.5734\text{dB}$

Note: The measurement uncertainty is not included in the test result.



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Hoteza Tablet																							
Trademark:	HOTEZA																							
Model Name:	HTZ1108A																							
Series Model:	N/A																							
Model Difference:	N/A																							
Product Description:	<table><tr><td rowspan="10">Operation Frequency:</td><td>IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz</td></tr><tr><td>IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz</td></tr><tr><td>IEEE 802.11ac(VHT80): 5.210GHz</td></tr><tr><td>IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz</td></tr><tr><td>IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz</td></tr><tr><td>IEEE 802.11ac(VHT80): 5.290GHz</td></tr><tr><td>IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz</td></tr><tr><td>IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz</td></tr><tr><td>IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz</td></tr><tr><td>I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz</td></tr><tr><td rowspan="2">Modulation Type:</td><td>IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz</td></tr><tr><td>IEEE 802.11ac(VHT80): 5.775GHz</td></tr><tr><td rowspan="2">Antenna Designation:</td><td>802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM</td></tr><tr><td>802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM</td></tr><tr><td rowspan="2">Antenna Gain(dBi)</td><td>802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM</td></tr><tr><td>FPC</td></tr><tr><td colspan="2">More details of EUT technical specification, please refer to the User Manual.</td></tr></table>		Operation Frequency:	IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz	IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz	IEEE 802.11ac(VHT80): 5.210GHz	IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz	IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz	IEEE 802.11ac(VHT80): 5.290GHz	IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz	IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz	IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz	I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz	Modulation Type:	IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz	IEEE 802.11ac(VHT80): 5.775GHz	Antenna Designation:	802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM	802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM	Antenna Gain(dBi)	802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM	FPC	More details of EUT technical specification, please refer to the User Manual.	
Operation Frequency:	IEEE 802.11a/n(HT20)/ac(VHT20): 5.180GHz-5.240GHz																							
	IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz																							
	IEEE 802.11ac(VHT80): 5.210GHz																							
	IEEE 802.11a/n(HT20)/ac(VHT20): 5.260GHz-5.320GHz																							
	IEEE 802.11 n(HT40)/ac(VHT40): 5.270GHz-5.310GHz																							
	IEEE 802.11ac(VHT80): 5.290GHz																							
	IEEE 802.11a/n(HT20)/ac(VHT20): 5.500GHz-5.700GHz																							
	IEEE 802.11 n(HT40)/ac(VHT40): 5.510GHz-5.670GHz																							
	IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz																							
	I IEEE 802.11a/n(HT20)/ac(VHT20): 5.745GHz-5.825GHz																							
Modulation Type:	IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz																							
	IEEE 802.11ac(VHT80): 5.775GHz																							
Antenna Designation:	802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM																							
	802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM																							
Antenna Gain(dBi)	802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM																							
	FPC																							
More details of EUT technical specification, please refer to the User Manual.																								
Test Channel:	Please refer to the Note 3.																							
Adapter:	Model: JBT050200-T10EUU Input: 100-240V 50/60Hz 0.5A Output: 5V 2A Charging Base adapter: Model: K-A141203000E Input: 100-240V 50/60Hz 0.8A Output: 12V, 3A																							
Battery:	Capacity: 5000mAh Rated Voltage: 3.8V																							
Hardware Version:	P301-MB-V1.0.0																							
Software Version:	N/A																							
Connecting I/O Port(s):	Please refer to the Note 1.																							



Note

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.

Operation Frequency of channel			
5.180GHz-5.240GHz		5.260GHz-5.320GHz	
Channel	Frequency	Channel	Frequency
36	5180	52	5260
38	5190	54	5270
40	5200	56	5280
42	5210	58	5290
44	5220	60	5300
46	5230	62	5310
48	5240	64	5320
5.500GHz-5.720GHz		5.745GHz-5.825GHz	
Channel	Frequency	Channel	Frequency
100	5500	149	5745
102	5510	151	5755
104	5520	153	5765
108	5540	157	5785
110	5550	159	5795
112	5560	161	5805
116	5580	165	5825
118	5590		
120	5600		
124	5620		
126	5630		
128	5640		
132	5660		
134	5670		
136	5680		
140	5700		
142	5710		
144	5720		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

Channel List for 802.11a/n/ac(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	60	5300	116	5580	157	5785
48	5240	64	5320	140	5700	165	5825



Channel List for 802.11n/ac(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
134	5670						

Channel List for 802.11ac(80MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
122	5610						



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 4	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 5	TX IEEE 802.11ac VHT20 CH36&CH40&CH48	NSS1 MCS0
Mode 6	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 7	TX IEEE 802.11ac VHT20 CH52&CH60&CH64	NSS1 MCS0
Mode 8	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 9	TX IEEE 802.11ac VHT20 CH149&CH157&CH165	NSS1 MCS0
Mode 10	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 11	TX IEEE 802.11ac VHT40 CH38&CH46	NSS1 MCS0
Mode 12	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 13	TX IEEE 802.11ac VHT40 CH54 &CH62	NSS1 MCS0
Mode 14	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 15	TX IEEE 802.11ac VHT40 CH151&CH159	NSS1 MCS0
Mode 16	TX IEEE 802.11ac VHT80 CH42	NSS1 MCS0
Mode 17	TX IEEE 802.11ac VHT80 CH58	NSS1 MCS0
Mode 18	TX IEEE 802.11ac VHT80 CH155	NSS1 MCS0

Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.
(5) All 20M, 40M bandwidth modes have been tested, and the report only shows the worst mode data

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 19: TX Mode



2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test software Version	Test program: 5G WIFI B1	
Engineering Mode	Mode Or Modulation type	Power setting
	a	8
	n20	7
	n40	7
	ac20	7
	ac40	7
	ac80	7
Test software Version	Test program: 5G WIFI B2	
Engineering Mode	Mode Or Modulation type	Power setting
	a	8
	n20	7
	n40	7
	ac20	7
	ac40	7
	ac80	7
Test software Version	Test program: 5G WIFI B3	
Engineering Mode	Mode Or Modulation type	Power setting
	a	8
	n20	7
	n40	7
	ac20	7
	ac40	7
	ac80	7
Test software Version	Test program: 5G WIFI B4	
Engineering Mode	Mode Or Modulation type	Power setting
	a	8
	n20	7
	n40	7
	ac20	7
	ac40	7
	ac80	7



2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	Dongguan Bestgk Smart Technology Co.,Ltd	JBT050200-T10EUU	N/A	Input: 100-240V ~ 50/60Hz 0.5A Output: 5V, 2A
USB-A to USB-C Cable	N/A	N/A	N/A	0.5m
Adapter	Dongguan Bestgk Smart Technology Co.,Ltd	K-A141203000E	N/A	Input: 100-240V ~ 50/60Hz 0.8A Output: 12V, 3A
Charging Base	N/A	N/A	N/A	Input: 12V, 3A

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	HKF-16	N/A	N/A
Earphone	VESAFE	39630078	N/A	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
LISN	COM-POWER	LI-115	02032	2024.03.09	2025.03.08
LISN	SCHWARZBECK	NNLK 8122	00160	2024.03.09	2025.03.08
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2024.03.09	2025.03.08
Temperature & Humidity	KTJ	TA218B	N.A	2024.03.09	2025.03.08
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2024.03.09	2025.03.08
Active loop Antenna	ETS	6502	00049544	2023.10.13	2025.10.12
Spectrum Analyzer	Keysight	N9010B	MY60242508	2024.08.05	2025.08.04
Bilog Antenna(30M-1G)	SCHWARZBECK	VULB 9168	2705	2022.12.12	2025.12.11
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Horn Antenna(18-40G)	A-INFO	LB-180400-KF	J211060273	2022.06.08	2025.06.07
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2024.03.09	2025.03.08
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2024.03.09	2025.03.08
Pre-amplifier(18-40G)	com-mw	LNPA_18-40-01	18050003	2024.03.09	2025.03.08
Wireless Communications Test Set	R&S	CMW 500	137737	2024.03.09	2025.03.08
Antenna Tower	SAEMC	BK-4AT-BS-D	SK2021093008	N.A	N.A
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2024.03.11	2025.03.10
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9010B	MY60242508	2024.08.05	2025.08.04
Signal Analyzer	Keysight	N9020A	MY50530994	2024.03.09	2025.03.08
RF Automatic Test system	MW	MW100-RFCB	MW220322LG-033	2024.03.09	2025.03.08
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2024.03.09	2025.03.08
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2024.03.09	2025.03.08
Attenuator	eastsheep	90db	N.A	2024.03.09	2025.03.08
Temperature & Humidity	JINGCHUANG	BT-3	N.A	2024.03.11	2025.03.10
Digital multimeter	MASTECH	MS8261	MBGBC83053	2024.03.09	2025.03.08
Testing Software	MTS8310_V2.0.0.0_MW				



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Project: LGT24L002	Test Engineer: LiuH
EUT: Hoteza Tablet	Temperature: 24.2°C
M/N: HTZ1108A	Humidity: 41%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-12-05
Test Mode: TX 802.11a 5180	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.218	39.76	10.61	50.37	62.89	-12.52	QP	L1
2*	0.438	38.77	10.57	49.34	57.10	-7.76	QP	L1
3*	0.582	38.56	10.57	49.13	56.00	-6.87	QP	L1
4*	0.834	38.23	10.62	48.85	56.00	-7.15	QP	L1
5*	1.302	33.81	10.78	44.59	56.00	-11.41	QP	L1
6*	9.702	30.30	11.02	41.32	60.00	-18.68	QP	L1
7*	0.218	26.84	10.61	37.45	52.89	-15.45	AV	L1
8*	0.298	23.84	10.58	34.42	50.30	-15.88	AV	L1
9*	0.570	24.18	10.57	34.75	46.00	-11.25	AV	L1
10*	0.826	22.95	10.62	33.57	46.00	-12.43	AV	L1
11*	1.406	18.51	10.81	29.32	46.00	-16.68	AV	L1
12*	9.890	17.34	11.02	28.36	50.00	-21.64	AV	L1



Project: LGT24L002	Test Engineer: LiuH
EUT: Hoteza Tablet	Temperature: 24.2°C
M/N: HTZ1108A	Humidity: 41%RH
Test Voltage: AC 120V/60Hz	Test Data: 2024-12-05
Test Mode: TX 802.11a 5180	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.174	40.45	10.56	51.01	64.77	-13.76	QP	N
2*	0.306	38.71	10.59	49.30	60.08	-10.78	QP	N
3*	0.570	38.45	10.55	49.00	56.00	-7.00	QP	N
4*	0.882	37.78	10.55	48.33	56.00	-7.67	QP	N
5*	1.394	32.69	10.63	43.32	56.00	-12.68	QP	N
6*	12.626	26.62	11.19	37.81	60.00	-22.19	QP	N
7*	0.178	27.10	10.56	37.66	54.58	-16.92	AV	N
8*	0.354	25.04	10.59	35.63	48.87	-13.24	AV	N
9*	0.530	24.14	10.54	34.68	46.00	-11.32	AV	N
10*	0.882	22.87	10.55	33.42	46.00	-12.58	AV	N
11*	1.634	16.41	10.68	27.09	46.00	-18.91	AV	N
12*	10.346	11.36	11.01	22.37	50.00	-27.63	AV	N



3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.



LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: $\text{dBuV/m(at 3M)} = \text{EIRP(dBm)} + 95.2$.

Peak Limit = $-27\text{dBm/MHz} + 95.2 = 68.2 \text{ dBuV/m}$.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.2 DEVIATION FROM TEST STANDARD


No deviation

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.6 TEST RESULTS

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.




Results of Radiated Emissions (30MHz~1000MHz)

Project: LGT24L002	Test Engineer: LiuH
EUT: Hoteza Tablet	Temperature: 27°C
M/N: HTZ1108A	Humidity: 51%RH
Test Voltage: Battery	Test Data: 2024-12-11
Test Mode: TX 802.11a 5180	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	35.093	3.68	19.40	23.08	40.00	-16.92	QP	Hor
2*	54.008	3.95	20.29	24.24	40.00	-15.76	QP	Hor
3*	147.006	4.08	21.68	25.76	43.50	-17.74	QP	Hor
4*	497.055	3.88	26.66	30.54	46.00	-15.46	QP	Hor
5*	757.379	5.16	31.06	36.22	46.00	-9.78	QP	Hor
6*	964.110	4.92	33.57	38.49	54.00	-15.51	QP	Hor



No.	Frequency MHz	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	40.670	3.75	20.25	24.00	40.00	-16.00	QP	Ver
2*	57.403	4.47	19.86	24.33	40.00	-15.67	QP	Ver
3*	160.586	4.09	21.46	25.55	43.50	-17.95	QP	Ver
4*	451.223	3.20	26.00	29.20	46.00	-16.80	QP	Ver
5*	715.790	4.33	30.73	35.06	46.00	-10.94	QP	Ver
6*	987.511	5.27	34.01	39.28	54.00	-14.72	QP	Ver



Results of Radiated Emissions (Above 1000MHz)

Band I(5.15-5.25) GHz							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (802.11a/ 5180 MHz)							
3992.77	52.75	-6.89	45.86	74.00	-28.14	PK	Vertical
3992.77	43.13	-6.89	36.24	54.00	-17.76	AV	Vertical
3982.77	53.29	-6.89	46.40	74.00	-27.60	PK	Horizontal
3982.77	43.29	-6.89	36.40	54.00	-17.60	AV	Horizontal
8922.67	54.13	-3.80	50.33	68.20	-17.87	PK	Vertical
8922.67	43.60	-3.80	39.80	54.00	-14.20	AV	Vertical
8912.17	53.79	-3.80	49.99	68.20	-18.21	PK	Horizontal
8912.17	43.27	-3.80	39.47	54.00	-14.53	AV	Horizontal
10360.40	56.00	-2.92	53.08	68.20	-15.12	PK	Vertical
10360.40	45.37	-2.92	42.45	54.00	-11.55	AV	Vertical
10360.33	56.09	-2.92	53.17	68.20	-15.03	PK	Horizontal
10360.33	45.12	-2.92	42.20	54.00	-11.80	AV	Horizontal
13288.32	54.62	-0.67	53.95	74.00	-20.05	PK	Vertical
13288.32	43.52	-0.67	42.85	54.00	-11.15	AV	Vertical
13296.28	54.41	-0.67	53.74	74.00	-20.26	PK	Horizontal
13296.28	43.85	-0.67	43.18	54.00	-10.82	AV	Horizontal
Mid Channel (802.11a/ 5200 MHz)							
3991.17	52.47	-6.89	45.58	74.00	-28.42	PK	Vertical
3991.17	42.68	-6.89	35.79	54.00	-18.21	AV	Vertical
3983.96	52.96	-6.89	46.07	74.00	-27.93	PK	Horizontal
3983.96	42.96	-6.89	36.07	54.00	-17.93	AV	Horizontal
7234.05	54.49	-3.80	50.69	68.20	-17.51	PK	Vertical
7234.05	43.49	-3.80	39.69	54.00	-14.31	AV	Vertical
7225.44	53.26	-3.80	49.46	68.20	-18.74	PK	Horizontal
7225.44	43.77	-3.80	39.97	54.00	-14.03	AV	Horizontal
10400.37	55.43	-2.92	52.51	68.20	-15.69	PK	Vertical
10400.37	45.09	-2.92	42.17	54.00	-11.83	AV	Vertical
10400.40	56.33	-2.92	53.41	68.20	-14.79	PK	Horizontal
10400.40	44.02	-2.92	41.10	54.00	-12.90	AV	Horizontal
13288.99	53.61	-0.67	52.94	74.00	-21.06	PK	Vertical
13288.99	44.56	-0.67	43.89	54.00	-10.11	AV	Vertical
13295.34	54.69	-0.67	54.02	74.00	-19.98	PK	Horizontal
13295.34	43.56	-0.67	42.89	54.00	-11.11	AV	Horizontal
High Channel (802.11a/ 5240 MHz)							
3997.04	53.46	-6.89	46.57	74.00	-27.43	PK	Vertical
3997.04	42.15	-6.89	35.26	54.00	-18.74	AV	Vertical
3990.61	52.71	-6.89	45.82	74.00	-28.18	PK	Horizontal
3990.61	42.53	-6.89	35.64	54.00	-18.36	AV	Horizontal
7216.72	54.15	-3.80	50.35	68.20	-17.85	PK	Vertical
7216.72	43.62	-3.80	39.82	54.00	-14.18	AV	Vertical
7224.27	53.24	-3.80	49.44	68.20	-18.76	PK	Horizontal
7224.27	44.05	-3.80	40.25	54.00	-13.75	AV	Horizontal
10480.07	55.30	-2.92	52.38	68.20	-15.82	PK	Vertical
10480.07	44.28	-2.92	41.36	54.00	-12.64	AV	Vertical
10480.26	56.22	-2.92	53.30	68.20	-14.90	PK	Horizontal
10480.26	44.65	-2.92	41.73	54.00	-12.27	AV	Horizontal
13286.91	54.61	-0.67	53.94	74.00	-20.06	PK	Vertical
13286.91	44.24	-0.67	43.57	54.00	-10.43	AV	Vertical
13281.97	54.38	-0.67	53.71	74.00	-20.29	PK	Horizontal
13281.97	43.70	-0.67	43.03	54.00	-10.97	AV	Horizontal



Band II(5.25-5.35) GHz							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (802.11a/ 5260 MHz)							
3991.10	52.36	-6.89	45.47	74.00	-28.53	PK	Vertical
3991.10	42.66	-6.89	35.77	54.00	-18.23	AV	Vertical
3996.16	52.94	-6.89	46.05	74.00	-27.95	PK	Horizontal
3996.16	43.49	-6.89	36.60	54.00	-17.40	AV	Horizontal
8914.80	53.80	-3.80	50.00	68.20	-18.20	PK	Vertical
8914.80	43.74	-3.80	39.94	54.00	-14.06	AV	Vertical
8910.03	54.39	-3.80	50.59	68.20	-17.61	PK	Horizontal
8910.03	44.11	-3.80	40.31	54.00	-13.69	AV	Horizontal
10520.06	55.52	-2.92	52.60	68.20	-15.60	PK	Vertical
10520.06	45.49	-2.92	42.57	54.00	-11.43	AV	Vertical
10520.15	55.69	-2.92	52.77	68.20	-15.43	PK	Horizontal
10520.15	44.89	-2.92	41.97	54.00	-12.03	AV	Horizontal
13293.69	54.07	-0.67	53.40	74.00	-20.60	PK	Vertical
13293.69	43.91	-0.67	43.24	54.00	-10.76	AV	Vertical
13283.99	54.06	-0.67	53.39	74.00	-20.61	PK	Horizontal
13283.99	44.58	-0.67	43.91	54.00	-10.09	AV	Horizontal
Mid Channel (802.11a/ 5300 MHz)							
3998.76	52.00	-6.89	45.11	74.00	-28.89	PK	Vertical
3998.76	42.04	-6.89	35.15	54.00	-18.85	AV	Vertical
3991.48	53.08	-6.89	46.19	74.00	-27.81	PK	Horizontal
3991.48	42.27	-6.89	35.38	54.00	-18.62	AV	Horizontal
8923.77	54.19	-3.80	50.39	68.20	-17.81	PK	Vertical
8923.77	43.07	-3.80	39.27	54.00	-14.73	AV	Vertical
8920.89	54.16	-3.80	50.36	68.20	-17.84	PK	Horizontal
8920.89	43.97	-3.80	40.17	54.00	-13.83	AV	Horizontal
10600.36	55.88	-2.92	52.96	74.00	-21.04	PK	Vertical
10600.36	45.06	-2.92	42.14	54.00	-11.86	AV	Vertical
10600.07	56.14	-2.92	53.22	74.00	-20.78	PK	Horizontal
10600.07	44.14	-2.92	41.22	54.00	-12.78	AV	Horizontal
13291.47	54.97	-0.67	54.30	74.00	-19.70	PK	Vertical
13291.47	43.90	-0.67	43.23	54.00	-10.77	AV	Vertical
13289.18	53.80	-0.67	53.13	74.00	-20.87	PK	Horizontal
13289.18	44.32	-0.67	43.65	54.00	-10.35	AV	Horizontal
High Channel (802.11a/ 5320 MHz)							
3982.95	52.50	-6.89	45.61	74.00	-28.39	PK	Vertical
3982.95	42.80	-6.89	35.91	54.00	-18.09	AV	Vertical
3997.75	53.28	-6.89	46.39	74.00	-27.61	PK	Horizontal
3997.75	43.13	-6.89	36.24	54.00	-17.76	AV	Horizontal
8919.22	54.35	-3.80	50.55	68.20	-17.65	PK	Vertical
8919.22	44.26	-3.80	40.46	54.00	-13.54	AV	Vertical
8916.47	53.69	-3.80	49.89	68.20	-18.31	PK	Horizontal
8916.47	43.25	-3.80	39.45	54.00	-14.55	AV	Horizontal
10640.07	56.16	-2.92	53.24	74.00	-20.76	PK	Vertical
10640.07	45.03	-2.92	42.11	54.00	-11.89	AV	Vertical
10640.15	55.94	-2.92	53.02	74.00	-20.98	PK	Horizontal
10640.15	44.87	-2.92	41.95	54.00	-12.05	AV	Horizontal
13283.49	54.47	-0.67	53.80	74.00	-20.20	PK	Vertical
13283.49	44.23	-0.67	43.56	54.00	-10.44	AV	Vertical
13282.98	53.66	-0.67	52.99	74.00	-21.01	PK	Horizontal
13282.98	44.17	-0.67	43.50	54.00	-10.50	AV	Horizontal



Band III(5.47-5.725) GHz							
Frequency (MHz)	Reading (dBμV)	Orrected Factor (dB)	Reslut (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (802.11a/ 5500 MHz)							
3986.56	52.56	-6.89	45.67	74.00	-28.33	PK	Vertical
3986.56	42.30	-6.89	35.41	54.00	-18.59	AV	Vertical
3993.32	53.22	-6.89	46.33	74.00	-27.67	PK	Horizontal
3993.32	42.71	-6.89	35.82	54.00	-18.18	AV	Horizontal
8922.02	53.29	-3.80	49.49	68.20	-18.71	PK	Vertical
8922.02	44.28	-3.80	40.48	54.00	-13.52	AV	Vertical
8921.36	54.29	-3.80	50.49	68.20	-17.71	PK	Horizontal
8921.36	43.69	-3.80	39.89	54.00	-14.11	AV	Horizontal
10996.24	56.35	-2.92	53.43	74.00	-20.57	PK	Vertical
10996.24	44.64	-2.92	41.72	54.00	-12.28	AV	Vertical
10981.50	56.39	-2.92	53.47	74.00	-20.53	PK	Horizontal
10981.50	45.02	-2.92	42.10	54.00	-11.90	AV	Horizontal
13298.27	54.73	-0.35	54.38	74.00	-19.62	PK	Vertical
13298.27	43.77	-0.35	43.42	54.00	-10.58	AV	Vertical
13291.59	53.72	-0.35	53.37	74.00	-20.63	PK	Horizontal
13291.59	44.19	-0.35	43.84	54.00	-10.16	AV	Horizontal
Mid Channel (802.11a/ 5580 MHz)							
3995.52	52.31	-6.89	45.42	74.00	-28.58	PK	Vertical
3995.52	42.39	-6.89	35.50	54.00	-18.50	AV	Vertical
3983.88	53.10	-6.89	46.21	74.00	-27.79	PK	Horizontal
3983.88	43.35	-6.89	36.46	54.00	-17.54	AV	Horizontal
8916.26	54.12	-3.80	50.32	68.20	-17.88	PK	Vertical
8916.26	44.14	-3.80	40.34	54.00	-13.66	AV	Vertical
8908.45	54.23	-3.80	50.43	68.20	-17.77	PK	Horizontal
8908.45	43.74	-3.80	39.94	54.00	-14.06	AV	Horizontal
11146.66	56.17	-2.92	53.25	74.00	-20.75	PK	Vertical
11146.66	44.12	-2.92	41.20	54.00	-12.80	AV	Vertical
11150.47	55.46	-2.92	52.54	74.00	-21.46	PK	Horizontal
11150.47	44.02	-2.92	41.10	54.00	-12.90	AV	Horizontal
13284.96	54.12	-0.35	53.77	74.00	-20.23	PK	Vertical
13284.96	43.92	-0.35	43.57	54.00	-10.43	AV	Vertical
13287.36	53.74	-0.35	53.39	74.00	-20.61	PK	Horizontal
13287.36	43.90	-0.35	43.55	54.00	-10.45	AV	Horizontal
High Channel (802.11a/ 5700 MHz)							
3983.16	52.75	-6.89	45.86	74.00	-28.14	PK	Vertical
3983.16	43.31	-6.89	36.42	54.00	-17.58	AV	Vertical
3981.83	52.37	-6.89	45.48	74.00	-28.52	PK	Horizontal
3981.83	42.40	-6.89	35.51	54.00	-18.49	AV	Horizontal
8925.48	53.56	-3.80	49.76	68.20	-18.44	PK	Vertical
8925.48	43.12	-3.80	39.32	54.00	-14.68	AV	Vertical
8919.35	53.12	-3.80	49.32	68.20	-18.88	PK	Horizontal
8919.35	44.08	-3.80	40.28	54.00	-13.72	AV	Horizontal
11397.91	55.07	-2.92	52.15	74.00	-21.85	PK	Vertical
11397.91	45.32	-2.92	42.40	54.00	-11.60	AV	Vertical
11399.75	56.01	-2.92	53.09	74.00	-20.91	PK	Horizontal
11399.75	45.12	-2.92	42.20	54.00	-11.80	AV	Horizontal
13296.89	54.35	-0.35	54.00	74.00	-20.00	PK	Vertical
13296.89	44.75	-0.35	44.40	54.00	-9.60	AV	Vertical
13286.06	53.60	-0.35	53.25	74.00	-20.75	PK	Horizontal
13286.06	44.73	-0.35	44.38	54.00	-9.62	AV	Horizontal



Band IV(5.725-5.85) GHz							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
Low Channel (802.11a/ 5745 MHz)							
3985.08	52.23	-6.89	45.34	74.00	-28.66	PK	Vertical
3985.08	43.23	-6.89	36.34	54.00	-17.66	AV	Vertical
3992.60	52.82	-6.89	45.93	74.00	-28.07	PK	Horizontal
3992.60	42.59	-6.89	35.70	54.00	-18.30	AV	Horizontal
8906.63	54.43	-3.80	50.63	68.20	-17.57	PK	Vertical
8906.63	43.99	-3.80	40.19	54.00	-13.81	AV	Vertical
8919.41	54.28	-3.80	50.48	68.20	-17.72	PK	Horizontal
8919.41	44.47	-3.80	40.67	54.00	-13.33	AV	Horizontal
11470.77	55.71	-2.92	52.79	74.00	-21.21	PK	Vertical
11470.77	44.73	-2.92	41.81	54.00	-12.19	AV	Vertical
11486.46	55.05	-2.92	52.13	74.00	-21.87	PK	Horizontal
11486.46	45.18	-2.92	42.26	54.00	-11.74	AV	Horizontal
13291.51	54.07	-0.35	53.72	74.00	-20.28	PK	Vertical
13291.51	44.99	-0.35	44.64	54.00	-9.36	AV	Vertical
13288.92	53.71	-0.35	53.36	74.00	-20.64	PK	Horizontal
13288.92	44.49	-0.35	44.14	54.00	-9.86	AV	Horizontal
Mid Channel (802.11a/ 5785 MHz)							
3994.27	52.54	-6.89	45.65	74.00	-28.35	PK	Vertical
3994.27	42.62	-6.89	35.73	54.00	-18.27	AV	Vertical
3982.34	52.73	-6.89	45.84	74.00	-28.16	PK	Horizontal
3982.34	42.19	-6.89	35.30	54.00	-18.70	AV	Horizontal
8911.08	53.04	-3.80	49.24	68.20	-18.96	PK	Vertical
8911.08	43.76	-3.80	39.96	54.00	-14.04	AV	Vertical
8909.78	53.31	-3.80	49.51	68.20	-18.69	PK	Horizontal
8909.78	44.32	-3.80	40.52	54.00	-13.48	AV	Horizontal
11566.76	55.48	-2.92	52.56	74.00	-21.44	PK	Vertical
11566.76	44.51	-2.92	41.59	54.00	-12.41	AV	Vertical
11560.61	55.69	-2.92	52.77	74.00	-21.23	PK	Horizontal
11560.61	44.10	-2.92	41.18	54.00	-12.82	AV	Horizontal
13283.65	54.99	-0.35	54.64	74.00	-19.36	PK	Vertical
13283.65	43.80	-0.35	43.45	54.00	-10.55	AV	Vertical
13285.00	54.33	-0.35	53.98	74.00	-20.02	PK	Horizontal
13285.00	44.97	-0.35	44.62	54.00	-9.38	AV	Horizontal
High Channel (802.11a/ 5825 MHz)							
3991.61	53.17	-6.89	46.28	74.00	-27.72	PK	Vertical
3991.61	43.03	-6.89	36.14	54.00	-17.86	AV	Vertical
3993.98	53.38	-6.89	46.49	74.00	-27.51	PK	Horizontal
3993.98	43.46	-6.89	36.57	54.00	-17.43	AV	Horizontal
8924.84	53.33	-3.80	49.53	68.20	-18.67	PK	Vertical
8924.84	43.54	-3.80	39.74	54.00	-14.26	AV	Vertical
8921.49	53.97	-3.80	50.17	68.20	-18.03	PK	Horizontal
8921.49	43.79	-3.80	39.99	54.00	-14.01	AV	Horizontal
11642.98	56.39	-2.92	53.47	74.00	-20.53	PK	Vertical
11642.98	44.26	-2.92	41.34	54.00	-12.66	AV	Vertical
11649.94	55.41	-2.92	52.49	74.00	-21.51	PK	Horizontal
11649.94	44.60	-2.92	41.68	54.00	-12.32	AV	Horizontal
13289.61	54.11	-0.35	53.76	74.00	-20.24	PK	Vertical
13289.61	43.69	-0.35	43.34	54.00	-10.66	AV	Vertical
13295.24	54.17	-0.35	53.82	74.00	-20.18	PK	Horizontal
13295.24	44.54	-0.35	44.19	54.00	-9.81	AV	Horizontal

Remark:

In frequency ranges 18~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.



3.2.7 TEST RESULTS(Band edge Requirements)

Band I & Band II (5.15-5.35) GHz							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
802.11n BW20MHz							
5150	55.39	-7.51	47.88	74	-26.12	PK	Vertical
5150	44.27	-7.51	36.76	54	-17.24	AV	Vertical
5150	55.48	-7.51	47.97	74	-26.03	PK	Horizontal
5150	44.70	-7.51	37.19	54	-16.81	AV	Horizontal
5350	54.96	-8.19	46.77	74	-27.23	PK	Vertical
5350	44.65	-8.19	36.46	54	-17.54	AV	Vertical
5350	54.19	-8.19	46.00	74	-28.00	PK	Horizontal
5350	44.29	-8.19	36.10	54	-17.90	AV	Horizontal
802.11n BW40MHz							
5150	56.36	-7.51	48.85	74	-25.15	Peak	Vertical
5150	45.40	-7.51	37.89	54	-16.11	AVG	Vertical
5150	55.59	-7.51	48.08	74	-25.92	Peak	Horizontal
5150	45.13	-7.51	37.62	54	-16.38	AVG	Horizontal
5350	55.01	-8.19	46.82	74	-27.18	Peak	Vertical
5350	44.82	-8.19	36.63	54	-17.37	AVG	Vertical
5350	55.36	-8.19	47.17	74	-26.83	Peak	Horizontal
5350	44.42	-8.19	36.23	54	-17.77	AVG	Horizontal
802.11ac BW80MHz							
5150	56.17	-7.51	48.66	74	-25.34	Peak	Vertical
5150	45.29	-7.51	37.78	54	-16.22	AVG	Vertical
5150	56.22	-7.51	48.71	74	-25.29	Peak	Horizontal
5150	45.34	-7.51	37.83	54	-16.17	AVG	Horizontal
5350	54.70	-8.19	46.51	74	-27.49	Peak	Vertical
5350	44.85	-8.19	36.66	54	-17.34	AVG	Vertical
5350	54.46	-8.19	46.27	74	-27.73	Peak	Horizontal
5350	43.75	-8.19	35.56	54	-18.44	AVG	Horizontal



Band IV(5.47-5.725 GHz)							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
802.11n BW20MHz							
5460	53.40	-8.27	45.13	74	-28.87	PK	Vertical
5460	43.44	-8.27	35.17	54	-18.83	AV	Vertical
5460	53.85	-8.27	45.58	74	-28.42	PK	Horizontal
5460	43.42	-8.27	35.15	54	-18.85	AV	Horizontal
7250	55.11	-6.33	48.78	74	-25.22	PK	Vertical
7250	44.33	-6.33	38.00	54	-16.00	AV	Vertical
7250	55.47	-6.33	49.14	74	-24.86	PK	Horizontal
7250	44.21	-6.33	37.88	54	-16.12	AV	Horizontal
802.11n BW40MHz							
5460	54.10	-8.27	45.83	74	-28.17	PK	Vertical
5460	43.48	-8.27	35.21	54	-18.79	AV	Vertical
5460	53.97	-8.27	45.70	74	-28.30	PK	Horizontal
5460	43.29	-8.27	35.02	54	-18.98	AV	Horizontal
7250	55.20	-6.33	48.87	74	-25.13	PK	Vertical
7250	44.67	-6.33	38.34	54	-15.66	AV	Vertical
7250	54.17	-6.33	47.84	74	-26.16	PK	Horizontal
7250	44.09	-6.33	37.76	54	-16.24	AV	Horizontal
802.11ac BW80MHz							
5460	53.74	-8.27	45.47	74	-28.53	PK	Vertical
5460	42.84	-8.27	34.57	54	-19.43	AV	Vertical
5460	53.79	-8.27	45.52	74	-28.48	PK	Horizontal
5460	43.28	-8.27	35.01	54	-18.99	AV	Horizontal
7250	55.03	-6.33	48.70	74	-25.30	PK	Vertical
7250	43.82	-6.33	37.49	54	-16.51	AV	Vertical
7250	54.71	-6.33	48.38	74	-25.62	PK	Horizontal
7250	44.88	-6.33	38.55	54	-15.45	AV	Horizontal



Band IV(5.725-5.85 GHz)							
Frequency (MHz)	Reading (dBμV)	Corrected Factor (dB)	Result (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector	Polarity
802.11n BW20MHz							
5460	53.17	-8.27	44.90	74	-29.10	PK	Vertical
5460	43.36	-8.27	35.09	54	-18.91	AV	Vertical
5460	53.88	-8.27	45.61	74	-28.39	PK	Horizontal
5460	43.83	-8.27	35.56	54	-18.44	AV	Horizontal
7250	54.79	-6.33	48.46	74	-25.54	PK	Vertical
7250	44.94	-6.33	38.61	54	-15.39	AV	Vertical
7250	55.26	-6.33	48.93	74	-25.07	PK	Horizontal
7250	44.10	-6.33	37.77	54	-16.23	AV	Horizontal
802.11n BW40MHz							
5460	53.98	-8.27	45.71	74	-28.29	PK	Vertical
5460	42.86	-8.27	34.59	54	-19.41	AV	Vertical
5460	54.37	-8.27	46.10	74	-27.90	PK	Horizontal
5460	42.80	-8.27	34.53	54	-19.47	AV	Horizontal
7250	54.25	-6.33	47.92	74	-26.08	PK	Vertical
7250	43.75	-6.33	37.42	54	-16.58	AV	Vertical
7250	55.30	-6.33	48.97	74	-25.03	PK	Horizontal
7250	44.95	-6.33	38.62	54	-15.38	AV	Horizontal
802.11ac BW80MHz							
5460	53.98	-8.27	45.71	74	-28.29	PK	Vertical
5460	42.94	-8.27	34.67	54	-19.33	AV	Vertical
5460	53.73	-8.27	45.46	74	-28.54	PK	Horizontal
5460	43.98	-8.27	35.71	54	-18.29	AV	Horizontal
7250	54.41	-6.33	48.08	74	-25.92	PK	Vertical
7250	44.63	-6.33	38.30	54	-15.70	AV	Vertical
7250	54.28	-6.33	47.95	74	-26.05	PK	Horizontal
7250	44.48	-6.33	38.15	54	-15.85	AV	Horizontal



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-1 of FCC KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

For devices operating in the band, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (*i.e.*, 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

For the measurement records, refer to the appendix I.



5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

For the measurement records, refer to the appendix I.



5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.2.5 TEST RESULTS

For the measurement records, refer to the appendix I.



5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.3.5 TEST RESULTS

For the measurement records, refer to the appendix I.



6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or $11 \text{ dBm} + 10 \log (26 \text{ dB emission bandwidth})$	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULTS

For the measurement records, refer to the appendix I.



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

Part 15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.




APPENDIX I - TEST RESULTS

Duty Cycle


Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	100	0	0
NVNT	a	5200	100	0	0
NVNT	a	5240	100	0	0
NVNT	a	5260	100	0	0
NVNT	a	5300	100	0	0
NVNT	a	5320	100	0	0
NVNT	a	5500	100	0	0
NVNT	a	5580	100	0	0
NVNT	a	5700	100	0	0
NVNT	a	5745	100	0	0
NVNT	a	5785	100	0	0
NVNT	a	5825	100	0	0
NVNT	n20	5180	100	0	0
NVNT	n20	5200	100	0	0
NVNT	n20	5240	100	0	0
NVNT	n20	5260	100	0	0
NVNT	n20	5300	100	0	0
NVNT	n20	5320	100	0	0
NVNT	n20	5500	100	0	0
NVNT	n20	5580	100	0	0
NVNT	n20	5700	100	0	0
NVNT	n20	5745	100	0	0
NVNT	n20	5785	100	0	0
NVNT	n20	5825	100	0	0
NVNT	n40	5190	100	0	0
NVNT	n40	5230	100	0	0
NVNT	n40	5270	100	0	0
NVNT	n40	5310	100	0	0
NVNT	n40	5510	100	0	0
NVNT	n40	5550	100	0	0
NVNT	n40	5670	100	0	0
NVNT	n40	5755	100	0	0
NVNT	n40	5795	100	0	0
NVNT	ac20	5180	100	0	0
NVNT	ac20	5200	100	0	0
NVNT	ac20	5240	100	0	0
NVNT	ac20	5260	100	0	0
NVNT	ac20	5300	100	0	0
NVNT	ac20	5320	100	0	0
NVNT	ac20	5500	100	0	0
NVNT	ac20	5580	100	0	0
NVNT	ac20	5700	100	0	0
NVNT	ac20	5745	100	0	0
NVNT	ac20	5785	100	0	0
NVNT	ac20	5825	100	0	0
NVNT	ac40	5190	100	0	0
NVNT	ac40	5230	100	0	0
NVNT	ac40	5270	100	0	0
NVNT	ac40	5310	100	0	0
NVNT	ac40	5510	100	0	0
NVNT	ac40	5550	100	0	0




NVNT	ac40	5670	100	0	0
NVNT	ac40	5755	100	0	0
NVNT	ac40	5795	100	0	0
NVNT	ac80	5210	100	0	0
NVNT	ac80	5290	100	0	0
NVNT	ac80	5530	100	0	0
NVNT	ac80	5610	100	0	0
NVNT	ac80	5775	100	0	0













































Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	6	0	6	24	Pass
NVNT	a	5200	6.9	0	6.9	24	Pass
NVNT	a	5240	6.46	0	6.46	24	Pass
NVNT	a	5260	6.64	0	6.64	24	Pass
NVNT	a	5300	6.38	0	6.38	24	Pass
NVNT	a	5320	6.22	0	6.22	24	Pass
NVNT	a	5500	6.36	0	6.36	24	Pass
NVNT	a	5580	6.87	0	6.87	24	Pass
NVNT	a	5700	7.76	0	7.49	24	Pass
NVNT	a	5745	7.59	0	7.39	30	Pass
NVNT	a	5785	7.3	0	7.1	30	Pass
NVNT	a	5825	7.65	0	7.45	30	Pass
NVNT	n20	5180	4.52	0	4.52	24	Pass
NVNT	n20	5200	5.53	0	5.53	24	Pass
NVNT	n20	5240	5.74	0	5.74	24	Pass
NVNT	n20	5260	5.61	0	5.61	24	Pass
NVNT	n20	5300	4.83	0	4.83	24	Pass
NVNT	n20	5320	5.14	0	5.14	24	Pass
NVNT	n20	5500	5.47	0	5.47	24	Pass
NVNT	n20	5580	6.24	0	6.24	24	Pass
NVNT	n20	5700	6.87	0	6.87	24	Pass
NVNT	n20	5745	6.67	0	6.67	30	Pass
NVNT	n20	5785	5.8	0	5.8	30	Pass
NVNT	n20	5825	6.67	0	6.67	30	Pass
NVNT	n40	5190	5.41	0	5.41	24	Pass
NVNT	n40	5230	5.55	0	5.55	24	Pass
NVNT	n40	5270	5.41	0	5.41	24	Pass
NVNT	n40	5310	5.18	0	5.18	24	Pass
NVNT	n40	5510	4.66	0	4.66	24	Pass
NVNT	n40	5550	5.6	0	5.6	24	Pass
NVNT	n40	5670	6.01	0	6.01	24	Pass
NVNT	n40	5755	6.5	0	6.5	30	Pass
NVNT	n40	5795	6.11	0	6.11	30	Pass
NVNT	ac20	5180	4.66	0	4.66	24	Pass
NVNT	ac20	5200	5.12	0	5.12	24	Pass
NVNT	ac20	5240	4.94	0	4.94	24	Pass
NVNT	ac20	5260	4.93	0	4.93	24	Pass
NVNT	ac20	5300	5.28	0	5.28	24	Pass
NVNT	ac20	5320	4.49	0	4.49	24	Pass
NVNT	ac20	5500	4.88	0	4.88	24	Pass
NVNT	ac20	5580	5.48	0	5.48	24	Pass
NVNT	ac20	5700	5.78	0	5.78	24	Pass
NVNT	ac20	5745	5.9	0	5.9	30	Pass
NVNT	ac20	5785	5.82	0	5.82	30	Pass
NVNT	ac20	5825	5.83	0	5.83	30	Pass
NVNT	ac40	5190	4.91	0	4.91	24	Pass
NVNT	ac40	5230	5.24	0	5.24	24	Pass
NVNT	ac40	5270	5.12	0	5.12	24	Pass
NVNT	ac40	5310	5.05	0	5.05	24	Pass
NVNT	ac40	5510	5.23	0	5.23	24	Pass
NVNT	ac40	5550	5.61	0	5.61	24	Pass



NVNT	ac40	5670	6.33	0	6.33	24	Pass
NVNT	ac40	5755	6.54	0	6.54	30	Pass
NVNT	ac40	5795	6.71	0	6.71	30	Pass
NVNT	ac80	5210	4.55	0	4.55	24	Pass
NVNT	ac80	5290	5.13	0	5.13	24	Pass
NVNT	ac80	5530	5.22	0	5.22	24	Pass
NVNT	ac80	5610	5.51	0	5.51	24	Pass
NVNT	ac80	5775	6.22	0	6.22	30	Pass



-26dB Bandwidth

Condition	Mode	Frequency (MHz)	-26 dB Bandwidth (MHz)	Verdict
NVNT	a	5180	19.817	Pass
NVNT	a	5200	19.997	Pass
NVNT	a	5240	19.922	Pass
NVNT	a	5260	20.069	Pass
NVNT	a	5300	20.415	Pass
NVNT	a	5320	19.987	Pass
NVNT	a	5500	19.833	Pass
NVNT	a	5580	19.676	Pass
NVNT	a	5700	19.842	Pass
NVNT	n20	5180	20.346	Pass
NVNT	n20	5200	20.293	Pass
NVNT	n20	5240	20.405	Pass
NVNT	n20	5260	20.248	Pass
NVNT	n20	5300	20.338	Pass
NVNT	n20	5320	20.29	Pass
NVNT	n20	5500	20.313	Pass
NVNT	n20	5580	20.159	Pass
NVNT	n20	5700	20.356	Pass
NVNT	n40	5190	39.477	Pass
NVNT	n40	5230	39.848	Pass
NVNT	n40	5270	39.971	Pass
NVNT	n40	5310	40.076	Pass
NVNT	n40	5510	39.5	Pass
NVNT	n40	5550	39.574	Pass
NVNT	n40	5670	39.764	Pass
NVNT	ac20	5180	20.292	Pass
NVNT	ac20	5200	20.119	Pass
NVNT	ac20	5240	20.364	Pass
NVNT	ac20	5260	20.29	Pass
NVNT	ac20	5300	20.269	Pass
NVNT	ac20	5320	20.249	Pass
NVNT	ac20	5500	20.5	Pass
NVNT	ac20	5580	20.258	Pass
NVNT	ac20	5700	20.332	Pass
NVNT	ac40	5190	39.381	Pass
NVNT	ac40	5230	40.194	Pass
NVNT	ac40	5270	39.912	Pass
NVNT	ac40	5310	39.997	Pass
NVNT	ac40	5510	39.692	Pass
NVNT	ac40	5550	39.631	Pass
NVNT	ac40	5670	39.671	Pass
NVNT	ac80	5210	80.49	Pass
NVNT	ac80	5290	80.66	Pass
NVNT	ac80	5530	80.43	Pass
NVNT	ac80	5610	80.55	Pass




Test Graphs


-26dB Bandwidth NVNT a 5180MHz





-26dB Bandwidth NVNT a 5200MHz



-26dB Bandwidth NVNT a 5240MHz














-26dB Bandwidth NVNT n20 5260MHz



-26dB Bandwidth NVNT n20 5300MHz




-26dB Bandwidth NVNT n20 5320MHz






-26dB Bandwidth NVNT n20 5500MHz



-26dB Bandwidth NVNT n20 5580MHz



-26dB Bandwidth NVNT n20 5700MHz





-26dB Bandwidth NVNT n40 5190MHz



-26dB Bandwidth NVNT n40 5230MHz



-26dB Bandwidth NVNT n40 5270MHz





-26dB Bandwidth NVNT n40 5310MHz



-26dB Bandwidth NVNT n40 5510MHz



-26dB Bandwidth NVNT n40 5550MHz



