



TEST REPORT

No. I19Z60257-EMC01

HMD Global Oy

phone

Model Name: TA-1182

FCC ID: 2AJOTTA-1182

with

Hardware Version: 1.0

Software Version: 00VZW_0_150

Issued Date: 2019-04-11



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I19Z60257-EMC01	Rev.0	1 st edition	2019-04-11

CONTENTS

1. TEST LABORATORY	4
1.1. INTRODUCTION & ACCREDITATION	4
1.2. TESTING LOCATION	4
1.3. TESTING ENVIRONMENT	4
1.4. PROJECT DATA	4
1.5. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	6
3.4. EUT SET-UPS	7
4. REFERENCE DOCUMENTS	8
4.1. REFERENCE DOCUMENTS FOR TESTING	8
5. LABORATORY ENVIRONMENT	9
6. SUMMARY OF TEST RESULTS	10
7. TEST EQUIPMENTS UTILIZED	11
ANNEX A: MEASUREMENT RESULTS	12
ANNEX B: PERSONS INVOLVED IN THIS TESTING	22

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

CTTL (BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology Development Area, Beijing, P. R. China 100176

1.3. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-02-28

Testing End Date: 2019-03-15

1.5. Signature




Li Yan

(Prepared this test report)



Zhang Ying

(Reviewed this test report)



Liu Baodian

Deputy Director of the laboratory

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: HMD Global Oy
Address: Bertel Jungin aukio 9,02600 Espoo, Finland
City: /
Postal Code: /
Country: /
Contact: /
Email: /
Telephone: /

2.2. Manufacturer Information

Company Name: HMD Global Oy
Address: Bertel Jungin aukio 9,02600 Espoo, Finland
City: /
Postal Code: /
Country: /
Contact: /
Email: /
Telephone: /

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	phone
Model Name	TA-1182
FCC ID	2AJOTTA-1182
Extreme vol. Limits	3.6VDC to 4.40VDC (nominal: 3.9VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT3	352910100006141	1.0	00VZW_0_150

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Charger	/	/
AE3	USB Cable	/	/
AE4	USB Cable	/	/
AE5	Headset	/	/

AE1

Model	WT241
Manufacturer	Jiade Energy Technology(Zhuhai) Co.,Ltd.
Capacitance	4000mAh
Nominal voltage	3.85V

AE2

Model	YUTCH22TVL
Manufacturer	Yutong electronics(Huizhou) co.,ltd
Length of cable	/

AE3

Model	CB-25A
Manufacturer	Leagtech Electronics Co.,Ltd
Length of cable	/

AE4

Model	CB-25A
Manufacturer	Shenzhen BRL Technology Co.,Ltd.
Length of cable	/

AE8

Model	HS-34
Manufacturer	New Leader Industry Co.,Ltd
Length of cable	/

Note: The USB cables are shielded.



3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT3+ AE1 + AE2+ AE3/ AE4+AE5	Charger + FM
Set.2	EUT3+ AE1 + AE3/ AE4	USB mode+MP3+GNSS

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17 meters×10 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m/10m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Semi-anechoic chamber SAC-2 (10 meters×6.7meters×6.1meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail
	BR	Re-use test data from basic model report.

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	A.1	P	CTTL(BDA)
2	Conducted Emission	15.107(a)	A.2	P	CTTL(BDA)

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATI ON INTERVAL
1	Test Receiver	ESU26	100376	R&S	2019-11-27	1 year
2	Test Receiver	ESCI	100766	R&S	2019-04-16	1 year
3	Universal Radio Communication Tester	CMW500	127406	R&S	2020-01-19	1 year
4	LISN	ESH3-Z5	825562/028	R&S	2019-08-22	1 year
5	EMI Antenna	VULB9163	9163-482	Schwarzbeck	2019-09-21	1 year
6	EMI Antenna	3117	00139065	ETS-Lindgren	2019-11-15	1 year
7	Signal Generator	SMF100A	101295	R&S	2019-11-27	1 year
8	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
9	Keyboard	KU-1601	2048361	Lenovo	N/A	N/A
10	Mouse	EMS-537A	8021S3MC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

ANNEX A: MEASUREMENT RESULTS

A.1 Radiated Emission

Reference

FCC: CFR Part 15.109(a).

A.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 3 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

A.1.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. During the charging mode the FM application is started up. During the USB mode The EUT is keeping on playing MP3 and the GNSS application is started up. The model of the PC is Lenovo M4000e-17, and the serial number of the PC is M706RMW2. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.1.3 Measurement Limit

Frequency range (MHz)	Field strength limit ($\mu\text{V/m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

A.1.4 Test Condition

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

A.1.5 Measurement Results

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

G_A : Antenna factor of receive antenna

G_{PL} : Path Loss

P_{Mea} : Measurement result on receiver.

Measurement uncertainty (worst case): 30MHz-1GHz: 5.40dB, 1GHz-18GHz: 4.32dB, $k=2$.

Measurement results for Set.1:

Charging Mode+ FM /Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17113.500	39.7	-25.5	41.3	23.88	54.0	14.3	V
17052.750	39.7	-25.5	41.4	23.90	54.0	14.3	V
17086.500	39.7	-25.5	41.3	23.86	54.0	14.3	V
17087.250	39.6	-25.5	41.3	23.78	54.0	14.4	H
17090.250	39.6	-25.5	41.3	23.76	54.0	14.4	H
17100.000	39.6	-25.5	41.3	23.75	54.0	14.4	V

Charging Mode+ FM/Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17382.750	51.6	-25.5	41.2	35.90	74.0	22.4	V
17524.500	51.6	-25.4	41.2	35.82	74.0	22.4	V
17559.000	51.4	-25.6	41.2	35.83	74.0	22.6	H
17976.000	51.4	-25.2	40.8	35.76	74.0	22.6	H
17901.000	51.3	-24.2	40.9	34.69	74.0	22.7	H
17976.750	51.2	-25.2	40.8	35.66	74.0	22.8	V

Measurement results for Set.2:
USB Mode +MP3+GNSS /Average detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17100.000	39.7	-25.5	41.3	23.89	54.0	14.3	V
17095.500	39.4	-25.5	41.3	23.60	54.0	14.6	V
17096.250	39.4	-25.5	41.3	23.60	54.0	14.6	H
17115.750	39.4	-25.5	41.3	23.59	54.0	14.6	H
17055.750	39.4	-25.5	41.4	23.60	54.0	14.6	V
17136.000	39.4	-25.5	41.3	23.65	54.0	14.6	H

USB Mode +MP3+GNSS /Peak detector

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
3590.250	53.4	-34.2	33.5	54.11	74.0	20.6	H
17949.000	52.1	-24.9	40.8	36.09	74.0	21.9	H
17922.000	51.4	-24.5	40.9	35.06	74.0	22.6	H
16284.000	51.3	-25.3	40.7	35.98	74.0	22.7	V
17902.500	51.2	-24.2	40.9	34.61	74.0	22.8	H
17004.000	51.2	-25.6	41.4	35.38	74.0	22.8	V

Note: The measurement results of Set.1, Set.2 showed here are worst cases of the combinations of different USB cables.

Charging Mode + FM, Set.1

15B RE 30MHz-1GHz




Figure A.1 Radiated Emission from 30MHz to 1GHz

Note: the spike (98MHz) is coming from FM signal source.

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
34.656000	22.3	100.0	V	131.0	-0.4	17.7	40.0
40.088000	22.4	100.0	V	98.0	0.8	17.6	40.0
49.982000	23.9	100.0	V	76.0	0.8	16.1	40.0
64.629000	19.9	100.0	V	262.0	-2.2	20.1	40.0
101.19800	18.6	125.0	V	287.0	-1.2	24.9	43.5
206.15200	21.5	100.0	V	-3.0	-1.2	22.0	43.5

15B RE - 1GHz-3GHz




Figure A.2 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Figure A.3 Radiated Emission from 3GHz to 18GHz

USB Mode +MP3+GNSS, Set.2

15B RE 30MHz-1GHz




Figure A.4 Radiated Emission from 30MHz to 1GHz

Note: the spike (519.85MHz) is occurred by Printer

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
74.135000	23.5	125.0	H	232.0	-5.0	16.5	40.0
135.34200	22.2	100.0	V	80.0	-4.4	21.3	43.5
194.41500	28.4	100.0	H	-21.0	-1.8	15.1	43.5
222.73900	22.4	119.0	V	200.0	-0.9	23.6	46.0
338.75100	28.8	100.0	V	82.0	2.8	17.2	46.0
519.85000	43.0	125.0	V	-28.0	7.4	3.0	46.0

15B RE - 1GHz-3GHz




Figure A.5 Radiated Emission from 1GHz to 3GHz

15b RE - 3GHz-18GHz




Figure A.6 Radiated Emission from 3GHz to 18GHz

A.2 Conducted Emission

Reference

FCC: CFR Part 15.107(a).

A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. During the charging mode the FM application is started up. During the USB mode The EUT is keeping on playing MP3 and the GNSS application is started up. The model of the PC is Lenovo M4000e-17, and the serial number of the PC is M706RMW2. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

A.2.5 Measurement Results

Measurement uncertainty: $U= 3.10$ dB, $k=2$.

Charging Mode +FM, Set.1




Figure A.7 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.190500	45.9	10000.0	9.000	GND	L1	10.3	18.1	64.0
0.384000	36.8	10000.0	9.000	GND	N	10.3	21.4	58.2
0.532500	33.6	10000.0	9.000	GND	L1	10.3	22.4	56.0
0.609000	33.1	10000.0	9.000	GND	N	10.4	22.9	56.0
0.852000	34.7	10000.0	9.000	GND	L1	10.3	21.3	56.0
1.491000	38.1	10000.0	9.000	GND	L1	10.4	17.9	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.190500	34.9	10000.0	9.000	GND	L1	10.3	19.1	54.0
0.510000	28.7	10000.0	9.000	GND	L1	10.3	17.3	46.0
0.600000	24.1	10000.0	9.000	GND	L1	10.4	21.9	46.0
1.428000	26.3	10000.0	9.000	GND	L1	10.4	19.7	46.0
1.554000	25.0	10000.0	9.000	GND	L1	10.4	21.0	46.0
1.621500	25.6	10000.0	9.000	GND	L1	10.4	20.4	46.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

USB Mode +MP3+GNSS, Set.2




Figure A.8 Conducted Emission

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	54.7	10000.0	9.000	GND	L1	10.2	11.3	66.0
0.357000	43.0	10000.0	9.000	GND	L1	10.3	15.8	58.8
0.897000	37.4	10000.0	9.000	GND	N	10.4	18.6	56.0
2.085000	39.2	10000.0	9.000	GND	N	10.4	16.8	56.0
11.872500	40.6	10000.0	9.000	GND	L1	10.9	19.4	60.0
17.614500	41.4	10000.0	9.000	GND	L1	11.3	18.6	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.204000	39.1	10000.0	9.000	GND	L1	10.3	14.3	53.4
0.343500	32.6	10000.0	9.000	GND	N	10.3	16.5	49.1
0.874500	28.4	10000.0	9.000	GND	N	10.3	17.6	46.0
2.080500	30.6	10000.0	9.000	GND	N	10.4	15.4	46.0
11.863500	29.9	10000.0	9.000	GND	N	10.8	20.1	50.0
17.619000	33.6	10000.0	9.000	GND	L1	11.3	16.4	50.0

Note: The measurement results showed here are worst cases of the combinations of different USB cables.

ANNEX B: Persons involved in this testing

Test Item	Tester
Radiated Emission	Li Zongliang
Conducted Emission	Guo Qian

*****END OF REPORT*****