

FCC Test Report (Part 90 – LTE B26)

Report No.: RFBDKX-WTW-P22120419-6

FCC ID: 2ATIO4

Test Model: H4

Received Date: Dec. 13, 2022

Test Date: Feb. 02, 2023 ~ Feb. 07, 2023

Issued Date: Mar. 31, 2023

Applicant: Level Home Inc.

Address: 935 Main Street, Redwood City, California 94063, United States of America

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number (1):** 788550 / TW0003

Test Location(2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

**FCC Registration /
Designation Number(2):** 281270 / TW0032



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/>, and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Test Site and Instruments.....	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Configuration of System under Test.....	8
3.2.1 Description of Support Units.....	8
3.3 Test Mode Applicability and Tested Channel Detail	9
3.4 EUT Operating Conditions	11
3.5 General Description of Applied Standards and References	11
4 Test Types and Results	12
4.1 Output Power Measurement	12
4.1.1 Limits of Output Power Measurement.....	12
4.1.2 Test Procedures.....	12
4.1.3 Test Setup.....	12
4.1.4 Test Results	13
4.2 Modulation Characteristics Measurement.....	17
4.2.1 Limits of Modulation Characteristics.....	17
4.2.2 Test Procedure	17
4.2.3 Test Setup.....	17
4.2.4 Test Results	17
4.3 Frequency Stability Measurement	18
4.3.1 Limits of Frequency Stability Measurement	18
4.3.2 Test Procedure	18
4.3.3 Test Setup.....	18
4.3.4 Test Results	19
4.4 Occupied Bandwidth Measurement	23
4.4.1 Limits of Occupied Bandwidth Measurement.....	23
4.4.2 Test Procedure	23
4.4.3 Test Setup.....	23
4.4.4 Test Result.....	24
4.5 Emission Mask Measurement.....	28
4.5.1 Limits of Emission Mask Measurement.....	28
4.5.2 Test Setup.....	28
4.5.3 Test Procedures.....	28
4.5.4 Test Results	29
4.6 Conducted Spurious Emissions	39
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	39
4.6.2 Test Setup.....	39
4.6.3 Test Procedure	39
4.6.4 Test Results	40
4.7 Radiated Emission Measurement	44
4.7.1 Limits of Radiated Emission Measurement.....	44
4.7.2 Test Procedure	44
4.7.3 Deviation from Test Standard	44
4.7.4 Test Setup.....	45
4.7.5 Test Results	46
5 Pictures of Test Arrangements.....	53
Appendix – Information of the Testing Laboratories	54

Release Control Record

Issue No.	Description	Date Issued
RFBDKX-WTW-P22120419-6	Original Release	Mar. 31, 2023

1 Certificate of Conformity

Product: Home IOT Gateway

Brand: Level

Test Model: H4

Sample Status: Engineering Sample

Applicant: Level Home Inc.

Test Date: Feb. 02, 2023 ~ Feb. 07, 2023

Standards: FCC Part 90, Subpart I, S

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang, **Date:** Mar. 31, 2023
Vera Huang / Specialist

Approved by : Jeremy Lin, **Date:** Mar. 31, 2023
Jeremy Lin / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 90 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 90.635 (b)	Effective Radiated Power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement of limit.
2.1055 90.213	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 90.209	Occupied Bandwidth	Pass	Meet the requirement of limit.
2.1051 90.691	Emission Masks	Pass	Meet the requirement of limit.
2.1051 90.691	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 90.691	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -26.36dB at 49.40MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3 dB
	30MHz ~ 1000MHz	2.93 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	1.76 dB
	18GHz ~ 40GHz	1.77 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver KEYSIGHT	N9038B	MY60180018	Feb. 18, 2022	Feb. 17, 2023
Spectrum Analyzer KEYSIGHT	N9020B	MY60110513	Dec. 26, 2022	Dec. 25, 2023
BILOG Antenna SCHWARZBECK	VULB9168	9168-1214	Oct. 20, 2022	Oct. 19, 2023
HORN Antenna RF SPIN	DRH18-E	210101A18E	Nov. 13, 2022	Nov. 12, 2023
HORN Antenna SCHWARZBECK	BBHA 9170	9170-1048	Nov. 13, 2022	Nov. 12, 2023
Loop Antenna TESEQ	HLA 6121	45745	Jul. 27, 2022	Jul. 26, 2023
Preamplifier EMCI	EMC330N	980798	Jan. 16, 2023	Jan. 15, 2024
Preamplifier EMCI	EMC 012645	980115	Oct. 01, 2022	Sep. 30, 2023
Preamplifier EMCI	EMC184045SE	980786	Jan. 16, 2023	Jan. 15, 2024
RF signal cable EMCI	EMC104-SM-SM- (9000+3000+1000)	201244+ 201232+ 210103	Jan. 16, 2023	Jan. 15, 2024
RF signal cable EMCI	EMCCFD400-NM- NM- (9000+300+500)	201251+ 201249+ 201248	Jan. 16, 2023	Jan. 15, 2024
RF signal cable EMCI	EMC101G-KM-KM- (5000+3000+2000)	201261+201258+ 201255	Jan. 16, 2023	Jan. 15, 2024
Software BV ADT	ADT_Radiated_V7. 6.15.9.5	NA	NA	NA
Antenna Tower Max-Full	MFA-515BSN	NA	NA	NA
Turn Table Max-Full	MFT-201SS	NA	NA	NA
Turn Table Controller Max-Full	MF-7802BS	MF780208676	NA	NA
Radio Communication Analyzer Anritsu	MT8821C	6201462755	Mar. 03, 2022	Mar. 02, 2023
DC power supply Keysight	U8002A	MY56330015	NA	NA
Digital Multimeter Fluke	87-III	70360742	Jun. 23, 2022	Jun. 22, 2023
Spectrum Analyzer KEYSIGHT	N9030B	MY57140953	Jul. 01, 2022	Jun. 30, 2023
Temperature & Humidity Chamber TERCHY	HRM-120RF	931022	Dec. 27, 2022	Dec. 26, 2023
Radio Communication Analyzer Anritsu	MT8820C	6201010284	Dec. 26, 2022	Dec. 25, 2023

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in WM Chamber 9.

3 General Information

3.1 General Description of EUT

Product	Home IOT Gateway	
Brand	Level	
Test Model	H4	
Sample Status	Engineering Sample	
Power Supply Rating	5 Vdc (From adapter) 3.6 Vdc (From battery)	
Modulation Type	QPSK, 16QAM	
Operating Frequency	LTE Band 26 (Channel Bandwidth 1.4MHz)	814.7MHz ~ 823.3MHz
	LTE Band 26 (Channel Bandwidth 3MHz)	815.5MHz ~ 822.5MHz
	LTE Band 26 (Channel Bandwidth 5MHz)	816.5MHz ~ 821.5MHz
	LTE Band 26 (Channel Bandwidth 10MHz)	819.0MHz
Max. ERP Power	LTE Band 26 (Channel Bandwidth 1.4MHz)	138.357mW(21.41dBm)
	LTE Band 26 (Channel Bandwidth 3MHz)	140.605mW(21.48dBm)
	LTE Band 26 (Channel Bandwidth 5MHz)	142.561mW(21.54dBm)
	LTE Band 26 (Channel Bandwidth 10MHz)	138.038mW(21.40dBm)
Emission Designator	LTE Band 26 (Channel Bandwidth 1.4MHz)	1M09G7D
	LTE Band 26 (Channel Bandwidth 3MHz)	2M70G7D
	LTE Band 26 (Channel Bandwidth 5MHz)	4M49G7D
	LTE Band 26 (Channel Bandwidth 10MHz)	8M95G7D
Antenna Type	PIFA Antenna with 0.05 dBi gain * Detail antenna specification please refer to antenna datasheet or an antenna gain measurement report.	
Accessory Device	Refer to note	
Cable Supplied	Refer to note	

Note:


1. The EUT contains following accessory devices.

Battery	Brand	Grand-Pro
	Model	INR18650
	Power Rating	3.6Vdc, 3350mAh, 12.06Wh
AC Adapter	Brand	TENPO
	Model	S024AMP0500350
	AC Input	100-240Vac, 50/60Hz, 0.6A
	DC Output	5.0Vdc, 3.5A, 17.5W
	DC Output Cable	Non-shielded without cord, 1.0m
	AC Cable	Non-shielded without cord, 1.0m
Lan Cable	Signal Line	Non-shielded without cord, 1.0m

2. For WWAN 16QAM modulation bandwidths ≥ 10 MHz, EUT only supports up to 25RB.

3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Notebook	Lenovo	20J4 MD A003TW	PF-11H9AK	N/A	Provided by Lab
B	LAN to LAN	N/A	N/A	N/A	N/A	Provided by Lab
C	Radio Communication Analyzer	Anritsu	MT8820C	6201010284	N/A	Provided by Lab

Note: Item C acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Micro USB	1	1	N	0	Provided by Lab
2.	RJ45	1	1	N	0	Provided by client
3.	RJ45	1	6	N	0	Provided by Lab

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, and antenna ports. The EUT is designed to be positioned on the X-plane only.

LTE Band 26

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	26697 to 26783	26697 (814.7MHz), 26740 (819.0MHz), 26783 (823.3MHz)	1.4MHz	QPSK / 16QAM	1 Half Full
		26705 to 26775	26705 (815.5MHz), 26740 (819.0MHz), 26775 (822.5MHz)	3MHz	QPSK / 16QAM	1 Half Full
		26715 to 26765	26715 (816.5MHz), 26740 (819.0MHz), 26765 (821.5MHz)	5MHz	QPSK / 16QAM	1 Half Full
		26740	26740 (819.0MHz)	10MHz	QPSK / 16QAM	1 Half Full
-	Modulation Characteristics	26740	26740 (819.0MHz)	10MHz	QPSK / 16QAM	Full
-	Frequency Stability	26697 to 26783	26697 (814.7MHz), 26783 (823.3MHz)	1.4MHz	QPSK	Full
		26705 to 26775	26705 (815.5MHz), 26775 (822.5MHz)	3MHz	QPSK	Full
		26715 to 26765	26715 (816.5MHz), 26765 (821.5MHz)	5MHz	QPSK	Full
		26740	26740 (819.0MHz)	10MHz	QPSK	Full
-	Occupied Bandwidth	26697 to 26783	26697 (814.7MHz), 26740 (819.0MHz), 26783 (823.3MHz)	1.4MHz	QPSK / 16QAM	Full
		26705 to 26775	26705 (815.5MHz), 26740 (819.0MHz), 26775 (822.5MHz)	3MHz	QPSK / 16QAM	Full
		26715 to 26765	26715 (816.5MHz), 26740 (819.0MHz), 26765 (821.5MHz)	5MHz	QPSK / 16QAM	Full
		26740	26740 (819.0MHz)	10MHz	QPSK / 16QAM	Full
-	Emission Masks	26697 to 26783	26697 (814.7MHz), 26783 (823.3MHz)	1.4MHz	QPSK	1 Half Full
		26705 to 26775	26705 (815.5MHz), 26775 (822.5MHz)	3MHz	QPSK	1 Half Full
		26715 to 26765	26715 (816.5MHz), 26765 (821.5MHz)	5MHz	QPSK	1 Half Full
		26740	26740 (819.0MHz)	10MHz	QPSK	1 Half Full

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Conducted Emission	26697 to 26783	26697 (814.7MHz), 26740 (819.0MHz), 26783 (823.3MHz)	1.4MHz	QPSK	1
		26705 to 26775	26705 (815.5MHz), 26740 (819.0MHz), 26775 (822.5MHz)	3MHz	QPSK	1
		26715 to 26765	26715 (816.5MHz), 26740 (819.0MHz), 26765 (821.5MHz)	5MHz	QPSK	1
		26740	26740 (819.0MHz)	10MHz	QPSK	1
-	Radiated Emission Below 1GHz	26740	26740 (819.0MHz)	10MHz	QPSK	1
-	Radiated Emission Above 1GHz	26697 to 26783	26697 (814.7MHz), 26740 (819.0MHz), 26783 (823.3MHz)	1.4MHz	QPSK	1
		26715 to 26765	26715 (816.5MHz), 26740 (819.0MHz), 26765 (821.5MHz)	5MHz	QPSK	1
		26740	26740 (819.0MHz)	10MHz	QPSK	1

Note:

1. For radiated emission below 1GHz, select the worst radiated emission channel (above 1GHz) for final testing.
2. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5MHz & highest channel bandwidth for final test.
3. The output power for QPSK and 16QAM, measured value of QPSK is higher than 16QAM mode. Therefore, only Modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under QPSK and 16QAM modes, the other test items were performed under worse mode according to the maximum output power.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25deg. C, 60%RH	120Vac, 60Hz	Willy Cheng
Modulation characteristics	25deg. C, 60%RH	120Vac, 60Hz	Willy Cheng
Frequency Stability	25deg. C, 60%RH	3.6Vdc	Willy Cheng
Occupied Bandwidth	25deg. C, 60%RH	120Vac, 60Hz	Willy Cheng
Emission Mask	25deg. C, 60%RH	120Vac, 60Hz	Willy Cheng
Conducted Emission	25deg. C, 60%RH	120Vac, 60Hz	Willy Cheng
Radiated Emission	23deg. C, 67%RH	120Vac, 60Hz	Adair Peng

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 90

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

KDB 971168 D02 Misc Rev Approv License Devices v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

The output power shall be according to the specific rule Part 90.635 that “Mobile station are limited to 100 watts e.r.p”.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
The average (rms) power measurement was performed on emulator and power value was measured from power function on emulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is

given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where


ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively
(expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

4.1.3 Test Setup

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

LTE Band 26				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		26740
		Frequency (MHz)		819
10M	QPSK	1	0	23.50
		1	24	23.24
		1	49	23.11
		25	0	23.30
		25	12	23.25
		25	25	23.29
		50	0	22.12
10M	16QAM	1	0	22.22
		1	24	22.26
		1	49	22.35
		25	0	22.48
		25	12	22.41
		25	25	22.27
		50	0	-

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26715	26740	26765
		Frequency (MHz)		816.5	819	821.5
5M	QPSK	1	0	23.36	23.45	23.26
		1	12	23.32	23.36	23.20
		1	24	23.41	23.33	23.00
		12	0	23.56	23.38	23.22
		12	6	23.41	23.41	23.64
		12	13	22.89	23.29	23.31
		25	0	22.09	22.07	22.17
5M	16QAM	1	0	22.33	22.37	22.78
		1	12	22.05	22.06	21.85
		1	24	22.01	22.45	22.66
		12	0	22.50	22.51	22.67
		12	6	22.20	22.56	21.95
		12	13	22.64	22.61	22.86
		25	0	21.53	21.36	21.25

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26705	26740	26775
		Frequency (MHz)		815.5	819	822.5
3M	QPSK	1	0	23.39	23.54	23.47
		1	7	23.20	23.44	23.19
		1	14	23.16	23.47	23.22
		8	0	23.38	23.14	23.22
		8	3	23.43	23.58	23.57
		8	7	22.92	23.39	23.18
		15	0	22.08	22.36	21.99
3M	16QAM	1	0	22.32	22.28	22.79
		1	7	22.14	22.04	22.27
		1	14	22.41	22.14	22.64
		8	0	22.50	22.56	22.77
		8	3	22.41	22.22	22.17
		8	7	22.34	22.28	22.66
		15	0	21.30	21.15	21.08

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26697	26740	26783
		Frequency (MHz)		814.7	819	823.3
1.4M	QPSK	1	0	23.39	23.46	23.27
		1	2	23.33	23.30	23.29
		1	5	23.30	23.24	23.07
		3	0	23.51	23.32	23.33
		3	1	23.34	23.42	23.49
		3	3	23.01	23.20	23.08
		6	0	22.11	22.21	22.20
1.4M	16QAM	1	0	22.47	22.44	22.56
		1	2	22.02	22.10	22.07
		1	5	22.21	22.33	22.55
		3	0	22.58	22.42	22.54
		3	1	22.33	22.36	22.16
		3	3	22.45	22.45	22.66
		6	0	21.31	21.31	21.26

ERP Power (dBm)

LTE Band 26				
BW	MCS Index	RB Size	RB Offset	Mid
		Channel		26740
		Frequency (MHz)		819
10M	QPSK	1	0	21.40
		1	24	21.14
		1	49	21.01
		25	0	21.20
		25	12	21.15
		25	25	21.19
		50	0	20.02
10M	16QAM	1	0	20.12
		1	24	20.16
		1	49	20.25
		25	0	20.38
		25	12	20.31
		25	25	20.17
		50	0	-

*ERP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi) - 2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26715	26740	26765
		Frequency (MHz)		816.5	819	821.5
5M	QPSK	1	0	21.26	21.35	21.16
		1	12	21.22	21.26	21.10
		1	24	21.31	21.23	20.90
		12	0	21.46	21.28	21.12
		12	6	21.31	21.31	21.54
		12	13	20.79	21.19	21.21
		25	0	19.99	19.97	20.07
5M	16QAM	1	0	20.23	20.27	20.68
		1	12	19.95	19.96	19.75
		1	24	19.91	20.35	20.56
		12	0	20.40	20.41	20.57
		12	6	20.10	20.46	19.85
		12	13	20.54	20.51	20.76
		25	0	19.43	19.26	19.15

*ERP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi) - 2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26705	26740	26775
		Frequency (MHz)		815.5	819	822.5
3M	QPSK	1	0	21.29	21.44	21.37
		1	7	21.10	21.34	21.09
		1	14	21.06	21.37	21.12
		8	0	21.28	21.04	21.12
		8	3	21.33	21.48	21.47
		8	7	20.82	21.29	21.08
		15	0	19.98	20.26	19.89
3M	16QAM	1	0	20.22	20.18	20.69
		1	7	20.04	19.94	20.17
		1	14	20.31	20.04	20.54
		8	0	20.40	20.46	20.67
		8	3	20.31	20.12	20.07
		8	7	20.24	20.18	20.56
		15	0	19.20	19.05	18.98

*ERP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi) - 2.15

LTE Band 26						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		26697	26740	26783
		Frequency (MHz)		814.7	819	823.3
1.4M	QPSK	1	0	21.29	21.36	21.17
		1	2	21.23	21.20	21.19
		1	5	21.20	21.14	20.97
		3	0	21.41	21.22	21.23
		3	1	21.24	21.32	21.39
		3	3	20.91	21.10	20.98
		6	0	20.01	20.11	20.10
1.4M	16QAM	1	0	20.37	20.34	20.46
		1	2	19.92	20.00	19.97
		1	5	20.11	20.23	20.45
		3	0	20.48	20.32	20.44
		3	1	20.23	20.26	20.06
		3	3	20.35	20.35	20.56
		6	0	19.21	19.21	19.16

*ERP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi) - 2.15

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A

4.2.2 Test Procedure


Connect the EUT to Communication Simulator via the antenna connector, The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.3 Test Setup



4.2.4 Test Results

LTE Band 26



4.3 Frequency Stability Measurement

4.3.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

4.3.3 Test Setup



4.3.4 Test Results

Frequency Error vs. Voltage

Voltage (Vdc)	LTE Band 26			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.06	814.7000030	0.004	823.3000030	0.004
3.60	814.7000030	0.004	823.3000040	0.005
4.14	814.6999980	-0.002	823.2999970	-0.004

Note: The applicant defined the normal working voltage is from 3.06Vdc to 4.14Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	814.6999990	-0.001	823.3000010	0.001
-20	814.7000040	0.005	823.2999970	-0.004
-10	814.6999980	-0.002	823.3000010	0.001
0	814.7000010	0.001	823.2999960	-0.005
10	814.7000040	0.005	823.3000030	0.004
20	814.6999980	-0.002	823.3000040	0.005
30	814.6999990	-0.001	823.2999960	-0.005
40	814.6999960	-0.005	823.2999990	-0.001
50	814.6999960	-0.005	823.2999990	-0.001

Frequency Error vs. Voltage

Voltage (Vdc)	LTE Band 26			
	Channel Bandwidth: 3MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.06	815.5000030	0.004	822.5000040	0.005
3.60	815.4999960	-0.005	822.4999980	-0.002
4.14	815.5000040	0.005	822.5000040	0.005

Note: The applicant defined the normal working voltage is from 3.06Vdc to 4.14Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26			
	Channel Bandwidth: 3MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	815.4999960	-0.005	822.4999990	-0.001
-20	815.4999990	-0.001	822.5000010	0.001
-10	815.4999960	-0.005	822.4999990	-0.001
0	815.5000030	0.004	822.4999980	-0.002
10	815.4999970	-0.004	822.4999960	-0.005
20	815.4999970	-0.004	822.4999960	-0.005
30	815.5000010	0.001	822.5000040	0.005
40	815.5000030	0.004	822.5000030	0.004
50	815.4999980	-0.002	822.4999980	-0.002

Frequency Error vs. Voltage

Voltage (Vdc)	LTE Band 26			
	Channel Bandwidth: 5MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
3.06	816.5000030	0.004	821.4999960	-0.005
3.60	816.5000010	0.001	821.5000030	0.004
4.14	816.5000030	0.004	821.5000040	0.005

Note: The applicant defined the normal working voltage is from 3.06Vdc to 4.14Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26			
	Channel Bandwidth: 5MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-30	816.5000020	0.002	821.5000020	0.002
-20	816.4999980	-0.002	821.4999970	-0.004
-10	816.4999990	-0.001	821.4999970	-0.004
0	816.4999970	-0.004	821.4999980	-0.002
10	816.4999980	-0.002	821.4999990	-0.001
20	816.5000040	0.005	821.4999970	-0.004
30	816.5000040	0.005	821.5000020	0.002
40	816.5000030	0.004	821.4999970	-0.004
50	816.4999990	-0.001	821.4999990	-0.001

Frequency Error vs. Voltage

Voltage (Vdc)	LTE Band 26	
	Channel Bandwidth: 10 MHz	
	Frequency (MHz)	Frequency Error (ppm)
3.06	818.9999980	-0.002
3.60	819.0000010	0.001
4.14	818.9999980	-0.002

Note: The applicant defined the normal working voltage is from 3.06Vdc to 4.14Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 26	
	Channel Bandwidth: 10 MHz	
	Frequency (MHz)	Frequency Error (ppm)
-30	818.9999990	-0.001
-20	819.0000030	0.004
-10	819.0000010	0.001
0	818.9999990	-0.001
10	818.9999960	-0.005
20	818.9999970	-0.004
30	819.0000030	0.004
40	818.9999990	-0.001
50	819.0000010	0.001

4.4 Occupied Bandwidth Measurement

4.4.1 Limits of Occupied Bandwidth Measurement

The occupied bandwidth (OBW), that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 % of the total mean power radiated by a given emission.


4.4.2 Test Procedure

For the 26dBc bandwidth measurement method, please refer to section 5.4.3 of ANSI C63.26.

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- Set spectrum analyzer detection mode to peak, and the trace mode to max hold.
- Determine the following reference values: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- Determine the “-X dB amplitude” as equal to (Reference Value - X). Alternatively, this calculation can be performed on the spectrum analyzer using the delta-marker measurement function.
- Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB amplitude” determined in step f). If a marker is below this “-X dB amplitude” value it should be as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- The OBW shall be reported by providing plot(s) of the measuring instrument display, to include markers depicting the relevant frequency and amplitude information (e.g., marker table). The frequency and amplitude axis and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

For the occupied bandwidth measurement method, please refer to section 5.4.4 of ANSI C63.26.

4.4.3 Test Setup




4.4.4 Test Result

LTE Band 26 (Channel Bandwidth 1.4MHz)

Test Condition	Channel	Frequency (MHz)	Occupied bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	26697	814.7	1.0888	1.252
QPSK	26740	819	1.0920	1.258
QPSK	26783	823.3	1.0901	1.251
16QAM	26697	814.7	1.0880	1.245
16QAM	26740	819	1.0873	1.239
16QAM	26783	823.3	1.0878	1.249


NOTE: For the test plots please refer to the below pages.



LTE Band 26 (Channel Bandwidth 3MHz)

Test Condition	Channel	Frequency (MHz)	Occupied bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	26705	815.5	2.6982	2.905
QPSK	26740	819	2.6965	2.916
QPSK	26775	822.5	2.6945	2.910
16QAM	26705	815.5	2.6958	2.907
16QAM	26740	819	2.6945	2.918
16QAM	26775	822.5	2.6953	2.915


NOTE: For the test plots please refer to the below pages.



LTE Band 26 (Channel Bandwidth 5MHz)

Test Condition	Channel	Frequency (MHz)	Occupied bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	26715	816.5	4.4942	4.828
QPSK	26740	819	4.4915	4.812
QPSK	26765	821.5	4.4933	4.832
16QAM	26715	816.5	4.4910	4.804
16QAM	26740	819	4.4900	4.826
16QAM	26765	821.5	4.4876	4.807


NOTE: For the test plots please refer to the below pages.



LTE Band 26 (Channel Bandwidth 10MHz)

Test Condition	Channel	Frequency (MHz)	Occupied bandwidth (MHz)	26 dB Bandwidth (MHz)
QPSK	26740	819	8.9534	9.499
16QAM	26740	819	4.5720	5.076

NOTE: For the test plots please refer to the below pages.



4.5 Emission Mask Measurement


4.5.1 Limits of Emission Mask Measurement

According to FCC part 90.691 shall be tested the emission mask. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

For § 90.691(a), RBW=300 Hz for offset less than 37.5 kHz from channel edge and RBW=100 kHz for offsets greater than 37.5 kHz is allowed, tested in accordance with FCC KDB 971168 D02 section VIII.

4.5.2 Test Setup






4.5.3 Test Procedures

- The measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer. The measurement method refers to FCC part 90.691(a) and FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01 section VIII. c).
- Set the detector to power averaging (rms) detector.
- Record the test plot.


4.5.4 Test Results

LTE Band 26 (Channel Bandwidth 1.4MHz)







1RB#MAX (814.7MHz)




1RB#MAX (819MHz)

1RB#MAX (823.3MHz)



1RB#0 (814.7MHz)





1RB#0 (819MHz)


1RB#0 (823.3MHz)

LTE Band 26 (Channel Bandwidth 3MHz)







1RB#MAX (815.5MHz)




1RB#MAX (819MHz)

1RB#MAX (822.5MHz)




1RB#0 (815.5MHz)





1RB#0 (819MHz)


1RB#0 (822.5MHz)

LTE Band 26 (Channel Bandwidth 5MHz)







1RB#MAX (816.5MHz)




1RB#MAX (819MHz)

1RB#MAX (821.5MHz)




1RB#0 (816.5MHz)



1RB#0 (819MHz)


1RB#0 (821.5MHz)

LTE Band 26 (Channel Bandwidth 10MHz)



FULL (819MHz)

1RB#MAX (819MHz)




1RB#0 (819MHz)

4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm .

4.6.2 Test Setup



4.6.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9kHz to 9GHz. 20dB attenuation pad is connected with spectrum. Detector = average, RBW=1MHz and VBW=3MHz for 9kHz to 9GHz are used for LTE band conducted emission measurement.

4.6.4 Test Results

LTE Band 26 (Channel Bandwidth 1.4MHz)



CH 26697 (814.7MHz)




CH 26740 (819MHz)




CH 26783 (823.3MHz)

*The 9kHz signal over the limit is from Spectrum.

LTE Band 26 (Channel Bandwidth 3MHz)



CH 26705 (815.5MHz)





CH 26740 (819MHz)





CH 26775 (822.5MHz)

*The 9kHz signal over the limit is from Spectrum.



LTE Band 26 (Channel Bandwidth 5MHz)



CH 26715 (816.5MHz)




CH 26740 (819MHz)



CH 26765 (821.5MHz)

*The 9kHz signal over the limit is from Spectrum.

LTE Band 26 (Channel Bandwidth 10MHz)



*The 9kHz signal over the limit is from Spectrum.

4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm .

4.7.2 Test Procedure

- a. In the semi-anechoic chamber, EUT placed on the 0.8m(below or equal 1GHz) and/or 1.5m(above 1GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following C63.26 section 5.5 and 5.2.7
 - $\text{EIRP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
 - $\text{ERP (dBm)} = E (\text{dB}\mu\text{V/m}) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz. Set detector = average.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.7.3 Deviation from Test Standard


No deviation.

4.7.4 Test Setup

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

Below 1GHz


LTE Band 26, Channel Bandwidth 10MHz

Mode	TX channel 26740 (819.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	-52.61	-13.00	-39.61	1.00 H	333	55.30	-107.91
2	48.43	-54.01	-13.00	-41.01	2.00 H	42	52.44	-106.45
3	70.74	-49.89	-13.00	-36.89	1.00 H	21	58.75	-108.64
4	84.32	-50.57	-13.00	-37.57	2.00 H	32	61.19	-111.76
5	523.73	-60.32	-13.00	-47.32	1.50 H	19	39.19	-99.51
6	647.89	-58.67	-13.00	-45.67	1.00 H	13	38.28	-96.95

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. $Margin\ value = ERP - Limit\ value$.
4. The other ERP levels were very low against the limit.




Mode	TX channel 26740 (819.0MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	49.40	-39.36	-13.00	-26.36	1.50 V	167	67.10	-106.46
2	68.80	-51.43	-13.00	-38.43	1.50 V	154	56.97	-108.40
3	199.75	-57.97	-13.00	-44.97	1.00 V	270	51.08	-109.05
4	353.98	-65.40	-13.00	-52.40	1.00 V	199	37.99	-103.39
5	502.39	-60.28	-13.00	-47.28	2.00 V	355	39.67	-99.95
6	574.17	-59.84	-13.00	-46.84	1.00 V	76	38.79	-98.63

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.



Above 1GHz

LTE Band 26, Channel Bandwidth 1.4MHz

Mode	TX channel 26697 (814.7MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1629.40	-52.57	-13.00	-39.57	1.60 H	192	49.81	-102.38
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1629.40	-52.27	-13.00	-39.27	2.01 V	325	50.11	-102.38

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

Mode	TX channel 26740 (819.0MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-52.45	-13.00	-39.45	1.62 H	193	49.94	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-51.70	-13.00	-38.70	2.00 V	324	50.69	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

Mode	TX channel 26783 (823.3MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1646.60	-52.34	-13.00	-39.34	1.61 H	194	50.05	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1646.60	-51.74	-13.00	-38.74	2.03 V	323	50.65	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

LTE Band 26, Channel Bandwidth 5MHz

Mode	TX channel 26715 (816.5MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1633.00	-52.20	-13.00	-39.20	1.63 H	191	50.19	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1633.00	-51.47	-13.00	-38.47	2.05 V	322	50.92	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

Mode	TX channel 26740 (819.0MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-52.17	-13.00	-39.17	1.60 H	193	50.22	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-51.26	-13.00	-38.26	2.04 V	329	51.13	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

Mode	TX channel 26765 (821.5MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1643.00	-52.12	-13.00	-39.12	1.56 H	196	50.27	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1643.00	-51.66	-13.00	-38.66	1.98 V	324	50.73	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$.
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

LTE Band 26, Channel Bandwidth 10MHz

Mode	TX channel 26740 (819.0MHz)	Frequency Range	1GHz ~ 9GHz
Environmental Conditions	23deg. C, 67%RH	Input Power	120Vac, 60Hz
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-52.17	-13.00	-39.17	1.57 H	189	50.22	-102.39
Antenna Polarity & Test Distance : Vertical at 3m								
No	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1638.00	-50.97	-13.00	-37.97	1.96 V	326	51.42	-102.39

Remarks:

1. $ERP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m).$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8 - 2.15$
3. Margin value = ERP – Limit value.
4. The other ERP levels were very low against the limit.

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---