



MPE/RF EXPOSURE REPORT

FCC CFR 47 Part 1.1310

Report No.: MIKO114-U10 Rev A FCC MPE

Company: Mikrotiks SIA

Evaluation of: RBD25G-5HPacQD2HPnD-US

MPE/RF EXPOSURE REPORT

FROM



Evaluation of: Mikrotikls SIA RBD25G-5HPacQD2HPnD-US

To: FCC CFR 47 Part 1.1310

Report Serial No.: MIKO114-U10 Rev A FCC MPE

This report supersedes: NONE

Applicant: Mikrotikls SIA
Brivibas gatve 214i
Riga, LV-1039
Latvia

Product Function: 802.11a/b/g/n/ac WLAN router

Issue Date: 25th May 2021

This Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

Calculations for RF Exposure Evaluation for RBD25G-5HPacQD2HPnD-US (Audience)

$$\text{Power Density} = P_d (\text{W/m}^2) = \text{EIRP} / (4 * \pi * d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (W)

G = Antenna numeric gain (numeric)

d = Separation distance (m)

$$\text{Numeric Gain} = 10 ^ { (G (\text{dBi}) / 10)}$$

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

The calculations in the table below use the highest conducted power values together with the antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

The RBD25G-5HPacQD2HPnD-US contains 2 Wi-Fi radios;

1) 2x2 covering the frequency ranges 2.4 GHz & 5150 – 5350 MHz; 2) 4x4 covering the frequency range 5470 – 5850 MHz.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
5150.0 - 5250.0	2.50	1.78	27.53	566.24	0.200	1.00	8.951
2400.0 - 2483.5	3.50	2.24	19.50	89.13	0.040	1.00	3.985
5725.0 - 5850.0	4.50	2.82	26.57	453.94	0.255	1.00	10.090
5250.0 – 5350.0	3.50	2.24	20.60	114.82	0.051	1.00	4.523
5470.0 – 5725.0	4.50	2.82	21.72	148.59	0.083	1.00	5.773

Assessment of worst case exposure conditions with the 2 radios transmitting simultaneously.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)
5150.0 - 5250.0	2.50	1.78	27.53	566.24	0.200	1.00
5725.0 - 5850.0	4.50	2.82	26.57	453.94	0.255	1.00

Evaluation for compliance of simultaneous transmission is determined by summation of the ratios of Pd Calc/Pd Limit < 1.

Pd – Power Density

$$S_{\text{WiFi 2x2}} + S_{\text{WiFi 4x4}} = 0.200 + 0.255 = 0.455$$

Minimum Safe Distance = 0.20 m

Note: for mobile or fixed location transmitters the minimum separation distance is 0.20m, even if calculations indicate the MPE distance to be less.

Specification - RF Exposure Evaluation Limits

The Limit is defined in Table 1 of FCC §1.1310.

Specification - Maximum Permissible Exposure Limits

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com