

Test Report

TEST PROCEDURES AND TEST SITE DESCRIPTION

DATE: January 10, 2006

FCC ID: AMWUT607A

UNI-NO.: UT607ZH

MODEL: VHF150

Description: VHF HANDHELD MARINE RADIO

MEASUREMENT ITEMS	Section No.
1. DC Voltage & Current into Final Device	2.1033(C)(8)
2. RF Output Power	2.1046
3. Reserved	
4. Reserved	
5. Reserved	
6. Occupied Bandwidth	2.1049(c)(1) & 80.211
7. Spurious & Harmonic Emission at Antenna Terminal	2.1051
8. Field Strength of Spurious & Harmonic Radiation	2.1053
9. Frequency Stability (Temperature)	2.1055 & 80.209
10. Frequency Stability (Voltage)	2.1055 & 80.209
11. Receiver radiated spurious emissions	80.217(b)

NOTE: List of measurement equipment and test site description are included in this EXHIBIT.

1. DC Voltage & Current into Final Device 2.1033(C)(8)

To measure the DC Voltage and Current into Final Amplifying Device, the measuring equipment was connected to the actual P.C.Board of the transmitter.

FCC limits: Not specified

Test Results: Refer to test data

2. RF Output Power 2.1046

The unit was tuned-up in accordance with the alignment procedure stated in the EXHIBIT-6, and was loaded into a 50-ohm resistive termination. The unit was powered through its normally supplied power cable by a DC power supply. Power supply voltage was set to nominal voltage at the power supply terminals with the transmitter off.

The unit was operated for three consecutive test cycles of 15 minutes standby and 5 minutes in transmitting. At the end of the third 5 minutes period, the RF output power is measured. During the test, no components of the emission spectrum exceed the limit specified in the applicable rule part for occupied bandwidth or emission limitations.

FCC limits: Not specified

Test Results: Refer to test data

3. Reserved

4. Reserved

5. Reserved

6. Occupied Bandwidth 2.1049(c)(1) & 80.211

The spectrum of the modulated carrier was monitored by a panoramic method capable of 60dB amplitude range. The unit was modulated with a 2500 Hz audio signal at an input level 16dB above that required for 50% of maximum system deviation.

In case the 100Hz of CTCSS tone or 100 bps of digital coded data modulation is indicated for this transmitter, a representative measurement data for this operation is also presented.

Since the total deviation of the unit is designed as 4.7 kHz Div.,

the deviation of 2500Hz audio signal was set to 3.7 kHz Div., as the maximum deviation of tone or digital coded signal was continuously set to 1.0 kHz Div.

At first, tone or digital signal was disabled and set the 2500 Hz audio signal to 1.85 kHz deviation (= 50% of 3.7 kHz deviation). Then, the input level of 2500Hz audio signal was increased by 16dB. In this condition, the tone or digital coded signal was then enabled and imposed with 2500Hz audio signal.

FCC limits: a) -25dB (50 - 100% of assigned frequency)
b) -35dB (100 - 250% of assigned frequency)
c) $43 + 10\log_{10}$ (RF output power in Watts) dB
or 80dB, whichever is lesser attenuation
for more than 250% of assigned frequency

Test Results: Refer to test data

7. Spurious & Harmonic Emission at Antenna Terminal 2.1051

Spurious radiation is the radio frequency voltage or power generated within the equipment and appearing at the equipment's output terminals when properly loaded with its characteristic non-radiating load.

The unit was modulated with a 2500 Hz tone at an input level 16dB greater than that required 50% modulation. The spectrum was scanned from the lowest frequency generated in the equipment to the tenth harmonic of the carrier.

FCC limits: $43 + 10\log_{10}$ (RF output power in Watts) dB

Test Results: Refer to test data

8. Field Strength of Spurious & Harmonic Radiation 2.1053

Measurement Procedure & Test Site Description

Field strength measurements of radiated spurious emissions were made on a 3-meter range maintained by Uniden Corporation in Japan. Complete description and measurement data of this test site have been placed on file with the Commission. The equipment was scanned for radiated emissions in a scheduled enclosure prior to open field-testing.

For each spurious or harmonic frequency, the antenna was raised and lowered to obtain a maximum reading on the Spectrum Analyzer with antenna horizontally polarized. Then the turntable, on which the equipment under test was placed, was rotated a minimum of 360

degree to further increase the reading on the Spectrum Analyzer.
This procedure was repeated with the antenna vertically polarized.

FCC limits: $43 + 10\log_{10}$ (RF output power in Watts) dB

Test Results: Refer to test data

9. Frequency Stability (Temperature) 2.1055 & 80.209

Frequency measurement was performed at the extremes of throughout the range -20°C to $+50^{\circ}\text{C}$ and at intervals of not more than 10 degrees C throughout the range. A period of time sufficient to stabilize all of the components in the equipment was allowed prior to frequency measurement.

The frequency of the unit was measured by extracting a sample of the carrier and measuring its center frequency by equipment having a degree accuracy at least 10 times that of the minimum to be measured.

FCC limits: $\pm 0.001\%$

Test Results: Refer to test data

10. Frequency Stability (Voltage) 2.1055 & 80.209

Frequency measurement was performed at the extremes of throughout the range 85% and 115% of the nominal voltage. Extracting a sample of the carrier and measuring its center frequency by equipment having degree accuracy at least 10 times that of the minimum to be measured measured the frequency of the unit.

FCC limits: $\pm 0.001\%$

Test Results: Refer to test data

11. Receiver radiated spurious emissions

80.217(b)

Regarding the electromagnetic field strength at a distance of over sea water of one nautical mile, the value of field strength in the range of visible distance, which will be emitted from 1/2 dipole antenna, results from the combination of the direct field component (free space field) and the ground reflected field component.

Therefore, assuming that the ground is a flat perfect conductor, the maximum value of field strength in cases of varying the antenna high at the test point should be extrapolated to indicate two as large as the value in free space field.

At the actual test site in the range of 10 feet of distance, the following formula can be considered to make up on an average, though it may include a little bit error. And, this fact is surely confirmed at our test site.

Accordingly, the value of field strength measured at the distance of 10 feet (3-meters) away shall be formulated as follows;

$$E_3 = 2 \times E_0 = 2 \times \sqrt{P} \times 1/r \text{ (V/m)} \text{ ----- (1)}$$

where: E_3 : Field strength at the distance of 3 m (V/m)
 E_0 : Field strength in free space field (V/m)
 P : Power into 1/2 dipole antenna (Watts)
 r : Distance from test point to dipole antenna (m)

Also, in the surface over seawater, since it can be supposed that the sea surface rather keeps better conductor condition, the above (1).

Therefore, the value of field strength at the distance of one nautical mile (1852 m) E_{1852} shall be calculated as below;

$$\begin{aligned} E_{1852} &= E_3 \times 14 \times \sqrt{P} / 1852 \\ &= E_3 \times 3 / 1852 \\ &= E_3 / 620 \text{ ----- (2)} \end{aligned}$$

Test Results: Refer to test data

TEST DATA

MEASUREMENT ITEMS	Section No.
1. DC Voltage & Current into Final Device	2.1033(C)(8)
2. RF Output Power	2.1046
3. Reserved	
4. Reserved	
5. Reserved	
6. Occupied Bandwidth	2.1049(c)(1) & 80.211
7. Spurious & Harmonic Emission at Antenna Terminal	2.1051
8. Field Strength of Spurious & Harmonic Radiation	2.1053
9. Frequency Stability (Temperature)	2.1055 & 80.209
10. Frequency Stability (Voltage)	2.1055 & 80.209
11. Receiver radiated spurious emissions	80.217(b)

1. DC Voltage & Current into Final Device

5W POWER MODE		TX FINAL FET	
MEASURED FREQUENCY (MHz)	OUTPUT POWER (Watts)	DRAIN VOLTAGE (V)	DRAIN CURRENT(A)
156.05	5.09	7.5	1.54
156.8	5.04	7.5	1.53
157.425	4.98	7.5	1.51

2.5W POWER MODE		TX FINAL FET	
MEASURED FREQUENCY (MHz)	OUTPUT POWER (Watts)	DRAIN VOLTAGE (V)	DRAIN CURRENT(A)
156.05	2.58	7.5	1.15
156.8	2.50	7.5	1.13
157.425	2.48	7.5	1.12

1W POWER MODE		TX FINAL FET	
MEASURED FREQUENCY (MHz)	OUTPUT POWER (Watts)	DRAIN VOLTAGE (V)	DRAIN CURRENT(A)
156.05	1.03	7.5	0.80
156.8	1.00	7.5	0.79
157.425	0.97	7.5	0.78

2. RF Output Power

2.1046

1)Li-ion BATTERY

MEASURED FREQUENCY (MHz)	5W POWER MODE (Watts)	2.5W POWER MODE (Watts)	1W POWER MODE (Watts)
156.05	5.85	2.76	1.13
156.8	5.68	2.67	1.10
157.425	5.73	2.67	1.07

*Li-ion Battery Voltage: 7.5V (Approx. 10 minutes after turn on the power.)

1)ALKALINE BATTERY


MEASURED FREQUENCY (MHz)	2.5W POWER MODE (Watts)	1W POWER MODE (Watts)
156.05	1.72	0.68
156.8	1.61	0.65
157.425	1.62	0.66

*Alkaline Battery Voltage: 6.0V (Within 1 minute after turn on the power.)


6. OCCUPIED BANDWIDTH

2.1049(c)(1) & 80.211


Freq.:157.425MHz, Power:5W




Freq.:157.425MHz, Power:2.5W




Freq.:157.425MHz, Power:1W




Freq.:156.800MHz, Power:5W




Freq.:156.800MHz, Power:2.5W




Freq.:156.800MHz, Power:1W




Freq.:156.050MHz, Power:5W



Freq.:156.050MHz, Power:2.5W



Freq.:156.050MHz, Power:1W



7. SPURIOUS & HARMONICS EMISSION AT ANTENNA TERMINAL

2.1051

1) TX

Full Power : 5W

Harmonics of Carrier	156.05MHz [dBc]	156.8MHz [dBc]	157.425MHz [dBc]
1	-	-	-
2	88.6	89.2	89.4
3	77.1	77.6	77.7
4	more than 90	more than 90	more than 90
5	85.4	85.0	84.2
6	78.6	78.2	78.1
7	85.5	87.4	89.5
8	more than 90	more than 90	more than 90
9	more than 90	more than 90	more than 90
10	more than 90	more than 90	more than 90

Reduced Power : 2.5W

Harmonics of Carrier	156.05MHz [dBc]	156.8MHz [dBc]	157.425MHz [dBc]
1	-	-	-
2	more than 90	more than 90	more than 90
3	80.3	80.4	80.9
4	more than 90	89.6	89.9
5	more than 90	more than 90	more than 90
6	85.2	84.7	85.2
7	more than 90	more than 90	more than 90
8	more than 90	more than 90	more than 90
9	more than 90	more than 90	more than 90
10	more than 90	more than 90	more than 90

Reduced Power : 1W

Harmonics of Carrier	156.05MHz [dBc]	156.8MHz [dBc]	157.425MHz [dBc]
1	-	-	-
2	more than 90	more than 90	more than 90
3	81.9	81.7	81.7
4	88.7	88.5	88.3
5	more than 90	more than 90	more than 90
6	87.6	88.1	88.1
7	more than 90	more than 90	more than 90
8	more than 90	more than 90	more than 90
9	more than 90	more than 90	more than 90
10	more than 90	more than 90	more than 90

2) RX

CONDUCTED	156.05-21.4MHz [dBm]	156.8-21.4MHz [dBm]	157.425-21.4MHz [dBm]
1	-77.0	-76.5	-75.9
2	less than -90	less than -90	-85.9
3	less than -90	less than -90	less than -90
4	less than -90	less than -90	less than -90
5	less than -90	less than -90	less than -90
6	less than -90	less than -90	less than -90
7	less than -90	less than -90	less than -90
8	less than -90	less than -90	less than -90
9	less than -90	less than -90	less than -90
10	less than -90	less than -90	less than -90

8. FIELD STRENGTH OF SPURIOUS & HARMONICS RADIATION

*Li-ion BATTERY

1) Frequency at which tuned: 156.050 MHz

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
FULL POWER: 5 WATTS					
312.100	V	V	66.5	50	16.5
468.150	V	V	69.0	50	19.0
624.200	-	-	-	50	>20
780.250	-	-	-	50	>20
936.300	-	-	-	50	>20
1092.350	-	-	-	50	>20
1248.400	-	-	-	50	>20
1404.450	-	-	-	50	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 2.5 WATT					
312.100	H	V	68.3	43	25.3
468.150	H	V	73.0	43	30.0
624.200	-	-	-	43	>20
780.250	-	-	-	43	>20
936.300	-	-	-	43	>20
1092.350	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 1 WATT					
312.100	H	V	74.3	43	31.3
468.150	-	-	-	43	>20
624.200	-	-	-	43	>20
780.250	-	-	-	43	>20
936.300	-	-	-	43	>20
1092.350	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20

2) Frequency at which tuned: 156.700 MHz

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
FULL POWER: 5 WATTS					
313.400	V	V	70.6	50	20.6
470.100	V	V	69.5	50	19.5
626.800	-	-	-	50	>20
783.500	-	-	-	50	>20
940.200	-	-	-	50	>20
1096.900	-	-	-	50	>20
1248.400	-	-	-	50	>20
1404.450	-	-	-	50	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 2.5 WATT					
313.400	H	V	68.8	43	25.8
470.100	V	V	72.2	43	29.2
626.800	-	-	-	43	>20
783.500	-	-	-	43	>20
940.200	-	-	-	43	>20
1096.900	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 1 WATT					
313.400	H	V	70.7	43	27.7
470.100	-	-	-	43	>20
626.800	-	-	-	43	>20
783.500	-	-	-	43	>20
940.200	-	-	-	43	>20
1096.900	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20

3) Frequency at which tuned: 157.425 MHz

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
FULL POWER: 5 WATTS					
314.850	H	V	67.5	50	17.5
472.275	V	V	70.0	50	20.0
629.700	-	-	-	50	>20
787.125	-	-	-	50	>20
944.550	-	-	-	50	>20
1101.975	-	-	-	50	>20
1248.400	-	-	-	50	>20
1404.450	-	-	-	50	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 2.5 WATT					
314.850	H	V	69.6	43	26.6
472.275	H	V	73.3	43	30.3
629.700	-	-	-	43	>20
787.125	-	-	-	43	>20
944.550	-	-	-	43	>20
1101.975	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20

EMISSIONS (MHz)	DUT, PLACED V/H	ANT, POLARITY V/H	ATTENUATION (dBc)	FCC LIMIT (dBc)	MARGIN (dB)
REDUCED POWER: 1 WATT					
314.850	H	V	72.4	43	29.4
472.275	-	-	-	43	>20
629.700	-	-	-	43	>20
787.125	-	-	-	43	>20
944.550	-	-	-	43	>20
1101.975	-	-	-	43	>20
1248.400	-	-	-	43	>20
1404.450	-	-	-	43	>20


Note: All spurious emissions note reported were attenuated by at least 20 dB below the FCC limit.

9. FREQUENCY STABILITY (TEMPERATURE RANGE)

2.1055 & 80.209

CENTER FREQUENCY : 156.800 MHz

TEMPERATURE	FREQ. MHz	TOLERANCE		FCC LIMIT	
		Hz	%	+%	-%
-20	156.80092	919	0.0005861	0.001	-0.001
-10	156.80102	1024	0.0006531	0.001	-0.001
0	156.80097	965	0.0006154	0.001	-0.001
10	156.80085	851	0.0005427	0.001	-0.001
20	156.80039	387	0.0002468	0.001	-0.001
30	156.79984	-158	-0.0001008	0.001	-0.001
40	156.79964	-356	-0.0002270	0.001	-0.001
50	156.79942	-578	-0.0003686	0.001	-0.001



10. FREQUENCY STABILITY (VOLTAGE RANGE)


2.1055 & 80.209

CENTER FREQUENCY 156.700 MHz

VOLTAGE	FREQ.	TOLERANCE		FCC LIMIT	
		Hz	%	+ %	- %
(V)	MHz				
3.3		-390	-0.0002489	0.001	-0.001
3.5		-208	-0.0001327	0.001	-0.001
4.0		64	0.0000408	0.001	-0.001
4.5		57	0.0000364	0.001	-0.001
5.0		55	0.0000351	0.001	-0.001
5.5		56	0.0000357	0.001	-0.001
5.6		66	0.0000421	0.001	-0.001
6.0		58	0.0000370	0.001	-0.001
6.5		67	0.0000428	0.001	-0.001
7.0		75	0.0000479	0.001	-0.001
7.5		85	0.0000542	0.001	-0.001
8.0		104	0.0000664	0.001	-0.001
8.5		126	0.0000804	0.001	-0.001

*Battery end point(Li-ion Battery): 5.6V

*Battery end point(Alkaline Battery): 3.3V



11. FIELD STRENGTH OF SPURIOUS & HARMONICS RADIATIO

80.217(b)

EMISSIONS (MHz)	ATTENUATION (dB)	FCC LIMIT (dB)	MARGIN (dB)
1) Frequency at which tuned: 156.050 MHz No emissions exceed 20dB below the FCC limits.			
2) Frequency at which tuned: 156.700 MHz No emissions exceed 20dB below the FCC limits.			
3) Frequency at which tuned: 157.425 MHz No emissions exceed 20dB below the FCC limits.			

Note: All spurious emissions note reported were attenuated
by at least 20 dB below the FCC limit.

LIST OF MEASUREMENT EQUIPMENTS

ENG-NO	TEST EQUIPMENT	TYPE	MFR	SERIAL NO.	Last Calibrtation
1287	AMPLIFIER	AFS30010040020	MITEQ	138315	N/A
2022	MICROWAVE PREAMPLIFIER	8349B	ADVANTEST	3205A04450	N/A
1294	ANTENNA(BILOG)	CBL6112A	CHASE	2350	N/A
1602	ANTENNA(DI POLE)	3120-B1	EMCO	0075	11-Jul-03
1603	ANTENNA(DI POLE)	3120-B2	EMCO	0076	11-Jul-03
1604	ANTENNA(DI POLE)	3120-B3	EMCO	0076	11-Jul-03
1560	ANTENNA(HORN) (18GHz)	3115	EMCO	2167	N/A
N/A	ANTENNA(HORN) (24GHz)	94287.24	NIPPON KOSYUHA	60.1	N/A
1388	LISN	KNW407	KYOURITSU	8-833-21	N/A
0682	POWER SUPPLY	AA300	TAKASAGO	31783013	N/A
0857	SPECTRUM ANALYZER (13GHz)	E7400A	AGILENT	US40240145	20-Jun-05
0205	SPECTRUM ANALYZER (8.4GHz)	R3265	ADVANTEST	25060158	N/A
1008	SPECTRUM ANALYZER (40GHz)	8564E	ADVANTEST	3425A00182	18-Apr-05