

RF Exposure evaluation

Exposure category: General population/uncontrolled environment EUT

Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06 FCC

Part 2 §2.1091

FCC ID: 2AFF6-AOCIDL1

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB 447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a givendistance

Equation from page 18 of OET Bulletin 65, Edition97-01

$$S=PG/4\pi R^2$$

Where: S=powerdensity

P=power input toantenna

G=power gain of the antenna in the direction of interest relative to an isotropicradiator

R=distance to the center of radiation of theantenna

4. Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, atleast20 cm from any body part of the user or nearby persons; from the maximum EUT

RFoutputpower, the minimum separation distance, r =20cm, as well as the gain of the used BT antenna is 1.7Bi, the RF power density can beobtained.

EDR								
Freq.(MHz)	Output Power (dBm)	TargetpowerW/tolerance (dBm)	Max tuneuppower tolerance (dBm)	Outputpower toantenna	Ant Gain (dBi)	PowerDensity atR=20cm (mW/cm2)	Limit(mW/cm2)	Result
GFSK								
2402	-2.237	-2±1.0	-1	0.794	1.7	0.00023	1	Pass
2441	-3.567	-3±1.0	-2	0.631	1.7	0.00019	1	Pass
2480	-4.626	-4±1.0	-3	0.501	1.7	0.00015	1	Pass
π/4DQPSK								
2402	0.056	1±1.0	2	1.585	1.7	0.00047	1	Pass
2441	-1.302	-1±1.0	0	1.000	1.7	0.00029	1	Pass
2480	-2.340	-2±1.0	-1	0.794	1.7	0.00023	1	Pass
8DPSK								
2402	0.564	1±1.0	2	1.585	1.7	0.00047	1	Pass
2441	-0.778	0±1.0	1	1.259	1.7	0.00037	1	Pass
2480	-1.859	-1±1.0	0	1.000	1.7	0.00029	1	Pass

BLE								
Freq.(MHz)	Output Power (dBm)	Target powerW/tolerance (dBm)	Max tuneup power tolerance (dBm)	Output power to antenna	Ant Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK								
2402	-2.162	-2±1.0	-1	0.794	1.7	0.00023	1	Pass
2440	-3.356	-3±1.0	-2	0.631	1.7	0.00019	1	Pass
2480	-4.429	-4±1.0	-3	0.501	7.7	0.00015	1	Pass

Note: The estimation distance is 20cm

5. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.