



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Specification

1.1 Electrical Properties

Characteristics	Specifications
Working Band	2.4G WiFi/5G WiFi
Antenna From	PIFA
Impedance	50 Ω
Polarization	Linear
Peak Effi	36%@2.4G; 33%@5G
Peak Gain	1.3dBi@2.4G; 2.7dBi@5G

1.2 Physical Properties

Characteristics	Specifications
Operating Temp	-10°C~+60°C
Storage Temp	-10°C~+70°C
Humidity	10~95%RH

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506



Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



Test Data

S11 Parameter-VSWR



Frequency (MHZ)	2400	2500	5150	5850
VSWR	1.42	1.16	1.82	1.62
Return Loss (DB)	-15.17	-22.20	-10.67	-12.42

WiFi Active Test Data

802.11b	Frequency	TRP		TIS	
	2412	CH1 11Mbps	12.77	CH1 11Mbps	-83.61
	2437	CH6 11Mbps	12.21	CH6 11Mbps	-83.12
	2467	CH11 11Mbps	12.14	CH11 11Mbps	-82.03
802.11a		TRP		TIS	
	5180	CH36 6Mbps	11.17	CH36 54Mbps	-74.10
	5300	CH60 6Mbps	11.81	CH60 54Mbps	-72.89
	5805	CH161 6Mbps	12.28	CH161 54Mbps	-73.0

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Efficiency Table

Passive Test For 2.4G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	Directivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
2400	36.24	-4.41	1.35	-0.8	16.502	19.742	1.35	-20.47	5.76	60	52.44	52.61
2410	31.86	-4.97	0.51	-1.64	14.58	17.28	0.51	-18.59	5.48	60	52.37	52.53
2420	32.71	-4.85	0.31	-1.84	15.063	17.648	0.31	-19.26	5.16	60	52.38	52.56
2430	31.99	-4.95	-0.27	-2.42	14.814	17.176	-0.27	-17.9	4.68	60	52.56	52.67
2440	32.43	-4.89	0.05	-2.1	15.053	17.382	0.05	-17.22	4.94	90	52.86	53.02
2450	31.33	-5.04	0.14	-2.01	14.535	16.799	0.14	-18.11	5.18	90	52.73	52.84
2460	29.59	-5.29	0.04	-2.11	13.715	15.878	0.04	-19.27	5.33	90	52.67	52.76
2470	29.59	-5.29	0.35	-1.8	13.806	15.779	0.35	-19.19	5.64	90	52.57	52.66
2480	31.74	-4.98	0.54	-1.61	14.832	16.903	0.54	-18.09	5.52	90	52.78	52.88
2490	34.72	-4.59	0.91	-1.24	16.304	18.413	0.91	-19.59	5.5	90	53.06	53.25
2500	35.03	-4.56	0.57	-1.58	16.527	18.504	0.57	-21.41	5.13	90	52.92	53.06
Passive Test For 5G												
Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)	Gain (dBd)	UHS (%)	DHS (%)	Max (dB)	Min (dB)	Directivity (dBi)	Beamwidth (3dB)	AttH (dB)	AttV (dB)
5150	26.98	-5.69	0.38	-1.77	16.201	10.78	0.38	-20.42	6.07	15	62.66	62.14
5170	24.76	-6.06	0.16	-1.99	15.063	9.695	0.16	-19.83	6.22	30	62.13	61.73
5190	21.43	-6.69	-0.1	-2.25	13.247	8.182	-0.1	-23.49	6.59	30	61.9	61.56
5210	25.12	-6	1.03	-1.12	15.623	9.498	1.03	-21.18	7.03	30	62.58	62.08
5230	24.83	-6.05	1.28	-0.87	15.484	9.343	1.28	-25.83	7.34	30	62	61.81
5250	24.69	-6.07	1.62	-0.53	15.463	9.231	1.62	-30.22	7.69	30	61.89	61.7
5270	23.84	-6.23	1.72	-0.43	14.911	8.927	1.72	-21.59	7.95	30	61.76	61.41
5290	25.22	-5.98	2.1	-0.05	15.824	9.394	2.1	-22.46	8.08	30	61.94	61.89
5310	21.9	-6.6	1.38	-0.77	13.763	8.136	1.38	-21.85	7.98	30	61.61	61.56
5330	22.08	-6.56	1.33	-0.82	13.938	8.141	1.33	-26.65	7.89	30	61.83	61.76
5350	22.16	-6.55	1.11	-1.04	14.121	8.035	1.11	-23.16	7.66	30	62.08	62.46
5370	24.2	-6.16	1.35	-0.8	15.51	8.687	1.35	-22.99	7.51	30	62.14	62.36
5390	22.26	-6.52	1.14	-1.01	14.354	7.907	1.14	-24.75	7.67	30	61.64	61.88
5410	27.24	-5.65	1.92	-0.23	17.735	9.503	1.92	-18.63	7.57	30	62.69	63.01
5430	28.76	-5.41	2.15	0	18.843	9.914	2.15	-19.98	7.56	30	62.41	62.93
5450	29.21	-5.34	2.28	0.13	19.279	9.936	2.28	-20.26	7.62	15	62.21	62.94
5470	29.09	-5.36	2.27	0.12	19.388	9.701	2.27	-23.62	7.63	15	62.56	63.24
5490	28.92	-5.39	2.1	-0.05	19.368	9.552	2.1	-22.04	7.49	0	63.06	63.84
5510	28.07	-5.52	1.94	-0.21	18.875	9.195	1.94	-20.82	7.45	15	63.46	64.44
5530	31.13	-5.07	2.01	-0.14	20.909	10.219	2.01	-26.07	7.08	15	63.75	64.89
5550	32	-4.95	2.45	0.3	21.487	10.51	2.45	-24.1	7.4	15	64.34	65.2
5570	31.87	-4.97	2.75	0.6	21.17	10.697	2.75	-18.73	7.72	15	64.38	65.25
5590	30.96	-5.09	2.45	0.3	20.457	10.5	2.45	-20.56	7.54	15	64.47	64.74
5610	31.15	-5.07	2.76	0.61	20.416	10.732	2.76	-21.46	7.82	15	64.28	65.11
5630	33.31	-4.77	2.9	0.75	21.468	11.846	2.9	-22.49	7.67	15	64.52	65.32
5650	32.96	-4.82	2.69	0.54	20.903	12.06	2.69	-18.67	7.51	15	64.43	65.08
5670	30.9	-5.1	2.36	0.21	19.299	11.598	2.36	-20.87	7.47	15	64.58	65.06
5690	33.2	-4.79	2.59	0.44	20.651	12.548	2.59	-17.64	7.38	30	64.65	66
5710	30.25	-5.19	2.54	0.39	18.844	11.408	2.54	-16.85	7.74	30	65.18	65.08
5730	34.11	-4.67	2.74	0.59	20.844	13.264	2.74	-17.91	7.41	30	64.91	65.55
5750	29.49	-5.3	1.98	-0.17	18.204	11.283	1.98	-21.04	7.28	30	64.64	64.89
5770	29.67	-5.28	1.95	-0.2	18.348	11.32	1.95	-23.63	7.23	30	64.61	65.28
5790	28.66	-5.43	2.08	-0.07	17.763	10.894	2.08	-22.59	7.51	30	64.83	64.78
5810	31.19	-5.06	2.46	0.31	19.207	11.979	2.46	-22.06	7.53	0	64.97	65.66
5830	30.56	-5.15	2.49	0.34	18.866	11.694	2.49	-21.33	7.64	0	65.45	66.02
5850	31.94	-4.96	2.76	0.61	19.486	12.452	2.76	-22.55	7.72	30	65.65	66.39

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address:1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen


Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com




深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Radiation Pattern (2.4G)



Radiation Pattern (5G)



BT Test

测试环境：开放空间（通道）

Testing environment: Open space (passageway)

测试工具：蓝牙音响

Testing tool: Bluetooth speaker

测试距离：10+m

Testing distance: More than 10 meters

结果：播放音乐流畅，无杂音

Result: The music plays smoothly without any noise

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen



Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com





深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Throughput Test(2.4G)

上行 Upload	369M	下行 Downstream	409M
图片 Pic.		图片 Pic.	

Throughput Test(5G)

上行 Upload	939M	下行 Downstream	880M
图片 Pic.		图片 Pic.	

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen


Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com



深圳星源创科技有限公司

Shen Zhen Xing Yuan Chuang Technology Co., Ltd

Antenna Assembly



地址: 深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address: 1506, Tangwei Business Building, Fuhai Street, Fuyong Town, Baoan District, Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stepdeng_Vis@126.com



Inspection Standard

Shenzhen Xingyuan Chuang Technology Co., Ltd.	Document Code	XYC-WI-PZ-02	Page
	Document Version	A0	1 of 1
Document Name	Sampling Plan		

Sampling Level Comparison Table

Special Inspection Level				General Inspection Level			Lot Size Range	Sample Code Letter	Sample Size	0.65		1.0		1.5		2.5		4.0		6.0	
S-1	S-2	S-3	S-4	I	II	III				AC	RE	AC	RE	AC	RE	AC	RE	AC	RE	AC	RE
A	A	A	A	A	A	B	2---8	A	2	0	1	0	1	0	1	0	1	0	1	0	1
A	A	A	A	A	B	C	9---15	B	3	0	1	0	1	0	1	0	1	0	1	0	1
A	A	B	B	B	C	D	16---25	C	5	0	1	0	1	0	1	0	1	0	1	1	2
A	B	B	C	C	D	E	26---50	D	8	0	1	0	1	0	1	0	1	1	2	1	2
B	B	C	C	C	E	F	51---90	E	13	0	1	0	1	0	1	1	2	1	2	2	3
B	B	C	D	D	F	G	91---150	F	20	0	1	0	1	1	2	1	2	2	3	3	4
B	C	D	E	E	G	H	151---280	G	32	0	1	1	2	1	2	2	3	3	4	5	6
B	C	D	E	F	H	J	281---500	H	50	1	2	1	2	2	3	3	4	5	6	7	8
C	C	E	F	G	J	K	501---1200	J	80	1	2	2	3	3	4	5	6	7	8	10	11
C	D	E	G	H	K	L	1201---3200	K	125	2	3	3	4	5	6	7	8	10	11	14	15
C	D	F	G	J	L	M	3201---10000	L	200	3	4	5	6	7	8	10	11	14	15	21	22
C	D	F	H	K	M	N	10001---35000	M	315	5	6	7	8	10	11	14	15	21	22	21	22
D	E	G	J	L	N	P	35001---150000	N	500	7	8	10	11	14	15	21	22	21	22	21	22
D	E	G	J	M	P	Q	150001---500000	P	800	10	11	14	15	21	22	21	22	21	22	21	22
D	E	H	K	N	Q	R	500001and over	Q	1250	14	15	21	22	21	22	21	22	21	22	21	22
								R	2000	21	22	21	22	21	22	21	22	21	22	21	22

AC is the acceptable item RE is the reject item

地址：深圳市宝安区福永镇福海街道塘尾股份商务大厦1506

Address:1506,Tangwei Business Building,Fuhai Street,Fuyong Town,Baoan District,Shenzhen

Tel: 0755-82103639 QQ: 487580356 Email: Stephdeng_Vis@126.com