



中国认可  
国际互认  
检测  
TESTING  
CNAS L0310



## FCC Maximum Permissible Exposure(MPE) Estimation Report

Product Name: LTE CPE

Model: B311-520

Report No.: SYBH(Z-SAR)20181120036001-2

FCC ID: QISB311-520

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>Zhang Zufu</i>
DATE	2019-01-14	2019-01-14

**Reliability Laboratory of Huawei Technologies Co., Ltd.**

**(Global Compliance and Testing Center of Huawei Technologies Co., Ltd)**

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bastian, Longing  
District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518

**※ ※ Notice ※ ※**

1. The laboratory has passed the accreditation by China National Accreditation Service for Conformity Assessment (CNAS). The accreditation number is L0310.
2. The laboratory has passed the accreditation by The American Association for Laboratory Accreditation (A2LA). The accreditation number is 2174.01 & 2174.02 & 2174.03
3. The laboratory (Reliability Lab of Huawei Technologies Co., Ltd) is also named as “Global Compliance and Testing Center of Huawei Technologies Co., Ltd”, the both names have coexisted since 2009.
4. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
5. The test report is invalid if there is any evidence of erasure and/or falsification.
6. The test report is only valid for the test samples.
7. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

## ※ ※ Modified History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
v.1.0	Initial Test Report Release	2019-01-14	Zhang Zufu

## Table of Contents

1	EUT Description .....	6
1.1	General Description .....	7
2	Test specification(s) .....	8
3	Testing laboratory .....	8
4	Applicant and Manufacturer .....	8
5	Application details .....	8
6	Ambient Condition .....	8
7	RF Exposure Requirements .....	9
7.1	FCC MPE Limits .....	10
8	RF Exposure Evaluation .....	11
8.1	Operation in UMTS Band II .....	11
8.2	Operation in UMTS Band IV .....	11
8.3	Operation in UMTS Band V .....	12
8.4	Operation in LTE Band 2 .....	12
8.5	Operation in LTE Band 4 .....	13
8.6	Operation in LTE Band 5 .....	13
8.7	Operation in LTE Band 7 .....	14
8.8	Operation in LTE Band 66 .....	14
8.9	Operation in WLAN 2.4G .....	15
9	Exposure calculations for multiple sources .....	16

---

9.1	Estimation for WLAN 2.4G MIMO .....	17
9.2	Estimation for UMTS Band II & WLAN 2.4G .....	17
9.3	Estimation for UMTS Band IV & WLAN 2.4G.....	17
9.4	Estimation for UMTS Band V & WLAN 2.4G.....	17
9.5	Estimation for LTE Band 2 & WLAN 2.4G.....	18
9.6	Estimation for LTE Band 4 & WLAN 2.4G.....	18
9.7	Estimation for LTE Band 5 & WLAN 2.4G.....	18
9.8	Estimation for LTE Band 7 & WLAN 2.4G.....	19
9.9	Estimation for LTE Band 66 & WLAN 2.4G.....	19

# 1 EUT Description

Device Information:			
Product Name :	LTE CPE		
Model :	B311-520		
FCC ID:	QISB311-520		
Device Type :	Mobile Device		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment/general population		
Hardware Version :	WL3B311SW06		
Software Version :	8.0.1.1(H183SP3C00)		
Antenna Type :	Internal Antenna/ External Antenna		
Device Operating Configurations:			
Supporting Mode(s)	LTE B2/B4/B5/B7/B66, UMTS Band II/IV/V, WLAN 2.4 GHz		
Test Modulation	UMTS(QPSK), LTE(QPSK/16QAM), WLAN 2.4G (DSSS/OFDM)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	UMTS Band II	1850-1910	1930-1990
	UMTS Band IV	1710-1755	2110-2155
	UMTS Band V	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 66	1710-1780	2110-2180
	WLAN 2.4G	2412-2462	2412-2462

## 1.1 General Description

The HUAWEI LTE CPE B311-520 is a Long Term Evolution (LTE) wireless gateway for multiple users in household or small office environments. It enables users to access the Internet, supports 3GPP Release 9 with UE downlink/uplink category 4. Working band: LTE: B2/B4/B5/B7/B66, UMTS: Band II/IV/V, Wi-Fi: 2.4 GHz 802.11b/g/n 2x2 MIMO up to 300Mbps. Maximum Users: 32.

## 2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB 447498 D01	General RF Exposure Guidance v06

## 3 Testing laboratory

Test Site	Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	NO.2 New City Avenue Songshan Lake Sci. & Tech. Industry Park, Dongguan, Guangdong, P.R.C
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01 & 2174.02 & 2174.03

## 4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

## 5 Application details

Start Date of test	2019-01-14
End Date of test	2019-01-14

## 6 Ambient Condition

Ambient temperature	18°C – 25°C
Relative Humidity	30% – 70%



## 7 RF Exposure Requirements

An estimation of MPE in this application for product is used to ensure if it complies with the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

EIRP = P \* G

The antenna of the product, under normal use condition is at least 20 cm away from the

body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

## 7.1 FCC MPE Limits

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

**Table: Limits for Maximum Permissible Exposure (MPE)**

<b>(A) Limits for Occupational/controlled Exposure</b>				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Time (minute) E  <sup>2</sup> , H  <sup>2</sup> or S
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
<b>(B) Limits for General Population/uncontrolled Exposure</b>				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Time (minute) E  <sup>2</sup> , H  <sup>2</sup> or S
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
f=frequency in MHz			*Plane-wave equivalent power density	

## 8 RF Exposure Evaluation

### 8.1 Operation in UMTS Band II

(Uplink: 1850-1910MHz, downlink: 1930-1990MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.5	1.08	25.58	361.41	20	0.072	1.000	PASS
External antenna 1	24.5	1.0	25.5	354.8	20	0.071	1.000	PASS
External antenna 2	24.5	3.0	27.5	562.3	20	<b>0.112</b>	1.000	PASS

Note: \*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.112** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

### 8.2 Operation in UMTS Band IV

(Uplink: 1710-1755MHz, downlink: 2110-2155MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.5	0.26	24.76	299.23	20	0.060	1.000	PASS
External antenna 1	24.5	1.0	25.5	354.8	20	0.071	1.000	PASS
External antenna 2	24.5	3.0	27.5	562.3	20	<b>0.112</b>	1.000	PASS

Note: \*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.112** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

### 8.3 Operation in UMTS Band V

(Uplink: 824-849MHz, downlink: 869-894MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	25.0	0.98	25.98	396.28	20	0.079	0.549	PASS
External antenna 1	25.0	1.0	26.0	398.1	20	0.079	0.549	PASS
External antenna 2	25.0	3.0	28.0	631.0	20	<b>0.126</b>	0.549	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.126mW/cm<sup>2</sup>**, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

### 8.4 Operation in LTE Band 2

(Uplink: 1850-1910MHz, downlink: 1930-1990MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.0	1.08	25.08	322.11	20	0.064	1.000	PASS
External antenna 1	24.0	1.0	25.0	316.2	20	0.063	1.000	PASS
External antenna 2	24.0	3.0	27.0	501.2	20	<b>0.100</b>	1.000	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.100mW/cm<sup>2</sup>**, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 8.5 Operation in LTE Band 4

(Uplink: 1710-1755MHz, downlink: 2110-2155MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.0	0.26	24.26	266.69	20	0.053	1.000	PASS
External antenna 1	24.0	1.0	25.0	316.2	20	0.063	1.000	PASS
External antenna 2	24.0	3.0	27.0	501.2	20	<b>0.100</b>	1.000	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.100** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 8.6 Operation in LTE Band 5

(Uplink: 824-849MHz, downlink: 869-894MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.5	0.98	25.48	353.18	20	0.070	0.549	PASS
External antenna 1	24.5	1.0	25.5	354.8	20	0.071	0.549	PASS
External antenna 2	24.5	3.0	27.5	562.3	20	<b>0.112</b>	0.549	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.112** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 8.7 Operation in LTE Band 7

(Uplink: 2500-2570MHz, downlink: 2620-2690MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.5	1.91	26.41	437.52	20	0.087	1.000	PASS
External antenna 1	24.5	1.0	25.5	354.8	20	0.071	1.000	PASS
External antenna 2	24.5	3.0	27.5	562.3	20	<b>0.112</b>	1.000	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.112** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 8.8 Operation in LTE Band 66

(Uplink: 1710-1780MHz, downlink: 2110-2180MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Internal antenna 1	24.0	0.26	24.26	266.69	20	0.053	1.000	PASS
External antenna 1	24.0	1.0	25.0	316.2	20	0.063	1.000	PASS
External antenna 2	24.0	3.0	27.0	501.2	20	<b>0.100</b>	1.000	PASS

Note:\*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.100** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 8.9 Operation in WLAN 2.4G

(Uplink: 2412-2462MHz, downlink: 2412-2462MHz)

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Conclusion
Antenna 1	18.5	4.17	22.67	184.93	20	<b>0.037</b>	1.000	PASS
Antenna 2	17.5	3.40	20.90	123.03	20	0.024	1.000	PASS

Note:\* - based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is **0.037** mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit, so we can conclude it is into compliance.

## 9 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table (A) and Table (B). To comply with the MPE, the fraction of the MPE in terms of  $E^2$ ,  $H^2$  (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WLAN 2.4G MIMO
2	UMTS/LTE +WLAN 2.4G SISO
3	UMTS/LTE+WLAN 2.4G MIMO



### 9.1 Estimation for WLAN 2.4G MIMO

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
Antenna 1	17.5	4.17	21.67	146.89	20	0.029	1.000	0.053	PASS
Antenna 2	17.5	3.40	20.90	123.03	20	0.024	1.000		

Note: \*- based on the maximum tune-up tolerance limit declared by manufacturer

### 9.2 Estimation for UMTS Band II & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	UMTS Band II	0.112	1.000	0.149	PASS
	WLAN2.4G SISO	0.037	1.000		
2	UMTS Band II	0.112	1.000	0.165	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.3 Estimation for UMTS Band IV & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	UMTS Band IV	0.112	1.000	0.149	PASS
	WLAN2.4G SISO	0.037	1.000		
2	UMTS Band IV	0.112	1.000	0.165	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.4 Estimation for UMTS Band V & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	UMTS Band V	0.126	0.549	0.267	PASS
	WLAN2.4G SISO	0.037	1.000		
2	UMTS Band V	0.126	0.549	0.283	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.5 Estimation for LTE Band 2 & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	LTE Band 2	0.100	1.000	0.137	PASS
	WLAN2.4G SISO	0.037	1.000		
2	LTE Band 2	0.100	1.000	0.153	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.6 Estimation for LTE Band 4 & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	LTE Band 4	0.100	1.000	0.137	PASS
	WLAN2.4G SISO	0.037	1.000		
2	LTE Band 4	0.100	1.000	0.153	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.7 Estimation for LTE Band 5 & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	LTE Band 5	0.112	0.549	0.241	PASS
	WLAN2.4G SISO	0.037	1.000		
2	LTE Band 5	0.112	0.549	0.257	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.8 Estimation for LTE Band 7 & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	LTE Band 7	0.112	1.000	0.149	PASS
	WLAN2.4G SISO	0.037	1.000		
2	LTE Band 7	0.112	1.000	0.165	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

### 9.9 Estimation for LTE Band 66 & WLAN 2.4G

No.	Mode	S (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Calculation result	Conclusion
1	LTE Band 66	0.100	1.000	0.137	PASS
	WLAN2.4G SISO	0.037	1.000		
2	LTE Band 66	0.100	1.000	0.153	PASS
	WLAN MIMO with Antenna 1	0.029	1.000		
	WLAN MIMO with Antenna 2	0.024	1.000		

According to the Table above, we can conclude that the calculation results of all simultaneous transmission possibilities are less than 1, so it is into compliance.  
Therefore the product also meets the requirements under multiple sources condition.

-----END-----